1 of 10

Signetics

Programmable Logic Data Manual

Signetics

Application Specific Products

PLD
Data Manual
1987

Signetics' Approach to Logic Flexibility for the '80's

Signetics reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Signetics assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified. Applications that are described herein for any of these products are for illustrative purposes only. Signetics makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

LIFE SUPPORT POLICY

SIGNETICS PRODUCTS ARE NOT FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF AN OFFICER OF SIGNETICS CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Signetics registers eligible circuits under
the Semiconductor Chip Protection Act.

© Copyright 1986 Signetics Corporation

All rights reserved.

Preface

Application Specific Products

The continuing trend of system integration has created new challenges for Design Engineering. They must strive to consolidate higher complexity, and more feature intensive circuits into designs without sacrificing flexibility. Today's competitive electronic marketplace has created the need for logic devices, which can provide cost effective methods of reducing random logic requirements, interface with fixed and custom LSI logic, and maintain the flexible features required to make necessary system modifications prior to production. Signetics has responded to this need with Signetics Programmable Logic Devices (Signetics PLD).

The Signetics Programmable Logic family consists of a relatively few devices which are designed to address logic needs ranging from random gates in the case of the Field Programmable Gate Arrays, to highly sophisticated state machines in the case of Field Programmable Logic Sequencers. Signetics pioneered the fully-programmable AND/OR/INVERT architecture in 1975. In 1987, Signetics will introduce a new concept in PLD architectures. Moving away from an AND-OR array structure, the Signetics' Programmable Macro Logic architecture relies on a single NAND array concept. Signetics' novel architectural approach to Programmable Logic incorporates all the advantages associated with more dense complex gate arrays while retaining all the benefits of instantly programmable PLDs. By using the programmable features allowed by either powerful architecture, Signetics Programmable Logic can encompass wide-ranging levels of integration without the necessity of a multitude of devices, each with a different I/O configuration. The flexible programming structure allows the designer to "mold" the device architecture to the range of applications typically found in system design. In this way, one device can be used to perform several functions in the same design.

The 1987 Signetics Programmable Logic Data Manual contains information that the designer will require in order to effectively utilize these products.

Signetics Application Specific Products Marketing

Product Status

DEFINITIONS

Data Sheet Identification	Product Status	Definition
Objective Specification	**Formative or In Design**	This data sheet contains the design target or goal specifications for product development. Specifications may change in any manner without notice.
Preliminary Specification	**Preproduction Product**	This data sheet contains preliminary data and supplementary data will be published at a later date. Signetics reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.
Product Specification	**Full Production**	This data sheet contains Final Specifications. Signetics reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.

Signetics

Contents

Application Specific Products

Preface ... iii

Product Status ... iv

Section 1

Quality and Reliability ... 1-3
Alphanumeric Index ... 1-9
Selection Guide ... 1-10
Ordering Information ... 1-11
Note to Users ... 1-12

Section 2 – Introduction

What Is Signetics' Programmable Logic ... 2-3
Programming Information ... 2-48

Section 3 – Advanced Product Preview

PLMC153 Mask-Programmable Logic Array (18 × 42 × 10) ... 3-3
PLUS153 Field-Programmable Logic Array (18 × 42 × 10) ... 3-5
PLUS173 Field-Programmable Logic Array (22 × 42 × 10) ... 3-7
PLHS501 Programmable Macro Logic Random Logic Unit (32 × 72 × 24) ... 3-9
PLHS502 Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24) ... 3-19

Section 4 – PLD Data Sheets

Series 20

PLS151 Field-Programmable Gate Array (18 × 15 × 12) ... 4-3
PLS153 Field-Programmable Logic Array (18 × 42 × 10) ... 4-9
PLS153A Field-Programmable Logic Array (18 × 42 × 10) ... 4-15
PLHS153 Field-Programmable Logic Array (18 × 42 × 10) ... 4-21
PLS155 Field-Programmable Logic Sequencer (16 × 45 × 12) ... 4-27
PLS157 Field-Programmable Logic Sequencer (16 × 45 × 12) ... 4-37
PLS159 Field-Programmable Logic Sequencer (16 × 45 × 12) ... 4-47
PLS159A Field-Programmable Logic Sequencer (16 × 45 × 12) ... 4-57
PLHS18P8A Programmable AND Array Logic (18 × 72 × 8) ... 4-67

Section 5 – PLD Data Sheets

Series 24

PLS161 Field-Programmable Logic Array (12 × 48 × 8) ... 5-3
PLS162 Field-Programmable Address Decoder (16 × 5) ... 5-9
PLS163 Field-Programmable Address Decoder (12 × 9) ... 5-15
PLS167 Field-Programmable Logic Sequencer (14 × 48 × 6) ... 5-21
PLS167A Field-Programmable Logic Sequencer; Enhanced Speed (14 × 48 × 6) ... 5-33
PLS168 Field-Programmable Logic Sequencer (12 × 48 × 8) ... 5-45
PLS168A Field-Programmable Logic Sequencer; Enhanced Speed (12 × 48 × 8) ... 5-57
PLS173 Field-Programmable Logic Array (22 × 42 × 10) ... 5-69
PLS179 Field-Programmable Logic Sequencer (20 × 45 × 12) ... 5-75
PLHS473 Field-Programmable Logic Array (20 × 24 × 11) ... 5-85
PLC473 Erasable-Programmable Logic Array (20 × 24 × 11) ... 5-91

Section 6 – PLD Data Sheets

Series 28

PLS100/PLS101 Field-Programmable Logic Array (16 × 48 × 8) ... 6-3
PLS103 Field-Programmable Gate Array (16 × 9 × 9) ... 6-10
PLS105 Field-Programmable Logic Sequencer (16 × 48 × 8) ... 6-16
PLS105A Field-Programmable Logic Sequencer (16 × 48 × 8) ... 6-27
PLUS405A Field-Programmable Logic Sequencer (16 × 64 × 8) ... 6-38

Section 7 – Military Products

Military Errata ... 7-1

Contents

Section 8 – Development Software

AMAZE – Automatic Map and Zap Equations Design Software 8-3

Section 9 – Application Notes

AN7 Single Chip Multiprocessor Arbiter 9-3
AN8 Introduction to Signetics Programmable Logic 9-15
AN10 4-Bit Binary-to-7 Segment Decoder 9-27
AN11 PLD Programmable Retriggerable One-Shot 9-51
AN12 Low Cost Programmer for PLD 20-Pin Series 9-55
AN13 Oscillator With PLS159 9-71
AN14 Latches and Flip-Flops With PLS153 9-76
AN15 PLS159 Primer 9-89
AN16 PLS159 as Modulo Counters 9-100
AN17 Electronic Combination Lock 9-107
AN18 Schmitt Trigger Using PLS153 and PLS159 9-110
AN19 Electronic Dice 9-118
AN20 Single Pin Debouncer Using PLS153/159 9-122
AN21 9-Bit Parity Generator/Checker With PLS153/153A 9-125
AN22 PLS151 Toolkit 9-131
AN23 PLS168/168A Primer 9-139
AN24 PLS173 as a 10-Bit Comparator, 74LS460 9-152
AN25 A Simple Entry/Exit Meeting Device (PLS157) 9-158
AN26 PLHS18P8A Primer 9-164
AN27 PLHS473 Primer 9-172
AN28 High-Speed 12-Bit Tracking A/D Converter Using PLS179 9-180
AN29 PLHS501 Programmable Macro Logic Primer 9-190

Section 10 – Package Outlines

Package Outlines

A PLASTIC: Leaded Chip Carrier 10-3
F CERAMIC: Dual-In-Line 10-5
FA CERAMIC: Dual-In-Line With Quartz Window 10-7
N PLASTIC: Dual-In-Line 10-9

Section 11 – Sales Offices

Office Listing 11-3

Section 1

INDEX

Section 1

Quality and Reliability 1-3
Alphanumeric Index 1-9
Selection Guide 1-10
Ordering Information 1-11
Note to Users 1-12

Quality and Reliability

SIGNETICS PROGRAMMABLE LOGIC QUALITY

Signetics has put together winning processes for manufacturing Programmable Logic. Our standard is zero defects, and current customer quality statistics demonstrate our commitment to this goal.

The PLD's produced in the Application Specific Products Division must meet rigid criteria as defined by our design rules and as evaluated with a thorough product characterization and quality process. The capabilities of our manufacturing process are measured and the results evaluated and reported through our corporate-wide QA05 data base system. The SURE (Systematic Uniform Reliability Evaluation) program monitors the performance of our product in a variety of accelerated environmental stress conditions. All of these programs and systems are intended to prevent product-related problems and to inform our customers and employees of our progress in achieving zero defects.

RELIABILITY BEGINS WITH THE DESIGN

Quality and reliability must begin with design. No amount of extra testing or inspection will produce reliable ICs from a design that is inherently unreliable. Signetics follows very strict design and layout practices with its circuits. To eliminate the possibility of metal migration, current density in any path cannot exceed 2×10^5 amps/cm^2. Layout rules are followed to minimize the possibility of shorts, circuit anomalies, and SCR type latch-up effects. Numerous ground-to-substrate connections are required to ensure that the entire chip is at the same ground potential, thereby precluding internal noise problems.

PRODUCT CHARACTERIZATION

Before a new design is released, the characterization phase is completed to insure that the distribution of parameters resulting from lot-to-lot variations is well within specified limits. Such extensive characterization data also provides a basis for identifying unique application-related problems which are not part of normal data sheet guarantees. Characterization takes place from −55°C to +125°C and at +10% supply voltage.

QUALIFICATION

Formal qualification procedures are required for all new or changed products, processes and facilities. These procedures ensure the high level of product reliability our customers expect. New facilities are qualified by corporate groups as well as by the quality organizations of specific units that will operate in the facility. After qualification, products manufactured by the new facility are subjected to highly accelerated environmental stresses to ensure that they can meet rigorous failure rate requirements. New or changed processes are similarly qualified.

QA05 – QUALITY DATA BASE REPORTING SYSTEM

The QA05 data reporting system collects the results of product assurance testing on all finished lots and feeds this data back to concerned organizations where appropriate action can be taken. The QA05 reports EPQ (Estimated Process Quality) and AOQ (Average Outgoing Quality) results for electrical, visual/mechanical, hermeticity, and documentation audits. Data from this system is available on request.

THE SURE PROGRAM

The SURE (Systematic Uniform Reliability Evaluation) program audits/monitors products from all Signetics' divisions under a variety of accelerated environmental stress conditions. This program, first introduced in 1964, has evolved to suit changing product complexities and performance requirements.

The SURE program has two major functions: Long-term accelerated stress performance audit and a short-term accelerated stress monitor. In the case of Bipolar Memory and Programmable Logic products, samples are selected that represent all generic product groups in all wafer fabrication and assembly locations.

THE LONG-TERM AUDIT

One-hundred devices from each generic family are subjected to each of the following stresses every eight weeks:

- High Temperature Operating Life: $T_J = 150°C$, 1000 hours, static biased or dynamic operation, as appropriate (worst case bias configuration is chosen)
- High Temperature Storage: $T_J = 150°C$, 1000 hours
- Temperature Humidity Biased Life: 85°C, 85% relative humidity, 1000 hours, static biased
- Temperature Cycling (Air-to-Air): −65°C to +150°C, 1000 cycles

THE SHORT-TERM MONITOR

Every other week a 50-piece sample from each generic family is run to 168 hours of pressure pot (15psig, 121°C, 100% saturated steam) and 300 cycles of thermal shock (−65°C to +150°C).

In addition, each Signetics assembly plant performs SURE product monitor stresses weekly on each generic family and molded package by pin count and frame type. Fifty-piece samples are run on each stress, pressure pot to 96 hours, thermal shock to 300 cycles.

SURE REPORTS

The data from these test matrices provides a basic understanding of product capability, an indication of major failure mechanisms and an estimated failure rate resulting from each stress. This data is compiled periodically and is available to customers upon request.

Many customers use this information in lieu of running their own qualification tests, thereby eliminating time-consuming and costly additional testing.

Quality and Reliability

RELIABILITY ENGINEERING

In addition to the product performance monitors encompassed in the Programmable Logic SURE program, Signetics' Corporate and Division Reliability Engineering departments sustain a broad range of evaluation and qualification activities.

Included in the engineering process are:

- Evaluation and qualification of new or changed materials, assembly/wafer-fab processes and equipment, product designs, facilities and subcontractors.
- Device or generic group failure rate studies.
- Advanced environmental stress development.
- Failure mechanism characterization and corrective action/prevention reporting.

The environmental stresses utilized in the engineering programs are similar to those utilized for the SURE monitor; however, more highly-accelerated conditions and extended durations typify the engineering projects. Additional stress systems such as biased pressure pot, power-temperature cycling, and cycle-biased temperature-humidity, are also included in the evaluation programs.

FAILURE ANALYSIS

The SURE Program and the Reliability Engineering Program both include failure analysis activities and are complemented by corporate, divisional and plant failure analysis departments. These engineering units provide a service to our customers who desire detailed failure analysis support, who in turn provide Signetics with the technical understanding of the failure modes and mechanisms actually experienced in service. This information is essential in our ongoing effort to accelerate and improve our understanding of product failure mechanisms and their prevention.

ZERO DEFECTS PROGRAM

In recent years, United States industry has increasingly demanded improved product quality. We at Signetics believe that the customer has every right to expect quality products from a supplier. The benefits which are derived from quality products can be summed up in the words, *lower cost of ownership.*

Those of you who invest in costly test equipment and engineering to assure that incoming products meet your specifications have a special understanding of the cost of ownership. And your cost does not end there; you are also burdened with inflated inventories, lengthened lead times and more rework.

SIGNETICS UNDERSTANDS CUSTOMERS' NEEDS

Signetics has long had an organization of quality professionals, inside all operating units, coordinated by a corporate quality department. This broad decentralized organization provides leadership, feedback, and direction for achieving a high level of quality. Special programs are targeted on specific quality issues. For example, in 1978 a program to reduce electrically defective units for a major automotive manufacturer improved outgoing quality levels by an order of magnitude.

In 1980 we recognized that in order to achieve outgoing levels on the order of 100PPM (parts per million), down from an industry practice of 10,000PPM, we needed to supplement our traditional quality programs with one that encompassed all activities and all levels of the company. Such unprecedented low defect levels could only be achieved by contributions from all employees, from the R and D laboratory to the shipping dock. In short, from a program that would effect a total cultural change within Signetics in our attitude toward quality.

QUALITY PAYS OFF FOR OUR CUSTOMERS

Signetics' dedicated programs in product quality improvement, supplemented by close working relationships with many of our customers, have improved outgoing product quality more than twenty-fold since 1980. Today, many major customers no longer test Signetics circuits. Incoming product moves directly from the receiving dock to the production line, greatly accelerating throughput and reducing inventories. Other customers have pared significantly the amount of sampling done on our products. Others are beginning to adopt these cost-saving practices.

We closely monitor the electrical, visual, and mechanical quality of all our products and review each return to find and correct the cause. Since 1981, over 90% of our customers report a significant improvement in overall quality (see Figure 1).



Figure 1. Signetics Quality Progress

Quality and Reliability



Figure 2. Performance To Schedule On-Time Delivery

At Signetics, quality means more than working circuits. It means on-time delivery of the right product at the agreed upon price (see Figure 2). Signetics considers Performance to Customer Request and Performance to Original Schedule Date to be key Quality issues. Employees treat delinquencies as quality defects. They analyze the cause for the delinquency and seek corrective action to prevent future occurance. Continuous effort is given to try to acheive the ultimate goal of zero delinquencies.

ONGOING QUALITY PROGRAM

The quality improvement program at Signetics is based on "Do it Right the First Time". The intent of this innovative program is to change the perception of Signetics' employees that somehow quality is solely a manufacturing issue where some level of defects is inevitable. This attitude has been replaced by one of acceptance of the fact that all errors and defects are preventable, a point of view shared by all technical and administrative functions equally.

This program extends into every area of the company, and more than 40 quality improvement teams throughout the organization drive its ongoing refinement and progress.

Key components of the program are the Quality College, the "Make Certain" Program, Corrective Action Teams, and the Error Cause Removal System.

The core concepts of doing it right the first time are embodied in the four absolutes of quality:

1. The definition of quality is conformance to requirements.
2. The system to achieve quality improvement is prevention.
3. The performance standard is zero defects.
4. The measurement system is the cost of quality.

QUALITY COLLEGE

Almost continuously in session, Quality College is a prerequisite for all employees. The intensive curriculum is built around the four absolutes of quality; colleges are conducted at company facilities throughout the world.

"MAKING CERTAIN" – ADMINISTRATIVE QUALITY IMPROVEMENT

Signetics' experience has shown that the largest source of errors affecting product and service quality is found in paperwork and in other administrative functions. The "Make Certain" program focuses the attention of management and administrative personnel on error prevention, beginning with each employee's own actions.

This program promotes defect prevention in three ways: by educating employees as to the impact and cost of administrative errors, by changing attitudes from accepting occasional errors to one of accepting a personal work standard of zero defects, and by providing a formal mechanism for the prevention of errors.

CORRECTIVE ACTION TEAMS

Employees with the perspective, knowledge, and necessary skills to solve a problem are formed into ad hoc groups called Corrective Action Teams. These teams, a major force within the company for quality improvement, resolve administrative, technical and manufacturing problems.

ECR SYSTEM (ERROR CAUSE REMOVAL)

The ECR System permits employees to report to management any impediments to doing the job right the first time. Once such an impediment is reported, management is obliged to respond promptly with a corrective program. Doing it right the first time in all company activities produces lower cost of ownership through defect prevention.

PRODUCT QUALITY PROGRAM

To reduce defects in outgoing products, we created the Product Quality Program. This is managed by the Product Engineering Council, composed of the top product engineering and test professionals in the company. This group:

1. Sets aggressive product quality improvement goals;
2. provides corporate-level visibility and focus on problem areas;
3. serves as a corporate resource for any group requiring assistance in quality improvement; and
4. drives quality improvement projects.

As a result of this aggressive program, every major customer who reports back to us on product performance is reporting significant progress.

VENDOR CERTIFICATION PROGRAM

Our vendors are taking ownership of their own product quality by establishing improved process control and inspection systems. They subscribe to the zero defects philosophy. Progress has been excellent.

Quality and Reliability



Figure 3. Lot Acceptance Rate From Signetics Vendors

Through intensive work with vendors, we have improved our lot acceptance rate on incoming materials as shown in Figure 3. Simultaneously, waivers of incoming material have been eliminated.

MATERIAL WAIVERS

1986 – (0) (Goal)
1985 – 0
1984 – 0
1983 – 0
1982 – 2
1981 – 134

Higher incoming quality material ensures higher outgoing quality products.

QUALITY AND RELIABILITY ORGANIZATION

Quality and reliability professionals at the divisional level are involved with all aspects of the product, from design through every step in the manufacturing process, and provide product assurance testing of outgoing product. A separate corporate-level group provides direction and common facilities.

Quality and Reliability Functions

- Manufacturing quality control
- Product assurance testing
- Laboratory facilities – failure analysis, chemical, metallurgy, thin film, oxides
- Environmental stress testing
- Quality and reliability engineering
- Customer liaison

COMMUNICATING WITH EACH OTHER

For information on Signetics' quality programs or for any question concerning product quality, the field salesperson in your area will provide you with the quickest access to answers. Or, write on your letter-head directly to the corporate director of quality at the corporate address shown at the back of this manual.

We are dedicated to preventing defects. When product problems do occur, we want to know about them so we can eliminate their causes. Here are some ways we can help each other:

- Provide us with one informed contact within your organization. This will establish continuity and build confidence levels.
- Periodic face-to-face exchanges of data and quality improvement ideas between your engineers and ours can help prevent problems before they occur.
- Test correlation data is very useful. Line-pull information and field failure reports also help us improve product performance.
- Provide us with as much specific data on the problem as soon as possible to speed analysis and enable us to take corrective action.
- An advance sample of the devices in question can start us on the problem resolution before physical return of shipment.

This team work with you will allow us to achieve our mutual goal of improved product quality.

MANUFACTURING: DOING IT RIGHT THE FIRST TIME

In dealing with the standard manufacturing flows, it was recognized that significant improvement would be achieved by "doing every job right the first time", a key concept of the quality improvement program. During the development of the program many profound changes were made. Figure 4, *Programmable Logic Process Flow*, shows the result. Key changes included such things as implementing 100% temperature testing on all products as well as upgrading test handlers to insure 100% positive binning. Some of the other changes and additions were to tighten the outgoing QA lot acceptance criteria to the tightest in the industry, with zero defect lot acceptance sampling across all three temperatures.

The achievements resulting from the improved process flow have helped Signetics to be recognized as the leading Quality supplier of Programmable Logic. These achievements have also led to our participation in several Ship-to-Stock programs, which our customers use to eliminate incoming inspection. Such programs reduce the user *cost of ownership* by saving both time and money.

OUR GOAL: 100% PROGRAMMING YIELD

Our original goal back in the early 1970s was to develop a broad line of programmable products which would be recognized as having the best programming yield in the industry. Within the framework of a formal quality program, our efforts to improve circuit designs and refine manufacturing controls have resulted in major advances toward that goal.

Also within the framework of our formal quality program we have now established a stated goal of 100% programming yield. Through the increasing effectiveness of a quality attitude of "Do It Right The First Time" we're moving ever closer to that target.

Signetics PLD programming yields have been shown in collected data from internal audits and customer reporting to be consistently higher than comparable devices produced by our competition. We use systematic methods involving publication of exacting specifications of our programming algorithms, and through evaluation of those algorithms as implemented in industry standard programming equipment. Because of this we can assure our customers who program Signetics PLD's on such qualified equipment they will see consistently high yields. Our data base shows that average lot programming yield exceeds 97%.



SCANNING ELECTRON MICROSCOPE CONTROL

Wafers are sampled daily by the Quality Control Laboratory from each fabrication area and subjected to SEM analysis. This process control reveals manufacturing defects such as contact and oxide step coverage in the metalization process which may result in early failures.

DIE SORT VISUAL ACCEPTANCE

Product is inspected for defects caused during fabrication, wafer testing, or the mechanical scribe and break operation. Defects such as scratches, smears and glassivated bonding pads are included in the lot acceptance criteria.

PRE-SEAL VISUAL ACCEPTANCE

Product is inspected to detect any damage incurred at the die attach and wire bonding stations. Defects such as scratches, contamination and smeared ball bonds are included in the lot acceptance criteria.

STABILIZATION BAKE PRECONDITIONING

Plastic molded devices are baked to stress wire and die bonds and help eliminate marginal devices. It also ensures an optimum plastic seal to enhance moisture resistance. Hermetic devices are baked to ensure the elimination of any remaining cavity moisture.

TEMPERATURE CYCLING

Using MIL-STD-883 Method 1010.1 Condition C devices are cycled from cold to hot temperatures imposing a very severe stress which weakens loose bonds and package seals without degrading good devices. A loosened bond is later detected during 100% electrical tests.

SEAL TESTS

Hermetic package seal integrity is ensured by 100% gross leak testing.

100% ELECTRICAL TEST

Every device is tested for functional and AC/DC parameters at high temperature with guard bands to assure performance to data sheet limits.

BURN IN (SUPR II LEVEL B OPTION)

Devices are burned in for 21 hours at 155°C maximum junction temperature.

SYMBOL

Devices are marked with the Signetics logo, device number and date code or custom symbol per individual specification requirements.

VISUAL

All products are 100% visually inspected per the requirements specified in Signetics or customer documents.

100% PRODUCTION ELECTRICAL TESTING

Every device is tested for functional and AC/DC parameters at 25°C with guard bands to assure performance to data sheet limits.

FINAL QUALITY ASSURANCE GATE

The final QA inspection step guarantees that the specified mechanical and electrical AQL's have been met. Every shipment is sealed and identified by QA personnel.

Figure 4. Application Specific Products Programmable Logic Process Flow

Quality and Reliability

As time goes on the drive for a product line that has Zero Defects will grow in intensity. These efforts will provide both Signetics and our customers with the ability to achieve the mutual goal of improved product quality.

The Application Specific Quality Assurance department has monitored PPM progress, which can be seen in Figure 5. We are pleased with the progress that has been made, and expect to achieve even more impressive results as the procedures for accomplishing these tasks are fine tuned.

The real measure of any quality improvement program is the result that our customers see. The meaning of *Quality* is more than just working circuits. It means commitment to *On Time Delivery* at the *Right Place* of the *Right Quantity* of the *Right Product* at the *Agreed Upon Price.*



Figure 5. Programmable Logic AOQ (Average Outgoing Quality)

Alphanumeric Index

Application Specific Products

AN7		Single Chip Multiprocessor Arbiter	9-3
AN8		Introduction To Signetics Programmable Logic	9-15
AN10		4-Bit Binary-To-7 Segment Decoder	9-27
AN11		PLD Programmable Retriggerable One-Shot	9-51
AN12		Low Cost Programmer For PLD 20-Pin Series	9-55
AN13		Oscillator With PLS159	9-71
AN14		Latches & Flip-Flops With PLS153	9-76
AN15		PLS159 Primer	9-89
AN16		PLS159 As Modulo Counters	9-100
AN17		Electronic Combination Lock	9-107
AN18		Schmitt Trigger Using PLS153 and PLS159	9-110
AN19		Electronic Dice	9-118
AN20		Single Pin Debouncer Using 82S153/159	9-122
AN21		9-Bit Parity Generator/Checker With 82S153/153A	9-125
AN22		PLS151 Toolkit	9-131
AN23		PLS168/168A Primer	9-139
AN24		PLS173 As A 10-Bit Comparator, 74LS460	9-152
AN25		A Simple Entry/Exit Meeting Device (PLS157)	9-158
AN26		PLHS18P8A Primer	9-164
AN27		PLHS473 Primer	9-172
AN28		High-Speed 12-Bit Tracking A/D Converter Using PLS179	9-180
AN29		PLHS501 Programmable Macro Logic Primer	9-191
PLC473	Series 24	Erasable-Programmable Logic Array (20 × 24 × 11)	5-91
PLHS153	Series 20	Field-Programmable Logic Array (18 × 42 × 10)	4-21
PLHS473	Series 24	Field-Programmable Logic Array (20 × 24 × 11)	5-85
PLHS501	Series 52	Programmable Macro Logic Random Logic Unit (32 × 72 × 24)	3-9
PLHS502	Series 52	Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24)	3-19
PLHS18P8A	Series 20	Programmable AND Array Logic (18 × 72 × 8)	4-67
PLMC153	Series 20	Mask-Programmable Logic Array (18 × 42 × 10)	3-3
PLS100/PLS101	Series 28	Field-Programmable Logic Array (16 × 48 × 8)	6-3
PLS103	Series 28	Field-Programmable Gate Array (16 × 9 × 9)	6-10
PLS105	Series 28	Field-Programmable Logic Sequencer (16 × 48 × 8)	6-16
PLS105A	Series 28	Field-Programmable Logic Sequencer (16 × 48 × 8)	6-27
PLS151	Series 20	Field-Programmable Gate Array (18 × 15 × 12)	4-3
PLS153	Series 20	Field-Programmable Logic Array (18 × 42 × 10)	4-9
PLS153A	Series 20	Field-Programmable Logic Array (18 × 42 × 10)	4-15
PLS155	Series 20	Field-Programmable Logic Sequencer (16 × 45 × 12)	4-27
PLS157	Series 20	Field-Programmable Logic Sequencer (16 × 45 × 12)	4-37
PLS159	Series 20	Field-Programmable Logic Sequencer (16 × 45 × 12)	4-47
PLS159A	Series 20	Field-Programmable Logic Sequencer (16 × 45 × 12)	4-57
PLS161	Series 24	Field-Programmable Logic Array (12 × 48 × 8)	5-3
PLS162	Series 24	Field-Programmable Address Decoder (16 × 5)	5-9
PLS163	Series 24	Field-Programmable Address Decoder (12 × 9)	5-15
PLS167	Series 24	Field-Programmable Logic Sequencer (14 × 48 × 6)	5-21
PLS167A	Series 24	Field-Programmable Logic Sequencer; Enhanced Speed (14 × 48 × 6)	5-33
PLS168	Series 24	Field-Programmable Logic Sequencer (12 × 48 × 8)	5-45
PLS168A	Series 24	Field-Programmable Logic Sequencer; Enhanced Speed (12 × 48 × 8)	5-57
PLS173	Series 24	Field-Programmable Logic Array (22 × 42 × 10)	5-69
PLS179	Series 24	Field-Programmable Logic Sequencer (20 × 45 × 12)	5-75
PLUS153	Series 20	Field-Programmable Logic Array (18 × 42 × 10)	3-5
PLUS173	Series 24	Field-Programmable Logic Array (22 × 42 × 10)	3-7
PLUS405A	Series 28	Field-Programmable Logic Sequencer (16 × 64 × 8)	6-38

Selection Guide

Application Specific Products

SIGNETICS PN	ARCHITECTURE	PACKAGE	TOTAL INPUTS (# DEDICATED)	PRODUCT TERMS	INTERNAL STATE REGISTERS	OUTPUTS	T_{PD}	I_{CC}
						C, I/O, R, RI/O	(Typical Values)^{1,2}	
	FPGA							
PLS103	16 × 9 × 9	28 Pin	16	9	0	9 C	20ns	120mA
PLS151	18 × 15 × 12	20 Pin	18 (6)	15	0	12 I/O	15ns	130mA
	FPAD							
PLS162	16 × 5	24 Pin	16	5	0	5 C	20ns	120mA
PLS163	12 × 9	24 Pin	12	9	0	9 C	20ns	120mA
	FPLA							
PLS100	16 × 48 × 8	28 Pin	16	48	0	8 C	35ns	120mA
PLS153	18 × 42 × 10	20 Pin	18 (8)	42	0	10 I/O	30ns	130mA
PLS153A	18 × 42 × 10	20 Pin	18 (8)	42	0	10 I/O	20ns	130mA
PLHS153**	18 × 42 × 10	20 Pin	18 (8)	42	0	10 I/O	15ns	150mA
PLUS153**	18 × 42 × 10	20 Pin	18 (8)	42	0	10 I/O	9ns	175mA
PLC153**	18 × 42 × 10	20 Pin	18 (8)	42	0	10 I/O	35ns	25mA
PLS161	12 × 48 × 8	24 Pin	12	48	0	8 C	35ns	120mA
PLS173	22 × 42 × 10	24 Pin	22 (12)	42	0	10 I/O	20ns	150mA
PLC173**	22 × 42 × 10	24 Pin	22 (12)	42	0	10 I/O	35ns	25mA
PLUS173**	22 × 42 × 10	24 Pin	22 (12)	42	0	10 I/O	9ns	175mA
PLHS473	20 × 24 × 11	24 Pin	20 (11)	24	0	2 C & 9 I/O	15ns	140mA
PLC473**	20 × 24 × 11	24 Pin	20 (11)	24	0	2 C & 9 I/O	30ns	25mA
PLHS18P8A	18 × 72 × 8	20 Pin	18 (10)	72	0	8 I/O	15ns	120mA
	FPLS							
PLS105	16 × 48 × 8	28 Pin	16	48	6	8 R	60ns	120mA
PLS105A	16 × 48 × 8	28 Pin	16	48	6	8 R	45ns	120mA
PLC105**	16 × 48 × 8	28 Pin	16	48	6	8 R	50ns	40mA
PLUS405**	16 × 64 × 8	28 Pin	16	64	8	8 R	15ns	160mA
PLS155	16 × 45 × 12	20 Pin	16 (4)	45	4*	8 I/O & 4 R I/O	55ns	150mA
PLS157	16 × 45 × 12	20 Pin	16 (4)	45	6*	6 I/O & 6 R I/O	55ns	150mA
PLS159	16 × 45 × 12	20 Pin	16 (4)	45	8*	4 I/O & 8 R I/O	55ns	150mA
PLS167	14 × 48 × 6	24 Pin	14	48	6 plus 2*	6 R	60ns	120mA
PLS167A	14 × 48 × 6	24 Pin	14	48	6 plus 2*	6 R	45ns	120mA
PLS168	12 × 48 × 8	24 Pin	12	48	6 plus 4*	8 R	60ns	120mA
PLS168A	12 × 48 × 8	24 Pin	12	48	6 plus 4*	8 R	45ns	120mA
PLS179	20 × 45 × 12	24 Pin	20 (8)	45	8*	4 I/O & 8 R I/O	45ns	145mA
	FPML							
PLHS501	32 × 72 × 24	52 Pin	32 (24)	72	0	16 C and 8 I/O	20ns	250mA
PLHS502	32 × 64 × 24	52 Pin	32 (24)	64	16	16 C or R and 8 C or R I/O	15/30ns	250mA

OUTPUTS:

C = Combinatorial output

R = Registered output

I/O = Combinatorial I/O

R I/O = Registered I/O

* State registers shared with output registers

** Under development

NOTES:

1. $T_{PD} = T_{IS} + T_{CKO}$ for registered devices
2. For worst case specifications refer to data sheets for individual product.

Ordering Information

Application Specific Products

Signetics Programmable Logic Devices may be ordered by contacting either the local Signetics sales office, Signetics representatives or authorized distributors. A complete listing is located in the back of this manual.

Table 1 provides part number definition for Signetics PLD's. The Signetics part number system allows complete ordering information to be specified in the part number. The part number and product description is located on each data sheet.

Military versions of these commercial products may be ordered. Please refer to the military products data manual for complete ordering information.

Table 1. New Signetics PLD Part Numbering System



PL – Indicator for Signetics Programmable Logic

(XX) – Process Indicator
- S – Bipolar Junction Isolated Schottky – Nichrome fuses
- M – Mask Programmable
- C – CMOS – EPROM cells
- HS – High Speed Bipolar Oxide Isolated – Vertical Fuse
- US – High Speed Bipolar Oxide Isolated – Lateral Fuse

(YYYY) – Basic Part Number (3 or 4 characters) (e.g. 100, 105, 153, 168, 173, 18P8, 151)

(Z) – Performance Indicator (may be blank, A, B, C etc. to designate speed variations in basic part.)

(P) – Package Designator
- F – 20-, 24-, 28-pin CERDIP DIP
- N – 20-, 24-, 28-pin Plastic DIP
- A – 20-, 28-lead Plastic Leaded Chip Carrier
- FA – 24-, 28-pin CERDIP DIP With Quartz Window

Signetics

Application Specific Products

Note To Users Of 82SXXX Part Numbering System

Signetics has changed its part numbering system for Programmable Logic Products. The change is simple and straightforward. Simply replace the old temperature code and ''82'' Bipolar Memory designator with ''PL.'' This change in part numbering has been done to create a unique, identifiable image for Signetics Programmable Logic Products. As we continue to introduce PLD's with new features, processes, and fusing technology, the new system will allow us to better describe these products through the product part number. In addition, more critical information can be placed on the device itself even when plastic leaded chip carriers are used. The new part number system does not indicate any change in process or technology has occurred. The only thing changing is the nomenclature.

We sincerely hope this necessary change causes no inconveniences to our many customers. Thank you for your loyalty.

PART NUMBERING EXAMPLES

OLD PART NUMBER	NEW PART NUMBER	DESCRIPTION
N82S100N	PLS100N	Signetics Programmable Logic Field Programmable Logic Array (FPLA) Bipolar Schottky Process – Nichrome Fuses – 28-Lead Dual-In-Line Package.
N82S105AA	PLS105AA	Signetics Programmable Logic Field Programmable Logic Sequencer (FPLS) Bipolar Schottky Process – Nichrome Fuses – High Speed Option – 28-Lead Plastic Leaded Chip Carrier.
N/A	PLC473FA	Signetics Programmable Logic Field Programmable Logic Array (FPLA) CMOS – UV Erasable Fuses – 24-Lead Cerdip Dual-In-Line Package with quartz window.
N/A	PLMC153F	Signetics Programmable Logic Programmable Logic Array CMOS – Mask Programmable – 20-Lead Cerdip Dual-In-Line Package.
N/A	PLHS18P8AA	Signetics Programmable Logic Field Programmable Array Oxide Isolated, Bipolar-Vertical Fuses – High Speed Option – 20-Pin Plastic Leaded Chip Carrier.

This change affects **commercial product only.**

Signetics

Section 2
Introduction

Application Specific Products

INDEX

Section 2 – Introduction

What is Signetics' Programmable Logic 2-3
Programming Information 2-48

Introduction

Signetics Programmable Logic

WHAT IS PROGRAMMABLE LOGIC

In 1975, Signetics Corporation developed a new product family by combining its expertise in semi-custom gate array products and fuse-link Programmable Read Only Memories (PROMs). Out of this marriage came Signetics Programmable Logic Family. The PLS100 Field-Programmable Logic Array (FPLA) was the first member of this family. The FPLA was an important industry first in two ways. First, the AND/OR/INVERT architecture allowed the custom implementations of Sum of Product logic equations. Second, the three-level fusing allows complete flexibility in the use of this device family. All logic interconnections from input to output are programmable. Development of this family did not stop with the PLS100. In 1977, the PLS103 Field-Programmable Gate Array (FPGA) and the PLS107 Field-Programmable ROM Patch (FPRP) were introduced.

The PLS105 Field-Programmable Logic Sequencer (FPLS) was announced in 1979. This device represents a significant step forward for PLD. The FPLS is a fully-implemented Mealy State Machine on a chip. Incorporated into its architecture are 48 P-terms, an 8-bit Output Register, and a 6-bit internal State Register. Reference Figure 1.

The FPLS can synchronously perform sequential routines at 20MHz. All of these products are now known as the Signetics PLD Series 28 Programmable Logic Family.

Signetics' next innovation in this area was the Series 20 Programmable Logic Family. All members of this family are assembled in 20-pin packages. While reducing the number of pins in this family, Signetics has utilized controlled I/O in order to maintain the utility of the Series 20. Appropriate control terms have been included to allow active control of pin direction. Reference Figure 2.

The latest addition to the Signetics Programmable Logic families is the Series 24 devices. The PLS161 FPLA and the PLS167 FPLS are 24-pin devices comparable to the 28-pin PLS100 and PLS105 respectively. These devices have been followed by the PLS162/PLS163 Field-Programmable Address Decoder and the PLS168 FPLS.



NOTE:
I, P, C, N, F and P/E are user-programmable connections.

Figure 1. FPLS

Table 1. PLD Product Family

20-PIN, SERIES 20		
PART NUMBER	**TYPE**	**CONFIGURATION**
PLS151	FPGA	18-Input/12-Output
PLS153/153A/PLHS153	FPLA	18-Input/10-Output – 42-Term
PLS155-159	FPLS	16-Input/12-Output – 45-Term
PLS155	FPLS	4 Registered Outputs
PLS157	FPLS	6 Registered Outputs
PLS159	FPLS	8 Registered Outputs
PLHS18P8A	FPAA	18-Input/10-Output – 72-Term
24-PIN, SERIES 24		
PLS161	FPLA	12-Input/8-Output – 48-Term
PLS162	FPGA	16-Input/5-Output
PLS163	FPGA	12-Input/9-Output
PLS167	FPLS	14-Input/6-Output – 48-Term
		8-Bit State Registers
		6-Output Registers
PLS168	FPLS	12-Input/8-Output – 48-Term
		10-Bit State Registers
		8-Output Registers
PLS173/PLUS173	FPLA	22-Input/10-Output – 42-Term
PLS179	FPLS	16-Input/12-Output – 42-Term
		8-Bit State and Output Registers
PLHS473/PLC473	FPLA	20-Inputs/11-Output – 24-Term
28-PIN, SERIES 28		
PLS100/101	FPLA	16-Inputs/8-Output – 48-Term
PLS103	FPGA	16-Inputs/9-Output
PLS105/105A/PLC105	FPLS	16-Inputs/8-Output – 48-Term
		6-Bit State Register
		8-Output Registers
PLUS405	FPLS	16-Inputs/8-Outputs – 64-Terms
		8-Bit State and Output Registers



Figure 2. PLS153 20-Pin Functional Diagram

Signetics Programmable Logic

Introduction



7450 2 × 2 × 2 Fixed Interconnections Dual, 2-Wide, 2-Input, AND/OR/INVERT



PLS100 16 × 48 × 8 Octal, 48-Wide, 16-Input, AND/OR/INVERT

Table 2. Gate Replacement (All Terms Used)

	Gates	I.C.s
Each P-Term = 2 8-Input AND Gates & 1 2-Input AND Gate =	144	108
OR Matrix = 16 4-Input OR Gates =	128	32
	272	140

Table 3. Typical Application

4 Variables/P-Term	40 Gates
4 P-Terms/Output	15-20 I.C.s

PRODUCT DESCRIPTION

While all PLD devices are architecturally similar, the Field-Programmable Logic Array is most representative of the concepts involved. The FPLA is an AND/OR/INVERT device, with all internal interconnections programmable via fuse links. If we compare the PLS100 FPLS to the familiar 7450 AOI gate, the similarity of function becomes apparent.

Package-Gate Replacement Potential

All Signetics PLD devices are capable of replacing multiple discrete logic devices. The number of packages is dependent on the application and the device used.

If all product terms and inputs on the PLS100 are utilized, a total of 272 gates and 140 I.C.s can theoretically be replaced. (See Table 2.) Since the PLS100 is made up of logic structures which are not available as commercial logic devices, such as 32 input AND gates and 48 input OR gates, these numbers are based on breakdowns of these high complexity logic structures into structures which are available as discrete logic.

The typical application does not fully utilize the FPLA, however. We can assume that the typical application is as defined in Table 3.

The replacement of 15-20 I.C.s with one PLS100 is not unusual.

PLD ECONOMICS

The reason any product line exists is because it solves a problem in a cost-effective manner.

PLD is no different in this respect. Let's assume that one PLS100 is replacing only 10 TTL logic packages.

If we assume that the average selling price of an SSI level device is \$0.25, then we have a basis for comparison.

10 I.C.s @ 0.35 = \$3.50
1 PLS100 FPLA = \$7.00

Considering piece-part cost alone does not fare well for the PLS100 FPLA. **But**, part cost is one of the smaller costs in systems manufacturing. Let's next consider PC board costs.

PC BOARD

The purchase price of a PCB is calculated on a per square inch basis. Typical costs at the 5K level are \$0.23/in^2, the cost for LS is 1.2in^2 = \$0.23/in^2 = \$0.28. For a 28-pin FPLA device, the packing density is 1-PLS100 per 2.5in^2, giving a cost of 2.5in^2 × \$0.23/in^2 = \$0.58.

PCB FABRICATION

Now let's consider the cost of building the board. The primary cost for PCB fabrication is parts preparation and stuffing.

Estimates by PCB manufacturers indicate a nominal cost of \$0.14 per device for LS TTL and \$0.16 for 28-pin FPLA. There is also a basic cost of \$0.02 per in^2 for handling, soldering, and inspecting.

The cost of incoming inspection and inventory/usage must also be considered in any fair comparison.

INCOMING INSPECTION

The cost of incoming inspection can be calculated on a per-pin basis. Assuming an equal mix of 14- and 16-pin SSI parts and a testing cost of \$0.01 per pin, the LS TTL cost is \$0.15 per I.C. The corresponding cost for the PLS100 would be \$0.01 × 28 or \$0.28 total.

COMPONENT INVENTORY/ USAGE

The inventory cost for LS TTL parts is dominated by inventory maintenance, while the LSI type parts, the piece price dominates. Assuming a 2% usage rate due to parts breakage, burnout, etc., in the manufacturing process, the parts cost for LS TTL is 2% × \$0.25 = \$0.005. Adding \$0.02 per device for inventory maintenance, the total LS cost \$0.03. For FPLA, 2% = \$7.00± \$0.02 = \$0.16.

Consideration must also be given to testing the completed PCB and Rework costs.

PCB TESTING

Testing costs are generally figured on a PCB basis and are usually go-no-go tests using a "bed of nails". For this comparison, assume a PCB of 5" × 7". The cost for testing the completed PCB is estimated to be \$3.60 for 20 I.C.s. This breaks down as \$0.18 per LS TTL device or about \$0.45 per FPLA device.

PCB REWORK

The main causes of rework are poorly plated holes, solder bridges, and parts inserted incorrectly. The "bed of nails" test can usually detect all of the faults. Rework costs about 50% of test costs. The result is \$1.80 per PCB, or \$0.09 per device for LS TTL and \$0.18 for the 28-pin FPLA.

System manufacturing costs are harder to define. For this comparison we estimated \$0.28 for each LS device and about \$0.65 for the FPLA. These costs include backplane wiring, final system assembly and test costs.

Now using these figures, the comparison in Table 4 can be made.

Table 4. Cost Analysis

	LS TTL	**FPLA**
IC COMPONENTS	.35	7.00
PCB MANUFACTURING		
Incoming Inspection	.15	.28
Component Inventory/Usage	.03	.16
PC Board	.28	.58
Fabrication	.14	.16
Test	.18	.45
Rework	.09	.18
ASSEMBLY LABOR	.28	.65
COST PER COMPONENT	1.50	9.46
NUMBER OF COMPONENTS	× 10	× 1
TOTAL	15.00	9.46

CONCLUSION:
THE FPLA is a 37% savings over the LS TTL DESIGN.

PLD LOGIC SYNTHESIS

28-PIN

PLD is capable of Logic Synthesis. No intermediate step is required to implement Boolean Logic Equations with PLD. Each term in each equation simply becomes a direct entry into the Logic Program Table. The following example illustrates this straightforward concept:

$X_0 = AB + \overline{C}D + B\overline{D}$

$\overline{X}_1 = \overline{A}B + \overline{C}D + EFG$



P-Terms
$P_0 = AB$
$P_1 = \overline{C}D$
$P_2 = B\overline{D}$
$P_3 = \overline{A}B$
$P_4 = EFG$

$X_0 = P_0 + P_1 + P_2$
$\overline{X}_1 = P_3 + P_1 + P_4$

	AND																POLARITY							
	INPUT(I_m)																						L	H
																	OR							
																	OUTPUT F_P							
TERM	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0	—	—	—	—	—	—	—	—	—	H	H	—	—	—	—	—							•	A
1	—	—	—	—	—	—	—	—	—	—	—	L	H	—	—	—							A	A
2	—	—	—	—	—	—	—	—	—	—	H	—	L	—	—	—							•	A
3	—	—	—	—	—	—	—	—	—	L	H	—	—	—	—	—							A	•
4	—	—	—	—	—	—	—	—	—	—	—	—	—	H	H	H							A	•
44																								
45																								
46																								
47																								
PIN NO.	20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9	10	11	12	13	15	16	17	18
VARIABLE NAME										A	B	C	D	E	F	G							X_1	X_0

TB01910S

Figure 3. Field-Programmable Logic Array (16 × 48 × 8) PLS100/PLS101


A
B
C
D
D
X_0
$X_0 = AB + \overline{C}D + B\overline{D}$
A
B
C
D
E
F
G
X_1
$\overline{X}_1 = \overline{A}B + \overline{C}D + EFG$

LD02471S

Figure 4. Equivalent Fixed Logic Diagram

In the previous example, the two Boolean Logic equations were broken into Product terms. Each P-term was then programmed into the P-term section of the PLS100 FPLA Program Table. This was accomplished in the following manner:

Step 1

Select which input pins $I_0 - I_{15}$ will correspond to the input variables. In this case A – G are the input variable names. I_6 through I_0 were selected to accept inputs A – G respectively.



AND																
TERM	INPUT(I_m) 15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0																
1																
2																
3																
4																
44																
45																
46																
47																
PIN NO.	20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9
VARIABLE NAME										A	B	C	D	E	F	G

POLARITY / OR OUTPUT F_P							
7	6	5	4	3	2	1	0
10	11	12	13	15	16	17	18

L H
TB01900S

Figure 5

Step 2

Transfer the Boolean Terms to the FPLA Program Table. This is done simply by defining each term and entering it on the Program Table.

e.g., $P_0 = AB$

This P-term translates to the Program Table by selecting $A = I_6 = H$ and $B = I_5 = H$ and entering the information in the appropriate column.

$P_1 = \overline{C}D$

This term is defined by selecting $C = I_4 = L$ and $D = I_3 = H$, and entering the data into the Program Table. Continue this operation until all P-terms are entered into the Program Table.



AND																
TERM	INPUT(I_m) 15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	—	—	—	—	—	—	—	—	—	H	H	—	—	—	—	—
1	—	—	—	—	—	—	—	—	—	—	—	L	H	—	—	—
2	—	—	—	—	—	—	—	—	—	—	H	—	L	—	—	—
3	—	—	—	—	—	—	—	—	—	L	H	—	—	—	—	—
4	—	—	—	—	—	—	—	—	—	—	—	—	—	H	H	H
44																
45																
46																
47																
PIN NO.	20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9
VARIABLE NAME										A	B	C	D	E	F	G

POLARITY / OR OUTPUT F_P							
7	6	5	4	3	2	1	0
10	11	12	13	15	16	17	18

L H
TB01890S

Figure 6

Step 3

Select which output pins correspond to each output function. In this case F_0 = Pin 18 = X_0, and F_1 = Pin 17 = X_1.



	AND INPUT(I_m)																POLARITY OR OUTPUT F_P							
TERM	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0	—	—	—	—	—	—	—	—	—	H	H	—	—	—	—	—								
1	—	—	—	—	—	—	—	—	—	—	—	L	H	—	—	—								
2	—	—	—	—	—	—	—	—	—	—	H	—	L	—	—	—								
3	—	—	—	—	—	—	—	—	—	L	H	—	—	—	—	—								
4	—	—	—	—	—	—	—	—	—	—	—	—	—	H	H	H								
44																								
45																								
46																								
47																								
PIN NO.	20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9	10	11	12	13	15	16	17	18
VARIABLE NAME										A	B	C	D	E	F	G							X_1	X_0

TB01882S

Figure 7

Step 4

Select the Output Active Level desired for each Output Function. For X_0 the active level is high for a positive logic expression of this equation. Therefore, it is only necessary to place an (H) in the Active Level box above Output Function 0, (F_0). Conversely, X_1 can be expressed as $\overline{X}_1$ by placing an (L) in the Active Level box above Output Function 1, (F_1).



	AND INPUT(I_m)																POLARITY OR OUTPUT F_P							
																							L	H
TERM	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0	—	—	—	—	—	—	—	—	—	H	H	—	—	—	—	—								
1	—	—	—	—	—	—	—	—	—	—	—	L	H	—	—	—								
2	—	—	—	—	—	—	—	—	—	—	H	—	L	—	—	—								
3	—	—	—	—	—	—	—	—	—	L	H	—	—	—	—	—								
4	—	—	—	—	—	—	—	—	—	—	—	—	—	H	H	H								
44																								
45																								
46																								
47																								
PIN NO.	20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9	10	11	12	13	15	16	17	18
VARIABLE NAME										A	B	C	D	E	F	G							X_1	X_0

TB01870S

Figure 8

Step 5

Select the P-Terms you wish to make active for each Output Function. In this case $X_0 = P_0 + P_1 + P_2$, so an A has been placed in the intersection box for P_0 and X_0, P_1 and X_0 and P_2 and X_0.

Terms which are not active for a given output are made inactive by placing a (●) in the box under that P-term. Leave all unused P-terms unprogrammed.

Continue this operation until all outputs have been defined in the Program Table.

Step 6

Enter the data into a Signetics approved programmer. The input format is identical to the Signetics Program Table. You specify the P-terms, Output Active Level, and which P-terms are active for each output exactly the way it appears on the Program Table.



$X_0 = P_0 + P_1 + P_2$

$\overline{X}_1 = P_3 + P_1 + P_4$

	AND																POLARITY							
	INPUT(I_m)																						L	H
																	OR							
																	OUTPUT F_P							
TERM	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0	—	—	—	—	—	—	—	—	—	H	H	—	—	—	—	—							•	A
1	—	—	—	—	—	—	—	—	—	—	—	L	H	—	—	—							A	A
2	—	—	—	—	—	—	—	—	—	—	H	—	L	—	—	—							•	A
3	—	—	—	—	—	—	—	—	—	L	H	—	—	—	—	—							A	•
4	—	—	—	—	—	—	—	—	—	—	—	—	—	H	H	H							A	•
44																								
45																								
46																								
47																								
PIN NO.	20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9	10	11	12	13	15	16	17	18
VARIABLE NAME										A	B	C	D	E	F	G							X_1	X_0

TB01861S

Figure 9

PLD LOGIC SYNTHESIS

20-PIN

When fewer inputs and outputs are required in a logic design and low cost is most important, the Signetics 20-pin PLD should be considered first choice. The PLS153 is an FPLA with 8 inputs, 10 I/O pins, and 42 product terms. The user can configure the device by defining the direction of the I/O pins. This is easily accomplished by using the direction control terms $D_0 - D_9$ to establish the direction of pins $B_0 - B_9$. The D-terms control the Tri-state buffers found on the outputs of the EX-OR gates. Figures 10 and 11 show how the D-term configures each B_x pin.


P31
P0
D0
D9
I0
I7
S0
S9
X0
X9
CONTROL GATES
TRI-STATE BUFFER
TRI-STATE BUFFER
B9
B0
AF02200S

Figure 10. PLS153 Functional Diagram


P31
P0
D9
I0
I7
(I)
OUTPUT B9
TRI-STATE BUFFER ACTIVE
LD02450S
P31
P0
D9
I0
I7
(O)
INPUT B9
TRI-STATE BUFFER INACTIVE (OPEN)
LD02460S

a. D_9 Active Makes B_9 Appear As An Output With Feedback

b. D_9 Inactive Makes B_9 Appear As An Input

Figure 11

To control each D-term, it is necessary to understand that each control gate is a 36-input AND gate. To make the Tri-state buffer active (B_x pin an output), the output of the control gate must be at logic HIGH (1). This can be accomplished in one of two ways. A HIGH can be forced on all control gate input nodes, or fuses can be programmed. When a fuse is programmed, that control gate input node is internally pulled up to HIGH (1). See Figure 12 and Figure 13.

Programming the fuse permanently places a HIGH (1) on the input to the control gate. The input pin no longer has any effect on that state.


VCC
FUSE INTACT
IH
I
I = HIGH (1)
H
H
CONTROL GATE
TO AND ARRAY
OR-ARRAY
Bx = OUTPUT
TRI-STATE BUFFER
VCC
F
IL
L
IL
I = LOW (0)
L
L
CONTROL GATE
L
TO AND ARRAY
OR-ARRAY
Bx = INPUT
TRI-STATE BUFFER
TC02360S

Figure 12. Input Effect On Control Gates (Fuse Intact)


VCC
FUSE PROGRAMMED
IH
I
I = HIGH (1)
H
H
CONTROL GATE
TO AND ARRAY
OR-ARRAY
Bx = OUTPUT
TRI-STATE BUFFER
TC02370S

Figure 13. Effect On Control Gate If Fuse Is Programmed

DEDICATING B_X PIN DIRECTION

Since each input to the D-terms is true and complement buffered (see Figure 11), when the device is shipped with all fuses intact, all control gates have half of the 36 input lines at logic low (0). The result of this is all Control Gate outputs are low (0) and the Tri-state buffers are inactive. This results in all B_X pins being in the input condition. The resultant device is, therefore, an 18-input, 0-output FPLA. While useful as a bit bucket or Write-Only-Memory (WOM), most applications require at least one output. Clearly, the first task is to determine which of the B_x pins are to be outputs. The next step is to condition the control gate to make the Tri-state buffer for those gates active. To dedicate B_0 and B_1 as outputs, it is necessary to program all fuses to the inputs to Control Gates D_0 and D_1. This internally pulls all inputs to those gates to HIGH (1) permanently. Since all inputs to the Control Gates are HIGH (1), the output is HIGH (1) and the Tri-state buffers for B_0 and B_1 are active. This permanently enables B_0 and B_1 as outputs. Note that even though B_0 and B_1 are outputs, the output data is available to the AND array via the internal feedback (see Figure 11a).

To program this data, the PLS153 Program Table is used as shown in Figure 14.


PROGRAM TABLE ENTRIES
OR
ACTIVE | A
INACTIVE | •
B (0)
CONTROL
HIGH | H
LOW | L
(POL.)
AND
INACTIVE | 0
I, B | H
I, B | L
DON'T CARE | —
I,B(I)
POLARITY
VARIABLE NAME
TB01830S

TERM	AND I 7	6	5	4	3	2	1	0	AND B(I) 9	8	7	6	5	4	3	2	1	0	OR B(0) 9	8	7	6	5	4	3	2	1	0
0																												
1																												
2																												
3																												
4																												
30																												
31																												
D9	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D8	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
PIN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9										

NOTES:

1. The FPLA is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Unused I and B bits in the AND array are normally programmed Don't Care (—).
3. Unused product terms can be left blank.

Figure 14. Dedicating B_0 And B_1 As Outputs And B_2 Through B_9 As Inputs

By placing a (—) Don't Care in each input box you are specifying that the True and Complement fuses are programmed on each Control Gate, thus permanently dedicating the B_0 and B_1 pins as outputs. By placing a (0) in all input boxes for $B_2 - B_9$, you are specifying that both True and Complement fuses are intact. This causes a low (0) to be forced on half of the Control Gate inputs, guaranteeing the output of the Control Gate will be low (0). When the Control Gate outputs are low (0), the Tri-state buffer is inactive and the $B_2 - B_9$ pins are enabled as inputs. All B_x pin directions can be controlled in this manner.

ACTIVE DIRECTION CONTROL

Sometimes it is necessary to be able to actively change the direction of the B_x pins without permanently dedicating them. Some applications which require this include Tri-state bus enable, multi-function decoding, etc. This can easily be done by programming the Control Gate to respond to one or more input pins. It is only necessary to select which I_x and B_x pins will control the pin directions and the active level HIGH (H) or LOW (L) that will be used. The PLS153 Program Table in Figure 15 shows the method of controlling $B_0 - B_9$ with I_7. When I_7 is LOW (L), pins $B_0 - B_9$ are outputs when I_7 is HIGH (H), pins $B_0 - B_9$ are inputs. Note that by programming all other I_x and B_x pins as DON'T CARE (—), they are permanently disconnected from control of B_x pin direction.


PROGRAM TABLE ENTRIES
OR
ACTIVE A
INACTIVE •
B (0)
CONTROL
HIGH H
LOW L
(POL.)
AND
INACTIVE 0
I, B H
I, B L
DON'T CARE —
I,B(I)
POLARITY
VARIABLE NAME
TB01840S

TERM	AND																		OR									
	I								B(I)										B(0)									
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0
0																												
1																												
2																												
3																												
4																												
30																												
31																												
D9	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D8	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D7	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D6	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D5	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D4	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D3	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D2	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D1	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D0	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
PIN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9										

NOTES:
1. The FPLA is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Unused I and B bits in the AND array are normally programmed Don't Care (—).
3. Unused product terms can be left blank.

Figure 15. Active Control of B_0-B_9 Using I_7 Active Low (L)

The previous 28-pin logic synthesis example (Page 2-5) could be done on the PLS153 as follows:

$$X_0 = AB + \overline{C}D + B\overline{D}$$

$$\overline{X}_1 = \overline{A}B + \overline{C}D + EFG$$

Note that B_0 was used as a CHANGE input. When B_0 is HIGH (H) the outputs appear on B_8 and B_9. When B_0 is LOW (L), the outputs appear on B_6 and B_7. B_1 through B_5 are not used and therefore left unprogrammed.

THE ROLE OF AMAZE (AUTOMATIC MAP AND ZAP ENTRY) IN LOGIC DEVELOPMENT

AMAZE is a software development package which provides the logic designer with a multi-mode data input capability. This software package, which has been developed for both mainframe and microcomputer environments, allows data entry in the program table format previously described, or on one of two equation formats. Both Boolean Logic Equations and State Variable Equations are supported on AMAZE. In addition to the flexible input formats offered, AMAZE also provides full device documentation, and a functional simulator. The simulator features manual and automatic modes. In the automatic mode, the software generates a set of input vectors which can be used as functional test vectors. The manual mode is an interactive procedure which allows the designer to input vectors to the simulator. The AMAZE simulator then responds with the appropriate output vector. In both modes, the simulator uses the functional model generated by the user's input data.

For more information on AMAZE refer to Section 8 of the 1987 Signetics Programmable Logic Data Manual.


PROGRAM TABLE ENTRIES
OR
B(0)
ACTIVE A
INACTIVE •
CONTROL
(POL.)
HIGH H
LOW L
AND
I,B(I)
INACTIVE 0
I, B H
I, B̄ L
DON'T CARE —
POLARITY
TB01850S

	POLARITY									
B(0)	9	8	7	6	5	4	3	2	1	0
	L	H	L	H						

TERM	I 7	I 6	I 5	I 4	I 3	I 2	I 1	I 0	B(I) 9	B(I) 8	B(I) 7	B(I) 6	B(I) 5	B(I) 4	B(I) 3	B(I) 2	B(I) 1	B(I) 0	B(0) 9	B(0) 8	B(0) 7	B(0) 6	B(0) 5	B(0) 4	B(0) 3	B(0) 2	B(0) 1	B(0) 0
0	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	•	A	•	A						
1	—	—	L	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	A	A	A	A						
2	—	H	—	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	•	A	•	A						
3	L	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	A	•	A	•						
4	—	—	—	—	H	H	H	—	—	—	—	—	—	—	—	—	—	—	A	•	A	•						
•																												
30																												
31																												
D9	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D6	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
D0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0										
PIN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9	19	18	17	16	15	14	13	12	11	9
VARIABLE NAME	A	B	C	D	E	F	G											CHANGE	X_1 CHANGE	X_0 CHANGE	X_1	X_0						

Figure 16. PLS153 Example

SEQUENTIAL LOGIC CONSIDERATIONS

The PLS105 and PLS155 – PLS159 represent significant increases in complexity when compared to the combinatorial logic devices previously discussed. By combining the AND/OR combinatorial logic with clocked output flip-flops and appropriate feedback, Signetics has created the first family of totally flexible sequential logic machines.



Figure 17. Basic Architecture Of PLS105 FPLS. I, P, N, And F Are Multi-line Paths Denoting Groups Of Binary Variables Programmed By The User.



Figure 18. Typical State Diagram. I_{1-3} Are Jump Conditions Which Must Be Satisfied Before Any Transitions Take Place. F_r Are Changes In Output Triggered By I_m, And Stored In The Output Register. State Transitions a → b and c → d Involve No Output Change.



Figure 19. Typical State Transition Between Any Two States Of Figure 18. The Arrow Connecting The Two States Gives Rise To A Transition Term T_n. I Is The Jump Condition.

The PLS105 FPLS (Field-Programmable Logic Sequencer) is an example of a high-order machine whose applications are manifold. Application areas for this device include high-speed data controllers, microprocessor and minicomputer bus arbitration, industrial controls, timing generation, multi-function counters and shift registers, and microprocessor-driven microcontrollers. The PLS105 is fully capable of performing fast sequential operations in relatively low-speed processor systems. By placing repetitive sequential operations on the PLS105, processor overhead is reduced. Each PLS105 can be viewed as a high-speed, 48-state subroutine.

The following pages summarize the PLS105 architecture and features.

FPLS Architecture

The PLS105 Logic Sequencer is a programmable state machine of the Mealy type, in which the output is a function of the present state and the present input.

With the FPLS a user can program any logic sequence expressed as a series of jumps between stable states, triggered by a valid input condition (I) at clock time (t). All stable states are arbitrarily assigned and stored in the State Register. The logic output of the machine is also programmable, and is stored in the Output Register.

Clocked Sequence

A synchronous logic sequence can be represented as a group of circles interconnected with arrows. The circles represent stable states, labeled with an arbitrary numerical code (binary, hex, etc.) corresponding to discrete states of a suitable register. The arrows represent state transitions, labeled with symbols denoting the jump condition and the required **change** in output. The number of states in the sequence depends on the length and complexity of the desired algorithm.



Figure 20. Typical State Jump From State (0) To State (1), If Inputs A = B = "1". The Jump Also Forces F = "1", As Required.



Figure 21. Simplified Logic Diagram Of PLS105 FPLS

State Jumps

The state from which a jump originates is referred to as the Present state (P), and the state to which a jump terminates is defined as the Next state (N). A state jump always causes a change in state, but may or may not cause a change in machine output (F).

State jumps can occur only via "transition terms" T_n. These are logical AND functions of the clock (t), the Present state (P), and a valid input (I). Since the clock is actually applied to the State Register, $T_n = I \bullet P$. When T_n is "true", a control signal is generated and used at clock time (t) to force the contents of the State Register from (P) to (N), and to change the contents of the Output Register (if necessary). The simple state jump in Figure 20, involving 2 inputs, 1 state bit, and 1 output bit, illustrates the equivalence of discrete and programmable logic implementations.

FPLS Logic Structure

The FPLS consists of programmable AND and OR gate arrays which control the Set and Reset inputs of a State Register, as well as monitor its output via an internal feedback path. The arrays also control an independent Output Register, added to store output commands generated during state transitions, and to hold the output constant during state sequences involving no output changes. If desired, any number of bits of the Output Register can be used to extend the width of the State Register, via external feedback.



Figure 22. Typical AND Gate Coupled To (I) And (P) Inputs. If At Least One Link Pair Remains Intact, T_n Is Unconditionally Forced Low.



Figure 23. Choice Of Input Polarity Coupling To A Typical AND Gate. With Both Links Open, (I) Is Logically Don't Care.



Figure 24. Typical Transition Terms Involving Arbitrary Inputs And State Variables. All Remaining Gate Inputs Are Programmed Don't Care. Note That T_2 Output Is State Independent.

Input Buffers

16 external inputs (I_m) and 6 internal inputs (P_s), fed back from the State Register, are combined in the AND array through two sets of True/Complement (T/C) buffers. There are a total of 22 T/C buffers, all connected to multi-input AND gates via fusible links which are initially intact.

Selective fusing of these links allows coupling either True, Complement, or Don't Care values of (I_m) and (P_s).

"AND" Array

State jumps and output changes are triggered at clock time by valid transition terms T_n. These are logical AND functions of the present state (P) and the present input (I).

The FPLS AND Array contains a total of 48 AND gates. Each gate has 45 inputs — 44 connected to 22 T/C input buffers, and 1 dedicated to the Complement Array. The outputs of all AND gates are propagated through the OR Array, and used at clock time (t) to force the contents of the State Register from (P) to (N). They are also used to control the Output Register, so that the FPLS 8-bit output F_r is a function of the inputs and present state.



Figure 25. Typical OR Array Gating Of Transition Terms $T_{1,2,3}$ Controlling Arbitrary State And Output Register Stages.



Figure 26. The COMPLEMENT Array Is Logically Constructed From A 48-Input Programmable OR Gate Followed By An Inverter. All AND Terms Coupled To The OR Gate Are Complemented At The Inverter Output, And Can Be Fed Back As Inputs To The AND Array.

"OR" Array

In general, a clocked sequence will consist of several stable states and transitions, as determined by the complexity of the desired algorithm. All state and output changes in the state diagram imply changes in the contents of State and Output Registers.

Thus, each flip-flop in both registers may need to be conditionally set or reset several times with T_n commands. This is accomplished by selectively ORing through a programmable OR Array all AND gate outputs T_n necessary to activate the proper flip-flop control inputs.

The FPLS OR Array consists of 14 pairs of OR gates, controlling the S/R inputs of 14 State and Output Register stages, and a single OR gate for the Complement Array. All gates have 48 inputs for connecting to all 48 AND gates.

Complement Array

The COMPLEMENT Array provides an asynchronous feedback path from the OR Array back to the AND Array.

This structure enables the FPLS to perform both direct and complement sequential state jumps with a minimum of transition (AND) terms.

Typically direct jumps, such as T_1 and T_2 in Figure 27 require only a single AND gate each.

But a complement jump such as T_3 generally requires many AND gates if implemented as a direct jump. However, by using the Complement Array, the logic requirements for this type of jump can be handled with just one more gate from the AND Array.



DIRECT
$T_1 = P_0X$
$T_2 = P_0Y$

COMPLEMENT
$T_3 = P_0(\bar{X} \cdot \bar{Y}) = P_0(\overline{T_1 + T_2})$

$T_3 = P_0(\overline{P_0X + P_0Y})$
$T_3 = P_0[\overline{P_0(X + Y)}]$
$T_3 = P_0[\overline{P_0} + \overline{(X + Y)}]$
$T_3 = 0 + P_0\overline{(X + Y)}$
$T_3 = P_0(\bar{X} \bullet \bar{Y})$

a. Typical State Sequence **b. Complement Jump**

Figure 27. a. X And Y Specify The Conditional Logic For Direct Jump Transition Terms T_1 And T_2. The Complement Jump Term T_3 Is True Only When Both T_1 and T_2 Are False. b. Note That The Complementary Logic Expression For T_3, $\overline{T_1 + T_2}$, Corresponds Exactly To The Logic Structure Of The Complement Array.

As indicated in Figure 28, the single Complement Array gate may be used for many states of the state diagram. This happens because all transition terms linked to the OR gate include the present state as a part of their conditional logic. In any particular state, only those transition terms which are a function of that state are enabled; all other terms coupled to different states are disabled and do not influence the output of the Complement Array. As a general rule of thumb, the Complement Array can be used as many times as there are states.


1
START
Td1
0
Td2
Tc3
6
2
Td6
3
Tc5
Td4
4
5
AF02150S

a. State Diagram

$T_{d1} = I_0\bar{I}_1P_0$
$T_{d2} = I_2P_0$
$T_{c3} = \overline{(T_{d1} + T_{d2})}P_0 = \overline{(I_0\bar{I}_1 + I_2)}P_0$

$T_{d4} = \bar{I}_2P_3$
$T_{d6} = I_0I_1P_3$
$T_{c5} = \overline{(T_{d4} + T_{d6})}P_3 = \overline{(I_0I_1 + \bar{I}_2)}P_3$

T_{cn} = COMPLEMENT STATE TRANSITION TERM
T_{dn} = DIRECT STATE TRANSITION TERM
P_s = PRESENT STATE

b. Logic Definition


I0
I1
I2
COMPLEMENT ARRAY
Q0 S
R
Q1 S
R
Q2 S
R
Td1
Td2
Tc3
Td4
Td6
Tc5
8 TRANSITION TERMS USED
LD02320S
I0
I1
I2
COMPLEMENT ARRAY
Q0 S
R
Q1 S
R
Q2 S
R
Td1
Td2
Tc3
Td4
Td6
Tc5
6 TRANSITION TERMS USED
LD02310S

c. State Logic Without Using The Complement Array

d. State Logic Using The Complement Array

Figure 28. Logic Reduction With The Complement Array. The Logic State Diagram In (a) Includes Complement Jumps T_{C3} And T_{C5} Defined In (b). When Using The Complement Array, A Savings Of 2 Transition Terms Results, As Shown In (c) And (d).

Table 5. 20-Pin PLD Sequential Family Summary

DEVICE	REGISTERED OUTPUTS	OUTPUT TYPE
PLS155	4-Bit Register	T.S.
PLS157	6-Bit Register	T.S.
PLS159	8-Bit Register	T.S.

PLD-20 SEQUENTIAL DEVICES

The 20-pin PLD family also includes sequential devices. These devices are all similar in architecture. The major difference consists of the number of outputs which are registered.

FEATURES

The PLD-20 sequencers have been designed with a maximum of flexibility in mind. Each element of the architecture contributes to the ease of use the PLD-20 family provides. Each part has the features listed:

- **J/K flip-flop Output Register**
- **Dynamic control of flip-flop type (J/K or D)**
- **Parallel bus load**
- **Asynchronous preset and reset capability**
- **Combinational I/O pins**
- **Programmable enable pins**
- **Output feedback to AND Array available**

OUTPUT REGISTER

The Output Register of the PLD-20 sequential devices are comprised of fully implemented J/K flip-flops. Each flip-flop is positive edge-triggered from a common clock.

In addition, a dynamically controllable "fold-back" buffer between the J and K inputs to the flip-flop allows the designer to change the function of the flip-flop from J/K to D-type under the control of the flip-flop control term (F). A fuse allows the designer to dedicate the flip-flop as a permanent D-type by programming the fuse.

By leaving the fuse intact, the flip-flop control line (F) is maintained as the active mode control. If the output of F is logic Low (0), then the flip-flop is configured as a D-type. If the output of F is a logic High (1), then the flip-flop is configured as a J/K type. Term F is programmed in the same manner as the 32 logic transition terms (T). It is well to note at this time that when the flip-flop is configured as a D-type, the OR-term driving the K input of the flip-flop must not be active.

During all modes of operation, the output register data is fed back to the AND Array. This feedback is used to establish present-state to next-state jumps.



Figure 29

PARALLEL BUS LOADING

The Output Register may be loaded from the bus via the load control term (L). This feature forces the data contained on the F_0 pin into the J/K flip-flop. It operates synchronously with the rising edge of the clock. This feature can be used to preload a state into the machine, or to latch input data into the AND Array.


(LOGIC TERMS)
(CONTROL TERMS)
a
b
a
ā
b
b̄
O̅E̅
Q
Q̄
C̄
C
P
R
L
D
E
S
X
B
J
P
R
Q
(n)
K
CK
M
F
T31
TO
FC
LD02440S

Figure 30

PRESET AND RESET

Asynchronous preset and reset capability has been provided on the PLD-20 sequential devices. This feature is controlled in the AND-Array on the PLS159. However, the preset and reset function on the PLS155 is controlled via the OR Array. The PLS157 preset and reset controls are split between the two arrays. See the individual data sheets for details.


(LOGIC TERMS)
(CONTROL TERMS)
a
b
a
$\overline{a}$
b
$\overline{b}$
Q
$\overline{Q}$
$\overline{C}$
$\overline{OE}$
C
S
X
M
P
R
L
D
E
B
F
J
K
Q
(n)
CK
T_{31}
T_O
F_C
LD02440S

Figure 31

COMBINATIONAL I/O PINS

Each PLD-20 sequential device has a number of combinational pins (B_n) which can be programmed and used exactly as the B pins on the PLS153 FPLA. The direction control term (D) establishes the data flow on these pins. The individual data sheet should be consulted for the quantity and pin number assignment for each device.


(LOGIC TERMS)
(CONTROL TERMS)
a
b
a
$\overline{a}$
b
$\overline{b}$
$\overline{OE}$
Q
$\overline{Q}$
$\overline{C}$
C
S
X
P
R
L
D
E
B
F
M
J
K
P
R
Q
(n)
CK
T_{31}
T_O
F_C
LD02440S

Figure 32

PLA vs. PAL® ARRAYS

The PLA architecture provides the most efficient means of implementing logic. The 28-pin devices, PLS100/101 and PLS103 are unique in their ability to directly implement logic.

They offer the most useable P-terms, the highest number of inputs and outputs, and the most straightforward programming of any logic device in the industry. The following diagrams illustrate the relative ease of programming the flexible PLA structure against the fixed OR Array of the PAL.

The Signetics approach to programmable logic gives the designer the flexibility he needs where he needs it — in the device itself. The combination of totally flexible architecture, more useable product terms, and ease of logic implementation make Signetics Programmable Logic Family the obvious choice.


A^2
UNUSED^1
B
UNUSED^1
C
$O_1 = \overline{A + B + C}$
A^2
UNUSED^1
D
E
F
$O_2 = \overline{A + D + E + F}$
EXTERNAL INVERTER
$O_2 = A + D + E + F$
LD02431S

NOTES:
1. Unused P-terms lost to designer.
2. Common P-term to 2 or more outputs requires 2 or more P-terms; one on each output.
3. External inverter required to change active level of output.
4. 10 P-terms used.

Figure 33. Application Example PAL Approach


4
A
B
C
D
E
F
D_1
D_0
$B_0 = O_1 = \overline{A + B + C}$
$B_1 = \overline{O_2} = A + D + E + F$
2
3
LD02481S

NOTES:
1. All P-terms usable.
2. Common P-terms available to all outputs.
3. Programmable outputs eliminate need for external component.
4. 6 P-terms used.

Figure 34. PLD Approach

---

*PAL is a registered trademark of Monolithic Memories, Inc.

FPLA PLS153/153A	**COMPATIBLE WITH PAL® LOW/MEDIUM COMPLEXITY PRODUCT, i.e., 14H/L4 16H/L2 16LS 10H/LS 16C1, 12H/LS** **ADDITIONAL FEATURES:** **1. PROGRAMMABLE OUTPUT POLARITY** **2. PROGRAMMABLE OR ARRAY** **3. 10 OUTPUTS vs. 8 FOR PAL** **4. 32 PRODUCT TERMS vs. 16 FOR LOW AND MEDIUM PALs**
FPLS PLS155/157/159	**COMPATIBLE WITH PAL REGISTERED TYPES 16R3, 16R5, 16R4, etc.** **ADDITIONAL FEATURES:** **1. PROGRAMMABLE AND/OR, ALSO CONTROLLABLE FLIP FLOPS; AS D, TOGGLE, OR JK**

***PAL is a trademark of Monolithic Memories, Inc.**

Figure 35. PLD-20 Product Comparison

PLD FAMILY SUMMARY

	Field-Programmable Gate Arrays		
PLS103	16 × 9	28-Pin	Tri-state (Combinatorial)
PLS151	18 × 12	20-Pin	Tri-state (Combinatorial)
	Field-Programmable Address Decoders		
PLS162	16 × 5	24-Pin	Tri-state (Combinatorial)
PLS163	12 × 9	24-Pin	Tri-state (Combinatorial)
	Field-Programmable Logic Arrays		
PLS100	16 × 48 × 8	28-Pin	Tri-state (Combinatorial)
PLS101	16 × 48 × 8	28-Pin	Open Collector (Combinatorial)
PLS153/153A/PLHS153	18 × 45 × 10	20-Pin	Tri-state (Combinatorial)
PLS161	12 × 48 × 8	24-Pin	Tri-state (Combinatorial)
PLS173/PLUS173	22 × 45 × 10	24-Pin	Tri-state (Combinatorial)
PLHS473	20 × 24 × 11	24-Pin	Tri-state and Open Collector
PLC473	20 × 24 × 11	24-Pin	Tri-state and Open Collector (CMOS)
PLHS18P8A	18 × 72 × 8	20-Pin	Tri-state (Combinatorial); Fixed OR Array
	Field-Programmable Logic Sequencers		
PLS105/105A	16 × 48 × 8	28-Pin	Tri-state Mealy State Machine
PLS155	16 × 42 × 12	20-Pin	Tri-state 4-Bit Sequencer
PLS157	16 × 42 × 12	20-Pin	Tri-state 6-Bit Sequencer
PLS159/159A	16 × 42 × 12	20-Pin	Tri-state 8-Bit Sequencer
PLS167/167A	14 × 48 × 6	24-Pin	Tri-state Mealy State Machine
PLS168/168A	12 × 48 × 8	24-Pin	Tri-state Mealy State Machine
PLS179	20 × 42 × 8	24-Pin	Tri-state 8-Bit Sequencer
PLUS405A	16 × 64 × 8	28-Pin	Tri-state Mealy State Machine
	Field-Programmable Macro Logic		
PLHS501	32 × 72 × 24	52-Pin	Random Logic Unit
PLHS502	32 × 64 × 24	52-Pin	Registered Logic Unit

FPGA LOGIC DIAGRAM **PLS103**


(LOGIC GATES—G)
I_0 8
I_1 7
I_2 6
I_3 5
I_4 4
I_5 3
I_6 2
I_7 1
I_8 27
I_9 26
I_{10} 25
I_{11} 24
I_{12} 23
I_{13} 22
I_{14} 21
I_{15} 20
8 7 6 5 4 3 2 1 0
X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
$\overline{CE}$ 19
9 10 11 12 13 15 16 17 18
F_8 F_7 F_6 F_5 F_4 F_3 F_2 F_1 F_0
LD01471S

NOTES:
1. All gate inputs when a blown link float to a logic "1".
2. ▨ Programmable connection.

FPGA LOGIC DIAGRAM

PLS151


(LOGIC GATES—G)
(CONTROL GATES)
11 10 9 8 7 6 5 4 3 2 1 0
D2 D1 D0
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
B11 B10 B9 B8 B7 B6 B5 B4 B3 B2 B1 B0
X11 X10 X9 X8 X7 X6 X5 X4 X3 X2 X1 X0
S11 S10 S9 S8 S7 S6 S5 S4 S3 S2 S1 S0
7 B0
8 B1
9 B2
11 B3
12 B4
13 B5
14 B6
15 B7
16 B8
17 B9
18 B10
19 B11
LD02270S

NOTES:
1. All gate inputs with a blown link float to a logic "1".
2. ▨ Programmable connection.

FPAD LOGIC DIAGRAM

PLS162


(LOGIC GATES—G)
I0 8
I1 7
I2 6
I3 5
I4 4
I5 3
I6 2
I7 1
I8 23
I9 22
I10 21
I11 20
I12 19
I13 18
I14 17
I15 16
4
3
2
1
0
X4
X3
X2
X1
X0
CE 15
9 F4
10 F3
11 F2
13 F1
14 F0
LD01240S

NOTE:

1. All gate inputs with a blown link float to a logic "1".
2. ▨ Programmable connection.

FPAD LOGIC DIAGRAM

PLS163


(LOGIC GATES—G)
I_0 6
I_1 5
I_2 4
I_3 3
I_4 2
I_5 1
I_6 23
I_7 22
I_8 21
I_9 20
I_{10} 19
I_{11} 18
8 7 6 5 4 3 2 1 0
X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
$\overline{CE}$ 17
7 8 9 10 11 13 14 15 16
F_8 F_7 F_6 F_5 F_4 F_3 F_2 F_1 F_0
LD01221S

NOTES:
1. All gate inputs with a blown link float to a logic "1".
2. ▨ Programmable connection.

FPLA LOGIC DIAGRAM

PLS100/101


(LOGIC TERMS—P)
I0 9
I1 8
I2 7
I3 6
I4 5
I5 4
I6 3
I7 2
I8 27
I9 26
I10 25
I11 24
I12 23
I13 22
I14 21
I15 20
S0
X0
S1
X1
S2
X2
S3
X3
S4
X4
S5
X5
S6
X6
S7
X7
18 F0
17 F1
16 F2
15 F3
13 F4
12 F5
11 F6
10 F7
19 CE
47 • • • • • • 40 39 • • • • • • 32 31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
LD01450S

NOTES:
1. All AND gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown fuse float to a logic "0".
3. ▨ Programmable connection.

FPLA LOGIC DIAGRAM

PLS153/153A/PLHS153


(LOGIC TERMS—P)
(CONTROL TERMS)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
B_9
S_9 S_8 S_7 S_6 S_5 S_4 S_3 S_2 S_1 S_0
X_9 X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
D_9 D_8 D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
19 B_9
18 B_8
17 B_7
16 B_6
15 B_5
14 B_4
13 B_3
12 B_2
11 B_1
9 B_0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
TB00943S

NOTES:

1. All programmed "AND" gate locations are pulled to a logic "1".
2. All programmed "OR" gate locations are pulled to a logic "0".
3. ▨ Programmable connection.

FPLA LOGIC DIAGRAM

PLS161


(SECTOR)
I_0 7
I_1 6
I_2 5
I_3 4
I_4 3
I_5 2
I_6 23
I_7 22
I_8 21
I_9 20
I_{10} 19
I_{11} 18
S_0 X_0 16 F_0
S_1 X_1 15 F_1
S_2 X_2 14 F_2
S_3 X_3 13 F_3
S_4 X_4 11 F_4
S_5 X_5 10 F_5
S_6 X_6 9 F_6
S_7 X_7 8 F_7
17 $\overline{CE}$
47 • • • • • • 40 39 • • • • • • 32 31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
LD02290S

NOTES:
1. All AND/EX-OR gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown link float to a logic "0".
3. ▨ Programmable connection.

FPLA LOGIC DIAGRAM

PLS173/PLUS173


(LOGIC TERMS—P)
(CONTROL TERMS)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
I_8 9
I_9 10
I_{10} 11
I_{11} 13
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
B_9
D_9 D_8 D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
S_9 S_8 S_7 S_6 S_5 S_4 S_3 S_2 S_1 S_0
X_9 X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
23 B_9
22 B_8
21 B_7
20 B_6
19 B_5
18 B_4
17 B_3
16 B_2
15 B_1
14 B_0
31 • • • • • • • 24 23 • • • • • • • 16 15 • • • • • • • 8 7 • • • • • • • 0

TB00941S

NOTES:
1. All programmed "AND" gate locations are pulled to a logic "1".
2. All programmed "OR" gate locations are pulled to a logic "0".
3. ▨ Programmable connection.

FPLA LOGIC DIAGRAM

PLHS473


(LOGIC TERMS–P)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
I9 10
I10 11
B0
B1
B2
B3
B4
B5
B6
B7
B8
D8
S8
D7
S7
D6
S6
D5
S5
D4
S4
D3
S3
D2
S2
D1
S1
D0
S0
EB
SB
EA
SA
X8
X7
X6
X5
X4
X3
X2
X1
X0
XB
XA
23 • • • • • • 16
15 • • • • • • 8
7 • • • • • • 0
23 B8
22 B7
21 B6
20 B5
17 B4
16 B3
15 B2
14 B1
13 B0
19 OB
18 OA
LD02630S

NOTES:

1. All unprogrammed or virgin 'AND' gate locations are pulled to a logic '1'.
2. All unprogrammed or virgin 'OR' gate locations are pulled to a logic '0'.
3. ▨ Programmable connection.

FPLA LOGIC DIAGRAM

PLC473


(LOGIC TERMS–P)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
I9 10
I10 11
B0
B1
B2
B3
B4
B5
B6
B7
B8
D8
S8
D7
S7
D6
S6
D5
S5
D4
S4
D3
S3
D2
S2
D1
S1
D0
S0
EB
SB
EA
SA
X8
X7
X6
X5
X4
X3
X2
X1
X0
XB
XA
23 • • • • • • 16
15 • • • • • • 8
7 • • • • • • 0
23 B8
22 B7
21 B6
20 B5
17 B4
16 B3
15 B2
14 B1
13 B0
19 OB
18 OA
LD02630S

NOTES:

1. All programmed 'AND' gate locations are pulled to a logic '1'.
2. All programmed 'OR' gate locations are pulled to a logic '0'.
3. ▨ Programmable connection.

FPLA LOGIC DIAGRAM

PLHS18P8A


INPUTS (0–35)
0
35
PRODUCT TERMS (0–71)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
I_8 9
0
8
9
17
18
26
27
35
36
44
45
53
54
62
63
71
19 B_7
18 B_6
17 B_5
16 B_4
15 B_3
14 B_2
13 B_1
12 B_0
11 I_9
0
35
LD02620S

NOTES:

1. All unprogrammed or virgin "AND" gate locations are pulled to a logic "1".
2. ▨ Programmable connections.

FPLS LOGIC DIAGRAM

PLS105/105A


(LOGIC TERMS - T)
(OPTION)
19 PR/OE
P
E
I
I0 9
I1 8
I2 7
I3 6
I4 5
I5 4
I6 3
I7 2
I8 27
I9 26
I10 25
I11 24
I12 23
I13 22
I14 21
I15 20
P0
P1
P2
P3
P4
P5
P
C̄
C
C
N
F
S Q
R P
18 F0
17 F1
16 F2
15 F3
13 F4
12 F5
11 F6
10 F7
1 CK
47 40 39 32 31 24 23 16 15 8 7 0
LD02240S

NOTES:

1. All AND gate inputs with a blown link float to a logic '1'.
2. All OR gate inputs with a blown fuse float to a logic '0'.
3. ▨ Programmable connections.

FPLS LOGIC DIAGRAM

PLS155


(LOGIC TERMS - T)
(CONTROL TERMS)
I0 2
I1 3
I2 4
I3 5
F0
F1
F2
F3
B0
B1
B2
B3
B4
B5
B6
B7
C̄
11 OE
LB LA D7 D6 D5 D4 D3 D2 D1 D0
EB EA
X7 S7
X6 S6
X5 S5
X4 S4
X3 S3
X2 S2
X1 S1
X0 S0
19 B7
18 B6
13 B5
12 B4
9 B3
8 B2
7 B1
6 B0
RB
PB
RA
PA
P R
J Q
K
CK′
M3
M2
M1
M0
17 F3
16 F2
15 F1
14 F0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0 FC
CK′ 1 CK
LD01702S

NOTES:
1. All OR gate inputs with a blown link float to a logic '0'.
2. All other gates and control inputs with a blown link float to a logic '1'.
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connections.

FPLS LOGIC DIAGRAM

PLS157


(LOGIC TERMS—T)
(CONTROL TERMS)
I_0 2
I_1 3
I_2 4
I_3 5
F_0
F_1
F_2
F_3
F_4
F_5
B_0
B_1
B_2
B_3
B_4
B_5
11 $\overline{OE}$
$\overline{C}$
C
P_B R_B L_B D_5 D_4 D_3 D_2 D_1 D_0 L_A
E_A E_B
X_5 S_5
X_4 S_4
X_3 S_3
X_2 S_2
X_1 S_1
X_0 S_0
P R
J Q
K
CK'
M_5
M_4
M_3
M_2
M_1
M_0
R_A
P_A
19 B_5
12 B_4
9 B_3
8 B_2
7 B_1
6 B_0
18 F_5
17 F_4
16 F_3
15 F_2
14 F_1
13 F_0
1 CK
CK'
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0 F_C
LD01693S

NOTES:

1. All OR gate inputs with a blown link float to a logic '0'.
2. All other gates and control inputs with a blown link float to a logic '1'.
3. ⊕ denotes WIRE-OR.
4. ● Programmable connections.

FPLS LOGIC DIAGRAM

PLS159/159A


(LOGIC TERMS — T)
(CONTROL TERMS)
OE
11
I0 2
I1 3
I2 4
I3 5
F0
F1
F2
F3
F4
F5
F6
F7
B0
B1
B2
B3
C
S3
S2
S1
S0
X3
X2
X1
X0
PB RB PA RA LB LA D3 D2 D1 D0
EA EB
9 B3
8 B2
7 B1
6 B0
M7
M6
M5
M4
M3
M2
M1
M0
P
R
J
Q
K
CK'
19 F7
18 F6
17 F5
16 F4
15 F3
14 F2
13 F1
12 F0
31 24 23 16 15 8 7 0 FC
CK'
1 CK
LD01684S

NOTES:

1. All OR gate inputs with a blown link float to a logic "0".
2. All other gates and control inputs with a blown link float to a logic "1".
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connection.

FPLS LOGIC DIAGRAM

PLS167/167A


(LOGIC TERMS—T)
I_0 8
I_1 7
I_2 6
I_3 5
I_4 4
I_5 3
I_6 2
I_7 23
I_8 22
I_9 21
I_{10} 20
I_{11} 19
I_{12} 18
I_{13} 17
P_0
P_1
P_2
P_3
P
P_4
P_5
P_6
P_7
$\overline{C}$
C
C
N
F
I
OPTION
16 PR/$\overline{OE}$
P
E
S Q
R P
P_2
P_3
P_4
P_5
P_6
P_7
Q_3
Q_2
Q_1
Q_0
15 P_1
14 P_0
13 F_3
11 F_2
10 F_1
9 F_0
1 CK
47 • • • • • • • 40 39 • • • • • • • • 32 31 • • • • • • • 24 23 • • • • • • • • • 16 15 • • • • • • • • 8 7 • • • • • • • • 0
LD02281S

NOTES:

1. All AND gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown link float to a logic "0".
3. ▨ Programmable connection.

FPLS LOGIC DIAGRAM

PLS168/168A


(LOGIC TERMS—T)
I_0 7
I_1 6
I_2 5
I_3 4
I_4 3
I_5 2
I_6 23
I_7 22
I_8 21
I_9 20
I_{10} 19
I_{11} 18
I
OPTION
17 PR/$\overline{OE}$
P
E
P
P_0
P_1
P_2
P_3
P_9
P_8
P_7
P_6
P_5
P_4
$\overline{C}$
C
C
N
F
S Q
R P
P_9
P_8
P_7
P_6
P_5
P_4
Q_3
Q_2
Q_1
Q_0
16 P_3
15 P_2
14 P_1
13 P_0
11 F_3
10 F_2
9 F_1
8 F_0
1 CK
47
0
TB00882S

NOTES:
1. All programmed "AND" gate locations are pulled to a logic "1".
2. All programmed "OR" gate locations are pulled to a logic "0".
3. ● Programmable connection.

FPLS LOGIC DIAGRAM

PLS179


(LOGIC TERMS — T)
(CONTROL TERMS)
I0 2
I1 3
I2 4
I3 5
I4 6
I5 7
I6 8
I7 9
F0
F1
F2
F3
F4
F5
F6
F7
B0
B1
B2
B3
C̄
C
OE 13
S3
S2
S1
S0
X3
X2
X1
X0
PB RB PA RA LB LA D3 D2 D1 D0
EA EB
23 B3
14 B2
11 B1
10 B0
M7
M6
M5
M4
M3
M2
M1
M0
P
R
J Q
K
CK'
22 F7
21 F6
20 F5
19 F4
18 F3
17 F2
16 F1
15 F0
31 • • • • • • • 24 23 • • • • • • • 16 15 • • • • • • • 8 7 • • • • • • • 0 FC
CK'
1 CLK
LD01672S

1. All OR gate inputs with a blown link float to a logic "0".
2. All other gates and control inputs with a blown link float to a logic "1".
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connection.

FPLS LOGIC DIAGRAM

PLUS405A



I_0 9
I_1 8
I_2 7
I_3 6
I_4 5
I_5 4
I_6/CLK 3
I_7 2
I_8 27
I_9 26
I_{10} 25
I_{11} 24
I_{12} 23
I_{13} 22
I_{14} 21
I_{15} 20
19 INIT/$\overline{OE}$
DETAIL A
P_0
P_1
P_2
P_3
P_4
P_5
P_6
P_7
$\overline{C}_1$
$\overline{C}_0$
C_0
C_1
DETAIL B
DETAIL C
18 F_0
17 F_1
16 F_2
15 F_3
13 F_4
12 F_5
11 F_6
10 F_7
1 CLK
DETAIL D
LD06872S

1. All OR gate inputs with a blown link float to a logic '0'.
2. All other gates and control inputs with a blown link float to a logic '1'.
3. ⊕ denotes WIRE-OR
4. ▨ Programmable connection.

FPML LOGIC DIAGRAM **PLHS501**


I0 41
I1 42
I2 43
I3 44
I4 45
I5 47
I6 48
I7 49
I8 50
I9 51
I10 52
I11 1
I12 2
I13 3
I14 4
I15 5
I16 6
I17 7
I18 9
I19 10
I20 11
I21 12
I22 13
I23 14
DETAIL A
40 B̄3
39 B̄2
38 B̄1
37 B̄0
15 B4
16 B5
17 B6
18 B7
28 X0
29 X1
30 X2
31 X3
32 X4
33 X5
35 X6
36 X7
19 O0
21 O1
22 O2
23 O3
24 Ō4
25 Ō5
26 Ō6
27 Ō7
LD06740S

PLD PROGRAMMING

The current Signetics family of Programmable Logic (PLD) products are high-performance bipolar and CMOS devices which use various fusing elements to provide the many benefits of field programming. Programming is accomplished by application of voltages above those used for normal operation; therefore, no special pins are required for programming. The programming voltages and timing requirements make unintentional programming virtually impossible.

PROGRAMMING INFORMATION

Complete programming system specifications for PLD 20-, 24-, and 28-pin and 52-pin PML products are available upon request from Application Specific Product Marketing.

Signetics encourages the purchase of programming equipment from a manufacturer who has a full-line of programming products to offer. Signetics also encourages the manufacturers of PLD programming equipment to submit their equipment for verification of electrical parameters and programming procedures. Information on manufacturers offering equipment certified by Signetics is available on request from Application Specific Product Marketing.

SIGNETICS DISCOURAGES THE CONSTRUCTION AND USE OF ''HOMEMADE'' PROGRAMMING EQUIPMENT

In order to consistently achieve excellent programming yields, periodic calibration of the programming equipment is required. Consult the equipment manufacturer for the recommended calibration interval. Records of programming yield, by device type, should be kept and any downward trend or sudden change should be considered as an indication of a need to recalibrate the programming equipment.

Section 3
Advanced Product Preview

INDEX

Section 3 – Advanced Product Preview

PLMC153 Mask-Programmable Logic Array (18 × 42 × 10) 3-3
PLUS153 Field-Programmable Logic Array (18 × 42 × 10) 3-5
PLUS173 Field-Programmable Logic Array (22 × 42 × 10) 3-7
PLHS501 Programmable Macro Logic Random Logic Unit (32 × 72 × 24) ... 3-9
PLHS502 Programmable Macro Logic Synchronous/Asynchronous Register Macro Unit (32 × 64 × 24) 3-19

Signetics

PLMC153

Mask-Programmable Logic Array (18 × 42 × 10)

Signetics Programmable Logic
Objective Specification

Application Specific Products
• Series 20

DESCRIPTION

The PLMC153 is a CMOS, mask-programmable functional equivalent of the PLS153 and PLS153A FPLAs. Custom logic patterns can be generated directly from working bipolar PLS153/153A devices. This enables the user to prototype and debug a device in a system prior to committing the pattern to a mask set. The programmed PLMC153 provides maximum production economy, while the CMOS process technology reduces the power consumption of the PLMC153 to less than one third of its bipolar counterparts.

Identical to the PLS153 and 153A, the PLMC153 is a two-level logic element, consisting of 42 AND gates and 10 OR gates, featuring programmable I/O polarity and direction.

All AND gates are linked to 8 inputs (I) and 10 bidirectional I/O lines (B). These yield variable I/O gate configurations via 10 direction control gates (D), ranging from 18 inputs to 10 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. Their output polarity, in turn, is individually programmable through a set of EX-OR gates for implementing AND/OR or AND/NOR logic functions.

FEATURES

- **Single Mask-Programmable**
- **Functionally identical to PLS153 and PLS153A**
- **8 inputs**
- **42 AND gates**
- **10 OR gates**
- **10 bidirectional I/O lines**
- **Active-High or -Low outputs**
- **42 product terms:**
  - **32 logic terms**
  - **10 control terms**
- **I/O propagation delay: 35ns (max.)**
- **Power dissipation: (typ.)**
  - **DC: 1mA**
  - **AC: 1mA/MHz**
- **Input Loading: −100μA (max.)**
- **Tri-state outputs**
- **TTL compatible**

FUNCTIONAL DIAGRAM



NOTE:
All points are mask-programmable.

PIN CONFIGURATIONS

N Package



N = Plastic

A Package



A = Plastic Leaded Chip Carrier

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
$Pn = A \cdot B \cdot C \cdot D \cdot \ldots$

TYPICAL LOGIC FUNCTION:

AT OUTPUT POLARITY = H
$Z = P0 + P1 + P2 \ldots$

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +} \ldots$
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \ldots$

NOTES:
1. For each of the 10 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

Mask-Programmable Logic Array (18 × 42 × 10) PLMC153

FPLS LOGIC DIAGRAM


(LOGIC TERMS—P)
(CONTROL TERMS)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
B0
B1
B2
B3
B4
B5
B6
B7
B8
B9
31 • • • • • • • 24
23 • • • • • • • 16
15 • • • • • • • 8
7 • • • • • • • 0
X9
X8
X7
X6
X5
X4
X3
X2
X1
X0
S9
S8
S7
S6
S5
S4
S3
S2
S1
S0
D9
D8
D7
D6
D5
D4
D3
D2
D1
D0
19 B9
18 B8
17 B7
16 B6
15 B5
14 B4
13 B3
12 B2
11 B1
9 B0
TB00943S

NOTE:
1. All points are mask-programmable.

Signetics

PLUS153
Field-Programmable Logic Array (18 × 42 × 10)

Signetics Programmable Logic
Objective Specification

Application Specific Products
- **Series 20**

DESCRIPTION

The PLUS153 is a two-level logic element, consisting of 42 AND gates and 10 OR gates with fusible link connections for programming I/O polarity and direction.

All AND gates are linked to 8 inputs (I) and 10 bidirectional I/O lines (B). These yield variable I/O gate configurations via 10 direction control gates (D), ranging from 18 inputs to 10 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. Their output polarity, in turn, is individually programmable through a set of EX-OR gates for implementing AND/OR or AND/NOR logic functions.

The PLUS153 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ti-W links)**
- **Functionally identical to PLS153/153A and PLHS153**
- **8 inputs**
- **42 AND gates**
- **10 OR gates**
- **10 bidirectional I/O lines**
- **Active-High or -Low outputs**
- **42 product terms:**
  - **32 logic terms**
  - **10 control terms**
- **I/O propagation delay: 12ns (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 700mW (typ.)**
- **Tri-state outputs**
- **TTL compatible**

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

PIN CONFIGURATIONS

N Package


I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
B0 9
GND 10
20 VCC
19 B9
18 B8
17 B7
16 B6
15 B5
14 B4
13 B3
12 B2
11 B1
CD04680S

N = Plastic

A Package


I2 I1 I0 VCC B9
3 2 1 20 19
I3 4
I4 5
I5 6
I6 7
I7 8
18 B8
17 B7
16 B6
15 B5
14 B4
9 10 11 12 13
B0 GND B1 B2 B3
CD04690S

A = Plastic Leaded Chip Carrier

FUNCTIONAL DIAGRAM


P31
P0
D0
D9
I0
I7
B0
B9
S9
X9
S0
X0
B9
B0
AF01832S

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
$Pn = A \cdot B \cdot C \cdot D \cdot \ldots$
TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
$Z = P0 + P1 + P2 \ldots$

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +} \ldots$
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot \ldots$

NOTES:
1. For each of the 10 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

Field-Programmable Logic Array (18 × 42 × 10)

PLUS153

FPLA LOGIC DIAGRAM


(LOGIC TERMS—P)
(CONTROL TERMS)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
B_9
D_9 D_8 D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
S_9 X_9
S_8 X_8
S_7 X_7
S_6 X_6
S_5 X_5
S_4 X_4
S_3 X_3
S_2 X_2
S_1 X_1
S_0 X_0
19 B_9
18 B_8
17 B_7
16 B_6
15 B_5
14 B_4
13 B_3
12 B_2
11 B_1
9 B_0
31 • • • • • • 24
23 • • • • • • 16
15 • • • • • • 8
7 • • • • • • 0
TB00943S

NOTES:

1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. ● Programmable connection.

Signetics

PLUS173
Field-Programmable Logic Array (22 × 42 × 10)

Signetics Programmable Logic
Objective Specification

Application Specific Products
- **Series 24**

DESCRIPTION

The PLUS173 is a high-speed version of the PLS173 FPLA. The Signetics state-of-the-art Oxide Isolated Bipolar fabrication process is employed to produce performance levels not yet achieved in devices of this complexity.

The PLUS173 is a two-level logic element consisting of 42 AND gates and 10 OR gates with fusible link connections for programming I/O polarity and direction.

All AND gates are linked to 12 inputs (I) and 10 bidirectional I/O lines (B). These yield variable I/O gate configurations via 10 direction control gates (D), ranging from 22 inputs to 10 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. Their output polarity, in turn, is individually programmable through a set of EX-OR gates for implementing AND/OR or AND/NOR logic functions.

The PLUS173 is field-programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

FUNCTIONAL DIAGRAM



P31
P0
D0
D9
I0
I11
B0
B9
S9
S0
X9
X0
B9
B0
AF01831S

FEATURES

- **Field-Programmable (Ti-W links)**
- **Functionally identical to PLS173**
- **12 inputs**
- **42 AND gates**
- **10 OR gates**
- **10 bidirectional I/O lines**
- **Active-High or -Low outputs**
- **42 product terms:**
  - **32 logic terms**
  - **10 control terms**
- **I/O propagation delay: 12ns (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 700mW (typ.)**
- **Tri-state outputs**
- **TTL compatible**

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

PIN CONFIGURATIONS



N Package
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
I9 10
I10 11
GND 12
24 VCC
23 B9
22 B8
21 B7
20 B6
19 B5
18 B4
17 B3
16 B2
15 B1
14 B0
13 I11
CD03290S

N = Plastic



A Package
N/C 11
I8 10
I7 9
I6 8
I5 7
I4 6
N/C 5
I9 12
I10 13
GND 14
I11 15
B0 16
B1 17
B2 18
4 I3
3 I2
2 I1
1 I0
28 VCC
27 B9
26 B8
19 N/C
20 B3
21 B4
22 B5
23 B6
24 B7
25 N/C
CD03390S

A = Plastic Leaded Chip Carrier

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
$Pn = A \cdot B \cdot C \cdot D \cdot \ ...$

TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
$Z = P0 + P1 + P2 \ ...$

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +} \ ...$
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot \ ...$

NOTES:
1. For each of the 10 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

FPLA LOGIC DIAGRAM


(LOGIC TERMS—P)
(CONTROL TERMS)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
I9 10
I10 11
I11 13
B0
B1
B2
B3
B4
B5
B6
B7
B8
B9
D9 D8 D7 D6 D5 D4 D3 D2 D1 D0
S9 S8 S7 S6 S5 S4 S3 S2 S1 S0
X9 X8 X7 X6 X5 X4 X3 X2 X1 X0
23 B9
22 B8
21 B7
20 B6
19 B5
18 B4
17 B3
16 B2
15 B1
14 B0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
TB00941S

NOTES:

1. All programmed 'AND' gate locations are pulled to logic "1".
2. All programmed 'OR' gate locations are pulled to logic "0".
3. ▨ Programmable connection.

Signetics

PLHS501

Programmable Macro Logic Random Logic Unit* (32 × 72 × 24)

Preliminary Specification

Application Specific Products
• PML Series 52

DESCRIPTION

The PLHS501 is a member of the Signetics Programmable Macro Logic family. PML is unique in its capability of performing other than two level logic functions without incurring I/O buffer delays. This allows the logic or system designer to imbed logical operations or macro structures within the framework of the I/O pins. Since the imbedded functions are independent of the delays created by the I/O buffers, they can be performed at speeds lesser architectures cannot reproduce.

The technique used to perform this operation is a NAND foldback network which allows the direct interconnection of any number of logic nodes within the single fuse matrix. Macros can be formed and then interconnected to the I/O structure. In addition, single-level and multi-level logic can be performed at speeds which reflect only the logic path utilized. Therefore, a single-level logic function has a very short path through the device. Additional levels incur only one NAND foldback delay per level. This delay is less than the combined delay created by previous generations of devices which stipulate that the logic signal must pass through I/O buffers after one or two levels of logic are performed.

The PLHS501 is fabricated with Signetics, ZA Oxide-Isolated Bipolar Process. ZA utilizes Vertical Avalanche Migration Programmed (VAMP^{TM}) Fuses as programming elements. These fuses provide high programming yield and reliability. Proprietary onboard test circuitry allows the PLHS501 to be thoroughly tested prior to programming.

FEATURES

- **Signetics NAND foldback architecture**
- **Field-Programmable**
- **24 dedicated inputs**
- **Fixed and programmable output buffers**
  - **8 I/O buffers**
  - **8 EX-OR buffers**
  - **4 Active-Low buffers**
  - **4 Active-High buffers**
- **72 internal NAND foldback terms**
- **Supported by AMAZE Development System**
- **Testable in unprogrammed state**
- **Verify Lock Fuse**
- **TTL compatible**
- **Power dissipation: 1.25W (typ.)**
- **Logic delay times**
  - **Single-level = 18ns (max.)**
  - **Two-level = 26ns (max.)**
  - **Internal NAND delay = 8ns (max.)**

ARCHITECTURE

- **24 dedicated Inputs; $I_0 - I_{23}$**
- **4 Active-High I/Os with individual enable: $B_4 - B_7$**
- **4 Active-Low I/Os with individual fused enable: $\overline{B}_0 - \overline{B}_3$**
- **2 Active-High output pairs; each pair with common enable: $O_0 - O_3$**
- **2 Active-Low output pairs; each pair with common enable: $\overline{O}_4 - \overline{O}_7$**
- **4 EX-OR output pairs; each pair with common enable: $X_0 - X_7$**
- **72 internal NAND foldback terms**

PIN CONFIGURATION

A Package (52-Pin PLCC)



Pin. No.		Pin No.	
1	I_{11}	27	$/O_7$
2	I_{12}	28	X_0
3	I_{13}	29	X_1
4	I_{14}	30	X_2
5	I_{15}	31	X_3
6	I_{16}	32	X_4
7	I_{17}	33	X_5
8	V_{CC}	34	GND
9	I_{18}	35	X_6
10	I_{19}	36	X_7
11	I_{20}	37	$/B_0$
12	I_{21}	38	$/B_1$
13	I_{22}	39	$/B_2$
14	I_{23}	40	$/B_3$
15	B_4	41	I_0
16	B_5	42	I_1
17	B_6	43	I_2
18	B_7	44	I_3
19	O_0	45	I_4
20	GND	46	V_{CC}
21	O_1	47	I_5
22	O_2	48	I_6
23	O_3	49	I_7
24	$/O_4$	50	I_8
25	$/O_5$	51	I_9
26	$/O_6$	52	I_{10}

---

*Patent Pending

Programmable Macro Logic Random Logic Unit* (32 × 72 × 24)

PLHS501

FUNCTIONAL DIAGRAM


71
0
I0
I23
$\overline{B}_0$ - $\overline{B}_3$
(×4)
B_4 - B_7
(×4)
X_0, X_2, X_4, X_6
(×4)
X_1, X_3, X_5, X_7
O_0, O_2
(×2)
O_1, O_3
$\overline{O}_4$, $\overline{O}_6$
(×2)
$\overline{O}_5$, $\overline{O}_7$
LD06731S

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
52-Pin Plastic Leaded Chip Carrier	PLHS501A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	-30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	-65	+150	

Programmable Macro Logic
Random Logic Unit* (32 × 72 × 24)

PLHS501

LOGIC DIAGRAM


I_0 41
I_1 42
I_2 43
I_3 44
I_4 45
I_5 47
I_6 48
I_7 49
I_8 50
I_9 51
I_{10} 52
I_{11} 1
I_{12} 2
I_{13} 3
I_{14} 4
I_{15} 5
I_{16} 6
I_{17} 7
I_{18} 9
I_{19} 10
I_{20} 11
I_{21} 12
I_{22} 13
I_{23} 14
DETAIL A
40 $\overline{B}_3$
39 $\overline{B}_2$
38 $\overline{B}_1$
37 $\overline{B}_0$
15 B_4
16 B_5
17 B_6
18 B_7
28 X_0
29 X_1
30 X_2
31 X_3
32 X_4
33 X_5
35 X_6
36 X_7
19 O_0
21 O_1
22 O_2
23 O_3
24 $\overline{O}_4$
25 $\overline{O}_5$
26 $\overline{O}_6$
27 $\overline{O}_7$
LD06740S


DETAIL A
40 $\overline{B}_3$
39 $\overline{B}_2$
38 $\overline{B}_1$
37 $\overline{B}_0$
15 B_4
16 B_5
17 B_6
18 B_7
28 X_0
29 X_1
30 X_2
31 X_3
32 X_4
33 X_5
35 X_6
36 X_7
19 O_0
21 O_1
22 O_2
23 O_3
24 $\overline{O}_4$
25 $\overline{O}_5$
26 $\overline{O}_6$
27 $\overline{O}_7$

LD06751S

Programmable Macro Logic Random Logic Unit* (32 × 72 × 24)

PLHS501

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			0.8	V
V_{IH}	High	V_{CC} = Max	2.0			
V_{IC}	Clamp[3,4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage						
		V_{CC} = Min				
V_{OL}	Low[3,5]	I_{OL} = 10mA			0.45	V
V_{OH}	High[3,6]	I_{OH} = −2mA	2.4			
Input current						
		V_{CC} = Max				
I_{IL}	Low	V_{IN} = 0.45V			−100	µA
I_{IH}	High	V_{IN} = 5.5V			40	
Output current						
$I_{O(OFF)}$	Hi-Z state[10]	V_{CC} = Max V_{OUT} = 5.5V V_{OUT} = 0.45V			80 −140	µA
I_{OS}	Short circuit[4,6,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		250	325	mA
Capacitance						
		V_{CC} = 5V				
I_{IN}	Input	V_{IN} = 2.0V		8		pF
C_B	I/O	V_{OUT} = 2.0V		15		

AC ELECTRICAL CHARACTERISTICS $T_A = 0°C$ to $+75°C$, $4.75 < V_{CC} < 5.25V$, $R_1 = 470\Omega$, $R_2 = 1000\Omega$

SYMBOL	PARAMETER		TEST CONDITIONS	LIMITS			UNIT
	TO	FROM		Min	Typ	Max	
t_{PD1}	Output±	Input±	C_L = 30pF			20	ns
t_{PD2}	Output±	Input±				18	ns
t_{PD3}	Output±	Input±				18	ns
t_{PD4}[11]	Output±	Input±				28	ns
t_{PD5}[11]	Output±	Input±				26	ns
t_{PD6}[11]	Output±	Input±				26	ns
t_{PD7}[11]	Internal					8	ns
t_{OE}	Output−	Input±				20	ns
t_{OD}[9]	Output+	Input±	C_L = 5pF			20	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = +25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. For Pins 15 − 19, 21 − 27 and 37 − 40, V_{OL} is measured with Pins 5 and 41 = 8.75V, Pin 43 = 0V and Pins 42 and 44 = 4.5V. For Pins 28 − 33 and 35 − 36, V_{OL} is measured under same conditions EXCEPT Pin 44 = 0V.
6. V_{OH} is measured with Pins 5 and 41 = 8.75V, Pins 42 and 43 = 4.5V and Pin 44 = 0V.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with all dedicated inputs at 0V and bidirectional and output pins open.
9. Measured at $V_T = V_{OL} + 0.5V$.
10. Leakage values are a combination of input and output leakage.
11. Limits are guaranteed with 10 terms maximum connected to each internal feedback line.

Programmable Macro Logic Random Logic Unit* (32 × 72 × 24)

PLHS501

TEST LOAD CIRCUIT



V_{CC}
I_0
I_{10}
B_W
B_X
B_Y
B_Z
O_X
GND
+5V
R_1
R_2
C_L
INCLUDES SCOPE AND JIG CAPACITANCE

TC02680S

TIMING DIAGRAM



I, B
1.5V
1.5V
1.5V
+3V
0V
B
1.5V
V_T
1.5V
V_{OH}
V_{OL}
t_{PD}
t_{OD}
t_{OE}

WF05411S

VOLTAGE WAVEFORM



+3.0V
0V
90%
10%
t_r
t_f
2.5ns
2.5ns
+3.0V
0V
90%
10%
2.5ns
2.5ns

WF05391S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

TIMING DEFINITIONS

t_{PD1}	Input to Output delay, one pass, with EX-OR buffer
t_{PD2}	Input to Output delay, one pass, with NAND buffer
t_{PD3}	Input to Output delay, one pass, with AND buffer
t_{PD4}	Input to Output delay, two passes, with EX-OR buffer
t_{PD5}	Input to Output delay, two passes, with NAND buffer
t_{PD6}	Input to Output delay, two passes, with AND buffer
t_{PD7}	Feedback delay per internal NAND function performed
t_{OD}	Delay between output change and when output is off (Hi-Z or High)
t_{OE}	Delay between input change and when the output reflects specified output level

VIRGIN STATE

A factory shipped virgin device contains all fusible links open, such that:

1. All product terms are enabled.
2. All bidirectional (B) pins are outputs.
3. All outputs are enabled.
4. All outputs are Active-High **except** $\overline{B}_0 - \overline{B}_3$ (fusable I/O) and $/O_4 - /O_7$ which are Active-Low.

Programmable Macro Logic Random Logic Unit* (32 × 72 × 24)

PLHS501

PROGRAMMABLE MACRO LOGIC

The architectures of current Programmable Logic Devices (PLDs) generally employ programmable AND-OR gate strings to permit implementing logic functions directly in Sum-of-Products form (SOP). Often, that becomes a bottleneck which interferes with the efficient allocation of the on-chip logic resources. This becomes very apparent when considering very dense PLDs in high pin-count packages.

PML is a novel architecture which breaks the AND-OR bottleneck by relying instead on a single NAND-gate array to implement SOP logic functions, and to provide a central programmable "interconnect" site supporting a periphery of multi-level macros on a chip.

INTRODUCTION

Today, system designers in a rush to bring their products to market are turning more than ever toward Programmable Logic Devices, lured by their blend of design elegance and efficiency with instant custom flexibility despite limitations in density and architecture.

To be sure, dramatic advances in Bipolar and CMOS processing technologies over the last decade have spawned denser and faster elements, with an occasional twist in architecture. Nevertheless, the structure of most current PLDs is still anchored on a fixed AND-OR gate chain linking primitive input, output, and function macros on a chip. Recently, to enhance the flexibility and design adaptability of early product offerings, denser devices have been introduced featuring logic macros with local programmable options and bypass circuitry.

However, as densities continue to increase, this approach is sure to breed devices with an overwhelming architectural maze which is altogether difficult to design, comprehend, and logically manipulate, complicating rather than simplifying their application.

PML, however, consists of various logic "access" and "process" macros coupled via a primitive, central programmable structure in the on-chip "interconnect" system (see Figure 1). Macros can have various local intelligence which, in turn, may be fixed or variable by means of programmable options also embedded in the central programmable core.



Figure 1. General PML Architecture Based on a Central Programmable "Interconnect" System Interlocking Peripheral Macros



Figure 2. Typical SOP Function With Elementary AND-OR Gates



Figure 3. Basic Architecture of Current PLDs

AND-OR PLD ARCHITECTURE

From a fundamental theorem of Boolean algebra, any combinational logic function can be expressed in Sum-of-Products form involving only two levels of logic transformation. Such functions can be implemented in hardware by chaining two primitive logic macros as indicated in Figure 2.

The outputs of an AND-OR gate chains can be interlaced with higher level macros, such as flip-flops, to form sequential logic functions. These may be further combined into standard or custom super-macros which, in turn, are interwoven into final system configurations. Presently, a number of PLDs are available which contain fixed sets of logic macros with programmable connections. Invariably, their architectures are anchored on a pair of concatenated AND-OR gate arrays, as diagrammed in Figure 3, to permit implementing logic functions directly in SOP form.

Virtually all PLDs fall in three main categories: PROM, Fixed OR, and PLA. As illustrated in Figure 4, these differ primarily in the programmability of the AND-OR gate chain which, by being irrevocably interposed as a two-level logic link between on-chip macros and I/O paths, often can turn into a design liability.

For example, in PROMs the exponential increase in AND array size with number of inputs is a severe drawback which limits their contention in the logic application arena.

In fixed OR devices, the fixed inputs to the OR array confine their architectures to essentially a composite of AND-OR, AND-OR-register logic slices defining independent I/O paths through the chip. This causes duplication of common product terms, and waste of unused AND gates in each slice. Also, since each slice is dedicated to an output pin, devices with registered, programmable I/O pins entail an even greater waste of on-chip logic resources when configured in register-bypass or fixed input modes. Moreover, no single level logic functions can be constructed, except dedicated on-chip control functions.

Finally, even as the twin programmability of the AND-OR arrays in current PLA-type devices lends greater flexibility, and may circumvent some of the above problems, it does pose difficult process, design and performance compromises in migrating toward more dense structures.

Thus, on the whole, the AND-OR gate chain forms a bottleneck which can impair the fragmentation and reallocation of the on-chip logic resources, curtailing the adaptability and efficiency of current PLDs in applications involving unstructured algorithms and scattered logic functions.



a. PROM: Programmable OR



b. PAL*: Programmable AND



c. PLA: Programmable AND-OR

Figure 4. Programmable AND-OR Chain of Current PLDs

---

*PAL is a registered trademark of Monolithic Memories, Inc.

Programmable Macro Logic Random Logic Unit* (32 × 72 × 24)

PLHS501

NAND-NAND GATE EQUIVALENCE

One way of relieving the burden placed on PLDs' architecture by the AND-OR gate string is to do away with it altogether, and replace it with a new programmable structure forged out of a new compromise on silicon between "interconnect" redundancy and ease of design and application. The approach adopted for PML is based on the fundamental equivalence between two-level AND-OR and NAND-NAND gate constructs in expressing combinatorial logic functions in SOP form, as illustrated in Figure 5.

Since programmable NAND-NAND logic chains can be formed by coupling identical NAND gates with programmable inputs, the NAND-array string in Figure 6 can be implemented as a single global array with feedback.

A basic NAND-array core linking a periphery of primitive macros is shown in Figure 7. When the feedback path is just a simple wire, the NAND-array can be fragmented into single-level or double-level true/complement logic functions by programming respectively single (a-c-d), or double (a-b-c-d), interconnecting paths through the array from inputs I to output F.

More complex functions can be implemented by programming multi-level logic loops through the array.



$$Y = \overline{C * D} \qquad X = \overline{A * B}$$

$$F = \overline{X * Y} = \overline{(\overline{A * B}) * (\overline{C * D})}$$

$$F = (\overline{\overline{A * B}}) + (\overline{\overline{C * D}})$$

$$\boxed{F = A * B + C * D}$$

LD06800S

Figure 5. Equivalent NAND-NAND SOP Expression



AF04450S

Figure 6. NAND-NAND Gate Chain Compressed Into a Single Array With Feedback



LD06810S

Figure 7. Elementary NAND Array Linking Primitive Macros. Note That No Programmable Connection is Implied at a Cross of a Solid Line With a Dotted Line

Programmable Macro Logic Random Logic Unit* (32 × 72 × 24)

PLHS501

BASIC PML ARCHITECTURE

The primitive NAND core can be expanded to support at its periphery a structure of logic macros of growing size and complexity, including various types of flip-flops, EX-OR gates, buffers, counters, shift registers, multiplexers, decoders, arithmetic/logic units, memories, etc. As illustrated in the general structure of Figure 8, I/O macros would provide off-chip paths to the outside world, while FUNCTION macros looped about the array would provide the necessary logic processing capability.

In deference to trade-offs in functionality and speed imposed by the array size and loading, Type-1 Output (or Function) macros may be driven directly from NAND gates, while Type-2 macros may be driven by gates first looped through the array. There are virtually no limits to the number, size, and functionality of the on-chip macros surrounding the central core, other than those imposed by processing and packaging capabilities.

The main design advantage of PML is that it relies upon a single array to interconnect all macros. This reduces the design task to that of building essentially a PROM-like programmable structure more forgiving than the double array in PLA-type devices, and more flexible than that in fixed OR devices. Also, the ability to forge the NAND core into multi-level logic paths at will increases the usage efficiency of the on-chip logic resources, and greatly enhances the versatility of PML in most applications.

THE FIRST PML OFFERING

The first PML device, designated PLHS501, is primarily a combinational logic device including only primitive macros. It is a "gate bucket" whose deceptively simple structure can implement virtually all logic functions provided by existing combinational PAL/PLA-type devices. Also, it is the first to provide true EX-OR output functions (in addition to output polarity inversion), as well as multi-level gate constructs and cross-coupled latches on-chip without involving output pins. These are shown in Figure 9.



Figure 8. General PML Structure



Figure 9. Novel Logic Constructs Available With PLHS501

Built with Signetics' proprietary ZA oxide isolation process, and vertical fuses, the PLHS501 has a NAND matrix about the size of a 16k-bit PROM. With a typical I_{CC} of 250mA, it features maximum input to output delays of 18/26ns over the commercial temperature range, reflecting respectively single and double passes through the NAND array. Assuming a conservative "interconnect" factor of 20%, the PLHS501 has a density roughly equivalent to 1,500 2-input NAND gates.

The PLHS501 is the first member of a growing family of devices slated for future introduction. Built with either Bipolar or Erasable CMOS technologies, these will incorporate sets of higher level macros, leading to devices with greater logic power and a more efficient utilization of the on-chip interconnect system.

Signetics

Application Specific Products
- **PML Series 52**

PLHS502
Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24)

Objective Specification

DESCRIPTION

The PLHS502 is a member of the Signetics Programmable Macro Logic family. PML is unique in its capability of performing other than two level logic functions without incurring I/O buffer delays. This allows the logic or system designer to imbed logical operations or macro structures such as registers within the framework of the I/O pins. Since the imbedded functions are independent of the delays created by the I/O buffers, they can be performed at speeds lesser architectures cannot reproduce.

The PLHS502 features a unique clock matrix that allows the user to individually connect each of the 16 buried registers to any of 8 different clock sources. The output $\overline{Q}$ of the 8D type and 8 S-R type registers is internally feedback to the NAND array. In addition the output Q of each register is internally feedback to both the NAND array and the clock array. Thus the PML architecture eliminates the requirement of utilizing external I/O pins for register feedback paths. The PLHS502 is therefore ideally suited for both Synchronous and Asynchronous State Machines as well as event driven controller functions.

The technique used to perform this operation is a NAND foldback network which allows the direct interconnection of any number of logic nodes within the single fuse matrix. Macros can be formed and then interconnected to the I/O structure. In addition, single level and multiple level logic can be performed at speeds which reflect only the logic path utilized. Therefore, a single-level logic function has a very short path through the device. Additional levels incur only one NAND foldback delay per level. This delay is less than the combined delay created by previous generations of devices which stipulate that the logic signal must pass through I/O buffers after one or two levels of logic are performed.

The PLHS502 is fabricated in Signetics ZA Oxide-Isolated Bipolar Process which utilizes Vertical Avalanche Migration Programmed (VAMP^{TM}) Fuses as programming elements. These fuses provide high programming yield and reliability. Proprietary onboard test circuitry allows the PLHS502 to be thoroughly tested prior to programming.

FEATURES

- **Signetics NAND foldback architecture**
- **Field-Programmable**
- **20 dedicated inputs**
- **4 input/clock pins**
- **16 buried registers**
  - **8 D type**
  - **8 S-R type**
- **8 individual clocks**
  - **4 from dedicated input/clock pins**
  - **4 from NAND array**
- **8 bidirectional I/O**
- **16 dedicated outputs**
  - **8 Active-High outputs**
  - **4 outputs with polarity control**
  - **4 Tri-statable outputs with polarity control**
- **64 internal NAND foldback terms**
- **Logic delay times:**
  - **Single level = 22ns (max.)**
  - **Two logic levels = 30ns (max.)**
  - **Each additional internal NAND delay = 8ns (max.)**
  - **Maximum operating frequency f_{MAX} = 35MHz**
- **Supported by AMAZE Development System**
- **Testable in unprogrammed state**
- **Verify Lock Fuse**
- **TTL compatible**
- **Power dissipation: 1.25W (typ.)**

APPLICATIONS

- **Any digital function requiring more than 2 levels of logic**
- **Systems requiring state/controller functions in conjunction with random logic**
- **Asynchronous state machines**
- **Event-driven state machines**
- **Logic sequencers**
- **Ripple counters**

PIN CONFIGURATION

A Package (52-Pin PLCC)



TOP VIEW

CD11940S

Pin No.		Pin No.	
1	I_{11}	27	O_3
2	I_{12}	28	O_4
3	I_{13}	29	O_5
4	I_{14}	30	O_6
5	I_{15}	31	O_7
6	I_{16}	32	O_8
7	I_{17}	33	O_9
8	V_{CC}	34	GND
9	I_{18}	35	O_{10}
10	I_{19}	36	O_{11}
11	I_{20}/CLK	37	O_{12}
12	I_{21}/CLK	38	O_{13}
13	$I_{22}/\overline{CLK}$	39	O_{14}
14	$I_{23}/\overline{CLK}$	40	O_{15}
15	/B0	41	I_0
16	/B1	42	I_1
17	/B2	43	I_2
18	/B3	44	I_3
19	/B4	45	I_4
20	GND	46	V_{CC}
21	/B5	47	I_5
22	/B6	48	I_6
23	/B7	49	I_7
24	O_0	50	I_8
25	O_1	51	I_9
26	O_2	52	I_{10}

---

*Patent Pending

Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24)

PLHS502

FUNCTIONAL DIAGRAM


(x8)
$\overline{B}_0$–$\overline{B}_7$
(x4)
O_{12}–O_{15}
(x4)
O_8–O_{11}
(x8)
O_0–O_7
DETAIL A
DETAIL B
15
0
Q
(8)
$\overline{Q}$
D
CLR
8
Q
(8)
$\overline{Q}$
S
R
CLR
8
0
1
62
63
(x20)
(x2)
(x2)
I_0–I_{19}
I_{20}/CLK, I_{21}/CLK
I_{22}/$\overline{CLK}$, I_{23}/$\overline{CLK}$
LD07671S

Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24)

PLHS502



Detail A

PROGRAMMABLE MACRO LOGIC

The architectures of current Programmable Logic Devices (PLDs) generally employ programmable AND-OR gate strings to permit implementing logic functions directly in Sum-of-Products form (SOP). Often, that becomes a bottleneck which interferes with the efficient allocation of the on-chip logic resources. This becomes very apparent when considering very dense PLDs in high pin-count packages.

PML is a novel architecture which breaks the AND-OR bottleneck by relying instead on a single NAND-gate array to implement SOP logic functions, and to provide a central programmable "interconnect" site supporting a periphery of multi-level macros on a chip.

INTRODUCTION

Today, system designers in a rush to bring their products to market are turning more than ever toward Programmable Logic Devices, lured by their blend of design elegance and efficiency with instant custom flexibility despite limitations in density and architecture.

To be sure, dramatic advances in Bipolar and CMOS processing technologies over the last decade have spawned denser and faster elements, with an occasional twist in architecture. Nevertheless, the structure of most current PLDs is still anchored on a fixed AND-OR gate chain linking primitive input, output, and function macros on a chip. Recently, to enhance the flexibility and design adaptability of early product offerings, denser devices have been introduced featuring logic macros with local programmable options and bypass circuitry.

However, as densities continue to increase, this approach is sure to breed devices with an overwhelming architectural maze which is altogether difficult to design, comprehend, and logically manipulate, complicating rather than simplifying their application.



Detail B



Figure 1. General PML Architecture Based on a Central Programmable "Interconnect" System Interlocking Peripheral Macros



Figure 2. Typical SOP Function With Elementary AND-OR Gates

PML, however, consists of various logic "access" and "process" macros coupled via a primitive, central programmable structure in the on-chip "interconnect" system (see Figure 1). Macros can have various local intelligence which, in turn, may be fixed or variable by means of programmable options also embedded in the central programmable core.

Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24)

PLHS502

AND-OR PLD ARCHITECTURE

From a fundamental theorem of Boolean algebra, any combinational logic function can be expressed in Sum-of-Products form involving only two levels of logic transformation. Such functions can be implemented in hardware by chaining two primitive logic macros as indicated in Figure 2.

The outputs of an AND-OR gate chains can be interlaced with higher level macros, such as flip-flops, to form sequential logic functions. These may be further combined into standard or custom super-macros which, in turn, are interwoven into final system configurations. Presently, a number of PLDs are available which contain fixed sets of logic macros with programmable connections. Invariably, their architectures are anchored on a pair of concatenated AND-OR gate arrays, as diagrammed in Figure 3, to permit implementing logic functions directly in SOP form.

Virtually all PLDs fall in three main categories: PROM, Fixed OR, and PLA. As illustrated in Figure 4, these differ primarily in the programmability of the AND-OR gate chain which, by being irrevocably interposed as a two-level logic link between on-chip macros and I/O paths, often can turn into a design liability.

For example, in PROMs the exponential increase in AND array size with number of inputs is a severe drawback which limits their contention in the logic application arena.

In fixed OR devices, the fixed inputs to the OR array confine their architectures to essentially a composite of AND-OR, AND-OR-register logic slices defining independent I/O paths through the chip. This causes duplication of common product terms, and waste of unused AND gates in each slice. Also, since each slice is dedicated to an output pin, devices with registered, programmable I/O pins entail an even greater waste of on-chip logic resources when configured in register-bypass or fixed input modes. Moreover, no single level logic functions can be constructed, except dedicated on-chip control functions.

Finally, even as the twin programmability of the AND-OR arrays in current PLA-type devices lends greater flexibility, and may circumvent some of the above problems, it does pose difficult process, design and performance compromises in migrating toward more dense structures.

Thus, on the whole, the AND-OR gate chain forms a bottleneck which can impair the fragmentation and reallocation of the on-chip logic resources, curtailing the adaptability and efficiency of current PLDs in applications involving unstructured algorithms and scattered logic functions.



Figure 3. Basic Architecture of Current PLDs



a. PROM: Programmable OR



b. PAL*: Programmable AND



c. PLA: Programmable AND-OR

Figure 4. Programmable AND-OR Chain of Current PLDs

---

*PAL is a registered trademark of Monolithic Memories, Inc.

Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24)

PLHS502

NAND-NAND GATE EQUIVALENCE

One way of relieving the burden placed on PLDs' architecture by the AND-OR gate string is to do away with it altogether, and replace it with a new programmable structure forged out of a new compromise on silicon between "interconnect" redundancy and ease of design and application. The approach adopted for PML is based on the fundamental equivalence between two-level AND-OR and NAND-NAND gate constructs in expressing combinatorial logic functions in SOP form, as illustrated in Figure 5.

Since programmable NAND-NAND logic chains can be formed by coupling identical NAND gates with programmable inputs, the NAND-array string in Figure 6 can be implemented as a single global array with feedback.

A basic NAND-array core linking a periphery of primitive macros is shown in Figure 7. When the feedback path is just a simple wire, the NAND-array can be fragmented into single-level or double-level true/complement logic functions by programming respectively single (a-c-d), or double (a-b-c-d), interconnecting paths through the array from inputs I to output F.

More complex functions can be implemented by programming multi-level logic loops through the array.



$Y = \overline{C * D} \quad X = \overline{A * B}$

$F = \overline{X * Y} = \overline{(\overline{A * B}) * (\overline{C * D})}$

$F = (\overline{\overline{A * B}}) + (\overline{\overline{C * D}})$

$\boxed{F = A * B + C * D}$

LD06800S

Figure 5. Equivalent NAND-NAND SOP Expression



AF04450S

Figure 6. NAND-NAND Gate Chain Compressed Into a Single Array With Feedback



LD06810S

Figure 7. Elementary NAND Array Linking Primitive Macros. Note That No Programmable Connection is Implied at a Cross of a Solid Line With a Dotted Line

Programmable Macro Logic Sync/Async Register Macro Unit (32 × 64 × 24)

PLHS502

BASIC PML ARCHITECTURE

The primitive NAND core can be expanded to support at its periphery a structure of logic macros of growing size and complexity, including various types of flip-flops, EX-OR gates, buffers, counters, shift registers, multiplexers, decoders, arithmetic/logic units, memories, etc. As illustrated in the general structure of Figure 8, I/O macros would provide off-chip paths to the outside world, while FUNCTION macros looped about the array would provide the necessary logic processing capability.

In deference to trade-offs in functionality and speed imposed by the array size and loading, Type-1 Output (or Function) macros may be driven directly from NAND gates, while Type-2 macros may be driven by gates first looped through the array. There are virtually no limits to the number, size, and functionality of the on-chip macros surrounding the central core, other than those imposed by processing and packaging capabilities.

The main design advantage of PML is that it relies upon a single array to interconnect all macros. This reduces the design task to that of building essentially a PROM-like programmable structure more forgiving than the double array in PLA-type devices, and more flexible than that in fixed OR devices. Also, the ability to forge the NAND core into multi-level logic paths at will increases the usage efficiency of the on-chip logic resources, and greatly enhances the versatility of PML in most applications.

THE FIRST PML OFFERING

The first PML device, designated PLHS501, is primarily a combinational logic device including only primitive macros. It is a ''gate bucket'' whose deceptively simple structure can implement virtually all logic functions provided by existing combinational PAL/PLA-type devices. Also, it is the first to provide true EX-OR output functions (in addition to output polarity inversion), as well as multi-level gate constructs and cross-coupled latches on-chip without involving output pins. These are shown in Figure 9.

Built with Signetics' proprietary ZA oxide isolation process, and vertical fuses, the PLHS501 has a NAND matrix about the size of a 16k-bit PROM. With a typical I_{CC} of 250mA, it features maximum input to output delays of 18/26ns over the commercial temperature range, reflecting respectively single and double passes through the NAND array. Assuming a conservative ''interconnect'' factor of 20%, the PLHS501 has a density roughly equivalent to 1,500 2-input NAND gates.

The PLHS501 is the first member of a growing family of devices slated for future introduction. Built with either Bipolar or Erasable CMOS technologies, these will incorporate sets of higher level macros, leading to devices with greater logic power and a more efficient utilization of the on-chip interconnect system.

Signetics

Section 4
PLD Data Sheets

Application Specific Products

INDEX

Section 4 – PLD Data Sheets

Series 20

PLS151 Field-Programmable Gate Array (18 × 15 × 12) 4-3
PLS153 Field-Programmable Logic Array (18 × 42 × 10) 4-9
PLS153A Field-Programmable Logic Array (18 × 42 × 10) 4-15
PLHS153 Field-Programmable Logic Array (18 × 42 × 10) 4-21
PLS155 Field-Programmable Logic Sequencer (16 × 45 × 12).. 4-27
PLS157 Field-Programmable Logic Sequencer (16 × 45 × 12).. 4-37
PLS159 Field-Programmable Logic Sequencer (16 × 45 × 12).. 4-47
PLS159A Field-Programmable Logic Sequencer (16 × 45 × 12).. 4-57
PLHS18P8A Programmable AND Array Logic (18 × 72 × 8).......... 4-67

Signetics

PLS151
Field-Programmable Gate Array (18 × 15 × 12)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 20

DESCRIPTION

The PLS151 is a single level logic element, consisting of 15 AND gates with fusible link connections for programming I/O polarity, I/O direction and output enable control.

All gates are linked to 6 inputs (I) and 12 bidirectional I/O lines (B). These yield variable I/O gate configurations via 3 direction control gates (D), ranging from 18 inputs to 12 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to each AND gate. The polarity of all gate outputs is individually programmable through a set of EX-OR gates for implementing AND/NAND logic functions. Alternately, if desired, OR/NOR logic functions can also be realized by programming for each gate the complement of its inputs and outputs (DeMorgan's Theorem).

The PLS151 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **6 inputs**
- **15 product terms:**
  - **12 logic terms**
  - **3 control terms**
- **12 bidirectional I/O lines**
- **Active-High or -Low outputs**
- **Programmable output enable**
- **Power dissipation: 575mW (typ.)**
- **I/O propagation delay: 25ns (max.)**
- **Input loading: −100μA (max.)**
- **TTL compatible**
- **Tri-state outputs**

APPLICATIONS

- **Random gating functions**
- **Address decoding**
- **Code detectors**
- **Memory mapped I/O**
- **Fault monitors**
- **I/O port decoders**

FUNCTIONAL DIAGRAM



G11
G0
D0-2
I0
I1
I5
X11
X0
B11
B0
LD01710S

All Ni-Cr links are initially intact.

PIN CONFIGURATIONS



N Package
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
B0 7
B1 8
B2 9
GND 10
20 VCC
19 B11
18 B10
17 B9
16 B8
15 B7
14 B6
13 B5
12 B4
11 B3
CD04540S

N = Plastic



A Package
I2 I1 I0 VCC B11
3 2 1 20 19
I3 4
I4 5
I5 6
B0 7
B1 8
18 B10
17 B9
16 B8
15 B7
14 B6
9 10 11 12 13
B2 GND B3 B4 B5
CD04550S

A = Plastic Leaded Chip Carrier

LOGIC FUNCTION

TYPICAL OUTPUT FUNCTIONS:
ACTIVE-HIGH

$$X = A \cdot \overline{B} \cdot C \cdot \ \ldots$$

ACTIVE-LOW

$$X = \overline{A \cdot \overline{B} \cdot C \cdot} \ \ldots$$
$$X = \overline{A} + B + \overline{C} + \ \ldots$$

NOTES:
1. For each of the 12 outputs, either function X (Active-High) or $\overline{X}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. X, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

Field-Programmable Gate Array (18 × 15 × 12)

FPGA LOGIC DIAGRAM


(LOGIC GATES—G)
(CONTROL GATES)
11 10 9 8 7 6 5 4 3 2 1 0
D2 D1 D0
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
B11
B10
B9
B8
B7
B6
B5
B4
B3
B2
B1
B0
X11 X10 X9 X8 X7 X6 X5 X4 X3 X2 X1 X0
D2 D1 D0
S3 S2 S1 S0
S7 S6 S5 S4
S11 S10 S9 S8
7 B0
8 B1
9 B2
11 B3
12 B4
13 B5
14 B6
15 B7
16 B8
17 B9
18 B10
19 B11
LD02270S

NOTES:

1. All gate inputs with a blown link float to a logic "1".
2. ▨ Programmable connection.

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLS151N
20-pin Plastic Leaded Chip Carrier	PLS151A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING[1]		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			0.8	V
V_{IH}	High	V_{CC} = Max	2.0			
V_{IC}	Clamp[3,4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OL}	Low	I_{OL} = 10mA			0.5	V
V_{OH}	High	I_{OH} = −2mA	2.4			
Input current[7]						
		V_{CC} = Max				
I_{IL}	Low	V_{IN} = 0.45V			−100	µA
I_{IH}	High	V_{IN} = 5.5V			40	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state	V_{OUT} = 5.5V			80	µA
		V_{OUT} = 0.45V			−140	
I_{OS}	Short circuit[4,5]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current	V_{CC} = Max		115	155	mA
Capacitance						
		V_{CC} = 5V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_B	I/O	V_B = 2.0V		15		

Notes on following page.

Field-Programmable Gate Array (18 × 15 × 12)

PLS151

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ[2]	Max	
t_{PD}	Propagation delay	Output ±	Input ±	$C_L = 30pF$		16	25	ns
t_{OE}	Output enable	Output –	Input ±			17	25	ns
t_{OD}	Output disable[6]	Ouput +	Input ±	$C_L = 5pF$		17	25	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other conditions above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one pin at a time.
5. Duration of short circuit should not exceed 1 second.
6. Measured at $V_T = V_{OL} + 0.5V$.
7. I_{IL} and I_{IH} limits are for dedicated inputs only ($I_O - I_S$).

TEST LOAD CIRCUIT


VCC
I0
I5
BW
BX
BY
BZ
GND
+5V
R1
R2
CL
INCLUDES SCOPE AND JIG CAPACITANCE
TC02000S

TIMING DIAGRAM


I, B
1.5V
1.5V
1.5V
+3V
0V
B
1.5V
VT
VOH
1.5V
VOL
tPD
tOD
tOE
WF05411S

TIMING DEFINITIONS

t_{PD}	Propagation delay between input and output.
t_{OD}	Delay between input change and when output is off (Hi-Z or High).
t_{OE}	Delay between input change and when output reflects specified output level.

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Gate Array (18 × 15 × 12)

PLS151

LOGIC PROGRAMMING

In a virgin device all Ni-Cr links are intact.

The FPGA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this Table the logic state of variables I and B associated with each gate G_n, D_n is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. All outputs at 'H' polarity.
2. All P_n terms are disabled.
3. All P_n terms are active on all outputs.
4. All B terms are I/O unless otherwise programmed.

I/O DIRECTION – (B)



DIRECTION	CODE
I/O [1]	A

LD01731S



DIRECTION	CODE
INPUT	•

LD01740S

OUTPUT POLARITY – (B)



ACTIVE LEVEL	CODE
HIGH[1]	H

LD01751S



ACTIVE LEVEL	CODE
LOW	L

LD01760S

"AND" ARRAY – (I, B)



STATE	CODE
INACTIVE[1,2]	O

LD01770S



STATE	CODE
I, B	H

LD01780S



STATE	CODE
$\bar{I}$, $\bar{B}$	L

LD01790S



STATE	CODE
DON'T CARE	-

LD01800S

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate P_n will be unconditionally inhibited if both the true and complement of an input (either I or B) are left intact.

FPGA PROGRAM TABLE

CUSTOMER NAME ____
PURCHASE ORDER # ____
SIGNETICS DEVICE # ____ CF (XXXX) ____
CUSTOMER SYMBOLIZED PART # ____
TOTAL NUMBER OF PARTS ____
PROGRAM TABLE # ____ REV ____ DATE ____

NOTES

1. The FPGA is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Unused I and B bits are normally programmed Don't Care (–).
3. Unused Gates can be left blank.
4. Disregard Polarity for Gates used only as inputs.

CONTROL

HIGH	H	(POL.)
LOW	L	
I/O	A	(DIR.)
INPUT	●	

AND

INACTIVE	0	I, B
I, B	H	
$\bar{I}$, $\bar{B}$	L	
Don't Care	–	

D2 = ____
G0 = ____
G1 = ____
G2 = ____
G3 = ____
D1 = ____
G4 = ____
G5 = ____
G6 = ____
G7 = ____
D0 = ____
G8 = ____
G9 = ____
G10 = ____
G11 = ____

PIN	GATE	DIR.	POL.	AND																	
				I						B (I)											
				5	4	3	2	1	0	11	10	9	8	7	6	5	4	3	2	1	0
	D2																				
7	00																				
8	01																				
9	02																				
11	03																				
	D1																				
12	04																				
13	05																				
14	06																				
15	07																				
	D0																				
16	08																				
17	09																				
18	10																				
19	11																				
		PIN		6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9	8	7
VARIABLE NAME																					

TB01720S

Signetics

PLS153

Field-Programmable Logic Array (18 × 42 × 10)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 20

DESCRIPTION

The PLS153 is a two-level logic element, consisting of 42 AND gates and 10 OR gates with fusible link connections for programming I/O polarity and direction.

All AND gates are linked to 8 inputs (I) and 10 bidirectional I/O lines (B). These yield variable I/O gate configurations via 10 direction control gates (D), ranging from 18 inputs to 10 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. Their output polarity, in turn, is individually programmable through a set of EX-OR gates for implementing AND/OR or AND/NOR logic functions.

The PLS153 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr links)**
- **8 inputs**
- **42 AND gates**
- **10 OR gates**
- **10 bidirectional I/O lines**
- **Active-High or -Low outputs**
- **42 product terms:**
  - **32 logic terms**
  - **10 control terms**
- **I/O propagation delay: 40ns (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 650mW (typ.)**
- **Tri-state outputs**
- **TTL compatible**

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

PIN CONFIGURATION



LOGIC FUNCTION

TYPICAL PRODUCT TERM:
Pn = A·B·C·D· . . .
TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
Z = P0 + P1 + P2 . . .

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +}$ . . .
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot$ . . .

NOTES:
1. For each of the 10 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

FUNCTIONAL DIAGRAM



Field-Programmable Logic Array (18 × 42 × 10) PLS153

FPLA LOGIC DIAGRAM


(LOGIC TERMS—P)
(CONTROL TERMS)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
B0
B1
B2
B3
B4
B5
B6
B7
B8
B9
D9 D8 D7 D6 D5 D4 D3 D2 D1 D0
S9 S8 S7 S6 S5 S4 S3 S2 S1 S0
X9 X8 X7 X6 X5 X4 X3 X2 X1 X0
19 B9
18 B8
17 B7
16 B6
15 B5
14 B4
13 B3
12 B2
11 B1
9 B0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
TB00943S

NOTES:

1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. ● Programmable connection.

Field-Programmable Logic Array (18 × 42 × 10) PLS153

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLS153N

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

The PLS153 device is also processed to military requirements for operation over the military temperature range. For specifications and ordering information consult the Signetics Military Data Book.

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			0.8	V
V_{IH}	High	V_{CC} = Max	2.0			
V_{IC}	Clamp[3,4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage						
		V_{CC} = Min				
V_{OL}	Low[3,5]	I_{OL} = 15mA			0.5	V
V_{OH}	High[3,6]	I_{OH} = −2mA	2.4			
Input current[11]						
		V_{CC} = Max				
I_{IL}	Low	V_{IN} = 0.45V			−100	µA
I_{IH}	High	V_{IN} = 5.5V			40	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[10]	V_{OUT} = 5.5V			80	µA
		V_{OUT} = 0.45V			−140	
I_{OS}	Short circuit[4,6,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		130	155	mA
Capacitance						
		V_{CC} = 5V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_B	I/O	V_B = 2.0V		15		

Notes on following page.

Field-Programmable Logic Array (18 × 42 × 10) PLS153

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ[2]	Max	
t_{PD}	Propagation delay	Output±	Input±	$C_L = 30pF$		30	40	ns
t_{OE}	Output enable	Output–	Input±	$C_L = 30pF$		25	35	ns
t_{OD}	Output disable[9]	Output+	Input±	$C_L = 5pF$		25	35	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other conditions above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with +10V applied to I_7.
6. Measured with +10V applied to I_{0-7}. Output sink current is supplied through a resistor to V_{CC}.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with I_0, I_1 at 0V, $I_2 - I_7$ and B_{0-9} at 4.5V.
9. Measured at $V_T = V_{OL} + 0.5V$.
10. Leakage values are a combination of input and output leakage.
11. I_{IL} and I_{IH} limits are for dedicated inputs only (I_0-I_7).

TEST LOAD CIRCUIT


V_{CC}
I_0
I_7
B_W
B_X
DUT
GND
B_Y
B_Z
+5V
R_1
R_2
C_L
INCLUDES SCOPE AND JIG CAPACITANCE
TC01602S

TIMING DIAGRAM


I, B
1.5V
1.5V
1.5V
+3V
0V
V_{OH}
B
1.5V
V_T
1.5V
V_{OL}
t_{PD}
t_{OD}
t_{OE}
WF05411S

TIMING DEFINITIONS

t_{PD}	Propagation delay between input and output.
t_{OD}	Delay between input change and when output is off (Hi-Z or High).
t_{OE}	Delay between input change and when output reflects specified output level.

VOLTAGE WAVEFORM


+3.0V
90%
10%
0V
5ns
t_r
t_f
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Array (18 × 42 × 10) PLS153

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this Table the logic state of variables I, P, and B associated with each Sum Term S is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

OUTPUT POLARITY – (B)


S
X
B
LS01950S

ACTIVE LEVEL	CODE
HIGH[1]	H


S
X
$\overline{B}$
LS01960S

ACTIVE LEVEL	CODE
LOW	L

"AND" ARRAY – (I, B)


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01990S

STATE	CODE
INACTIVE[1,2]	O


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS02000S

STATE	CODE
I, B	H


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01970S

STATE	CODE
$\overline{I}$, $\overline{B}$	L


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01980S

STATE	CODE
DON'T CARE	–

OR ARRAY – (B)


P
S
LS02010S

P_n STATUS	CODE
ACTIVE[1]	A


P
S
LS02020S

P_n STATUS	CODE
INACTIVE	•

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. All outputs at "H" polarity.
2. All P_n terms are disabled.
3. All P_n terms are active on all outputs.

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate P_n will be unconditionally inhibited if both the true and complement of an input (either I or B) are left intact.

Field-Programmable Logic Array (18 × 42 × 10) PLS153

FPLA PROGRAM TABLE

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # ____________ CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ________ REV ________ DATE ________

Notes

1. The FPLA is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table. (Shown BLANK for clarity.)
2. Unused I and B bits in the AND array must be programmed Don't Care (–).
3. Unused product terms can be left blank.

OR

B(O)	
ACTIVE	A
INACTIVE	•

CONTROL (POL)

HIGH	H
LOW	L

AND

I, B(I)	
INACTIVE	0
I, B	H
I, B̄	L
DON'T CARE	–

POLARITY

TERM	AND																		OR									
	I								B(I)										B(O)									
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0
0																												
1																												
2																												
3																												
4																												
5																												
6																												
7																												
8																												
9																												
10																												
11																												
12																												
13																												
14																												
15																												
16																												
17																												
18																												
19																												
20																												
21																												
22																												
23																												
24																												
25																												
26																												
27																												
28																												
29																												
30																												
31																												
D9																												
D8																												
D7																												
D6																												
D5																												
D4																												
D3																												
D2																												
D1																												
D0																												
PIN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9	19	18	17	16	15	14	13	12	11	9
VARIABLE NAME																												



TB00955S

Signetics

PLS153A
Field-Programmable Logic Array (18 × 42 × 10)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 20**

DESCRIPTION

The PLS153A is a two-level logic elements, consisting of 42 AND gates and 10 OR gates with fusible link connections for programming I/O polarity and direction.

All AND gates are linked to 8 inputs (I) and 10 bidirectional I/O lines (B). These yield variable I/O gate configurations via 10 direction control gates (D), ranging from 18 inputs to 10 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. Their output polarity, in turn, is individually programmable through a set of EX-OR gates for implementing AND/OR or AND/NOR logic functions.

The PLS153A is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr links)**
- **8 inputs**
- **42 AND gates**
- **10 OR gates**
- **10 bidirectional I/O lines**
- **Active-High or -Low outputs**
- **42 product terms:**
  - **32 logic terms**
  - **10 control terms**
- **I/O propagation delay: 30ns (max.)**
- **Input loading: −100µA (max.)**
- **Power dissipation: 650mW (typ.)**
- **Tri-state outputs**
- **TTL compatible**

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

PIN CONFIGURATIONS

N Package



I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
B0 9
GND 10
20 VCC
19 B9
18 B8
17 B7
16 B6
15 B5
14 B4
13 B3
12 B2
11 B1
CD04680S

N = Plastic

A Package



I2 3
I1 2
I0 1
VCC 20
B9 19
I3 4
I4 5
I5 6
I6 7
I7 8
18 B8
17 B7
16 B6
15 B5
14 B4
9 B0
10 GND
11 B1
12 B2
13 B3
CD04690S

A = Plastic Leaded Chip Carrier

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
Pn = A · B · C · D · . . .
TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
Z = P0 + P1 + P2 . . .

AT OUTPUT POLARITY = L
Z = $\overline{P0 + P1 + P2 +}$ . . .
Z = $\overline{P0} \cdot \overline{P1} \cdot \overline{P2}$ . . .

NOTES:
1. For each of the 10 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

FUNCTIONAL DIAGRAM



P31
P0
D0
D9
I0
I7
B0
B9
S9
S0
X9
X0
B9
B0
AF01832S

Field-Programmable Logic Array (18 × 42 × 10) PLS153A

FPLA LOGIC DIAGRAM


(LOGIC TERMS—P)
(CONTROL TERMS)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
B0
B1
B2
B3
B4
B5
B6
B7
B8
B9
D9 D8 D7 D6 D5 D4 D3 D2 D1 D0
S9 X9
S8 X8
S7 X7
S6 X6
S5 X5
S4 X4
S3 X3
S2 X2
S1 X1
S0 X0
19 B9
18 B8
17 B7
16 B6
15 B5
14 B4
13 B3
12 B2
11 B1
9 B0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
TB00943S

NOTES:
1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. ▨ Programmable connection.

Field-Programmable Logic Array (18 × 42 × 10) PLS153A

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLS153AN
20-pin Plastic Leaded Chip Carrier	PLS153AA

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING Min	RATING Max	UNIT
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS Min	LIMITS Typ[2]	LIMITS Max	UNIT
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			0.8	V
V_{IH}	High	V_{CC} = Max	2.0			
V_{IC}	Clamp[3,4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage						
		V_{CC} = Min				
V_{OL}	Low[3,5]	I_{OL} = 15mA			0.5	V
V_{OH}	High[3,6]	I_{OH} = −2mA	2.4			
Input current[11]						
		V_{CC} = Max				
I_{IL}	Low	V_{IN} = 0.45V			−100	µA
I_{IH}	High	V_{IN} = 5.5V			40	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[10]	V_{OUT} = 5.5V			80	µA
		V_{OUT} = 0.45V			−140	
I_{OS}	Short circuit[4,6,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		130	155	mA
Capacitance						
		V_{CC} = 5V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_B	I/O	V_B = 2.0V		15		

Notes on following page.

Field-Programmable Logic Array (18 × 42 × 10) PLS153A

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $0°C \leq T_A \leq +75°C$, $4.75V \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ[2]	Max	
t_{PD}	Propagation delay	Output±	Input±	$C_L = 30pF$		20	30	ns
t_{OE}	Output enable	Output±	Input±	$C_L = 30pF$		20	30	ns
t_{OD}	Output disable[9]	Output±	Input±	$C_L = 5pF$		20	30	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other conditions above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with +10V applied to I_7.
6. Measured with +10V applied to I_{0-7}. Output sink current is supplied through a resistor to V_{CC}.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with $I_{0,1}$ at 0V and I_{2-7} and B_{0-9} at 4.5V.
9. Measured at $V_T = V_{OL} + 0.5V$.
10. Leakage values are a combination of input and output leakage.
11. I_{IH} and I_{IL} limits are for dedicated inputs only (I_0-I_9).

TEST LOAD CIRCUIT


V_CC
I_0
I_7
B_W
B_X
DUT
B_Y
B_Z
GND
+5V
R_1
R_2
C_L
INCLUDES SCOPE AND JIG CAPACITANCE
TC01602S

TIMING DIAGRAM


I, B
1.5V
1.5V
1.5V
+3V
0V
B
1.5V
V_T
V_OH
1.5V
V_OL
t_PD
t_OD
t_OE
WF05411S

TIMING DEFINITIONS

t_{PD}	Propagation delay between input and output.
t_{OD}	Delay between input change and when output is off (Hi-Z or High).
t_{OE}	Delay between input change and when output reflects specified output level.

VOLTAGE WAVEFORM


+3.0V
90%
10%
0V
5ns
t_r
t_f
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Array (18 × 42 × 10) PLS153A

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this Table the logic state of variables I, P, and B associated with each Sum Term S is assigned a symbol which results in the proper fusing pattern of corresponding links, defined as follows:

OUTPUT POLARITY – (B)


S
X
B
LS01950S

ACTIVE LEVEL	CODE
HIGH[1]	H


S
X
$\overline{B}$
LS01960S

ACTIVE LEVEL	CODE
LOW	L

"AND" ARRAY – (I, B)


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01990S

STATE	CODE
INACTIVE[1,2]	O


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS02000S

STATE	CODE
I, B	H


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01970S

STATE	CODE
$\overline{I}$, $\overline{B}$	L


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01980S

STATE	CODE
DON'T CARE	–

OR ARRAY – (B)


P
S
LS02010S

P_n STATUS	CODE
ACTIVE[1]	A


P
S
LS02020S

P_n STATUS	CODE
INACTIVE	•

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate P_n will be unconditionally inhibited if both the true and complement of an input (either I or B) are left intact.

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. All outputs at "H" polarity.
2. All P_n terms are disabled.
3. All P_n terms are active on all outputs.

CAUTION: PLS153A TEST COLUMNS

The PLS153A incorporates two columns not shown in the logic block diagram. These columns are used for in-house testing of the device in the unprogrammed state. These columns must be disabled prior to using the PLS153A in your application. If you are using a Signetics-approved programmer the disabling is accomplished during the device programming sequence. If these columns are not disabled, abnormal operation is possible.

Furthermore, because of these test columns, the PLS153A cannot be programmed using the programmer algorithm for the PLS153.

Field-Programmable Logic Array (18 × 42 × 10) PLS153A

FPLA PROGRAM TABLE

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # ____________ CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ______ REV ______ DATE

Notes

1. The FPLA is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table. (Shown BLANK for clarity.)
2. Unused I and B bits in the AND array must be programmed Don't Care (–).
3. Unused product terms can be left blank.

AND

I, B(I)	
INACTIVE	0
I, B	H
$\bar{I}$, $\bar{B}$	L
DON'T CARE	–

OR

B(0)	
ACTIVE	A
INACTIVE	•

CONTROL

(POL)	
HIGH	H
LOW	L

																				POLARITY									
TERM	AND																			OR									
									B(I)											B(0)									
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0
0																													
1																													
2																													
3																													
4																													
5																													
6																													
7																													
8																													
9																													
10																													
11																													
12																													
13																													
14																													
15																													
16																													
17																													
18																													
19																													
20																													
21																													
22																													
23																													
24																													
25																													
26																													
27																													
28																													
29																													
30																													
31																													
D9																													
D8																													
D7																													
D6																													
D5																													
D4																													
D3																													
D2																													
D1																													
D0																													
PIN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9
VARIABLE NAME																													

TB00955S

Signetics

PLHS153

Field-Programmable Logic Array (18 × 42 × 10)

Signetics Programmable Logic
Preliminary Specification

Application Specific Products
- **Series 20**

DESCRIPTION

The PLHS153 is a high-speed version of the PLS153 and PLS153A FPLAs. The Signetics state-of-the-art Oxide Isolated Bipolar fabrication process is employed to produce performance levels not yet achieved in devices of this complexity.

The PLHS153 is a two-level logic elements, consisting of 42 AND gates and 10 OR gates with fusible link connections for programming I/O polarity and direction.

All AND gates are linked to 8 inputs (I) and 10 bidirectional I/O lines (B). These yield variable I/O gate configurations via 10 direction control gates (D), ranging from 18 inputs to 10 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. Their output polarity, in turn, is individually programmable through a set of EX-OR gates for implementing AND/OR or AND/NOR logic functions.

The PLHS153 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

FEATURES

- **Field-Programmable**
- **Functionally identical to PLS153/153A**
- **8 inputs**
- **42 AND gates**
- **10 OR gates**
- **10 bidirectional I/O lines**
- **Active-High or -Low outputs**
- **42 product terms:**
  - **32 logic terms**
  - **10 control terms**
- **I/O propagation delay: 20ns (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 650mW (typ.)**
- **Tri-state outputs**
- **TTL compatible**

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

PIN CONFIGURATIONS

N Package



N = Plastic

A Package



A = Plastic Leaded Chip Carrier

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
Pn = A · B · C · D · . . .

TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
Z = P0 + P1 + P2 . . .

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +}$ . . .
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2}$ . . .

NOTES:
1. For each of the 10 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

FUNCTIONAL DIAGRAM



Field-Programmable Logic Array (18 × 42 × 10) PLHS153

FPLA LOGIC DIAGRAM


(LOGIC TERMS—P)
(CONTROL TERMS)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
B0
B1
B2
B3
B4
B5
B6
B7
B8
B9
D9 D8 D7 D6 D5 D4 D3 D2 D1 D0
S9 S8 S7 S6 S5 S4 S3 S2 S1 S0
X9 X8 X7 X6 X5 X4 X3 X2 X1 X0
19 B9
18 B8
17 B7
16 B6
15 B5
14 B4
13 B3
12 B2
11 B1
9 B0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
TB00943S

NOTES:
1. All unprogrammed or virgin "AND" gate locations are pulled to logic "1".
2. All unprogrammed or virgin "OR" gate locations are pulled to logic "0".
3. ● Programmable connection.

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLHS153N
20-pin Plastic Leaded Chip Carrier	PLHS153A

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
 T_A T_{STG}	Temperature range Operating Storage	 0 −65	 +75 +150	°C

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

The PLHS153 device is also processed to military requirements for operation over the military temperature range. For specifications and ordering information consult the Signetics Military Data Book.

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			0.8	V
V_{IH}	High	V_{CC} = Max	2.0			
V_{IC}	Clamp[3,4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage						
V_{OL}	Low[3,5]	V_{CC} = Min I_{OL} = 15mA			0.5	V
V_{OH}	High[3,6]	I_{OH} = −2mA	2.4			
Input current[11]						
I_{IL}	Low	V_{CC} = Max V_{IN} = 0.45V			−100	µA
I_{IH}	High	V_{IN} = 5.5V			40	
Output current						
$I_{O(OFF)}$	Hi-Z state[10]	V_{CC} = Max V_{OUT} = 5.5V V_{OUT} = 0.45V			80 −140	µA
I_{OS}	Short circuit[4,6,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		130	155	mA
Capacitance						
C_{IN}	Input	V_{CC} = 5V V_{IN} = 2.0V		8		pF
C_B	I/O	V_B = 2.0V		15		

Notes on following page.

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ[2]	Max	
t_{PD}	Propagation delay	Output±	Input±	$C_L = 30pF$		14	20	ns
t_{OE}	Output enable	Output–	Input±	$C_L = 30pF$		16	20	ns
t_{OD}	Output disable[9]	Output+	Input±	$C_L = 5pF$		14	20	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other conditions above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with +10V applied to I_5.
6. Output sink current is supplied through a resistor to V_{CC}.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with all pins = open or 4.5V.
9. Measured at $V_T = V_{OL} + 0.5V$.
10. Leakage values are a combination of input and output leakage.
11. I_{IL} and I_{IH} limits are for dedicated inputs only (I_0-I_7).

TEST LOAD CIRCUIT


V_CC
I_0
I_7
B_W
B_X
DUT
GND
B_Y
B_Z
+5V
R_1
R_2
C_L
INCLUDES SCOPE AND JIG CAPACITANCE
TC01602S

TIMING DIAGRAM


I, B
1.5V
1.5V
1.5V
+3V
0V
B
1.5V
V_T
1.5V
V_OH
V_OL
t_PD
t_OD
t_OE
WF05411S

TIMING DEFINITIONS

t_{PD}	Propagation delay between input and output.
t_{OD}	Delay between input change and when output is off (Hi-Z or High).
t_{OE}	Delay between input change and when output reflects specified output level.

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
t_r
t_f
2.5ns
2.5ns
+3.0V
0V
90%
10%
2.5ns
2.5ns
WF05391S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Array (18 × 42 × 10) PLHS153

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this Table the logic state of variables I, P, and B associated with each Sum Term S is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

OUTPUT POLARITY – (B)


S
X
B
LS01950S

ACTIVE LEVEL	CODE
HIGH	H


S
X
$\bar{B}$
LS01960S

ACTIVE LEVEL	CODE
LOW[1]	L

"AND" ARRAY – (I, B)


I,B
I,B
$\bar{I},\bar{B}$
P,D
LS01990S

STATE	CODE
INACTIVE[2]	O


I,B
I,B
$\bar{I},\bar{B}$
P,D
LS02000S

STATE	CODE
I, B	H


I,B
I,B
$\bar{I},\bar{B}$
P,D
LS01970S

STATE	CODE
$\bar{I}$, $\bar{B}$	L


I,B
I,B
$\bar{I},\bar{B}$
P,D
LS01980S

STATE	CODE
DON'T CARE[1]	–

OR ARRAY – (B)


P
S
LS02010S

P_n STATUS	CODE
ACTIVE	A


P
S
LS02020S

P_n STATUS	CODE
INACTIVE[1]	•

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. All outputs at "L" polarity.
2. All P_n terms are enabled.
3. All P_n terms are inactive on all outputs.

NOTES:

1. This is the initial unprogrammed state of all links. It is normally associated with all unused (inactive) AND gates P_n, D_n.
2. Any gate P_n will be unconditionally inhibited if both the true and complement of an input (either I or B) are programmed for a connection.

Field-Programmable Logic Array (18 × 42 × 10) PLHS153

FPLA PROGRAM TABLE

CUSTOMER NAME ____
PURCHASE ORDER # ____
SIGNETICS DEVICE # ____ CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____
TOTAL NUMBER OF PARTS ____
PROGRAM TABLE # ____ REV ____ DATE ____

Notes
1. The FPLA is shipped with all links open.
2. Unused I and B bits in the AND array exist as Don't Care (-) in the virgin state.
3. All P-terms are inactive on all outputs (B,O) in the virgin array.
4. Unused product terms can be left blank.

AND

INACTIVE	0	I, B (I)
I, B	H	
Ī, B̄	L	
DON'T CARE	–	

OR

ACTIVE	A	B(O)
INACTIVE	•	

CONTROL

HIGH	H	(POL)
LOW	L	

																			POLARITY									
TERM	AND																		OR									
									B(I)										B(O)									
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0
0																												
1																												
2																												
3																												
4																												
5																												
6																												
7																												
8																												
9																												
10																												
11																												
12																												
13																												
14																												
15																												
16																												
17																												
18																												
19																												
20																												
21																												
22																												
23																												
24																												
25																												
26																												
27																												
28																												
29																												
30																												
31																												
D9																												
D8																												
D7																												
D6																												
D5																												
D4																												
D3																												
D2																												
D1																												
D0																												
PIN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9	19	18	17	16	15	14	13	12	11	9
VARIABLE NAME																												

TB00955S

Signetics

PLS155

Field-Programmable Logic Sequencer (16 × 45 × 12)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 20**

DESCRIPTION

The PLS155 is a Tri-state output, registered logic element combining AND/OR gate arrays with clocked J-K flip-flops. These J-K flip-flops are dynamically convertible to D-type via a "fold-back" inverting buffer and control gate F_C. It features 4 registered I/O outputs (F) in conjunction with 8 bidirectional I/O lines (B). These yield variable I/O gate and register configurations via control gates (D, L) ranging from 16 inputs to 12 outputs.

The AND/OR arrays consist of 32 logic AND gates, 13 control AND gates, and 21 OR gates with fusible link connections for programming I/O polarity and direction. All AND gates are linked to 4 inputs (I), bidirectional I/O lines (B), internal flip-flop outputs (Q), and Complement Array output ($\overline{C}$). The Complement Array consists of a NOR gate optionally linked to all AND gates for generating and propagating complementary AND terms.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **4 dedicated inputs**
- **13 control gates**
- **32 AND gates**
- **21 OR gates**
- **45 product terms:**
  - **– 32 logic terms**
  - **– 13 control terms**
- **8 bidirectional I/O lines**
- **4 bidirectional registers**
- **J-K, T, or D-type flip-flops**
- **Asynchronous Preset/Reset**
- **Complement Array**
- **Active-High or -Low outputs**
- **Programmable $\overline{OE}$ control**
- **Positive edge-triggered clock**
- **Clock frequency: 15MHz (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 750mW (typ.)**
- **TTL compatible**
- **Tri-state outputs**

PIN CONFIGURATIONS

N Package


CK 1
I0 2
I1 3
I2 4
I3 5
B0 6
B1 7
B2 8
B3 9
GND 10
20 VCC
19 B7
18 B6
17 F3
16 F2
15 F1
14 F0
13 B5
12 B4
11 OE
CD03310S

N = Plastic

A Package


I1 I0 CK VCC B7
3 2 1 20 19
I2 4
I3 5
B0 6
B1 7
B2 8
18 B6
17 F3
16 F2
15 F1
14 F0
9 10 11 12 13
B3 GND OE B4 B5
CD03320S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- **Random sequential logic**
- **Synchronous up/down counters**
- **Shift registers**
- **Bidirectional data buffers**
- **Timing function generators**
- **System controllers/synchronizers**
- **Priority encoder/registers**

FUNCTIONAL DIAGRAM


(LOGIC TERMS)
(CONTROL TERMS)
L
D
E
OE
a
b
a
ā
b
b̄
Q
Q̄
C̄
C
S
X
B
R
P
F
M
P
R
J
Q
(n)
K
CK
T31
T0
FC
AF01870S

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS155

On-chip T/C buffers couple either True (I, B, Q) or Complement ($\bar{I}$, $\overline{B}$, $\overline{Q}$, $\overline{C}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. One group of AND gates drives bidirectional I/O lines (B), whose output polarity is individually programmable through a set of EX-OR gates for implementing AND-OR or AND-NOR logic functions. Another group drives the J-K inputs of all flip-flops. The Asynchronous Preset and Reset lines (P, R), are driven from the OR matrix.

All flip-flops are positive edge-triggered and can be used as input, output or I/O (for interfacing with a bidirectional data bus) in conjunction with load control gates (L), steering inputs (I), (B), (Q) and programmable output select lines (E).

The PLS155 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

VIRGIN STATE

The factory shipped virgin device contains all fusible links intact, such that:

1. $\overline{OE}$ is always enabled.
2. Preset and Reset are always disabled.
3. All transition terms are disabled.
4. All flip-flops are in D-mode unless otherwise programmed to J/K only or J/K or D (controlled).
5. All B pins, are inputs and all F pins are outputs unless otherwise programmed.

LOGIC FUNCTION



SET Q_0: $J_0 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_0 = 0$

RESET Q_1: $J_1 = 0$
$K_1 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $J_2 = 0$
$K_2 = 0$

TOGGLE Q_3: $J_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

TB00901S

NOTES:

Similar logic functions are applicable for D and T mode flip-flops.

FLIP-FLOP TRUTH TABLE

$\overline{OE}$	L	CK	P	R	J	K	Q	F
H								Hi-Z
L	X	X	H	L	X	X	H	L
L	X	X	L	H	X	X	L	H
L	L	↑	L	L	L	L	Q	$\overline{Q}$
L	L	↑	L	L	L	H	L	H
L	L	↑	L	L	H	L	H	L
L	L	↑	L	L	H	H	$\overline{Q}$	Q
H	H	↑	L	L	L	H	L	H*
H	H	↑	L	L	H	L	H	L*
+10V	X	↑	X	X	L	H	L	H**
	X	↑	X	X	H	L	H	L**

NOTES:

1. Positive Logic:
   $J/K = T_0 + T_1 + T_2$ .... T_{31}
   $T_n = \overline{C} \bullet (I_0 \bullet I_1 \bullet I_2 \ldots) \bullet (Q_0 \bullet Q_1 \ldots) \bullet (B_0 \bullet B_1 \bullet \ldots)$
2. ↑denotes transition from Low to High level.
3. X = Don't care
4. * = Forced at F_n pin for loading J/K flip-flop in I/O mode. L must be enabled, and other active T_n disabled via steering input(s) I, B, or Q.
5. At P = R = H, Q = H. The final state of Q depends on which is released first.
6. * * = Forced at F_n pin to load J/K flip-flop independent of program code (Diagnostic mode), Tri-state B outputs.

Field-Programmable Logic Sequencer (16 × 45 × 12)

PLS155

FPLS LOGIC DIAGRAM


(LOGIC TERMS - T)
(CONTROL TERMS)
I0 2
I1 3
I2 4
I3 5
F0
F1
F2
F3
B0
B1
B2
B3
B4
B5
B6
B7
11 OE
C̄
LB LA D7 D6 D5 D4 D3 D2 D1 D0
EB EA
X7 X6 X5 X4 X3 X2 X1 X0
S7 S6 S5 S4 S3 S2 S1 S0
19 B7
18 B6
13 B5
12 B4
9 B3
8 B2
7 B1
6 B0
RB
PB
RA
PA
P R
J Q
K
CK'
M3 M2 M1 M0
17 F3
16 F2
15 F1
14 F0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • • 8 7 • • • • • • • 0 FC
CK' 1 CK
LD01702S

NOTES:

1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connection.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS155

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLS155N
20-pin Plastic Leaded Chip Carrier	PLS155A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High	I_{OH} = −2mA	2.4			V
V_{OL}	Low	I_{OL} = 10mA		0.35	0.5	
Input current[8]						
		V_{CC} = Max				
I_{IH}	High	V_{IN} = 5.5V		< 1	80	μA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
		V_{CC} = Max				
$I_{O\ (OFF)}$	Hi-Z state[8]	V_{OUT} = 5.5V		1	80	μA
		V_{OUT} = 0.45V		−1	−140	
I_{OS}	Short circuit[4]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[7]	V_{CC} = Max		150	190	mA
Capacitance						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		15		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = +25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IH} applied to $\overline{OE}$.
6. Duration of short circuit should not exceed 1 second.
7. I_{CC} is measured with the $\overline{OE}$ input grounded, all other inputs at 4.5V, and the outputs open.
8. Leakage values are a combination of input and output leakage.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS155

AC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$, $R_1 = 470\Omega$, $R_2 = 1k\Omega$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min[5]	Typ[1]	Max	
Pulse width								
t_{CKH}	Clock[2] high	CK −	CK +	$C_L = 30pF$	25	20		ns
t_{CKL}	Clock low	CK +	CK −		30	20		
t_{CKP}	Period	CK +	CK +		70	50		
t_{PRH}	Preset/Reset pulse	(I,B) +	(I,B) −		40	30		
Setup time								
t_{IS1}	Input	CK +	(I,B) ±	$C_L = 30pF$	40	30		ns
t_{IS2}	Input (through F_n)	CK +	F ±		20	10		
t_{IS3}	Input (through Complement Array)[4]	CK +	(I,B) ±		65	40		
Hold time								
t_{IH1}	Input	CK +	(I,B) ±	$C_L = 30pF$	0	−10		ns
t_{IH2}		CK +	F ±		15	10		
Propagation delays								
t_{CKO}	Clock	F ±	CK +	$C_L = 30pF$		25	30	ns
t_{OE1}	Output enable	F −	$\overline{OE}$ −	$C_L = 30pF$		20	30	
t_{OD1}	Output disable[3]	F +	$\overline{OE}$ +	$C_L = 5pF$		20	30	
t_{PD}	Output	B ±	(I,B) ±	$C_L = 30pF$		40	50	
t_{OE2}	Output enable	B ±	(I,B) +	$C_L = 30pF$		35	55	
t_{OD2}	Output disable[3]	B +	(I,B) −	$C_L = 5pF$		30	35	
t_{PRO}	Preset/Reset	F ±	(I,B) +	$C_L = 30pF$		50	55	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% − 90%) ⩽ 10ns.
3. Measured at $V_T = V_{OL} + 0.5V$.
4. When using the Complement Array $T_{CKP} = 95ns$ (min).
5. Limits are guaranteed with 12 product terms maximum connected to each sum term line.
6. For test circuits, waveforms and timing diagrams see the following pages.

TEST LOAD CIRCUIT


VCC
I0
In
BW
BX
CK
DUT
GND
BY
BZ
F0
FN
OE
+5V
R1
R2
CL
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01620S
TC01611S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05460S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

TIMING DIAGRAMS


I, B (INPUTS)
1.5V
1.5V
+3V
0V
tIH1
tIS1
1.5V
1.5V
1.5V
+3V
CK
0V
tIS1
tCKH
tCKL
tCKP
VOH
F (OUTPUTS)
1.5V
VT
tCKO
VOL
tOD1
+3V
OE
1.5V
1.5V
0V
tOE1
WF05471S

Flip-Flop Outputs


I, B (INPUTS)
1.5V
+3V
0V
tPD
B (OUTPUTS)
VOH
1.5V
VT
VOL
tOE2
tOD2
I, B (OUTPUT ENABLE)
+1.5V
+1.5V
+3V
0V
WF05481S

Gate Outputs

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP}	Clock period.
t_{PRH}	Width of preset input pulse.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{IS2}	Required delay between beginning of valid input forced at flip-flop output pins, and positive transition of clock.
t_{IH1}	Required delay between positive transition of clock and end of valid input data.
t_{IH2}	Required delay between positive transition of clock and end of valid input data forced at flip-flop output pins.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with $\overline{OE}$ low).
t_{OE1}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD1}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{PD}	Propagation delay between combinational inputs and outputs.
t_{OE2}	Delay between predefined Output Enable High, and when combinational Outputs become valid.
t_{OD2}	Delay between predefined Output Enable Low, and when combinational Outputs are in the off state.
t_{PRO}	Delay between positive transition of predefined Preset/Reset input, and when flip-flop outputs become valid.

TIMING DIAGRAMS (Continued)


I,B (INPUTS)
+3V
1.5V
0V
CK
+3V
1.5V
0V
0 ns MIN.
t_{IS1}
t_{CKO}
*PRESET RESET (I, B INPUTS)
+3V
1.5V
1.5V
0V
t_{PRH}
Q
(PRESET)
(RESET)
t_{PRO}
F (OUTPUTS)
V_{OH}
1.5V
(RESET)
(PRESET)
1.5V
V_{OL}
WF05491S

* The leading edge of preset/reset must occur only when the input clock is "low", and must remain "high" as long as required to override clock. The falling edge of preset/reset can never go "low" when the input clock is "high".

Asynchronous Preset/Reset


I,B (LOAD SELECT)
1.5V
1.5V
+3V
0V
$\overline{OE}$
1.5V
1.5V
+3V
0V
t_{OE1}
L
F (INPUTS)
V_T
(FORCED D_{IN})
1.5V
+3V V_{OH}
0V V_{OL}
t_{OD1}
t_{IS2}
t_{IH2}
CK
+3V
0V
t_{CKH}
t_{IH1}
Q
($\overline{D_{IN}}$)
WF05501S

Flip-Flop Input Mode

The FPLS can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/OR-EX-OR input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Tables on the following pages.

In these tables, the logic state or action of all I/O, control, and state variables is assigned a symbol which results in the proper fusing pattern of corresponding links, defined as follows:

"AND" ARRAY – (I), (B), (Q_p)


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
INACTIVE^{1,2}	O

LS02030S


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
I, B, Q	H

LS02040S


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
$\bar{I}, \bar{B}, \bar{Q}$	L

LS02050S


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
DON'T CARE	–

LS02060S

"COMPLEMENT" ARRAY – (C)



ACTION	CODE
INACTIVE^{1,3,5}	O

LS02070S



ACTION	CODE
GENERATE^{5}	A

LS02080S



ACTION	CODE
PROPAGATE	●

LS02090S



ACTION	CODE
TRANSPARENT	–

LS02100S


$\bar{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
PROPAGATE	●

LS02110S


$\bar{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
TRANSPARENT	–

LS02120S

"OR" ARRAY – (MODE)



ACTION	CODE
J/K OR D (CONTROLLED)	A

LS02130S



ACTION	CODE
J·K	●

LS02140S

Notes on following page.

"OR" ARRAY – (Q_n = D-Type)


T_n
M = ENABLED
J
K
Q

T_n STATUS	CODE
ACTIVE (Set)	A

LS02150S


T_n
M = ENABLED
J
K
Q

T_n STATUS	CODE
INACTIVE (Reset)	●

LS02160S

"OR" ARRAY – (Q_n = J-K Type)


T_n
M = DISABLED
J
K
Q

ACTION	CODE
TOGGLE	O

LS02170S


T_n
M = DISABLED
J
K
Q

ACTION	CODE
SET	H

LS02180S


T_n
M = DISABLED
J
K
Q

ACTION	CODE
RESET	L

LS02190S


T_n
M = DISABLED
J
K
Q

ACTION	CODE
HOLD	–

LS02200S

"OR" ARRAY – (S or B), (P), (R)



T_n STATUS	CODE
ACTIVE	A

LS02210S



T_n STATUS	CODE
INACTIVE	●

LS02220S

"EX-OR" ARRAY – (B)



POLARITY	CODE
LOW	L

LS02230S



POLARITY	CODE
HIGH	H

LS02240S

"$\overline{\text{OE}}$" ARRAY – (E)


$\overline{\text{OE}}$
E_n

ACTION	CODE
IDLE[4]	O

LS02250S


$\overline{\text{OE}}$
E_n

ACTION	CODE
CONTROL	A

LS02260S


$\overline{\text{OE}}$
E_n

ACTION	CODE
ENABLE[4]	●

LS02270S


$\overline{\text{OE}}$
E_n

ACTION	CODE
DISABLE	–

LS02280S

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates.
2. Any gate (T, F_C, L, P, R, D)$_n$ will be unconditionally inhibited if both of the I, B, or Q links are left intact.
3. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n, F_C.
4. E_n = O and E_n = • are logically equivalent states, since both cause F_n outputs to be unconditionally enabled.
5. These states are not allowed for control gates (L, P, R, D)$_n$ due to their lack of "OR" array links.

Field-Programmable Logic Sequencer (16 × 45 × 12) | PLS155

FPLS PROGRAM TABLE

AND

INACTIVE	O
I, B, Q	H
$\overline{I}, \overline{B}, \overline{Q}$	L
DON'T CARE	—

I, B (I), Q (P)

INACTIVE	O
GENERATE	A
PROPAGATE	●
TRANSPARENT	—

C

OR

ACTIVE	A
INACTIVE	●

P, R, B (O), (Q = D)

TOGGLE	O
SET	H
RESET	L
HOLD	—

(Q = J/K)

CONTROL

J/K	●
J/K or D (controlled)	A

F/F MODE

IDLE	O
CONTROL	A
ENABLE	●
DISABLE	—

$E_{A, B}$

HIGH	H
LOW	L

(POL.)

NOTES

1. The FPLS is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Program unused C, I, B, and Q bits in the AND array as (—). Program unused Q, B, P, and R bits in the OR array as (—) or (A), as applicable.
3. Unused Terms can be left blank.
4. Q (P) and Q (N) are respectively the present and next states of flip-flops Q.

F/F MODE				E_B	E_A	POLARITY							

THIS PORTION TO BE COMPLETED BY SIGNETICS

CF (XXXX) ____

CUSTOMER SYMBOLIZED PART # ____

DATE RECEIVED ____

COMMENTS ____

CUSTOMER NAME ____

PURCHASE ORDER # ____

SIGNETICS DEVICE # ____

TOTAL NUMBER OF PARTS ____

PROGRAM TABLE # ____ REV ____ DATE ____

TERM	AND																	OR															
	C	I				B(I)								Q(P)				Q(N)				P		R		B(O)							
		3	2	1	0	7	6	5	4	3	2	1	0	3	2	1	0	3	2	1	0	B	A	B	A	7	6	5	4	3	2	1	0
0																																	
1																																	
2																																	
3																																	
4																																	
5																																	
6																																	
7																																	
8																																	
9																																	
10																																	
11																																	
12																																	
13																																	
14																																	
15																																	
16																																	
17																																	
18																																	
19																																	
20																																	
21																																	
22																																	
23																																	
24																																	
25																																	
26																																	
27																																	
28																																	
29																																	
30																																	
31																																	
F_C																																	
L_B																																	
L_A																																	
D7																																	
D6																																	
D5																																	
D4																																	
D3																																	
D2																																	
D1																																	
D0																																	
PIN		5	4	3	2	19	18	13	12	9	8	7	6	17	16	15	14																

TB01211S

Signetics

PLS157
Field-Programmable Logic Sequencer (16 × 45 × 12)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 20

DESCRIPTION

The PLS157 is a Tri-state output, registered logic element combining AND/OR gate arrays with clocked J-K flip-flops. These J-K flip-flops are dynamically convertible to D-type via a "fold-back" inverting buffer and control gate F_C. It features 6 registered I/O outputs (F) in conjunction with 6 bidirectional I/O lines (B). These yield variable I/O gate and register configurations via control gates (D, L) ranging from 16 inputs to 12 outputs.

The AND/OR arrays consist of 32 logic AND gates, 13 control AND gates, and 21 OR gates with fusible link connections for programming I/O polarity and direction. All AND gates are linked to 4 inputs (I), bidirectional I/O lines (B), internal flip-flop outputs (Q), and Complement Array output ($\overline{C}$). The Complement Array consists of a NOR gate optionally linked to all AND gates for generating and propagating complementary AND terms.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **4 dedicated inputs**
- **13 control gates**
- **32 AND gates**
- **21 OR gates**
- **45 product terms:**
  - **32 logic terms**
  - **13 control terms**
- **6 bidirectional I/O lines**
- **6 bidirectional registers**
- **J-K, T, or D-type flip-flops**
- **Tri-state outputs**
- **Asynchronous Preset/Reset**
- **Complement Array**
- **Active-High or -Low outputs**
- **Programmable $\overline{OE}$ control**
- **Positive edge-triggered clock**
- **Clock frequency: 15MHz (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 750mW (typ.)**
- **TTL compatible**

PIN CONFIGURATIONS

N Package


CK 1
I0 2
I1 3
I2 4
I3 5
B0 6
B1 7
B2 8
B3 9
GND 10
20 VCC
19 B5
18 F5
17 F4
16 F3
15 F2
14 F1
13 F0
12 B4
11 OE
CD03370S

N = Plastic

A Package


I1 3
I0 2
CK 1
VCC 20
B5 19
I2 4
I3 5
B0 6
B1 7
B2 8
18 F5
17 F4
16 F3
15 F2
14 F1
9 B3
10 GND
11 OE
12 B4
13 F0
CD03380S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- Random sequential logic
- Synchronous up/down counters
- Shift registers
- Bidirectional data buffers
- Timing function generators
- System controllers/synchronizers
- Priority encoder/registers

FUNCTION DIAGRAM


(LOGIC TERMS)
(CONTROL TERMS)
P
R
L
L
D
E
E
OE
a
b
a
ā
b
Q
Q̄
C̄
C
S
X
B
F
M
J P R Q
(n)
K
CK
R
P
M
J P R Q
(n)
K
CK
F
T31
T0
FC
AF01891S

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS157

On-chip T/C buffers couple either True (I, B, Q) or Complement ($\overline{I}$, $\overline{B}$, $\overline{Q}$, $\overline{C}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. One group of AND gates drives bidirectional I/O lines (B), whose output polarity is individually programmable through a set of EX-OR gates for implementing AND-OR or AND-NOR logic functions. Another group drives the J-K inputs of all flip-flops. The Asynchronous Preset and Reset lines (P, R), for two of the registers are driven from the AND matrix. The Preset and Reset lines (P, R) controlling the lower four registers are driven from the OR matrix.

All flip-flops are positive edge-triggered and can be used as input, output or I/O (for interfacing with a bidirectional data bus) in conjunction with load control gates (L), steering inputs (I), (B), (Q) and programmable output select lines (E).

The PLS157 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

VIRGIN STATE

The factory shipped virgin device contains all fusible links intact, such that:

1. $\overline{OE}$ is always enabled.
2. Preset and Reset are always disabled.
3. All transition terms are disabled.
4. All flip-flops are in D-mode unless otherwise programmed to J/K only or J/K or D (controlled).
5. All B pins are inputs and all F pins are outputs unless otherwise programmed.

LOGIC FUNCTION



SET Q_0: $J_0 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_0 = 0$

RESET Q_1: $J_1 = 0$

$K_1 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $J_2 = 0$

$K_2 = 0$

TOGGLE Q_3: $J_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

TB00901S

NOTES:

Similar logic functions are applicable for D and T mode flip-flops.

FLIP-FLOP TRUTH TABLE

$\overline{OE}$	L	CK	P	R	J	K	Q	F
H								Hi-Z
L	X	X	H	L	X	X	H	L
L	X	X	L	H	X	X	L	H
L	L	↑	L	L	L	L	Q	$\overline{Q}$
L	L	↑	L	L	L	H	L	H
L	L	↑	L	L	H	L	H	L
L	L	↑	L	L	H	H	$\overline{Q}$	Q
H	H	↑	L	L	L	H	L	H*
H	H	↑	L	L	H	L	H	L*
+10V	X	↑	X	X	L	H	L	H**
	X	↑	X	X	H	L	H	L**

NOTES:

1. Positive Logic:
   $J/K = T_0 + T_1 + T_2$ .... T_{31}
   $T_n = \overline{C} \bullet (I_0 \bullet I_1 \bullet I_2 \ldots) \bullet (Q_0 \bullet Q_1 \ldots) \bullet (B_0 \bullet B_1 \bullet \ldots)$
2. ↑denotes transition from Low to High level.
3. X = Don't care
4. * = Forced at F_n pin for loading J/K flip-flop in I/O mode. L must be enabled, and other active T_n disabled via steering input(s) I, B, or Q.
5. At P = R = H, Q = H. The final state of Q depends on which is released first.
6. * * = Forced at F_n pin to load J/K flip-flop independent of program code (Diagnostic mode), Tri-state B outputs.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS157

FPLS LOGIC DIAGRAM


(LOGIC TERMS—T)
(CONTROL TERMS)
I_0 2
I_1 3
I_2 4
I_3 5
F_0
F_1
F_2
F_3
F_4
F_5
B_0
B_1
B_2
B_3
B_4
B_5
$\overline{C}$
11 $\overline{OE}$
P_B R_B L_B D_5 D_4 D_3 D_2 D_1 D_0 L_A
E_A E_B
C
X_5 X_4 X_3 X_2 X_1 X_0
S_5 S_4 S_3 S_2 S_1 S_0
19 B_5
12 B_4
9 B_3
8 B_2
7 B_1
6 B_0
18 F_5
17 F_4
16 F_3
15 F_2
14 F_1
13 F_0
1 CK
CK′
P R
J Q
K
M_5 M_4 M_3 M_2 M_1 M_0
R_A
P_A
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0 F_C
LD01693S

NOTES:
1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connection.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS157

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLS157N
20-pin Plastic Leaded Chip Carrier	PLS157A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leq T_A \leq +75°C$, $4.75 \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				V
V_{OH}	High	I_{OH} = −2mA	2.4			
V_{OL}	Low	I_{OL} = 10mA		0.35	0.5	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	80	µA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
		V_{CC} = Max				
$I_{O\ (OFF)}$	Hi-Z state[8]	V_{OUT} = 5.5V		1	80	µA
		V_{OUT} = 0.45V		−1	−140	
I_{OS}	Short circuit[4]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[7]	V_{CC} = Max		150	190	mA
Capacitance						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		15		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = +25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IH} applied to $\overline{OE}$.
6. Duration of short circuit should not exceed 1 second.
7. I_{CC} is measured with the $\overline{OE}$ input grounded, all other inputs at 4.5V, and the outputs open.
8. Leakage values are a combination of input and output leakage.

AC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$, $R_1 = 470\Omega$, $R_2 = 1k\Omega$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min[5]	Typ[1]	Max	
Pulse width								
t_{CKH}	Clock[2] high	CK −	CK +	$C_L = 30pF$	25	20		ns
t_{CKL}	Clock low	CK +	CK −		30	20		
t_{CKP}	Period	CK +	CK +		70	50		
t_{PRH}	Preset/Reset pulse	(I,B) +	(I,B) −		40	30		
Setup time								
t_{IS1}	Input	CK +	(I,B) ±	$C_L = 30pF$	40	30		ns
t_{IS2}	Input (through F_n)	CK +	F ±		20	10		
t_{IS3}	Input (through Complement Array)[4]	CK +	(I,B) ±		65	40		
Hold time								
t_{IH1}	Input	CK +	(I,B) ±	$C_L = 30pF$	0	−10		ns
t_{IH2}		CK +	F ±		15	10		
Propagation delays								
t_{CKO}	Clock	F ±	CK +	$C_L = 30pF$		25	30	ns
t_{OE1}	Output enable	F −	$\overline{OE}$ −	$C_L = 30pF$		20	30	
t_{OD1}	Output disable[3]	F +	$\overline{OE}$ +	$C_L = 5pF$		20	30	
t_{PD}	Output	B ±	(I,B) ±	$C_L = 30pF$		40	50	
t_{OE2}	Output enable	B ±	(I,B) +	$C_L = 30pF$		35	55	
t_{OD2}	Output disable[3]	B +	(I,B) −	$C_L = 5pF$		30	35	
t_{PRO}	Preset/Reset	F ±	(I,B) +	$C_L = 30pF$		50	55	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% − 90%) $\leqslant$ 10ns.
3. Measured at $V_T = V_{OL} + 0.5V$.
4. When using the Complement Array $T_{CKP} = 95ns$ (min).
5. Limits are guaranteed with 12 product terms maximum connected to each sum term line.
6. For test circuits, waveforms and timing diagrams see the following pages.

TEST LOAD CIRCUIT


VCC
I0
In
BW
BX
CK
DUT
GND
BY
BZ
F0
FN
OE
TC01610S


+5V
R1
R2
CL
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01620S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05460S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

TIMING DIAGRAMS


I, B (INPUTS)
1.5V
1.5V
+3V
0V
tIH1
tIS1
1.5V
1.5V
1.5V
+3V
CK
0V
tIS1
tCKH
tCKL
tCKP
VOH
F (OUTPUTS)
1.5V
VT
tCKO
VOL
tOD1
+3V
OE
1.5V
1.5V
0V
tOE1
WF05471S

Flip-Flop Outputs


I, B (INPUTS)
1.5V
+3V
0V
tPD
VOH
B (OUTPUTS)
1.5V
VT
VOL
tOE2
tOD2
+3V
I, B (OUTPUT ENABLE)
+1.5V
+1.5V
0V
WF05481S

Gate Outputs

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP}	Clock period.
t_{PRH}	Width of preset input pulse.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{IS2}	Required delay between beginning of valid input forced at flip-flop output pins, and positive transition of clock.
t_{IH1}	Required delay between positive transition of clock and end of valid input data.
t_{IH2}	Required delay between positive transition of clock and end of valid input data forced at flip-flop output pins.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with $\overline{OE}$ low).
t_{OE1}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD1}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{PD}	Propagation delay between combinational inputs and outputs.
t_{OE2}	Delay between predefined Output Enable High, and when combinational Outputs become valid.
t_{OD2}	Delay between predefined Output Enable Low, and when combinational Outputs are in the off state.
t_{PRO}	Delay between positive transition of predefined Preset/Reset input, and when flip-flop outputs become valid.

TIMING DIAGRAMS (Continued)


I,B
(INPUTS)
+3V
1.5V
0V
CK
+3V
1.5V
0V
0 ns MIN.
t_{IS1}
t_{CKO}
*PRESET RESET
(I, B INPUTS)
+3V
1.5V
1.5V
0V
t_{PRH}
Q
(PRESET)
(RESET)
t_{PRO}
F
(OUTPUTS)
V_{OH}
1.5V
(RESET)
(PRESET)
1.5V
V_{OL}
WF05491S

* The leading edge of preset/reset must occur only when the input clock is "low", and must remain "high" as long as required to override clock. The falling edge of preset/reset can never go "low" when the input clock is "high".

Asynchronous Preset/Reset


I,B
(LOAD SELECT)
1.5V
1.5V
+3V
0V
$\overline{OE}$
1.5V
1.5V
+3V
0V
t_{OE1}
L
F
(INPUTS)
V_T
(FORCED D_{IN})
1.5V
+3V V_{OH}
0V V_{OL}
t_{OD1}
t_{IS2}
t_{IH2}
CK
+3V
0V
t_{CKH}
t_{IH1}
Q
($\overline{D_{IN}}$)
WF05501S

Flip-Flop Input Mode

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS157

The FPLS can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/OR-EX-OR input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Tables on the following pages.

In these tables, the logic state or action of all I/O, control, and state variables is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

"AND" ARRAY – (I), (B), (Q_p)


I, B, Q
I, B, Q
Ī, B̄, Q̄
(T, F_C, L, P, R, D)_n

STATE	CODE
INACTIVE[1,2]	O

LS02030S


I, B, Q
I, B, Q
Ī, B̄, Q̄
(T, F_C, L, P, R, D)_n

STATE	CODE
I, B, Q	H

LS02040S


I, B, Q
I, B, Q
Ī, B̄, Q̄
(T, F_C, L, P, R, D)_n

STATE	CODE
Ī, B̄, Q̄	L

LS02050S


I, B, Q
I, B, Q
Ī, B̄, Q̄
(T, F_C, L, P, R, D)_n

STATE	CODE
DON'T CARE	–

LS02060S

"COMPLEMENT" ARRAY – (C)



ACTION	CODE
INACTIVE[1,3,5]	O

LS02070S



ACTION	CODE
GENERATE[5]	A

LS02080S



ACTION	CODE
PROPAGATE	•

LS02090S



ACTION	CODE
TRANSPARENT	–

LS02100S


C̄
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
PROPAGATE	•

LS02110S


C̄
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
TRANSPARENT	–

LS02120S

"OR" ARRAY – (MODE)



ACTION	CODE
J/K OR D (CONTROLLED)	A

LS02130S



ACTION	CODE
J-K	•

LS02140S

Notes on following page.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS157

"OR" ARRAY – (Q_n = D-Type)


Tn
M = ENABLED
J
K
Q

T_n STATUS	CODE
ACTIVE (Set)	A

LS02150S


Tn
M = ENABLED
J
K
Q

T_n STATUS	CODE
INACTIVE (Reset)	●

LS02160S

"OR" ARRAY – (Q_n = J-K Type)


Tn
M = DISABLED
J
K
Q

ACTION	CODE
TOGGLE	O

LS02170S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
SET	H

LS02180S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
RESET	L

LS02190S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
HOLD	–

LS02200S

"OR" ARRAY – (S or B), (P), (R)



T_n STATUS	CODE
ACTIVE	A

LS02210S



T_n STATUS	CODE
INACTIVE	●

LS02220S

"EX-OR" ARRAY – (B)



POLARITY	CODE
LOW	L

LS02230S



POLARITY	CODE
HIGH	H

LS02240S

"$\overline{OE}$" ARRAY – (E)



ACTION	CODE
IDLE[4]	O

LS02250S



ACTION	CODE
CONTROL	A

LS02260S



ACTION	CODE
ENABLE[4]	●

LS02270S



ACTION	CODE
DISABLE	–

LS02280S

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates.
2. Any gate (T, F_C, L, P, R, D)$_n$ will be unconditionally inhibited if both of the I, B, or Q links are left intact.
3. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n, F_C.
4. E_n = O and E_n = • are logically equivalent states, since both cause F_n outputs to be unconditionally enabled.
5. These states are not allowed for control gates (L, P, R, D)$_n$ due to their lack of "OR" array links.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS157

FPLS PROGRAM TABLE

AND

INACTIVE	O	I, B (I), Q (P)
I, B, Q	H	
$\overline{I}, \overline{B}, \overline{Q}$	L	
DON'T CARE	—	

INACTIVE	O	C
GENERATE	A	
PROPAGATE	●	
TRANSPARENT	—	

OR

ACTIVE	A	P, R, B (O), (Q = D)
INACTIVE	●	

TOGGLE	O	(Q = J/K)
SET	H	
RESET	L	
HOLD	—	

CONTROL

J/K	●	F/F MODE
J/K or D (controlled)	A	

IDLE	O	$E_{A,\ B}$
CONTROL	A	
ENABLE	●	
DISABLE	—	

HIGH	H	(POL.)
LOW	L	

NOTES
1. The FPLS is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Program unused C, I, B, and Q bits in the AND array as (—). Program unused Q, B, P, and R bits in the OR array as (—) or (A), as applicable.
3. Unused Terms can be left blank.
4. Q (P) and Q (N) are respectively the present and next states of flip-flops Q.

F/F MODE					

E_B	E_A

POLARITY					

TERM	AND																	OR													
	C	I				B(I)						Q (P)						Q (N)						P	R	B(O)					
		3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	A	A	5	4	3	2	1	0
0																															
1																															
2																															
3																															
4																															
5																															
6																															
7																															
8																															
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
F_C																															
P_B																															
R_B																															
L_B																															
L_A																															
D5																															
D4																															
D3																															
D2																															
D1																															
D0																															
PIN		5	4	3	2	19	12	9	8	7	6	18	17	16	15	14	13														

THIS PORTION TO BE COMPLETED BY SIGNETICS
CF (XXXX) ________
CUSTOMER SYMBOLIZED PART # ________
DATE RECEIVED ________
COMMENTS ________

CUSTOMER NAME ________
PURCHASE ORDER # ________
SIGNETICS DEVICE # ________
TOTAL NUMBER OF PARTS ________
PROGRAM TABLE # ________ REV ________ DATE ________

TB01350S

Signetics

PLS159

Field-Programmable Logic Sequencer (16 × 45 × 12)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 20

DESCRIPTION

The PLS159 is a Tri-state output, registered logic element combining AND/OR gate arrays with clocked J-K flip-flops. These J-K flip-flops are dynamically convertible to D-type via a "fold-back" inverting buffer and control gate F_C. It features 8 registered I/O outputs (F) in conjunction with 4 bidirectional I/O lines (B). These yield variable I/O gate and register configurations via control gates (D, L) ranging from 16 inputs to 12 outputs.

The AND/OR arrays consist of 32 logic AND gates, 13 control AND gates, and 21 OR gates with fusible link connections for programming I/O polarity and direction. All AND gates are linked to 4 inputs (I), bidirectional I/O lines (B), internal flip-flop outputs (Q), and Complement Array output $(\overline{C})$. The Complement Array consists of a NOR gate optionally linked to all AND gates for generating and propagating complementary AND terms.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **4 dedicated inputs**
- **13 control gates**
- **32 AND gates**
- **21 OR gates**
- **45 product terms:**
  - **32 logic terms**
  - **13 control terms**
- **4 bidirectional I/O lines**
- **8 bidirectional registers**
- **J/K, T, or D-type flip-flops**
- **Asynchronous Preset/Reset**
- **Complement Array**
- **Active-High or -Low outputs**
- **Programmable $\overline{OE}$ control**
- **Positive edge-triggered clock**
- **Clock frequency: 15MHz (max.)**
- **Input loading: $-100\mu A$ (max.)**
- **Power dissipation: 750mW (typ.)**
- **TTL compatible**
- **Tri-state outputs**

PIN CONFIGURATIONS



N Package

CK 1
I0 2
I1 3
I2 4
I3 5
B0 6
B1 7
B2 8
B3 9
GND 10
20 VCC
19 F7
18 F6
17 F5
16 F4
15 F3
14 F2
13 F1
12 F0
11 O.E.
CD03350S

N = Plastic

A Package

I1 3
I0 2
CK 1
VCC 20
F7 19
I2 4
I3 5
B0 6
B1 7
B2 8
18 F6
17 F5
16 F4
15 F3
14 F2
9 B3
10 GND
11 OE
12 F0
13 F1
CD03360S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- **Random sequential logic**
- **Synchronous up/down counters**
- **Shift registers**
- **Bidirectional data buffers**
- **Timing function generators**
- **System controllers/synchronizers**
- **Priority encoder/registers**

FUNCTIONAL DIAGRAM



(LOGIC TERMS)
(CONTROL TERMS)
P R L D
E
a
b
OE
a
ā
b
b̄
Q
Q̄
C̄
C
S
X
M
B
F
J P R Q
(n)
K
CK
T31
T0
FC
AF01882S

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159

On-chip T/C buffers couple either True (I, B, Q) or Complement ($\overline{I}$, $\overline{B}$, $\overline{Q}$, $\overline{C}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. One group of AND gates drives bidirectional I/O lines (B), whose output polarity is individually programmable through a set of EX-OR gates for implementing AND-OR or AND-NOR logic functions. Another group drives the J-K inputs of all flip-flops, as well as asynchronous Preset and Reset lines (P, R).

All flip-flops are positive edge-triggered and can be used as input, output or I/O (for interfacing with a bidirectional data bus) in conjunction with load control gates (L), steering inputs (I), (B), (Q) and programmable output select lines (E).

The PLS159 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

VIRGIN STATE

The factory shipped virgin device contains all fusible links intact, such that:

1. $\overline{OE}$ is always enabled.
2. Preset and Reset are always disabled.
3. All transition terms are disabled.
4. All flip-flops are in D-mode unless otherwise programmed to J/K only or J/K or D (controlled).
5. All B pins are inputs and all F pins are outputs unless otherwise programmed.

LOGIC FUNCTION



SET Q_0: $J_0 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_0 = 0$

RESET Q_1: $J_1 = 0$
$K_1 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $J_2 = 0$
$K_2 = 0$

TOGGLE Q_3: $J_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

TB00901S

NOTE:
Similar logic functions are applicable for D and T mode flip-flops.

FLIP-FLOP TRUTH TABLE

$\overline{OE}$	L	CK	P	R	J	K	Q	F
H								Hi-Z
L	X	X	L	X	X	X	L	H
L	X	X	H	L	X	X	H	L
L	X	X	L	H	X	X	L	H
L	L	↑	L	L	L	L	Q	$\overline{Q}$
L	L	↑	L	L	L	H	L	H
L	L	↑	L	L	H	L	H	L
L	L	↑	L	L	H	H	$\overline{Q}$	Q
H	H	↑	L	L	L	H	L	H*
H	H	↑	L	L	H	L	H	L*
+10V	X	↑	X	X	L	H	L	H**
	X	↑	X	X	H	L	H	L**

NOTES:
1. Positive Logic:
   $J/K = T_0 + T_1 + T_2$ .... T_{31}
   $T_n = \overline{C} \bullet (I_0 \bullet I_1 \bullet I_2 \ldots) \bullet (Q_0 \bullet Q_1 \ldots) \bullet (B_0 \bullet B_1 \bullet \ldots)$
2. ↑ denotes transition from Low to High level.
3. X = Don't care
4. * = Forced at F_n pin for loading J/K flip-flop in I/O mode. L must be enabled, and other active T_n disabled via steering input(s) I, B, or Q.
5. At P = R = H, Q = H. The final state of Q depends on which is released first.
6. * * = Forced at F_n pin to load J/K flip-flop independent of program code (Diagnostic mode), Tri-state B outputs.

FPLS LOGIC DIAGRAM


(LOGIC TERMS — T)
(CONTROL TERMS)
$\overline{OE}$
11
I_0 2
I_1 3
I_2 4
I_3 5
F_0
F_1
F_2
F_3
F_4
F_5
F_6
F_7
B_0
B_1
B_2
B_3
$\overline{C}$
C
P_B
R_B
P_A
R_A
L_B
L_A
D_3
D_2
D_1
D_0
E_A
E_B
S_3
S_2
S_1
S_0
X_3
X_2
X_1
X_0
9 B_3
8 B_2
7 B_1
6 B_0
P
R
J
Q
K
CK'
M_7
M_6
M_5
M_4
M_3
M_2
M_1
M_0
19 F_7
18 F_6
17 F_5
16 F_4
15 F_3
14 F_2
13 F_1
12 F_0
31 • • • • • • • 24
23 • • • • • • • 16
15 • • • • • • • 8
7 • • • • • • • 0
F_C
CK'
1 CK
LD01684S

NOTES:
1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connection.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLS159N
20-pin Plastic Leaded Chip Carrier	PLS159A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING Min	RATING Max	UNIT
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			°C
T_A	Operating	0	+75	
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS Min	LIMITS Typ[2]	LIMITS Max	UNIT
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				V
V_{OH}	High	I_{OH} = −2mA	2.4			
V_{OL}	Low	I_{OL} = 10mA		0.35	0.5	
Input current[8]						
		V_{CC} = Max				
I_{IH}	High	V_{IN} = 5.5V		< 1	80	
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	μA
Output current						
		V_{CC} = Max				
$I_{O\ (OFF)}$	Hi-Z state[8]	V_{OUT} = 5.5V		1	80	μA
		V_{OUT} = 0.45V		−1	−140	
I_{OS}	Short circuit[4]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[7]	V_{CC} = Max		150	190	mA
Capacitance						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		15		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = +25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IH} applied to $\overline{OE}$.
6. Duration of short circuit should not exceed 1 second.
7. I_{CC} is measured with the $\overline{OE}$ input grounded, all other inputs at 4.5V, and the outputs open.
8. Leakage values are a combination of input and output leakage.

AC ELECTRICAL CHARACTERISTICS 0°C ⩽ T_A ⩽ +75°C, 4.75 ⩽ V_{CC} ⩽ 5.25V, R_1 = 470Ω, R_2 = 1kΩ

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min[5]	Typ[1]	Max	
Pulse width								
t_{CKH}	Clock[2] high	CK −	CK +	C_L = 30pF	25	20		ns
t_{CKL}	Clock low	CK +	CK −		30	20		
t_{CKP}	Period	CK +	CK +		70	50		
t_{PRH}	Preset/Reset pulse	(I,B) +	(I,B) −		40	30		
Setup time								
t_{IS1}	Input	CK +	(I,B) ±	C_L = 30pF	40	30		ns
t_{IS2}	Input (through F_n)	CK +	F ±		20	10		
t_{IS3}	Input (through Complement Array)[4]	CK +	(I,B) ±		65	40		
Hold time								
t_{IH1}	Input	CK +	(I,B) ±	C_L = 30pF	0	−10		ns
t_{IH2}		CK +	F ±		15	10		
Propagation delays								
t_{CKO}	Clock	F ±	CK +	C_L = 30pF		25	30	ns
t_{OE1}	Output enable	F −	$\overline{OE}$ −	C_L = 30pF		20	30	
t_{OD1}	Output disable[3]	F +	$\overline{OE}$ +	C_L = 5pF		20	35	
t_{PD}	Output	B ±	(I,B) ±	C_L = 30pF		40	50	
t_{OE2}	Output enable	B ±	(I,B) +	C_L = 30pF		35	55	
t_{OD2}	Output disable[3]	B +	(I,B) −	C_L = 5pF		30	35	
t_{PRO}	Preset/Reset	F ±	(I,B) +	C_L = 30pF		50	55	

NOTES:

1. All typical values are at V_{CC} = 5V, T_A = +25°C.
2. To prevents spurious clocking, clock rise time (10% − 90%) ⩽ 10ns.
3. Measured at $V_T = V_{OL} + 0.5V$.
4. When using the Complement Array T_{CKP} = 95ns (min).
5. Limits are guaranteed with 12 product terms maximum connected to each sum term line.
6. For test circuits, waveforms and timing diagrams see the following pages.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159

TEST LOAD CIRCUIT


V_CC
I_0
I_n
B_W
B_X
CK
DUT
GND
B_Y
B_Z
F_0
F_N
OE
+5V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01620S
TC01611S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
t_r
t_f
+3.0V
0V
90%
10%
5ns
5ns
WF05460S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

TIMING DIAGRAMS


I, B (INPUTS)
1.5V
1.5V
+3V
0V
t_IH1
t_IS1
1.5V
1.5V
1.5V
+3V
CK
0V
t_IS1
t_CKH
t_CKL
t_CKP
V_OH
F (OUTPUTS)
1.5V
V_T
t_CKO
V_OL
t_OD1
OE
1.5V
1.5V
+3V
0V
t_OE1
WF05471S

Flip-Flop Outputs


I, B (INPUTS)
1.5V
+3V
0V
t_PD
B (OUTPUTS)
1.5V
V_OH
V_T
V_OL
t_OE2
t_OD2
I, B (OUTPUT ENABLE)
+1.5V
+1.5V
+3V
0V
WF05481S

Gate Outputs

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP}	Clock period.
t_{PRH}	Width of preset input pulse.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{IS2}	Required delay between beginning of valid input forced at flip-flop output pins, and positive transition of clock.
t_{IH1}	Required delay between positive transition of clock and end of valid input data.
t_{IH2}	Required delay between positive transition of clock and end of valid input data forced at flip-flop output pins.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with $\overline{OE}$ low).
t_{OE1}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD1}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{PD}	Propagation delay between combinational inputs and outputs.
t_{OE2}	Delay between predefined Output Enable High, and when combinational Outputs become valid.
t_{OD2}	Delay between predefined Output Enable Low, and when combinational Outputs are in the off state.
t_{PRO}	Delay between positive transition of predefined Preset/Reset input, and when flip-flop outputs become valid.

TIMING DIAGRAMS (Continued)


I,B
(INPUTS)
1.5V
+3V
0V
CK
1.5V
+3V
0V
0 ns MIN.
tIS1
tCKO
*PRESET RESET
(I, B INPUTS)
1.5V
1.5V
+3V
0V
tPRH
Q
(PRESET)
(RESET)
tPRO
F
(OUTPUTS)
1.5V
(RESET)
(PRESET)
1.5V
VOH
VOL
WF05491S

* The leading edge of preset/reset must occur only when the input clock is "low", and must remain "high" as long as required to override clock. The falling edge of preset/reset can never go "low" when the input clock is "high".

Asynchronous Preset/Reset


I,B
(LOAD SELECT)
1.5V
1.5V
+3V
0V
OE
1.5V
1.5V
+3V
0V
tOE1
L
F
(INPUTS)
VT
(FORCED DIN)
1.5V
+3V VOH
0V VOL
tOD1
tIS2
tIH2
CK
+3V
0V
tCKH
tIH1
Q
(DIN)
WF05501S

Flip-Flop Input Mode

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159

The FPLS can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/OR-EX-OR input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Tables on the following pages.

In these tables, the logic state or action of all I/O, control, and state variables is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

"AND" ARRAY – (I), (B), (Q_p)


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
INACTIVE[1,2]	O

LS02030S


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
I, B, Q	H

LS02040S


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
$\bar{I}, \bar{B}, \bar{Q}$	L

LS02050S


I, B, Q
I, B, Q
$\bar{I}, \bar{B}, \bar{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
DON'T CARE	–

LS02060S

"COMPLEMENT" ARRAY – (C)



ACTION	CODE
INACTIVE[1,3,5]	O

LS02070S



ACTION	CODE
GENERATE[5]	A

LS02080S



ACTION	CODE
PROPAGATE	●

LS02090S



ACTION	CODE
TRANSPARENT	–

LS02100S


$\bar{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
PROPAGATE	●

LS02110S


$\bar{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
TRANSPARENT	–

LS02120S

"OR" ARRAY – (MODE)



ACTION	CODE
J/K OR D (CONTROLLED)	A

LS02130S



ACTION	CODE
J-K	●

LS02140S

Notes on following page.

"OR" ARRAY – (Q_n = D-Type)


Tn
M = ENABLED
J
K
Q

T_n STATUS	CODE
ACTIVE (Set)	A

LS02150S


Tn
M = ENABLED
J
K
Q

T_n STATUS	CODE
INACTIVE (Reset)	●

LS02160S

"OR" ARRAY – (Q_n = J-K Type)


Tn
M = DISABLED
J
K
Q

ACTION	CODE
TOGGLE	O

LS02170S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
SET	H

LS02180S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
RESET	L

LS02190S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
HOLD	–

LS02200S

"OR" ARRAY – (S or B), (P), (R)



T_n STATUS	CODE
ACTIVE	A

LS02210S



T_n STATUS	CODE
INACTIVE	●

LS02220S

"EX-OR" ARRAY – (B)



POLARITY	CODE
LOW	L

LS02230S



POLARITY	CODE
HIGH	H

LS02240S

"$\overline{OE}$" ARRAY – (E)



ACTION	CODE
IDLE[4]	O

LS02230S



ACTION	CODE
CONTROL	A

LS02240S



ACTION	CODE
ENABLE[4]	●

LS02230S



ACTION	CODE
DISABLE	–

LS02240S

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates.
2. Any gate (T, F_C, L, P, R, D)$_n$ will be unconditionally inhibited if both of the I, B, or Q links are left intact.
3. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n, F_C.
4. E_n = O and E_n = • are logically equivalent states, since both cause F_n outputs to be unconditionally enabled.
5. These states are not allowed for control gates (L, P, R, D)$_n$ due to their lack of "OR" array links.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159

FPLS PROGRAM TABLE

AND

INACTIVE	O	I, B (I), Q (P)
I, B, Q	H	
$\bar{I}$, $\bar{B}$, $\bar{Q}$	L	
DON'T CARE	—	

INACTIVE	O	C
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	

OR

ACTIVE	A	P, R, B (O), (Q = D)
INACTIVE	•	

TOGGLE	O	(Q = J/K)
SET	H	
RESET	L	
HOLD	—	

CONTROL

J/K	•	F/F MODE
J/K or D (controlled)	A	

HIGH	H	(POL.)
LOW	L	

IDLE	O	$E_{A, B}$
CONTROL	A	
ENABLE	•	
DISABLE	--	

NOTES
1. The FPLS is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Program unused C, I, B, and Q bits in the AND array as (—). Program unused Q, B, P, and R bits in the OR array as (—) or (A), as applicable.
3. Unused Terms can be left blank.
4. Q (P) and Q (N) are respectively the present and next states of flip-flops Q.

F/F MODE							

E_B	E_A	POLARITY			

THIS PORTION TO BE COMPLETED BY SIGNETICS
CF (XXXX) ____
CUSTOMER SYMBOLIZED PART # ____
DATE RECEIVED ____
COMMENTS ____

CUSTOMER NAME ____
PURCHASE ORDER # ____
SIGNETICS DEVICE # ____
TOTAL NUMBER OF PARTS ____
PROGRAM TABLE # ____ REV ____ DATE ____

TERM	AND																	(OR)											
	C	I				B(I)				Q (P)								Q (N)								B(O)			
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0	3	2	1	0
0																													
1																													
2																													
3																													
4																													
5																													
6																													
7																													
8																													
9																													
10																													
11																													
12																													
13																													
14																													
15																													
16																													
17																													
18																													
19																													
20																													
21																													
22																													
23																													
24																													
25																													
26																													
27																													
28																													
29																													
30																													
31																													
F_C																													
P_B																													
R_B																													
L_B																													
P_A																													
R_A																													
L_A																													
D3																													
D2																													
D1																													
D0																													
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12												

TB01291S

Signetics

PLS159A

Field-Programmable Logic Sequencer (16 × 45 × 12)

Signetics Programmable Logic
Preliminary Specification

Application Specific Products
• Series 20

DESCRIPTION

The PLS159A is a Tri-state output, registered logic element combining AND/OR gate arrays with clocked J-K flip-flops. These J-K flip-flops are dynamically convertible to D-type via a "fold-back" inverting buffer and control gate F_C. It features 8 registered I/O outputs (F) in conjunction with 4 bidirectional I/O lines (B). These yield variable I/O gate and register configurations via control gates (D, L) ranging from 16 inputs to 12 outputs.

The AND/OR arrays consist of 32 logic AND gates, 13 control AND gates, and 21 OR gates with fusible link connections for programming I/O polarity and direction. All AND gates are linked to 4 inputs (I), bidirectional I/O lines (B), internal flip-flop outputs (Q), and Complement Array output ($\overline{C}$). The Complement Array consists of a NOR gate optionally linked to all AND gates for generating and propagating complementary AND terms.

FEATURES

- **High-speed version of PLS159**
- **Field-Programmable (Ni-Cr link)**
- **4 dedicated inputs**
- **13 control gates**
- **32 AND gates**
- **21 OR gates**
- **45 product terms:**
  - **32 logic terms**
  - **13 control terms**
- **4 bidirectional I/O lines**
- **8 bidirectional registers**
- **J/K, T, or D-type flip-flops**
- **Power on reset feature on all flip-flops ($F_n = 1$)**
- **Asynchronous Preset/Reset**
- **Complement Array**
- **Active-High or -Low outputs**
- **Programmable $\overline{OE}$ control**
- **Positive edge-triggered clock**
- **Clock frequency: 18MHz (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 750mW (typ.)**
- **TTL compatible**
- **Tri-state outputs**

PIN CONFIGURATIONS

N Package


CK 1
I0 2
I1 3
I2 4
I3 5
B0 6
B1 7
B2 8
B3 9
GND 10
20 VCC
19 F7
18 F6
17 F5
16 F4
15 F3
14 F2
13 F1
12 F0
11 O.E.

CD03350S

N = Plastic

A Package


I1 3
I0 2
CK 1
VCC 20
F7 19
I2 4
I3 5
B0 6
B1 7
B2 8
18 F6
17 F5
16 F4
15 F3
14 F2
9 B3
10 GND
11 OE
12 F0
13 F1

CD03360S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- **Random sequential logic**
- **Synchronous up/down counters**
- **Shift registers**
- **Bidirectional data buffers**
- **Timing function generators**
- **System controllers/synchronizers**
- **Priority encoder/registers**

FUNCTIONAL DIAGRAM


(LOGIC TERMS)
(CONTROL TERMS)
P
R
L
D
E
a
b
OE
a
ā
b
b̄
Q
Q̄
C̄
C
S
X
M
J
P
R
Q
(n)
K
CK
B
F
T31
T0
FC
AF01882S

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159A

On-chip T/C buffers couple either True (I, B, Q) or Complement ($\overline{I}$, $\overline{B}$, $\overline{Q}$, $\overline{C}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. One group of AND gates drives bidirectional I/O lines (B), whose output polarity is individually programmable through a set of EX-OR gates for implementing AND-OR or AND-NOR logic functions. Another group drives the J-K inputs of all flip-flops, as well as asynchronous Preset and Reset lines (P, R).

All flip-flops are positive edge-triggered and can be used as input, output or I/O (for interfacing with a bidirectional data bus) in conjunction with load control gates (L), steering inputs (I), (B), (Q) and programmable output select lines (E).

The PLS159A is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

VIRGIN STATE

The factory shipped virgin device contains all fusible links intact, such that:

1. $\overline{OE}$ is always enabled.
2. Preset and Reset are always disabled.
3. All transition terms are disabled.
4. All flip-flops are in D-mode unless otherwise programmed to J/K only or J/K or D (controlled).
5. All B pins are inputs and all F pins are outputs unless otherwise programmed.

LOGIC FUNCTION



SET Q_0: $J_0 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_0 = 0$

RESET Q_1: $J_1 = 0$

$K_1 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $J_2 = 0$

$K_2 = 0$

TOGGLE Q_3: $J_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

NOTE:
Similar logic functions are applicable for D and T mode flip-flops.

FLIP-FLOP TRUTH TABLE

$\overline{OE}$	L	CK	P	R	J	K	Q	F
H								Hi-Z
L	X	X	L	X	X	X	L	H
L	X	X	H	L	X	X	H	L
L	X	X	L	H	X	X	L	H
L	L	↑	L	L	L	L	Q	$\overline{Q}$
L	L	↑	L	L	L	H	L	H
L	L	↑	L	L	H	L	H	L
L	L	↑	L	L	H	H	$\overline{Q}$	Q
H	H	↑	L	L	L	H	L	H*
H	H	↑	L	L	H	L	H	L*
+10V	X	↑	X	X	L	H	L	H**
+10V	X	↑	X	X	H	L	H	L**

NOTES:

1. Positive Logic:
   $J/K = T_0 + T_1 + T_2$ .... T_{31}
   $T_n = \overline{C} \bullet (I_0 \bullet I_1 \bullet I_2 \ldots) \bullet (Q_0 \bullet Q_1 \ldots) \bullet (B_0 \bullet B_1 \bullet \ldots)$
2. ↑ denotes transition from Low to High level.
3. X = Don't Care
4. * = Forced at F_n pin for loading J/K flip-flop in I/O mode. L must be enabled, and other active T_n disabled via steering input(s) I, B, or Q.
5. At P = R = H, Q = H. The final state of Q depends on which is released first.
6. * * = Forced at F_n pin to load J/K flip-flop independent of program code (Diagnostic mode), Tri-state B outputs.

FPLS LOGIC DIAGRAM


(LOGIC TERMS — T)
(CONTROL TERMS)
OE
11
I0 2
I1 3
I2 4
I3 5
F0
F1
F2
F3
F4
F5
F6
F7
B0
B1
B2
B3
C̄
C
S3
S2
S1
S0
X3
X2
X1
X0
PB RB PA RA LB LA D3 D2 D1 D0
EA EB
9 B3
8 B2
7 B1
6 B0
M7
M6
M5
M4
M3
M2
M1
M0
P R
J Q
K
CK'
19 F7
18 F6
17 F5
16 F4
15 F3
14 F2
13 F1
12 F0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0 FC
CK
1 CK
LD01681S

NOTES:
1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connection.

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLS159AN
20-pin Plastic Leaded Chip Carrier	PLS159AA

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leq T_A \leq 75°C$, $4.75V \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
V_{OH}	High	V_{CC} = Min, I_{OH} = −2mA	2.4			V
V_{OL}	Low	I_{OL} = 10mA		0.35	0.5	
Input current						
I_{IH}	High	V_{CC} = Max, V_{IN} = 5.5V		< 1	40	μA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
$I_{O(OFF)}$	Hi-Z state[5,8]	V_{CC} = Max, V_{OUT} = 5.5V		1	80	μA
		V_{OUT} = 0.45V		−1	−140	
I_{OS}	Short circuit[4,6]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[7]	V_{CC} = Max		150	190	mA
Capacitance						
C_{IN}	Input	V_{CC} = 5.0V, V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		15		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = +25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IH} applied to $\overline{OE}$.
6. Duration of short circuit should not exceed 1 second.
7. I_{CC} is measured with the $\overline{OE}$ input grounded, all other inputs at 4.5V, and the outputs open.
8. Leakage values are a combination of input and output leakage.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159A

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, NPLS179: $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min[5]	Typ[1]	Max	
Pulse width								
t_{CKH}	Clock[2] high	CK −	CK +	$C_L = 30pF$	20	15		ns
t_{CKL}	Clock low	CK +	CK −		20	15		
t_{CKP}	Period	CK +	CK +		55	45		
t_{PRH}	Preset/Reset pulse	(I,B) +	(I,B) −		35	30		
Setup time								
t_{IS1}	Input	CK +	(I,B) ±		35	30		ns
t_{IS2}	Input (through F_n)	CK +	F ±		15	10		
t_{IS3}	Input (through Complement Array)[4]	CK +	(I,B) ±		55	45		
Hold time								
t_{IH1}	Input	CK +	(I,B) ±		0	−5		ns
t_{IH2}	Input (through F_n)	CK +	F ±		15	10		
Propagation delay								
t_{CKO}	Clock	F ±	CK ±			15	20	ns
t_{OE1}	Output enable	F −	$\overline{OE}$ −			20	30	
t_{OD1}	Output disable[3]	F +	$\overline{OE}$ +	$C_L = 5pF$		20	30	
t_{PD}	Output	B ±	(I,B) ±	$C_L = 30pF$		25	35	
t_{OE2}	Output enable	B ±	(I,B) +			20	30	
t_{OD2}	Output disable[3]	B +	(I,B) −	$C_L = 5pF$		20	30	
t_{PRO}	Preset/Reset	F ±	(I,B) +	$C_L = 30pF$		35	45	
t_{PPR}	Power-on preset	F −	V_{CC} +			0	10	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% − 90%) ⩽ 10ns.
3. Measured at $V_T = V_{OL} + 0.5V$.
4. When using the Complement Array $T_{CKP} = 75ns$ (min).
5. Limits are guaranteed with 12 product terms maximum connected to each sum term line.

TEST LOAD CIRCUIT


V_{CC}
I_0
I_n
B_W
B_X
CK
DUT
GND
B_Y
B_Z
F_0
F_N
$\overline{OE}$
TC01611S
+5V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01620S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
t_r
t_f
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05460S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159A

TIMING DIAGRAMS


I, B
(INPUTS)
1.5V
1.5V
+3V
0V
t_{IH1}
t_{IS1}
+3V
1.5V
1.5V
1.5V
CK
0V
t_{IS1}
t_{CKH}
t_{CKL}
t_{CKP}
V_{OH}
F
(OUTPUTS)
1.5V
V_T
t_{CKO}
V_{OL}
t_{OD1}
+3V
$\overline{OE}$
1.5V
1.5V
0V
t_{OE1}
WF05471S

Flip-Flop Outputs


I, B
(INPUTS)
1.5V
+3V
0V
t_{PD}
B
(OUTPUTS)
1.5V
V_T
V_{OH}
V_{OL}
t_{OE2}
t_{OD2}
I, B
(OUTPUT ENABLE)
+1.5V
+1.5V
+3V
0V
WF05481S

Gate Outputs


4.5V
+5V
V_{CC}
0V
t_{PPR}
F
(OUTPUTS)
1.5V
1.5V
V_{OH}
V_{OL}
t_{CKO}
I, B
(INPUTS)
1.5V
1.5V
+3V
0V
t_{IH1}
t_{IS1}
1.5V
1.5V
1.5V
+3V
CK
0V
t_{IS1}
t_{CKH}
t_{CKL}
t_{CKP}
WF06872S

Power-On Reset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP}	Clock period.
t_{PRH}	Width of preset input pulse.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{IS2}	Required delay between beginning of valid input forced at flip-flop output pins, and positive transition of clock.
t_{IH1}	Required delay between positive transition of clock and end of valid input data.
t_{IH2}	Required delay between positive transition of clock and end of valid input data forced at flip-flop output pins.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with $\overline{OE}$ low).
t_{OE1}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD1}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{PPR}	Delay between V_{CC} (after power-on) and when flip-flop outputs become preset at "1" (internal Q outputs at "0").
t_{PD}	Propagation delay between combinational inputs and outputs.
t_{OE2}	Delay between predefined Output Enable High, and when combinational Outputs become valid.
t_{OD2}	Delay between predefined Output Enable Low and when combinational Outputs are in the off state.
t_{PRO}	Delay between positive transition of predefined Preset/Reset input, and when flip-flop outputs become valid.

TIMING DIAGRAMS (Continued)


I,B
(INPUTS)
+3V
1.5V
0V
CK
+3V
1.5V
0V
T_{IS1}*
T_{IS1}
T_{CKO}
+3V
PRESET/RESET
(I, B INPUTS)
1.5V
1.5V
0V
T_{PRH}
Q
(PRESET)
(RESET)
T_{PRO}
F
(OUTPUTS)
(RESET)
(PRESET)
1.5V
1.5V
V_{OH}
V_{OL}
WF17070S

*Preset and Reset functions override Clock. However, F outputs may glitch with the first positive Clock Edge if T_{IS1} cannot be guaranteed by the user.

Asynchronous Preset/Reset


I,B
(LOAD SELECT)
1.5V
1.5V
+3V
0V
$\overline{OE}$
1.5V
1.5V
+3V
0V
t_{OE1}
L
F
(INPUTS)
V_T
(FORCED D_{IN})
1.5V
+3V V_{OH}
0V V_{OL}
t_{OD1}
t_{IS2}
t_{IH2}
CK
+3V
0V
t_{CKH}
t_{IH1}
Q
($\overline{D_{IN}}$)
WF05501S

Flip-Flop Input Mode

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159A

The FPLS can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/OR-EX-OR input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Tables on the following pages.

In these Tables, the logic state or action of all I/O, control, and state variables is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

"AND" ARRAY – (I), (B), (Qp)


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
(T, F_C, L, P, R, D)$_n$

STATE	CODE
INACTIVE[1,2]	O

LS02030S


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
(T, F_C, L, P, R, D)$_n$

STATE	CODE
I, B, Q	H

LS02040S


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
(T, F_C, L, P, R, D)$_n$

STATE	CODE
$\overline{I}, \overline{B}, \overline{Q}$	L

LS02050S


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
(T, F_C, L, P, R, D)$_n$

STATE	CODE
DON'T CARE	–

LS02060S

"COMPLEMENT" ARRAY – (C)


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
INACTIVE[1,3,5]	O

LS02070S


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
GENERATE[5]	A

LS02080S


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
PROPAGATE	●

LS02090S


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
TRANSPARENT	–

LS02100S


$\overline{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
PROPAGATE	●

LS02110S


$\overline{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
TRANSPARENT	–

LS02120S

"OR" ARRAY — (MODE)



ACTION	CODE
J/K OR D (CONTROLLED)	A

LS02130S



ACTION	CODE
J·K	●

LS02140S

Notes on following page.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159A

"OR" ARRAY — (Q_N = D – Type)


Tn
M = ENABLED
J
K
Q

Tn STATUS	CODE
ACTIVE (Set)	A

LS02150S


Tn
M = ENABLED
J
K
Q

Tn STATUS	CODE
INACTIVE (Reset)	●

LS02160S

CAUTION:
The PLS159A Programming Algorithm is different from the PLS159.

"AND" ARRAY — (Q_N = J – K Type)


Tn
M = DISABLED
J
K
Q

ACTION	CODE
TOGGLE	O

LS02170S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
SET	H

LS02180S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
RESET	L

LS02190S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
HOLD	–

LS02200S

"OR" ARRAY — (S or B),(P),(R)



Tn STATUS	CODE
ACTIVE	A

LS02210S



Tn STATUS	CODE
INACTIVE	●

LS02220S

"EX-OR" ARRAY — (B)



POLARITY	CODE
LOW	L

LS02230S



POLARITY	CODE
HIGH	H

LS02240S

"OE " ARRAY — (E)



ACTION	CODE
IDLE[4]	O

LS02250S



ACTION	CODE
CONTROL	A

LS02260S



ACTION	CODE
ENABLE[4]	●

LS02270S



ACTION	CODE
DISABLE	–

LS02280S

NOTES:
1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates.
2. Any gate (T, F_C, L, P, R, D)$_n$ will be unconditionally inhibited if both of the I, B, or Q links are left intact.
3. To prevent oscillations, this state is not allowed for C link, pairs coupled to active gates T_n, F_C.
4. E_n = O and E_n = • are logically equivalent states, since both cause F_n outputs to be unconditionally enabled.
5. These states are not allowed for control gates (L, P, R, D)$_n$ due to their lack of "OR" array links.

Field-Programmable Logic Sequencer (16 × 45 × 12) PLS159A

FPLS PROGRAM TABLE

AND

INACTIVE	O	I, B (I), Q (P)
I, B, Q	H	
$\bar{I}$, $\bar{B}$, $\bar{Q}$	L	
DON'T CARE	—	
INACTIVE	O	C
GENERATE	A	
PROPAGATE	●	
TRANSPARENT	—	

OR

ACTIVE	A	P, R, B (O), (Q = D)
INACTIVE	●	
TOGGLE	O	(Q = J/K)
SET	H	
RESET	L	
HOLD	—	

CONTROL

J/K	●	F/F MODE
J/K or D (controlled)	A	
HIGH	H	(POL.)
LOW	L	

IDLE	O	$E_{A, B}$
CONTROL	A	
ENABLE	●	
DISABLE	--	

NOTES

1. The FPLS is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Program unused C, I, B, and Q bits in the AND array as (—). Program unused Q, B, P, and R bits in the OR array as (—) or (A), as applicable.
3. Unused Terms can be left blank.
4. Q (P) and Q (N) are respectively the present and next states of flip-flops Q.

F/F MODE							

E_B	E_A	POLARITY			

THIS PORTION TO BE COMPLETED BY SIGNETICS

CF (XXXX) ____

CUSTOMER SYMBOLIZED PART # ____

DATE RECEIVED ____

COMMENTS ____

CUSTOMER NAME ____

PURCHASE ORDER # ____

SIGNETICS DEVICE # ____

TOTAL NUMBER OF PARTS ____

PROGRAM TABLE # ____ REV ____ DATE ____

TERM	AND																	(OR)											
	C	I				B(I)				Q (P)								Q (N)								B(O)			
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0	3	2	1	0
0																													
1																													
2																													
3																													
4																													
5																													
6																													
7																													
8																													
9																													
10																													
11																													
12																													
13																													
14																													
15																													
16																													
17																													
18																													
19																													
20																													
21																													
22																													
23																													
24																													
25																													
26																													
27																													
28																													
29																													
30																													
31																													
F_C																													
P_B																													
R_B																													
L_B																													
P_A																													
R_A																													
L_A																													
D3																													
D2																													
D1																													
D0																													
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12												

TB01291S

Signetics

PLHS18P8A
Programmable AND Array Logic (18 × 72 × 8)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 20**

DESCRIPTION

The PLHS18P8A is a two-level logic element consisting of 72 AND gates and 8 OR gates with fusible connections for programming I/O polarity and direction.

All AND gates are linked to 10 inputs (I) and 8 bidirectional I/O lines (B). These yield variable I/O gate configurations via 8 direction control gates, ranging from 18 inputs to 8 outputs.

On-chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates. The 72 AND gates are separated into 8 groups of 9 each. Each group of 9 is associated with one bidirectional pin. In each group, eight of the AND terms are ORed together, while the ninth is used to establish I/O direction. All outputs are individually programmable via an EX-OR gate to allow implementation of AND/OR or NAND/NOR logic functions.

In the virgin state, the AND array fuses are back-to-back CB-EB diode pairs which will act as open connections. Current is avalanched across individual diode pairs during fusing, which essentially short circuits the EB diode and provides the connection for the associated product term.

The PLHS18P8A is field-programmable, allowing the user to quickly generate custom pattern using standard programming equipment.

Order codes are contained in the pages following.

FEATURES

- **100% functionally compatible with AmPAL18P8A**
- **Field-Programmable**
- **10 inputs**
- **8 bidirectional I/O lines**
- **72 AND gates/product terms**
  - **configured into eight groups of nine**
- **Programmable output polarity (Tri-state output)**
- **I/O propagation delay: 20ns (max.)**
- **Power dissipation: 750mW (nominal)**
- **TTL compatible**
- **Verify Lock Fuse**
- **On-chip test features for extensive AC and DC parametric testing**

FUNCTIONAL DIAGRAM



PIN CONFIGURATIONS

N Package



N = Plastic

A Package



A = Plastic Leaded Chip Carrier

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
$Pn = A \cdot \overline{B} \cdot C \cdot D \cdot \ldots$

TYPICAL LOGIC FUNCTION:

AT OUTPUT POLARITY = H
$Z = P0 + P1 + P2 \ldots$

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2} + \ldots$
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot \ldots$

NOTES:
1. For each of the 8 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and bidirectional pins (B).

APPLICATIONS

- **100% functional replacement for all 20-pin combinatorial PALs***
- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

*PAL is a registered trademark of Monolithic Memories, Inc.

Programmable AND Array Logic (18 × 72 × 8)

PLHS18P8A

FPLA LOGIC DIAGRAM


INPUTS (0–35)
0
35
PRODUCT TERMS (0–71)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
0
8
9
17
18
26
27
35
36
44
45
53
54
62
63
71
19 B7
18 B6
17 B5
16 B4
15 B3
14 B2
13 B1
12 B0
11 I9
LD02620S

NOTES:
1. All unprogrammed or virgin "AND" gate locations are pulled to logic "1".
2. ▨ Programmable connections.

Programmable AND Array Logic (18 × 72 × 8) PLHS18P8A

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
20-pin Plastic DIP 300mil-wide	PLHS18P8AN
20-pin Plastic Leaded Chip Carrier	PLHS18P8AA

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		MIN	MAX	
V_{CC}	Supply voltage	−0.5	+7	V_{DC}
V_{IN}	Input voltage	−0.5	+5.5	V_{DC}
V_{OUT}	Output voltage	−0.5	V_{CC} Max	V_{DC}
V_{OUTPRG}	Output voltage (programming)		+21	V_{DC}
I_{IN}	Input current	−30	+5	mA
I_{OUT}	Output current		+100	mA
I_{OUTPRG}	Output current (programming)		+170	mA
	Temperature range			
T_A	Operating temp	0	+75	°C
T_{STG}	Storage temp	−65	+150	°C

Notes on following page.

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			+0.8	V
V_{IH}	High	V_{CC} = Max	+2.0			
V_I	Clamp	V_{CC} = Min, I_{IN} = −18mA		−0.9	−1.2	
Output voltage						
		V_{CC} = Min, V_{IN} = V_{IH} or V_{IL}				
V_{OL}	Low	I_{OL} = +24mA			+0.50	V
V_{OH}	High	I_{OH} = −3.2	+2.4	+3.5		
Input current						
		V_{CC} = Max				
I_{IL}	Low	V_{IN} = +0.40V		−20	−100	µA
I_{IH}	High	V_{IN} = +2.7V			+25	µA
I_I	High	V_{IN} = +5.5V			+1.0	mA
Output current						
		V_{CC} = Max, V_{IL} = 0.8V, V_{IH} = 2.0V				
I_{OZH}	Output leakage	V_{OUT} = +2.7V			+100	µA
I_{OZL}	Output leakage	V_{OUT} = +0.40V			−250	µA
I_{SC}	Short circuit[4]	V_{OUT} = +0.5V	−25	−60	−90	mA
I_{CC}	V_{CC} current	V_{CC} = Max, All inputs = GND		100	155	mA
Capacitance[5]						
		V_{CC} = +5V				
C_{IN}	Input	V_{IN} = 2.0V @ f = 1MHz		6		pF
C_{OUT}	I/O	V_{OUT} = 2.0V @ f = 1MHz		9		pF

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. Typical limits are at V_{CC} = 5.0V and T_A = + 25°C.
3. These are absolute values with respect to device ground and all overshoots due to system or tester noise are included.
4. Not more than one output should be tested at a time. Duration of the short circuit should not be more than one second. V_{OUT} = 0.5V has been chosen to avoid test problems caused by tester ground degradation.
5. These parameters are not 100% tested, but are periodically sampled.

AC ELECTRICAL CHARACTERISTICS $R_1 = 200\Omega$, $R_2 = 390\Omega$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ	Max	
t_{PD}	Propagation delay	Input ±	Output ±	$C_L = 50pF$		14	20	ns
t_{EA}	Output enable	Input ±	Output –	$C_L = 50pF$		14	20	ns
t_{ER}	Output disable	Input ±	Output +	$C_L = 5pF$		14	20	ns

NOTES:

1. Typical limits are at $V_{CC} = 5.0V$ and $T_A = +25°C$.
2. T_{PD} is tested with switch S_1 closed and $C_L = 50pF$.
3. For Tri-state output; output enable times are tested with $C_L = 50pF$ to the 1.5V level, and S_1 is open for high-impedance to High tests and closed for high-impedance to Low tests. Output disable times are tested with $C_L = 5pF$. High-to-High impedance tests are made to an output voltage of $V_{OH} = -0.5V$ with S_1 open, and Low-to-High impedance tests are made to the $V_{OL} = +0.5V$ level with S_1 closed.

VIRGIN STATE

A factory shipped virgin device contains all fusible links open, such that:

1. All outputs are at "L" polarity.
2. All outputs are enabled.
3. All p-terms are enabled.

TIMING DEFINITIONS

t_{PD}	Input to output propagation delay.
t_{ER}	Input to output disable (Tri-state) delay (Output Disable).
t_{EA}	Input to Output Enable delay (Output Enable).

TIMING DIAGRAM


INPUTS, I/O
3.0V
1.5V
0.0V
tPD
tER
tEA
OUTPUTS
VOH
VOL
WAVEFORM
INPUTS
OUTPUTS
MUST BE STEADY
WILL BE STEADY
WAVEFORM
INPUTS
OUTPUTS
DON'T CARE; ANY CHANGE PERMITTED
CHANGING; STATE UNKNOWN
DOES NOT APPLY
CENTER LINE IS HIGH IMPEDANCE "OFF" STATE
WF07381S

Programmable AND Array Logic (18 × 72 × 8) PLHS18P8A

AC TEST LOAD CIRCUIT


V_{CC}
+5V
S1
C1
C2
R1
R2
CL
I0
I9
BW
BX
BY
BZ
DUT
GND
INPUTS
OUTPUTS
TC02551S

NOTE:
C_1 and C_2 are to bypass V_{CC} to GND.

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this Table the logic state of variables I, P, and B associated with each Sum Term, S, is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

OUTPUT POLARITY – (B)



ACTIVE LEVEL	CODE
HIGH	H

TC02530S



ACTIVE LEVEL	CODE
LOW[1]	L

TC02541S

"AND" ARRAY – (I, B)



STATE	CODE
INACTIVE[2]	O

TC02650S



STATE	CODE
I, B	H

TC02660S



STATE	CODE
Ī, B̄	L

TC02670S



STATE	CODE
DON'T CARE[1]	–

TC02640S

NOTES:
1. This is the initial state of all link pairs.
2. All unused product terms must be programmed with all pairs of fuses in the INACTIVE state (all fuses on an unused p-term must be programmed).

Programmable AND Array Logic (18 × 72 × 8) PLHS18P8A

PROGRAM TABLE

CUSTOMER NAME ____
PURCHASE ORDER # ____
SIGNETICS DEVICE # ____ CF (XXXX) ____
CUSTOMER SYMBOLIZED PART # ____
TOTAL NUMBER OF PARTS ____
PROGRAM TABLE # ____ REV ____ DATE ____

AND

INACTIVE	O	I,B(I)
I, B	H	
Ī, B̄	L	
DON'T CARE	—	

CONTROL

HIGH	H	(POL)
LOW	L	

Notes

1. The FPLA is shipped with all links open.
2. Unused I and B bits in the AND array exist as Don't Care (–) in the virgin state.
3. All p-terms are active until programmed otherwise.
4. All unused product terms must be programmed with all pairs of fuses in the INACTIVE state (all fuses on an unused p-term must be programmed).
5. OR array is fixed as depicted.

																			POLARITY							
TERM	AND																		OR (FIXED)							
	I										B (I)								B (O)							
	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0																			D							
1																			A							
2																			A							
3																			A							
4																			A							
5																			A							
6																			A							
7																			A							
8																			A							
9																				D						
10																				A						
11																				A						
12																				A						
13																				A						
14																				A						
15																				A						
16																				A						
17																				A						
18																					D					
19																					A					
20																					A					
21																					A					
22																					A					
23																					A					
24																					A					
25																					A					
26																					A					
27																						D				
28																						A				
29																						A				
30																						A				
31																						A				
32																						A				
33																						A				
34																						A				
35																						A				
36																							D			
37																							A			
38																							A			
39																							A			
40																							A			
41																							A			
42																							A			
43																							A			
44																							A			
45																								D		
46																								A		
47																								A		
48																								A		
49																								A		
50																								A		
51																								A		
52																								A		
53																								A		
54																									D	
55																									A	
56																									A	
57																									A	
58																									A	
59																									A	
60																									A	
61																									A	
62																									A	
63																										D
64																										A
65																										A
66																										A
67																										A
68																										A
69																										A
70																										A
71																										A
PIN	11	9	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	19	18	17	16	15	14	13	12
VARIABLE NAME																										

TB02022S

Signetics

Section 5
PLD Data Sheets

Application Specific Products

INDEX

Section 5 – PLD Data Sheets

Series 24

PLS161 Field-Programmable Logic Array (12 × 48 × 8) 5-3
PLS162 Field-Programmable Address Decoder (16 × 5) 5-9
PLS163 Field-Programmable Address Decoder (12 × 9) 5-15
PLS167 Field-Programmable Logic Sequencer (14 × 48 × 6) ... 5-21
PLS167A Field-Programmable Logic Sequencer; Enhanced Speed (14 × 48 × 6) 5-33
PLS168 Field-Programmable Logic Sequencer (12 × 48 × 8) ... 5-45
PLS168A Field-Programmable Logic Sequencer; Enhanced Speed (12 × 48 × 8) 5-57
PLS173 Field-Programmable Logic Array (22 × 42 × 10) 5-69
PLS179 Field-Programmable Logic Sequencer (20 × 45 × 12).. 5-75
PLHS473 Field-Programmable Logic Array (20 × 24 × 11) 5-85
PLC473 Erasable-Programmable Logic Array (20 × 24 × 11).... 5-91

Signetics

PLS161
Field-Programmable Logic Array (12 × 48 × 8)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 24

DESCRIPTION

The PLS161 is a bipolar, Field-Programmable Logic Array (FPLA). The device utilizes the standard AND/OR/Invert architecture to directly implement custom sum of product logic equations.

This device consists of 12 dedicated inputs and 8 dedicated outputs. Each output is capable of being actively controlled by any or all of the 48 product terms. The True, Complement, or Don't Care condition of each of the 12 inputs ANDed together comprise one P-term. All 48 P-terms are selectively ORed to each output. The user must then only select which P-terms will activate an output by disconnecting terms which do not affect the output. In addition each output can be fused as Active-High (H) or Active-Low (L).

The PLS161 is fully TTL compatible, and includes a chip enable input for output inhibit control and expansion of input variables.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr Link)**
- **Input variables: 12**
- **Output functions: 8**
- **Product terms: 48**
- **I/O propagation delay: 50ns (max.)**
- **Power dissipation: 600mW (typ.)**
- **Input loading: −100μA (max.)**
- **Chip Enable input**
- **Output disable function**
- **Separate I/O architecture**
- **Tri-state outputs**

APPLICATIONS

- **CRT display systems**
- **Random logic**
- **Code conversion**
- **Peripheral controllers**
- **Function generators**
- **Look-up and decision tables**
- **Microprogramming**
- **Address mapping**
- **Character generators**
- **Sequential controllers**
- **Data security encoders**
- **Fault detectors**
- **Frequency synthesizers**

PIN CONFIGURATION

N Package



N = Plastic

LOGIC FUNCTION

TYPICAL PRODUCT TERM
$P_0 = I_0 \bullet I_1 \bullet \overline{I_2} \bullet I_5 \bullet \overline{I_{11}}$

TYPICAL OUTPUT FUNCTIONS:
@ $\overline{CE} = 0$:
$F_0 = (P_0 + P_1 + P_2)$ @ L = CLOSED
$F_0 = (\overline{P_0} \bullet \overline{P_1} \bullet \overline{P_2})$ @ L = OPEN

NOTE:
For each of the 8 outputs either the function F_p (Active-High) or $\overline{F_p}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.

FUNCTIONAL DIAGRAM



Field-Programmable Logic Array (12 × 48 × 8)

PLS161

FPLA LOGIC DIAGRAM


(SECTOR)
I0 7
I1 6
I2 5
I3 4
I4 3
I5 2
I6 23
I7 22
I8 21
I9 20
I10 19
I11 18
S0 X0 16 F0
S1 X1 15 F1
S2 X2 14 F2
S3 X3 13 F3
S4 X4 11 F4
S5 X5 10 F5
S6 X6 9 F6
S7 X7 8 F7
17 CE
47 • • • • • • 40 39 • • • • • • 32 31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
LD02290S

NOTES:
1. All AND/EX-OR gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown link float to a logic "0".
3. ▨ Programmable connection.

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS161N

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High[5]	I_{OH} = −2mA	2.4			V
V_{OL}	Low[6]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
		V_{CC} = Max				
I_{IH}	High	V_{IN} = 5.5V		< 1	40	µA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
		$\overline{CE}$ = High, V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state	V_{OUT} = 5.5V		1	40	µA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[4,7]	$\overline{CE}$ = Low, V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		120	170	mA
Capacitance						
		$\overline{CE}$ = High, V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2V		8		pF
C_{OUT}	Output	V_{OUT} = 2V		17		

Notes on following page.

Field-Programmable Logic Array (12 × 48 × 8) PLS161

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[2]	Max	
Propagation delay							
t_{PD}	Input	Output	Input		35	50	ns
t_{CE}	Chip enable	Output	Chip enable		15	30	ns
Disable time							
t_{CD}	Chip disable	Output	Chip enable		15	30	ns

NOTES:
1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other conditions above those indicated in the operational and programming specification of the device is not implied.
2. All values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one pin at a time.
5. Measured with V_{IL} applied to $\overline{CE}$ and a logic high stored.
6. Measured with a programmed logic condition for which the output test is at a low logic level. Output sink current is applied through a resistor to V_{CC}.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with the chip enable input grounded, all other inputs at 4.5V and the outputs open.

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this Table the logic state or action of variables I, P, and F, associated with each Sum Term S_n, is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

EX-OR ARRAY – (F)



ACTIVE LEVEL	CODE
LOW	L

LS02293S



ACTIVE LEVEL	CODE
HIGH[1]	H

LS02304S

"AND" ARRAY – (I)



STATE	CODE
INACTIVE[1,2]	O

LS02311S



STATE	CODE
I	H

LS02321S



STATE	CODE
Ī	L

LS02331S



STATE	CODE
DON'T CARE	—

LS02341S

"OR" ARRAY – (F)



LS02010S

P_n STATUS	CODE
ACTIVE	A



LS02020S

P_n STATUS	CODE
INACTIVE	●

NOTES:
1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates P_n.
2. Any gate P_n will be unconditionally inhibited if any one of its (I) link pairs is left intact.

TEST LOAD CIRCUIT


I0
VCC
DUT
F0
F7
I11
CE
GND
TC01652S
+5 V
R1
R2
CL
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01661S

VOLTAGE WAVEFORM


+3.0V
90%
10%
0V
5ns
tr
tf
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

TIMING DIAGRAMS


INPUT
1.5V
+3.0V
0V
CE
1.5V
1.5V
+3.0V
0V
tCE
tCD
F0-F7
1.5V
1.5V
VOH
VOL
tPD
WF06501S

Read Cycle

TIMING DEFINITIONS

t_{CE}	Delay between beginning of Chip Enable Low (with Input valid) and when Data Output becomes valid.
t_{CD}	Delay between when Chip Enable becomes High and Data Output is in off state (Hi-Z or High).
t_{PD}	Delay between beginning of valid Input (with Chip Enable Low) and when Data Output becomes valid.

VIRGIN STATE

The PLS161 virgin device is factory shipped in an unprogrammed state, with all fuses intact, such that:

1. All P_n terms are disabled. (Inactive).
2. All P_n terms are active on all outputs.
3. All outputs are Active-High.

FPLA PROGRAM TABLE

CUSTOMER NAME ____

PURCHASE ORDER # ____

SIGNETICS DEVICE # ____ CF (XXXX)

CUSTOMER SYMBOLIZED PART # ____

TOTAL NUMBER OF PARTS ____

PROGRAM TABLE # ____ REV ____ DATE ____

PROGRAM TABLE ENTRIES

INPUT VARIABLE			OUTPUT FUNCTION		OUTPUT ACTIVE LEVEL	
I_m	I_m	Don't Care	Prod Term Present in F_P	Prod Term Not Present in F_P	Active High	Active Low
H	L	—(dash)	A	· (period)	H	L

NOTE
Enter (-) for unused inputs of used P-terms.

NOTES
1. Entries independent of output polarity.
2. Enter (A) for unused outputs of used P-terms.

NOTES
1. Polarity programmed once only.
2. Enter (H) for all unused outputs.

	AND												POLARITY							
	INPUT (I_m)												OR							
													OUTPUT (F_P)							
TERM	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0																				
1																				
2																				
3																				
4																				
5																				
6																				
7																				
8																				
9																				
10																				
11																				
12																				
13																				
14																				
15																				
16																				
17																				
18																				
19																				
20																				
21																				
22																				
23																				
24																				
25																				
26																				
27																				
28																				
29																				
30																				
31																				
32																				
33																				
34																				
35																				
36																				
37																				
38																				
39																				
40																				
41																				
42																				
43																				
44																				
45																				
46																				
47																				
PIN NO.	18	19	20	21	22	23	2	3	4	5	6	7	8	9	10	11	13	14	15	16
VARIABLE NAME																				

TB01540S

Signetics

PLS162
Field-Programmable Address Decoder (16 × 5)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 24**

DESCRIPTION

The PLS162 is a bipolar, Field-Programmable Address Decoder. The device consists of five AND/NAND gates which share 16 common inputs. The type of gate is selected by programming the output as Active-High (H) or Active-Low (L). Each of the 16 inputs $I_0 - I_{15}$ can be programmed to provide the True (H), Complement (L), or Don't Care (—) state to each of the five AND/NAND gates. OR/NOR logic functions can also be implemented by complementing the inputs and outputs via on-chip inverting buffers.

The device is field programmable, which means that custom patterns are immediately available.

The PLS162 includes chip-enable control for output strobing and inhibit. It features Tri-state outputs for ease of expansion of input variables and application in bus-organized systems.

Order codes are contained on the following pages.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **16 input variables**
- **5 output functions**
- **Chip Enable input**
- **I/O propagation delay: 30ns (max.)**
- **Power dissipation: 500mW (typ.)**
- **Input loading: −100μA (max.)**
- **Tri-state outputs**
- **Output disable function: Hi-Z**
- **Fully TTL compatible**

APPLICATIONS

- **Random logic**
- **Address decoders**
- **Code detectors**
- **Peripheral selectors**
- **Fault monitors**
- **Machine state decoders**

PIN CONFIGURATION

N Package*



*N = Plastic

LOGIC FUNCTION

TYPICAL OUTPUT FUNCTIONS:
ACTIVE-HIGH
$X = A \cdot \overline{B} \cdot C \cdot \ldots$

ACTIVE-LOW
$X = \overline{A \cdot \overline{B} \cdot C \cdot \ldots}$
$X = \overline{A} + B + \overline{C} + \ldots$

NOTES:
1. For each of the 5 outputs, either function X (Active-High) or $\overline{X}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. X, A, B, C, etc. are user defined connections to fixed inputs (I) and output pins (F).

FUNCTIONAL DIAGRAM



Field-Programmable Address Decoder (16 × 5) PLS162

FPAD LOGIC DIAGRAM


(LOGIC GATES—G)
I_0 8
I_1 7
I_2 6
I_3 5
I_4 4
I_5 3
I_6 2
I_7 1
I_8 23
I_9 22
I_{10} 21
I_{11} 20
I_{12} 19
I_{13} 18
I_{14} 17
I_{15} 16
4
3
2
1
0
X_4
X_3
X_2
X_1
X_0
$\overline{CE}$ 15
9 F_4
10 F_3
11 F_2
13 F_1
14 F_0
LD01240S

NOTE:
1. All gate inputs with a blown link float to a logic "1".
2. ▨ Programmable connection.

Field-Programmable Address Decoder (16 × 5) PLS162

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS162N

ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER	RATING	UNIT
V_{CC}	Supply voltage	+7	V_{DC}
V_{IN}	Input voltage	+5.5	V_{DC}
V_O	Output voltage Off-state	+5.5	V_{DC}
I_{IN}	Input current	±30	mA
I_{OUT}	Output current	+100	mA
	Temperature range		
T_A	Operating	0 to +75	°C
T_{STG}	Storage	−65 to +150	

DC ELECTRICAL CHARACTERISTICS $0°C \leq T_A \leq +75°C$, $4.75 \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[1]						
V_{IH}	High	V_{CC} = Max	2.0			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[3]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[1]						
V_{OH}	High[5]	V_{CC} = Min I_{OH} = −2mA	2.4			V
V_{OL}	Low[4]	I_{OL} = 15mA		0.35	0.5	
Input current						
I_{IH}	High	V_{CC} = Max V_{IN} = 5.5V		< 1	40	µA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
$I_{O (OFF)}$	Hi-Z state[6]	V_{CC} = Max V_{OUT} = 5.5V		1	40	µA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[3,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		100	155	mA
Capacitance						
C_{IN}	Input	V_{CC} = 5.0V V_{IN} = 2.0V		8		pF
C_{OUT}	Output[6]	V_{OUT} = 2.0V		15		

AC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$, $R_1 = 470\Omega$, $R_2 = 1k\Omega$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ[1]	Max	
t_{PD}	Propagation delay	Output	Input	$C_L = 30pF$		20	30	ns
t_{CE}	Chip enable	Output	Chip enable	$C_L = 30pF$		20	30	ns
t_{CD}	Chip disable	Output	Chip enable	$C_L = 5pF$		20	30	ns

NOTES:

1. All voltage values are with respect to network ground terminal.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. Test each pin one at a time.
4. Measure with a programmed logic condition for which the output under test is at low logic level. Output sink current is supplied through a resistor to V_{CC}.
5. Measured with V_{IL} applied to $\overline{CE}$ and logic high at the output.
6. Measured with V_{IH} applied to $\overline{CE}$.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with the outputs open.

Field-Programmable Address Decoder (16 × 5) PLS162

TEST LOAD CIRCUIT


I0
VCC
F0
DUT
F4
I15
CE
GND
TC01650S


VCC
R1
R2
CL
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01660S

VOLTAGE WAVEFORM


3.0V
INPUT
1.5V
0V
3.0V
CE
1.5V
1.5V
0V
tCE
tCD
VOH
F0 ~ F4
1.5V
1.5V
VOL
tPD
WF05521S

All inputs: $t_r = t_f = 5\text{ns}$ (10% to 90%)

LOGIC PROGRAMMING

In a virgin device all Ni-Cr links are intact. The FPAD can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/EX-OR gate input connections necessary to implement the desired logic function are coded directly from the Program Table on the following page.

In this table, the logic state of variables I and F associated with each gate G_n is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

OUTPUT POLARITY – (F)



ACTIVE LEVEL	CODE
HIGH	H

LS02350S



ACTIVE LEVEL	CODE
LOW[1]	L

LS02361S

"AND" ARRAY – (I)



STATE	CODE
INACTIVE[1,2]	O

LS02370S



STATE	CODE
I	H

LS02380S



STATE	CODE
I	L

LS02390S



STATE	CODE
DON'T CARE	—

LS02400S

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate G_n will be unconditionally inhibited if both the true and complement of any input (either I or B) are left intact.

VIRGIN DEVICE

The PLS162 is shipped in an unprogrammed state, characterized by:

1. All P_n terms are disabled. (Inactive).
2. All P_n terms are active on all outputs.
3. All outputs are Active-Low.

FPAD PROGRAM TABLE

CUSTOMER NAME ____________________
PURCHASE ORDER # ____________________
SIGNETICS DEVICE # ____________________
TOTAL NUMBER OF PARTS ____________________
PROGRAM TABLE # ____________________

THIS PORTION TO BE COMPLETED BY SIGNETICS
CF (XXXX) ____________________
CUSTOMER SYMBOLIZED PART # ____________________
DATE RECEIVED ____________________
COMMENTS ____________________

F_0 (14) ____________ = ____________________
F_1 (13) ____________ = ____________________
F_2 (11) ____________ = ____________________
F_3 (10) ____________ = ____________________
F_4 (9) ____________ = ____________________

GATE		**INPUT**															
POLARITY		I_{15}	I_{14}	I_{13}	I_{12}	I_{11}	I_{10}	I_9	I_8	I_7	I_6	I_5	I_4	I_3	I_2	I_1	I_0
F_0																	
F_1																	
F_2																	
F_3																	
F_4																	
PIN NO.		16	17	18	19	20	21	22	23	1	2	3	4	5	6	7	8
VARIABLE NAME																	

NOTES
1. The FPAD is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Unused I bits are normally programmed Don't Care (—).
3. Unused Gates can be left blank.

PROGRAM TABLE ENTRIES

AND

INACTIVE	**0**
I	**H**
$\overline{I}$	**L**
Don't Care	**—**

(I)

CONTROL

HIGH	**H**
LOW	**L**

(POL.)

TB01281S

Signetics

PLS163

Field-Programmable Address Decoder (12 × 9)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 24

DESCRIPTION

The PLS163 is a bipolar, Field-Programmable Address Decoder. The device consists of nine AND/NAND gates which share 12 common inputs. The type of gate is selected by programming the output as Active-High (H) or Active-Low (L). Each of the 12 inputs $I_0 - I_{11}$ can be programmed to provide the True (H), Complement (L), or Don't Care (—) state to each of the nine AND/NAND gates. OR/NOR logic functions can also be implemented by complementing the inputs and outputs via on-chip inverting buffers.

The device is field programmable, which means that custom patterns are immediately available.

The PLS163 includes chip-enable control for output strobing and inhibit. It features Tri-state outputs for ease of expansion of input variables and application in bus-organized systems.

Order codes are contained on the following pages.

FEATURES

- Field-Programmable (Ni-Cr link)
- 12 input variables
- 9 output functions
- Chip Enable input
- I/O propagation delay: 30ns (max.)
- Power dissipation: 600mW (typ.)
- Input loading: −100μA (max.)
- Tri-state outputs
- Output disable function: Hi-Z
- Fully TTL compatible

APPLICATIONS

- Random logic
- Address decoders
- Code detectors
- Peripheral selectors
- Fault monitors
- Machine state decoders

PIN CONFIGURATION

N Package*



CD03330S

*N = Plastic

LOGIC FUNCTION

TYPICAL OUTPUT FUNCTIONS:
ACTIVE-HIGH

$X = A \cdot \overline{B} \cdot C \cdot \ldots$

ACTIVE-LOW

$X = \overline{A \cdot \overline{B} \cdot C \cdot \ldots}$
$X = \overline{A} + B + \overline{C} + \ldots$

NOTES:

1. For each of the 9 outputs, either function X (Active-High) or $\overline{X}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. X, A, B, C, etc. are user defined connections to fixed inputs (I) and output pins (F).

FUNCTIONAL DIAGRAM



Fusible Ni-Cr links are initially intact at all array cross-points.

Field-Programmable Address Decoder (12 × 9)

PLS163

FPAD LOGIC DIAGRAM


(LOGIC GATES—G)
I_0 6
I_1 5
I_2 4
I_3 3
I_4 2
I_5 1
I_6 23
I_7 22
I_8 21
I_9 20
I_{10} 19
I_{11} 18
8 7 6 5 4 3 2 1 0
X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
$\overline{CE}$ 17
7 8 9 10 11 13 14 15 16
F_8 F_7 F_6 F_5 F_4 F_3 F_2 F_1 F_0
LD01221S

NOTES:

1. All gate inputs with a blown link float to a logic "1".
2. ▨ Programmable connection.

Field-Programmable Address Decoder (12 × 9) PLS163

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS163N

ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER	RATING	UNIT
V_{CC}	Supply voltage	+7	V_{DC}
V_{IN}	Input voltage	+5.5	V_{DC}
V_O	Output voltage Off-state	+5.5	V_{DC}
I_{IN}	Input current	±30	mA
I_{OUT}	Output current	+100	mA
	Temperature range		°C
T_A	Operating	0 to +75	
T_{STG}	Storage	−65 to +150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage						
V_{IH}	High[1]	V_{CC} = Max	2.0			V
V_{IL}	Low[1]	V_{CC} = Min			0.8	
V_{IC}	Clamp[1,3]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage						
		V_{CC} = Min				
V_{OH}	High[1,5]	I_{OH} = −2mA	2.4			V
V_{OL}	Low[1,4]	I_{OL} = 15mA		0.35	0.5	
Input current						
		V_{CC} = Max				
I_{IH}	High	V_{IN} = 5.5V		< 1	40	μA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
		V_{CC} = Max				
$I_{O (OFF)}$	Hi-Z state[6]	V_{OUT} = 5.5V		1	40	μA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[3,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		120	155	mA
Capacitance						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output[6]	V_{OUT} = 2.0V		15		

Field-Programmable Address Decoder (12 × 9) PLS163

AC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$, $R_1 = 470\Omega$, $R_2 = 1k\Omega$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ[2]	Max	
t_{PD}	Propagation delay	Output	Input	$C_L = 30pF$		20	30	ns
t_{CE}	Chip enable	Output	Chip enable	$C_L = 30pF$		20	30	ns
t_{CD}	Chip disable	Output	Chip enable	$C_L = 5pF$		20	30	ns

NOTES:

1. All voltage values are with respect to network ground terminal.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. Test each pin one at a time.
4. Measure with a programmed logic condition for which the output under test is at low logic level. Output sink current is supplied through a resistor to V_{CC}.
5. Measured with V_{IL} applied to $\overline{CE}$ and logic high at the output.
6. Measured with V_{IH} applied to $\overline{CE}$.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with the outputs open.

Field-Programmable Address Decoder (12 × 9) PLS163

TEST LOAD CIRCUIT


I_0
VCC
DUT
F_0
F_8
I_{11}
$\overline{CE}$
GND
TC01630S
V_{CC}
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01640S

VOLTAGE WAVEFORM


INPUT
1.5V
+3.0V
0V
$\overline{CE}$
1.5V
1.5V
+3.0V
0V
t_{CE}
t_{CD}
$F_0 \sim F_8$
1.5V
1.5V
V_{OH}
V_{OL}
t_{PD}
WF05511S

All inputs: $t_r = t_f = 5\text{ns}$ (10% to 90%)

LOGIC PROGRAMMING

In a virgin device all Ni-Cr links are intact. The FPAD can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/EX-OR gate input connections necessary to implement the desired logic function are coded directly from the logic equations using the Program Table on the following page.

In this table, the logic state of variables I and F associated with each gate G_n is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

OUTPUT POLARITY – (F)


G
F
LS02290S
G
$\overline{F}$
LS02361S

ACTIVE LEVEL	CODE
HIGH	H

ACTIVE LEVEL	CODE
LOW[1]	L

"AND" ARRAY – (I)


I
i
$\overline{i}$
P
LS02311S
I
i
$\overline{i}$
G
LS02320S
I
i
$\overline{i}$
G
LS02330S
I
i
$\overline{i}$
G
LS02340S

STATE	CODE
INACTIVE[1,2]	O

STATE	CODE
I	H

STATE	CODE
I	L

STATE	CODE
DON'T CARE	—

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate G_n will be unconditionally inhibited if both the true and complement fuses of any input (I) are left intact.

VIRGIN DEVICE

The PLS163 is shipped in an unprogrammed state, characterized by:

1. All P_n terms are disabled. (Inactive).
2. All P_n terms are active on all outputs.
3. All outputs are Active-Low.

Field-Programmable Address Decoder (12 × 9) PLS163

FPAD PROGRAM TABLE

CUSTOMER NAME ______	*THIS PORTION TO BE COMPLETED BY SIGNETICS*
PURCHASE ORDER # ______	*CF (XXXX)* ______
SIGNETICS DEVICE # ______	*CUSTOMER SYMBOLIZED PART #* ______
TOTAL NUMBER OF PARTS ______	*DATE RECEIVED* ______
PROGRAM TABLE # ______	*COMMENTS* ______

F_0 (16) ______ = ______

F_1 (15) ______ = ______

F_2 (14) ______ = ______

F_3 (13) ______ = ______

F_4 (11) ______ = ______

F_5 (10) ______ = ______

F_6 (9) ______ = ______

F_7 (8) ______ = ______

F_8 (7) ______ = ______

GATE		**INPUT**											
POLARITY		I_{11}	I_{10}	I_9	I_8	I_7	I_6	I_5	I_4	I_3	I_2	I_1	I_0
F_0													
F_1													
F_2													
F_3													
F_4													
F_5													
F_6													
F_7													
F_8													
PIN NO.		18	19	20	21	22	23	1	2	3	4	5	6
VARIABLE NAME													

NOTES
1. The FPAD is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Unused I bits are normally programmed Don't Care (—).
3. Unused Gates can be left blank.

PROGRAM TABLE ENTRIES

AND

INACTIVE	0
I	H
$\overline{I}$	L
Don't Care	—

(I)

CONTROL

HIGH	H
LOW	L

(POL.)

TB01271S

Signetics

PLS167

Field-Programmable Logic Sequencer (14 × 48 × 6)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 24

DESCRIPTION

The PLS167 is a bipolar, programmable state machine of the Mealy type. The Field Programmable Logic Sequencer (FPLS) contains logic AND-OR gate arrays with user programmable connections which control the inputs of on-chip State and Output Registers. These consist respectively of 8 Q_p, and 4 Q_f edge-triggered, clocked S/R flip-flops, with an asynchronous preset option.

All flip-flops are unconditionally preset to "1" during power turn-on.

The AND Array combines 14 external inputs, I_{0-13}, with 8 internal inputs, P_{0-7}, fed back from the State Register to form up to 48 transition terms (AND terms). In addition, P_0 and P_1 of the internal State Register are brought off-chip to allow extending the Output Register to 6 bits, if so desired.

All transition terms can include True, False, or Don't Care states of the controlling variables, and are merged in the OR Array to issue next-state and next-output commands to their respective registers on the Low-to-High transition of the Clock pulse.

Both True and Complement transition terms can be generated by optional use of the internal variable (C) from the Complement Array. Also, if desired, the Preset input can be converted to Output-Enable function, as an additional user programmable option.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **14 True/Complement buffered inputs**
- **48 programmable AND gates**
- **25 programmable OR gates**
- **8-bit State Register**
- **2-bit shared State/Output Register**
- **4-bit Output Register**
- **Transition Complement Array**
- **Programmable Asynchronous Preset/Output Enable**
- **Positive edge-triggered clock**
- **Power-on preset to logic "1" of all registers**
- **Automatic logic "HOLD" state via S/R flip-flops**
- **On-chip Test Array**
- **f_{MAX}: 13.9MHz**
- **Power: 600mW (typ.)**
- **TTL compatible**
- **Tri-state outputs**
- **Single +5V supply**
- **300mil-wide 24-pin DIP**

PIN CONFIGURATIONS

N Package


CK 1
I6 2
I5 3
I4 4
I3 5
I2 6
I1 7
I0 8
F0 9
F1 10
F2 11
GND 12
24 VCC
23 I7
22 I8
21 I9
20 I10
19 I11
18 I12
17 I13
16 PR/OE
15 P1
14 P0
13 F3
CD04481S

N = Plastic

A Package


NC 11
F0 10
I0 9
I1 8
I2 7
I3 6
N/C 5
F1 12
F2 13
GND 14
F3 15
P0 16
P1 17
PR/OE 18
4 I4
3 I5
2 I6
1 CK
28 VCC
27 I7
26 I8
19 N/C
20 I13
21 I12
22 I11
23 I10
24 I9
25 N/C
CD04471S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- **Interface protocols**
- **Sequence detectors**
- **Peripheral controllers**
- **Timing generators**
- **Sequential circuits**
- **Security locking systems**

FUNCTIONAL DIAGRAM


IM
C̄
C
STATE REG.
S Q
(6)
R P
S Q
(2)
R P
S Q
(4)
R P
OUTPUT REG.
P
E
PR/OE
P
F
CK
T47
T0
LD01151S

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167

PIN DESCRIPTION

PIN NO.	SYMBOL	NAME AND FUNCTION	POLARITY
1	CK	**Clock:** The Clock input to the State and Output Registers. A Low-to-High transition on this line is necessary to update the contents of both registers.	Active-High
2 – 7 17 – 23	I_{1-13}	**Logic Inputs:** The 13 external inputs to the AND array used to program jump conditions between machine states, as determined by a given logic sequence.	Active-High/Low
8	I_0	**Logic/Diagnostic Input:** A 14th external logic input to the AND array, as above, when exercised with standard TTL levels. When I_0 is held at +10V, device outputs F_{0-3} and P_{0-1} reflect the contents of State Register bits P_{2-7} (see Diagnostic Output Mode diagram). The contents of flip-flops P_{0-1} and F_{0-3} remain unaltered.	Active-High/Low
9 – 11 13	F_{0-3}	**Logic/Diagnostic Outputs:** Four device outputs which normally reflect the contents of Output Register bits Q_{0-3}, when enabled. When I_0 is held at +10V, $F_{0-3} = (P_{2-5})$.	Active-High
14 – 15	P_{0-1}	**Logic/Diagnostic Outputs:** Two register bits with shared function as least significant State Register bits, or most significant Output Register bits. When I_0 is held at +10V, $P_{0-1} = (P_{6-7})$.	Active-High
16	PR/$\overline{OE}$	**Preset or $\overline{\text{Output Enable}}$ Input:** A user programmable function: • **Preset:** Provides an asynchronous preset to logic "1" of all State and Output Register bits. Preset overrides Clock, and when held High, clocking is inhibited and P_{0-1} and F_{0-3} are High. Normal clocking resumes with the first full clock pulse following a High-to-Low clock transition, after Preset goes Low. • **$\overline{\text{Output Enable}}$:** Provides an Output Enable function to all output buffers.	 Active-High (H) Active-Low (L)

LOGIC FUNCTION

Typical State Transition:



SET Q_0: $S_0 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$R_0 = 0$

RESET Q_1: $S_1 = 0$
$R_1 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $S_2 = 0$
$R_2 = 0$

TB00900S

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. PR/$\overline{OE}$ option is set to PR. Thus, all outputs will be at "1", as preset by initial power-up procedure.
2. All transition terms are disabled (0).
3. All S/R flip-flop inputs are disabled (0).
4. The device can be clocked via a Test Array pre-programmed with a standard test pattern.
   NOTE: The Test Array pattern MUST be deleted before incorporating a user program. This is accomplished automatically by any Signetics qualified programming equipment.

TRUTH TABLE [1, 2, 3, 4, 5, 6]

V_{CC}	OPTION		I_0	CK	S	R	$Q_{P/F}$	F
	PR	$\overline{OE}$						
+5V	H		*	X	X	X	H	H
	L		+10V	X	X	X	Q_n	$(Q_P)_n$
	L		X	X	X	X	Q_n	$(Q_F)_n$
		H	*	X	X	X	Q_n	Hi-Z
		L	+10V	X	X	X	Q_n	$(Q_P)_n$
		L	X	X	X	X	Q_n	$(Q_F)_n$
		L	X	↑	L	L	Q_n	$(Q_F)_n$
		L	X	↑	L	H	L	L
		L	X	↑	H	L	H	H
		L	X	↑	H	H	IND.	IND.
↑	X	X	X	X	X	X	H	

NOTES:

1. Positive Logic:
   $S/R = T_0 + T_1 + T_2 + \ldots + T_{47}$
   $T_n = C(I_0\ I_1\ I_2 \ldots)\ (P_0\ P_1 \ldots P_7)$
2. Either Preset (Active-High) or $\overline{\text{Output Enable}}$ (Active-Low) are available, but not both. The desired function is a user programmable option.
3. ↑ denotes transition from Low to High level.
4. R = S = High is an illegal input condition.
5. * = H/L/+10V
6. X = Don't Care ($\leqslant$ 5.5V)

FPLS LOGIC DIAGRAM


(LOGIC TERMS—T)
I_0 8
I_1 7
I_2 6
I_3 5
I_4 4
I_5 3
I_6 2
I_7 23
I_8 22
I_9 21
I_{10} 20
I_{11} 19
I_{12} 18
I_{13} 17
P
P_0 P_1 P_2 P_3 P_4 P_5 P_6 P_7
C
$\overline{C}$
N
F
I
OPTION
16 PR/$\overline{OE}$
P
E
S Q
R P
Q_3 Q_2 Q_1 Q_0
15 P_1
14 P_0
13 F_3
11 F_2
10 F_1
9 F_0
1 CK
47 40 39 32 31 24 23 16 15 8 7 0
LD02282S

NOTES:
1. All AND gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown fuse float to logic "0".
3. ▨ Programmable connection.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS167N
28-pin Plastic Leaded Chip Carrier	PLS167A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, I_{IN} = –12mA		–0.8	–1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High[5]	I_{OH} = –2mA	2.4			V
V_{OL}	Low[6]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	25	μA
I_{IL}	Low	V_{IN} = 0.45V		–10	–100	
I_{IL}	Low (CK input)	V_{IN} = 0.45V		–50	–250	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[7]	V_{OUT} = 5.5V		1	40	μA
		V_{OUT} = 0.45V		–1	–40	
I_{OS}	Short circuit[4,8]	V_{OUT} = 0V	–15		–70	mA
I_{CC}	V_{CC} supply current[9]	V_{CC} = Max		120	180	mA
Capacitance[7]						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		10		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = + 25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IL} applied to $\overline{OE}$ and a logic high stored, or with V_{IH} applied to PR.
6. Measured with a programmed logic condition for which the output is at a low logic level, and V_{IL} applied to PR/$\overline{OE}$ Output sink current is supplied through a resistor to V_{CC}.
7. Measured with V_{IH} applied to PR/$\overline{OE}$.
8. Duration of short circuit should not exceed 1 second.
9. I_{CC} is measured with the PR/$\overline{OE}$ input grounded, all other inputs at 4.5V and the outputs open.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[1]	Max	
Pulse width[3]							
t_{CKH}	Clock[2] high	CK −	CK +	25	15		ns
t_{CKL}	Clock low	CK +	CK −	25	15		
$t_{CKP1}B$	Period (without Complement Array)	CK +	CK +	80	40		
$t_{CKP2}B$	Period (with Complement Array)	CK +	CK +	120	60		
t_{PRH}	Preset pulse	PR −	PR +	25	15		
Setup time[3]							
$t_{IS1}A$	Input	CK +	Input ±	60			ns
$t_{IS1}B$	Input	CK +	Input ±	50			
$t_{IS1}C$	Input	CK +	Input ±	42			
$t_{IS2}A$	Input (through Complement Array)	CK +	Input ±	90			
$t_{IS2}B$	Input (through Complement Array)	CK +	Input	80			
$t_{IS2}C$	Input (through Complement Array)	CK +	Input	72			
t_{VS}	Power-on preset	CK −	V_{CC} +	0	−10		
t_{PRS}	Preset	CK −	PR −	0	−10		
Hold time							
t_{IH}	Input	Input ±	CK +	5	−10		ns
Propagation delay							
t_{CKO}	Clock	Output ±	CK +		15	30	ns
t_{OE}	Output enable	Output −	OE −		20	30	
t_{OD}	Output disable	Output +	OE +		20	30	
t_{PR}	Preset	Output +	PR +		18	30	
t_{PPR}	Power-on preset	Output +	V_{CC} +		0	10	
Frequency of operation[3]							
$f_{MAX}C$	Without Complement Array					13.9	MHz
$f_{MAX}C$	With Complement Array					9.8	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% − 90%) ⩽ 30ns.
3. See "Speed vs. OR Loading" diagrams.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167

TIMING DIAGRAMS


I_{0-13}
1.5V
1.5V
+3V
0V
t_{IH}
t_{IS}
CLK
1.5V
1.5V
1.5V
+3V
0V
t_{IS}
t_{CKH}
t_{CKL}
t_{CKP}
F_{0-3}/P_{0-1}
1.5V
1.5V
V_{OH}
V_{OL}
t_{CKO}
t_{OD}
$\overline{OE}$
1.5V
1.5V
+3V
0V
t_{OE}
WF05353S

Sequential Mode


I_{0-13}
1.5V
+3V
0V
t_{CKP}
CLK
1.5V
1.5V
1.5V
1.5V
+3V
0V
t_{IS}
t_{CKO}
t_{CKH}
t_{CKL}
F_{0-3}/P_{0-1}
1.5V
1.5V
1.5V
V_{OH}
V_{OL}
t_{PR}
t_{PRS}
t_{CKO}
PR
1.5V
1.5V
1.5V
+3V
0V
t_{PRH}
WF05363S

Asynchronous Preset


V_{CC}
4.5V
+5V
0V
t_{PPR}
F_{0-3}/P_{0-1}
1.5V
$(F_n) = 1$
1.5V
$(F_n = 1)$
V_{OH}
V_{OL}
t_{CKP}
t_{CKO}
CLK
1.5V
1.5V
1.5V
+3V
0V
t_{CKH}
t_{VS}
I_{0-13}
1.5V
1.5V
+3V
0V
t_{IS}
t_{IH}
WF05403S

Power-On Preset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP1}	Clock period – when not using Complement array.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{CKP2}	Clock period – when using complement array.
t_{IS2}	Required delay between beginning of valid input and positive transition of clock, when using optional Complement Array (two passes necessary through the AND array).
t_{VS}	Required delay between V_{CC} (after power-on) and negative transition of clock preceding first reliable clock pulse.
t_{PRS}	Required delay between negative transition of asynchronous Preset and negative transition of clock preceding first reliable clock pulse.
t_{IH}	Required delay between positive transition of clock and end of valid Input data.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with PR/$\overline{OE}$ low).
t_{OE}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{SRE}	Delay between input I_0 transition to Diagnostic mode and when the Outputs reflect the contents of the State Register.
t_{SRD}	Delay between input I_0 transition to Logic mode and when the Outputs reflect the contents of the Output Register.
t_{PR}	Delay between positive transition of Preset and when Outputs become valid at "1".
t_{PPR}	Delay between V_{CC} (after power-on) and when Outputs become preset at "1".
t_{PRH}	Width of preset input pulse.
f_{MAX}	Maximum clock frequency.

TIMING DIAGRAMS (Continued)


I
1.5V
+3V
0V
+10V
8.0V
8.0V
I_O
1.5V
1.5V
+3V
0V
t_{IH}
+3V
1.5V
1.5V
CLK
0V
t_{IS}
t_{CKH}
INTERNAL STATE REG.
(P_S)
(N_S)
V_{OH}
V_{OL}
t_{SRE}
t_{SRD}
V_{OH}
(F_n)
1.5V
(F_{n+1})
(N_S)
1.5V
(F_n + 1)
OUTPUT P, F
V_{OL}
t_{CKO}
$\overline{OE}$
0V
WF05381S

Diagnostic Output Mode

TEST LOAD CIRCUIT


V_{CC}
I_O
P_1
P_0
F_0
F_3
I_{13}
CK
PR/$\overline{OE}$
TC01571S


+5V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01580S

VOLTAGE WAVEFORM


+3.0V
90%
10%
0V
5ns
t_r
t_f
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

SPEED VS. "OR" LOADING

The maximum frequency at which the FPLS can be clocked while operating in *sequential mode* is given by:

$$(1/f_{MAX}) = t_{CY} = t_{IS} + t_{CKO}$$

This frequency depends on the number of transition terms T_n used. Having all 48 terms connected in the AND array does not appreciably impact performance; but the number of terms connected to each OR line affects t_{IS}, due to capacitive loading. The effect of this loading can be seen in Figure 1, showing the variation of t_{IS1} with the number of terms connected per OR.

The AC electrical characteristics contain three limits for the parameters t_{IS1} and t_{IS2}. The first, t_{IS1A} is guaranteed for a device with 48 terms connected to any OR line. t_{IS1B} is guaranteed for a device with 32 terms connected to any OR line. And t_{IS1C} is guaranteed for a device with 24 terms connected to any OR line.



Figure 1. t_{IS1} vs. Terms/OR Connected

The Three other entries in the AC table, t_{IS2} A, B, and C are corresponding 48, 32, and 24 term limits when using the on-chip Complement Array.

The worst case t_{IS} for a given application can be determined by identifying the OR line with the maximum number of T_n connections. This can be done by referring to the interconnect pattern in the FPLS logic diagram, typically illustrated in Figure 2, or by counting the maximum number of "H" *or* "L" entries in one of the columns of the device Program Table.

This number plotted on the curve in Figure 1 will yield the worst case t_{IS} and, by implication, the maximum clocking frequency for reliable operation.

Note that for maximum speed all UNUSED transition terms should be disconnected from the OR array.



Figure 2. Typical OR Array Interconnect Pattern

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table on the following page.

In this table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding links, defined as follows:

PRESET/$\overline{OE}$ OPTION – (P/E)


PR/$\overline{OE}$
P
E = 1
LS01810S

OPTION	CODE
PRESET^1	H


PR/$\overline{OE}$
P = 1
E
LS01820S

OPTION	CODE
$\overline{OE}$	L

PROGRAMMING:

The PLS167 has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (state and output register) at a logic High (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all Highs (H) as the present state.

"AND" ARRAY – (I), (P)


I,P
i,p
$\overline{i,p}$
T_n
LS01850S

STATE	CODE
INACTIVE^{1,2}	O


I,P
i,p
$\overline{i,p}$
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\overline{i,p}$
T_n
LS01830S

STATE	CODE
$\overline{I}$, $\overline{P}$	L


I,P
i,p
$\overline{i,p}$
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – (N), (F)


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01890S

ACTION	CODE
INACTIVE^{1,3}	O


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01900S

ACTION	CODE
SET	H


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01870S

ACTION	CODE
RESET	L


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01880S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)


$\overline{c}$
c
T_n
LS01930S

ACTION	CODE
INACTIVE^{1,4}	O


$\overline{c}$
c
T_n
LS01940S

ACTION	CODE
GENERATE	A


$\overline{c}$
c
T_n
LS01910S

ACTION	CODE
PROPAGATE	•


$\overline{c}$
c
T_n
LS01920S

ACTION	CODE
TRANSPARENT	–

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate T_n will be unconditionally inhibited if both the true and complement of any input (I, P) are left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.

Field-Programmable Logic Sequencer (14 × 48 × 6)

PLS167

FPLS PROGRAM TABLE

CUSTOMER NAME ____________________
PURCHASE ORDER # ____________________
SIGNETICS DEVICE # CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________________
TOTAL NUMBER OF PARTS ____________________
PROGRAM TABLE # ____________________
REV ____________________
DATE ____________________

PROGRAM TABLE ENTRIES

AND

INACTIVE	0	Cn
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	

INACTIVE	0	Im, Ps
I, P	H	
$\bar{I}$, $\bar{P}$	L	
DON'T CARE	—	

OR

INACTIVE	0	Ns, Fr
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

PRESET	H	P/E
$\overline{OE}$	L	

		AND																							OPTION (P/E)											
																									OR											
TERM	Cn	INPUT (I_M)														PRESENT STATE (P_S)								REMARKS	NEXT STATE (N_S)								OUTPUT (F_r)			
		13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0
0																																				
1																																				
2																																				
3																																				
4																																				
5																																				
6																																				
7																																				
8																																				
9																																				
10																																				
11																																				
12																																				
13																																				
14																																				
15																																				
16																																				
17																																				
18																																				
19																																				
20																																				
21																																				
22																																				
23																																				
24																																				
25																																				
26																																				
27																																				
28																																				
29																																				
30																																				
31																																				
32																																				
33																																				
34																																				
35																																				
36																																				
37																																				
38																																				
39																																				
40																																				
41																																				
42																																				
43																																				
44																																				
45																																				
46																																				
47																																				
PIN NO.		17	18	19	20	21	22	23	2	3	4	5	6	7	8																15	14	13	11	10	9
VARIABLE NAME																																				

TB01622S

NOTES:

1. The FPLS is shipped with all links initially intact. Thus, a background of "0" for all Terms, and an "H" for the P/E option, exits in the table, shown BLANK instead for clarity.
2. Unused C_n, I_m, and P_s bits are normally programmed Don't Care (—).
3. Unused Transition Terms can be left for future code modification or programmed as (—) for maximum speed.
4. Letters in variable fields are used as identifiers by logic type programmers.

TEST ARRAY

The FPLS may be subjected to AC and DC parametric tests prior to programming via an on-chip test array.

The array consists of test transition terms 48 and 49, factory programmed as shown below.

Testing is accomplished by clocking the FPLS and applying the proper input sequence to I_{0-13} as shown in the test circuit timing diagram.


0
255
$(I_n + F_n)/\bar{F}_n$
$(I_n \cdot F_n)/\bar{F}_n$
$(\bar{I} \cdot \bar{F}_n)/F_n$
$(\bar{I}_n + \bar{F}_n)/F_n$
AF01821S

State Diagram


V_{CC} +5V
V_{CC}
I_n
CLOCK
I_{0-13}
CK
PR/$\overline{OE}$
P_{0-7}
F_{0-3}
P_{0-1}
F_r
GND
TC01592S

FPLS Under Test

TERM	C	AND																					
		INPUT (Im)														PRESENT STATE (Ps)							
		13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	A	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L

OPTION (P/E)											H
OR											
NEXT STATE (Ns)								OUTPUT (Fr)			
7	6	5	4	3	2	1	0	3	2	1	0
L	L	L	L	L	L	L	L	L	L	L	L
H	H	H	H	H	H	H	H	H	H	H	H

TB01600S

Test Array Program

Both terms 48 and 49 must be deleted during user programming to avoid interfering with the desired logic function. This is accomplished automatically by any of Signetics' qualified programming equipment.


V_{CC}
4.75V
+5V
0V
t_{VS}
t_{CKH}
t_{CKL}
CK
1.5V
V_{IH}
V_{IL}
t_{IS1}
t_{IH}
t_{IS2}
I_{0-13}
t_{PPR}
t_{CKO}
F_{0-3}
3V
0V
STATE REGISTER
HIGH
LOW
WF05375S

Test Circuit Timing Diagram

TERM	C	AND																					
		INPUT (Im)														PRESENT STATE (Ps)							
		13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	—	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L

OPTION (P/E)											H
OR											
NEXT STATE (Ns)								OUTPUT (Fr)			
7	6	5	4	3	2	1	0	3	2	1	0
—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—

TB01610S

Test Array Deleted

Signetics

PLS167A
Field-Programmable Logic Sequencer (14 × 48 × 6)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 24**

DESCRIPTION

The PLS167A is a bipolar, programmable state machine of the Mealy type.The Field-Programmable Logic Sequencer (FPLS) contains logic AND-OR gate arrays with user programmable connections which control the inputs of on-chip State and Output Registers. These consist respectively of 8 Q_p, and 4 Q_f edge-triggered, clocked S/R flip-flops, with an Asynchronous Preset Option.

All flip-flops are unconditionally preset to "1" during power turn-on.

The AND array combines 14 external inputs, I_{0-13}, with 8 internal inputs, P_{0-7}, fed back from the State Register to form up to 48 transition terms (AND terms). In addition, P_0 and P_1 of the internal State Register are brought off-chip to allow extending the Output Register to 6 bits, if so desired.

All transition terms can include True, False, or Don't Care states of the controlling variables, and are merged in the OR array to issue next-state and next-output commands to their respective registers on the Low-to-High transition of the Clock pulse.

Both True and Complement transition terms can be generated by optional use of the internal variable (C) from the Complement Array. Also, if desired, the Preset input can be converted to output-enable function, as an additional user programmable option.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **14 True/Complement buffered inputs**
- **48 programmable AND gates**
- **25 programmable OR gates**
- **8-bit State Register**
- **2-bit shared State/Output Register**
- **4-bit Output Register**
- **Transition Complement Array**
- **Programmable Asynchronous Preset/Output Enable**
- **Positive edge-triggered clock**
- **Power-on preset to logic "1" of all registers**
- **Automatic logic "HOLD" state via S/R flip-flops**
- **On-chip Test Array**
- **f_{MAX}: 20MHz**
- **Power: 600mW (typ.)**
- **TTL compatible**
- **Tri-state outputs**
- **Single +5V supply**
- **300mil-wide 24-pin DIP**

FUNCTIONAL DIAGRAM



I_M
C̄
C
STATE REG.
S Q
(6)
R P
(2)
(4)
OUTPUT REG.
P
E
PR/OE
P
F
CK
T47
T0
LD01151S

PIN CONFIGURATIONS

N Package



CK 1
I6 2
I5 3
I4 4
I3 5
I2 6
I1 7
I0 8
F0 9
F1 10
F2 11
GND 12
24 VCC
23 I7
22 I8
21 I9
20 I10
19 I11
18 I12
17 I13
16 PR/OE
15 P1
14 P0
13 F3
CD04481S

N = Plastic

A Package



NC 11
F0 10
I0 9
I1 8
I2 7
I3 6
N/C 5
F1 12
F2 13
GND 14
F3 15
P0 16
P1 17
PR/OE 18
4 I4
3 I5
2 I6
1 CK
28 VCC
27 I7
26 I8
19 N/C
20 I13
21 I12
22 I11
23 I10
24 I9
25 N/C
CD04471S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- **Interface protocols**
- **Sequence detectors**
- **Peripheral controllers**
- **Timing generators**
- **Sequential circuits**
- **Security locking systems**

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

PIN DESCRIPTION

PIN NO.	SYMBOL	NAME AND FUNCTION	POLARITY
1	CK	**Clock:** The Clock input to the State and Output Registers. A low-to-high transition on this line is necessary to update the contents of both registers.	Active-High
2 – 7 17 – 23	I_{1-13}	**Logic Inputs:** The 13 external inputs to the AND array used to program jump conditions between machine states, as determined by a given logic sequence.	Active-High/Low
8	I_0	**Logic/Diagnostic Input:** A 14th external logic input to the AND array, as above, when exercised with standard TTL levels. When I_0 is held at +10V, device outputs F_{0-3} and P_{0-1} reflect the contents of state register bits P_{2-7} (see Diagnostic Output Mode diagram). The contents of flip-flops P_{0-1} and F_{0-3} remain unaltered.	Active-High/Low
9 – 11 13	F_{0-3}	**Logic/Diagnostic Outputs:** Four device outputs which normally reflect the contents of Output Register bits Q_{0-3}, when enabled. When I_0 is held at +10V, $F_{0-3} = (P_{2-5})$.	Active-High
14 – 15	P_{0-1}	**Logic/Diagnostic Outputs:** Two register bits with shared function as least significant State Register bits, or most significant Output Register bits. When I_0 is held at +10V, $P_{0-1} = (P_{6-7})$.	Active-High
16	PR/$\overline{OE}$	**Preset or $\overline{\text{Output Enable}}$ Input:** A user programmable function: • **Preset:** Provides an Asynchronous Preset to logic "1" of all State and Output Register bits. Preset overrides Clock, and when held High, clocking is inhibited and P_{0-1} and F_{0-3} are High. Normal clocking resumes with the first full clock pulse following a High-to-Low clock transition, after Preset goes Low.	 Active High (H)
		• **$\overline{\text{Output Enable}}$:** Provides an Output Enable function to all output buffers.	Active-Low (L)

LOGIC FUNCTION

Typical State Transition:



SET Q_0: $S_0 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$R_0 = 0$

RESET Q_1: $S_1 = 0$
$R_1 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $S_2 = 0$
$R_2 = 0$

TB00900S

TRUTH TABLE[1, 2, 3, 4, 5, 6]

V_{CC}	OPTION		I_O	CK	S	R	$Q_{P/F}$	F
	PR	$\overline{OE}$						
+5V	H	■	*	X	X	X	H	H
	L	■	+10V	X	X	X	Q_n	$(Q_P)_n$
	L	■	X	X	X	X	Q_n	$(Q_F)_n$
	■	H	*	X	X	X	Q_n	Hi-Z
	■	L	+10V	X	X	X	Q_n	$(Q_P)_n$
	■	L	X	X	X	X	Q_n	$(Q_F)_n$
	■	L	X	↑	L	L	Q_n	$(Q_F)_n$
	■	L	X	↑	L	H	L	L
	■	L	X	↑	H	L	H	H
	■	L	X	↑	H	H	IND.	IND.
↑	X	X	X	X	X	X	H	■

NOTES:

1. Positive Logic:
   $S/R = T_0 + T_1 + T_2 + \ldots + T_{47}$
   $T_n = C(I_0\ I_1\ I_2 \ldots)\ (P_0\ P_1 \ldots P_7)$
2. Either Preset (Active-High) or $\overline{\text{Output Enable}}$ (Active-Low) are available, but not both. The desired function is a user programmable option.
3. ↑ denotes transition from Low-to-High level.
4. R = S = High is an illegal input condition.
5. * = H/L/+10V
6. X = Don't care (⩽ 5.5V)

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. PR/$\overline{OE}$ option is set to PR. Thus, all outputs will be at "1", as preset by initial power-up procedure.
2. All transition terms are disabled (0).
3. All S/R flip-flop inputs are disabled (0).
4. The device can be clocked via a Test Array pre-programmed with a standard test pattern.

   NOTE: The Test Array pattern MUST be deleted before incorporating a user program. This is accomplished automatically by any Signetics qualified programming equipment.

FPLS LOGIC DIAGRAM


(LOGIC TERMS—T)
I0 8
I1 7
I2 6
I3 5
I4 4
I5 3
I6 2
I7 23
I8 22
I9 21
I10 20
I11 19
I12 18
I13 17
P P0 P1 P2 P3 P4 P5 P6 P7
C C̄ C
N
F
I
OPTION
16 PR/OE
P E
S Q R P
P2 P3 P4 P5 P6 P7
Q3 Q2 Q1 Q0
15 P1
14 P0
13 F3
11 F2
10 F1
9 F0
1 CK
47 40 39 32 31 24 23 16 15 8 7 0
LD02282S

NOTES:
1. All AND gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown link float to a logic "0".
3. ▨ Programmable connection.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS167AN
28-pin Plastic Leaded Chip Carrier	PLS167AA

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			°C
T_A	Operating	0	+75	
T_{STG}	Storage	−65	+150	

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
V_{OH}	High[5]	V_{CC} = Min I_{OH} = −2mA	2.4			V
V_{OL}	Low[6]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	25	μA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
I_{IL}	Low (CK input)	V_{IN} = 0.45V		−50	−250	
Output current						
$I_{O(OFF)}$	Hi-Z state[7]	V_{CC} = Max V_{OUT} = 5.5V		1	40	μA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[4,8]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[9]	V_{CC} = Max		120	180	mA
Capacitance[7]						
C_{IN}	Input	V_{CC} = 5.0V V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		10		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V. T_A = + 25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IL} applied to $\overline{OE}$ and a logic high stored, or with V_{IH} applied to PR.
6. Measured with a programmed logic condition for which the output is at a low logic level, and V_{IL} applied to PR/$\overline{OE}$ Output sink current is supplied through a resistor to V_{CC}.
7. Measured with V_{IH} applied to PR/$\overline{OE}$.
8. Duration of short circuit should not exceed 1 second.
9. I_{CC} is measured with the PR/$\overline{OE}$ input grounded, all other inputs at 4.5V and the outputs open.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[1]	Max	
Pulse width[3]							
t_{CKH}	Clock[2] high	CK –	CK +	25	15		ns
t_{CKL}	Clock low	CK +	CK –	25	15		
$t_{CKP1}B$	Period (without Complement Array)	CK +	CK +	50	40		
$t_{CKP2}B$	Period (with Complement Array)	CK +	CK +	80	50		
t_{PRH}	Preset pulse	PR –	PR +	25	15		
Setup time[3]							
$t_{IS1}A$	Input	CK +	Input ±	40			ns
$t_{IS1}B$	Input	CK +	Input ±	30			
$t_{IS2}A$	Input (through Complement Array)	CK +	Input ±	70			
$t_{IS2}B$	Input (through Complement Array)	CK +	Input	60			
t_{VS}	Power-on preset	CK –	V_{CC} +	0	–10		
t_{PRS}	Preset	CK –	PR –	0	–10		
Hold time							
t_{IH}	Input	Input ±	CK +	5	–10		ns
Propagation delay							
t_{CKO}	Clock	Output ±	CK +		15	20	ns
t_{OE}	Output enable	Output –	OE –		20	30	
t_{OD}	Output disable	Output +	OE +		20	30	
t_{PR}	Preset	Output +	PR +		18	30	
t_{PPR}	Power-on preset	Output +	V_{CC} +		0	10	
Frequency of operation[3]							
$f_{Max}B$	Without Complement Array					20.0	MHz
$f_{Max}B$	With Complement Array					12.5	

NOTES:
1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% – 90%) $\leqslant$ 30ns.
3. See "Speed vs. OR Loading" diagrams.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

TIMING DIAGRAMS


I_{0-13}
1.5V
+3V
0V
t_{IH}
t_{IS}
CLK
t_{CKH}
t_{CKL}
t_{CKP}
F_{0-3}/P_{0-1}
V_{OH}
V_{OL}
t_{CKO}
t_{OD}
$\overline{OE}$
t_{OE}
WF05353S

Sequential Mode


I_{0-13}
1.5V
+3V
0V
CLK
t_{CKP}
t_{IS}
t_{CKO}
t_{CKH}
t_{CKL}
F_{0-3}/P_{0-1}
V_{OH}
V_{OL}
t_{PR}
t_{PRS}
PR
t_{PRH}
WF05363S

Asynchronous Preset


V_{CC}
4.5V
+5V
0V
t_{PPR}
F_{0-3}/P_{0-1}
1.5V
$(F_n) = 1$
$(F_n = 1)$
V_{OH}
V_{OL}
t_{CKO}
t_{CKP}
CLK
+3V
t_{CKH}
t_{VS}
I_{0-13}
t_{IS}
t_{IH}
WF05403S

Power-On Preset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP1}	Clock period – when not using Complement array.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{CKP2}	Clock period – when using complement array.
t_{IS2}	Required delay between beginning of valid input and positive transition of clock, when using optional Complement Array (two passes necessary through the AND array).
t_{VS}	Required delay between V_{CC} (after power-on) and negative transition of clock preceding first reliable clock pulse.
t_{PRS}	Required delay between negative transition of asynchronous Preset and negative transition of clock preceding first reliable clock pulse.
t_{IH}	Required delay between positive transition of clock and end of valid Input data.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with PR/$\overline{OE}$ Low).
t_{OE}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{SRE}	Delay between input I_0 transition to Diagnostic mode and when the Outputs reflect the contents of the State Register.
t_{SRD}	Delay between input I_0 transition to Logic mode and when the Outputs reflect the contents of the Output Register.
t_{PR}	Delay between positive transition of Preset and when Outputs become valid at "1".
t_{PPR}	Delay between V_{CC} (after power-on) and when Outputs become preset at "1".
t_{PRH}	Width of preset input pulse.
f_{MAX}	Maximum clock frequency.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

TIMING DIAGRAMS (Continued)


I
1.5V
+3V
0V
I_O
1.5V
1.5V
8.0V
8.0V
+10V
+3V
0V
t_{IH}
CLK
1.5V
1.5V
+3V
0V
t_{IS}
t_{CKH}
INTERNAL STATE REG.
(P_S)
(N_S)
V_{OH}
V_{OL}
t_{SRE}
t_{SRD}
OUTPUT P, F
(F_n)
1.5V
(F_{n+1})
(N_S)
1.5V
(F_n + 1)
V_{OH}
V_{OL}
t_{CKO}
$\overline{OE}$
0V
WF05381S

Diagnostic Output Mode

TEST LOAD CIRCUIT


V_{CC}
I_O
I_{13}
CK
PR/$\overline{OE}$
P_1
P_0
F_0
F_3
TC01571S
+5V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01580S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
t_r
t_f
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

SPEED VS. "OR" LOADING

The maximum frequency at which the FPLS can be clocked while operating in *sequential mode* is given by:

$$(1/f_{MAX}) = t_{CY} = t_{IS} + t_{CKO}$$

This frequency depends on the number of transition terms T_n used. Having all 48 terms connected in the AND array does not appreciably impact performance; but the number of terms connected to each OR line affects t_{IS}, due to capacitive loading. The effect of this loading can be seen in Figure 1, showing the variation of t_{IS1} with the number of terms connected per OR.

The AC electrical characteristics contain two limits for the parameters t_{IS1} and t_{IS2}. The first, t_{IS1A} is guaranteed for a device with 24 terms connected to any OR line. t_{IS1B} is guaranteed for a device with 16 terms connected to any OR line.



OP01251S

Figure 1. t_{IS1} vs. Terms/OR Connected

The three other entries in the AC table, t_{IS2} A and B are corresponding 24 and 16 term limits when using the on-chip Complement Array.

The worst case of t_{IS} for a given application can be determined by identifying the OR line with the maximum number of T_n connections. This can be done by referring to the interconnect pattern in the FPLS logic diagram, typically illustrated in Figure 2, or by counting the maximum number of "H" *or* "L" entries in one of the columns of the device Program Table.

This number plotted on the curve in Figure 1 will yield the worst case t_{IS} and, by implication, the maximum clocking frequency for reliable operation.

Note that for maximum speed all UNUSED transition terms should be disconnected from the OR array.



AF01810S

Figure 2. Typical OR Array Interconnect Pattern

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table on the following page.

In this table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

PRESET/$\overline{OE}$ OPTION – (P/E)


PR/$\overline{OE}$
P
E = 1
LS01810S

OPTION	CODE
PRESET^{1}	H


PR/$\overline{OE}$
P = 1
E
LS01820S

OPTION	CODE
$\overline{OE}$	L

PROGRAMMING:

The PLS167A has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (state and output register) at a logic High (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all Highs (H) as the present state.

"AND" ARRAY – (I), (P)


I,P
i,p
$\overline{i,p}$
T_n
LS01850S

STATE	CODE
INACTIVE^{1,2}	O


I,P
i,p
$\overline{i,p}$
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\overline{i,p}$
T_n
LS01830S

STATE	CODE
$\overline{I}$, $\overline{P}$	L


I,P
i,p
$\overline{i,p}$
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – (N), (F)


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01890S

ACTION	CODE
INACTIVE^{1,3}	O


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01900S

ACTION	CODE
SET	H


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01870S

ACTION	CODE
RESET	L


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01880S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)


$\overline{c}$
c
T_n
LS01930S

ACTION	CODE
INACTIVE^{1,4}	O


$\overline{c}$
c
T_n
LS01940S

ACTION	CODE
GENERATE	A


$\overline{c}$
c
T_n
LS01910S

ACTION	CODE
PROPAGATE	●


$\overline{c}$
c
T_n
LS01920S

ACTION	CODE
TRANSPARENT	–

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate T_n will be unconditionally inhibited if both the true and the complement of any input (I, P) are left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

FPLS PROGRAM TABLE

CUSTOMER NAME ____________________
PURCHASE ORDER # ____________________
SIGNETICS DEVICE # CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________________
TOTAL NUMBER OF PARTS ____________________
PROGRAM TABLE # ____________________
REV ____________________
DATE ____________________

PROGRAM TABLE ENTRIES

AND

INACTIVE	0	Cn
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	

INACTIVE	0	Im, Ps
I, P	H	
$\overline{I}$, $\overline{P}$	L	
DON'T CARE	—	

OR

INACTIVE	0	Ns, Fr
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

PRESET	H	P/E
$\overline{OE}$	L	

		AND																							OPTION (P/E) OR											
TERM	Cn	INPUT (I_M)														PRESENT STATE (P_S)								REMARKS	NEXT STATE (N_S)								OUTPUT (Fr)			
		13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0
0																																				
1																																				
2																																				
3																																				
4																																				
5																																				
6																																				
7																																				
8																																				
9																																				
10																																				
11																																				
12																																				
13																																				
14																																				
15																																				
16																																				
17																																				
18																																				
19																																				
20																																				
21																																				
22																																				
23																																				
24																																				
25																																				
26																																				
27																																				
28																																				
29																																				
30																																				
31																																				
32																																				
33																																				
34																																				
35																																				
36																																				
37																																				
38																																				
39																																				
40																																				
41																																				
42																																				
43																																				
44																																				
45																																				
46																																				
47																																				
PIN NO.		17	18	19	20	21	22	23	2	3	4	5	6	7	8																15	14	13	11	10	9
VARIABLE NAME																																				

TB01622S

NOTES:

1. The FPLS is shipped with all links initially intact. Thus, a background of "0" for all Terms, and an "H" for P/E option, exists in the table, shown BLANK instead for clarity.
2. Unused C_n, I_m, and P_s bits are normally programmed Don't Care (–).
3. Unused Transition Terms can be left blank for future code modification or programmed as (–) for maximum speed.
4. Letters in variable fields are used as identifiers by logic programmers.

Field-Programmable Logic Sequencer (14 × 48 × 6) PLS167A

TEST ARRAY

The FPLS may be subjected to AC and DC parametric tests prior to programming via an on-chip test array.

The array consists of test transition terms 48 and 49, factory programmed as shown below.

Testing is accomplished by clocking the FPLS and applying the proper input sequence to I_{0-13} as shown in the test circuit timing diagram.


0
255
$(I_n + F_n)/\bar{F}_n$
$(I_n \cdot F_n)/F_n$
$(\bar{I} \cdot \bar{F}_n)/\bar{F}_n$
$(\bar{I}_n + \bar{F}_n)/F_n$
AF01821S

State Diagram


V_{CC} +5V
V_{CC}
I_n
CLOCK
I_{0-13}
CK
PR/$\overline{OE}$
P_{0-7}
F_{0-3}
P_{0-1}
F_r
GND
TC01592S

FPLS Under Test

T E R M	C	AND																					
		INPUT (Im)														PRESENT STATE (Ps)							
		13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	A	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L

OPTION (P/E)											H
OR											
NEXT STATE (Ns)								OUTPUT (Fr)			
7	6	5	4	3	2	1	0	3	2	1	0
L	L	L	L	L	L	L	L	L	L	L	L
H	H	H	H	H	H	H	H	H	H	H	H

TB01600S

Test Array Program

Both terms 48 and 49 must be deleted during user programming to avoid interfering with the desired logic function. This is accomplished automatically by any of Signetics' qualified programming equipment.


V_{CC}
4.75V
+5V
0V
CK
t_{VS}
t_{CKH}
t_{CKL}
1.5V
V_{IH}
V_{IL}
I_{0-13}
t_{IS1}
t_{IH}
t_{IS2}
t_{PPR}
t_{CKO}
F_{0-3}
3V
STATE REGISTER
HIGH
LOW
WF05375S

Test Circuit Timing Diagram

T E R M	C	AND																					
		INPUT (Im)														PRESENT STATE (Ps)							
		13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	—	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L

OPTION (P/E)											H
OR											
NEXT STATE (Ns)								OUTPUT (Fr)			
7	6	5	4	3	2	1	0	3	2	1	0
—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—

TB01610S

Test Array Deleted

Signetics

PLS168
Field-Programmable Logic Sequencer (12 × 48 × 8)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 24**

DESCRIPTION

The PLS168 is a bipolar, programmable state machine of the Mealy type. It contains logic AND-OR gate arrays with user programmable connections which control the inputs of on-chip State and Output Registers. These consist respectively of 10 Q_p, and 4 Q_f edge-triggered, clocked S/R flip-flops, with an Asynchronous Preset option.

All flip-flops are unconditionally preset to "1" during power turn-on.

The AND array combines 12 external inputs, I_{0-11}, with 10 internal inputs, P_{0-9}, fed back from the State Register to form up to 48 transition terms (AND terms). In addition, P_0-P_3 of the internal State Register are brought off-chip to allow extending the Output Register to 8 bits, if so desired.

All transition terms can include True, False, or Don't Care states of the controlling variables, and are merged in the OR array to issue next-state and next-output commands to their respective registers on the Low-to-High transition of the Clock pulse.

Both True and Complement transition terms can be generated by optional use of the internal variable (C) from the Complement Array. Also, if desired, the Preset input can be converted to output-enable function, as an additional user programmable option.

Order codes for this device are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **12 True/Complement buffered inputs**
- **48 programmable AND gates**
- **29 programmable OR gates**
- **10-bit State Register**
- **4-bit shared State/Output Register**
- **4-bit Output Register**
- **Transition Complement Array**
- **Programmable Asynchronous Preset/Output Enable**
- **Positive edge-triggered clock**
- **Power-on preset to logic "1" of all registers**
- **Automatic logic "HOLD" state via S/R flip-flops**
- **On-chip Test Array**
- **f_{MAX}: 13.9MHz**
- **Power: 600mW (typ.)**
- **TTL compatible**
- **Tri-state outputs**
- **Single +5V supply**
- **300mil-wide 24-pin DIP**

FUNCTIONAL DIAGRAM


I_M
$\overline{C}$
C
STATE REG.
S Q
(6)
R P
S Q
(4)
R P
S Q
(4)
R P
OUTPUT REG.
PR/$\overline{OE}$
P
E
P
F
CK
T_{47}
T_0
LD01150S

PIN CONFIGURATIONS

N Package


CK 1
I_5 2
I_4 3
I_3 4
I_2 5
I_1 6
I_0 7
F_0 8
F_1 9
F_2 10
F_3 11
GND 12
24 V_{CC}
23 I_6
22 I_7
21 I_8
20 I_9
19 I_{10}
18 I_{11}
17 PR/$\overline{OE}$
16 P_3
15 P_2
14 P_1
13 P_0
CD03281S

N = Plastic

A Package


N/C 11
F_1 10
F_0 9
I_0 8
I_1 7
I_2 6
N/C 5
F_2 12
F_3 13
GND 14
P_0 15
P_1 16
P_2 17
P_3 18
4 I_3
3 I_4
2 I_5
1 CK
28 V_{CC}
27 I_6
26 I_7
19 N/C
20 PR/$\overline{OE}$
21 I_{11}
22 I_{10}
23 I_9
24 I_8
25 N/C
CD04461S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- **Interface protocols**
- **Sequence detectors**
- **Peripheral controllers**
- **Timing generators**
- **Sequential circuits**
- **Elevator controllers**
- **Security locking systems**
- **Counters**
- **Shift registers**

PIN DESCRIPTION

PIN NO.	SYMBOL	NAME AND FUNCTION	POLARITY
1	CK	**Clock:** The Clock input to the State and Output Registers. A Low-to-High transition on this line is necessary to update the contents of both registers.	Active-High
2 – 6 18 – 23	I_{1-11}	**Logic Inputs:** The 11 external inputs to the AND array used to program jump conditions between machine states, as determined by a given logic sequence.	Active-High/Low
7	I_0	**Logic/Diagnostic Input:** A 12th external logic input to the AND array, as above, when exercised with standard TTL levels. When I_0 is held at +10V, device outputs F_{2-3} and P_{0-3} reflect the contents of State Register bits P_{4-9} (see Diagnostic Output Mode diagram). The contents of flip-flops P_{0-1} and F_{0-3} remain unaltered.	Active-High/Low
13 – 16	P_{0-3}	**Logic/Diagnostic Outputs:** Four device outputs which normally reflect the contents of State Register bits P_{0-3}. When I_0 is held at +10V these pins reflect ($P_6 - P_9$).	Active-High
10 – 11	$F_2 - F_3$	**Logic/Diagnostic Outputs:** Two register bits ($F_2 - F_3$) which normally reflect Output Register bits ($Q_2 - Q_3$). When I_0 is held at +10V these pins reflect ($P_4 - P_5$).	Active-High
17	PR/$\overline{OE}$	**Preset or $\overline{\text{Output Enable}}$ Input:** A user programmable function: • **Preset:** Provides an Asynchronous Preset to logic "1" of all State and Output Register bits. Preset overrides Clock, and when held high, clocking is inhibited and P_{0-9} and F_{0-3} are high. Normal clocking resumes with the first full clock pulse following a High-to-Low clock transition, after Preset goes low.	 Active-High (H)
		• **$\overline{\text{Output Enable}}$:** Provides an Output Enable function to all output buffers.	Active-Low (L)
8, 9	$F_0 - F_1$	**Logic Output:** Two device outputs which reflect Output Registers $Q_0 - Q_1$. When I_0 is held at +10V $F_0 - F_1$ = Logic "1".	

LOGIC FUNCTION

Typical State Transition:



SET Q_0: $S_0 = (\overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$R_0 = 0$

RESET Q_1: $S_1 = 0$
$R_1 = (\overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $S_2 = 0$
$R_2 = 0$

TB00900S

TRUTH TABLE[1, 2, 3, 4, 5, 6]

V_{CC}	OPTION		I_0	CK	S	R	$Q_{P/F}$	F
	PR	$\overline{OE}$						
+5V	H		*	X	X	X	H	H
	L		+10V	X	X	X	Q_n	$(Q_P)_n$
	L		X	X	X	X	Q_n	$(Q_F)_n$
		H	*	X	X	X	Q_n	Hi-Z
		L	+10V	X	X	X	Q_n	$(Q_P)_n$
		L	X	X	X	X	Q_n	$(Q_F)_n$
		L	X	↑	L	L	Q_n	$(Q_F)_n$
		L	X	↑	L	H	L	L
		L	X	↑	H	L	H	H
		L	X	↑	H	H	IND.	IND.
↑	X	X	X	X	X	X	H	

NOTES:

1. Positive Logic:
   $S/R = T_0 + T_1 + T_2 + \ldots + T_{47}$
   $T_n = C(I_0\ I_1\ I_2 \ldots)\ (P_0\ P_1 \ldots P_9)$
2. Either Preset (Active-High) or $\overline{\text{Output Enable}}$ (Active-Low) are available, but not both. The desired function is a user programmable option.
3. ↑ denotes transition from Low to High level.
4. R = S = High is an illegal input condition.
5. * = H/L/+10V
6. X = Don't care ($\leqslant$ 5.5V)

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. PR/$\overline{OE}$ option is set to PR. Thus, all outputs will be at "1", as preset by initial power-up procedure.
2. All transition terms are disabled (0).
3. All S/R flip-flop inputs are disabled (0).
4. The device can be clocked via a Test Array pre-programmed with a standard test pattern.

   NOTE: The Test Array pattern MUST be deleted before incorporating a user program. This is accomplished automatically by any Signetics qualified programming equipment.

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

FPLS LOGIC DIAGRAM


(LOGIC TERMS—T)
I_0 7
I_1 6
I_2 5
I_3 4
I_4 3
I_5 2
I_6 23
I_7 22
I_8 21
I_9 20
I_{10} 19
I_{11} 18
P
P_0 P_1 P_2 P_3 P_9 P_8 P_7 P_6 P_5 P_4
C
$\overline{C}$
N
F
I
OPTION
17 PR/$\overline{OE}$
P
E
S Q
R P
P_9 P_8 P_7 P_6 P_5 P_4
Q_3 Q_2 Q_1 Q_0
16 P_3
15 P_2
14 P_1
13 P_0
11 F_3
10 F_2
9 F_1
8 F_0
1 CK
47 0
TB00882S

NOTES:
1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. ▨ Programmable connection.

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS168N
28-pin Plastic Leaded Chip Carrier	PLS168A

THERMAL RATING

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{IN}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High[5]	I_{OH} = −2mA	2.4			V
V_{OL}	Low[6]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	25	µA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
I_{IL}	Low (CK input)	V_{IN} = 0.45V		−50	−250	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[7]	V_{OUT} = 5.5V		1	40	µA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[4,8]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[9]	V_{CC} = Max		120	180	mA
Capacitance[7]						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		10		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = +25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IL} applied to $\overline{OE}$ and a logic high stored, or with V_{IH} applied to PR.
6. Measured with a programmed logic condition for which the output is at a low logic level, and V_{IL} applied to PR/$\overline{OE}$ Output sink current is supplied through a resistor to V_{CC}.
7. Measured with V_{IH} applied to PR/$\overline{OE}$.
8. Duration of short circuit should not exceed 1 second.
9. I_{CC} is measured with the PR/$\overline{OE}$ input grounded, all other inputs at 4.5V and the outputs open.

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[1]	Max	
Pulse width[3]							
t_{CKH}	Clock[2] high	CK –	CK +	25	15		ns
t_{CKL}	Clock low	CK +	CK –	25	15		
$t_{CKP1}B$	Period (without Complement Array)	CK +	CK +	80	40		
$t_{CKP2}B$	Period (with Complement Array)	CK +	CK +	120	60		
t_{PRH}	Preset pulse	PR –	PR +	25	15		
Setup time[3]							
$t_{IS1}A$	Input	CK +	Input ±	60			ns
$t_{IS1}B$	Input	CK +	Input ±	50			
$t_{IS1}C$	Input	CK +	Input ±	42			
$t_{IS2}A$	Input (through Complement Array)	CK +	Input ±	90			
$t_{IS2}B$	Input (through Complement Array)	CK +	Input	80			
$t_{IS2}C$	Input (through Complement Array)	CK +	Input	72			
t_{VS}	Power-on preset	CK –	V_{CC} +	0	–10		
t_{PRS}	Preset	CK –	PR –	0	–10		
Hold time							
t_{IH}	Input	Input ±	CK +	5	–10		ns
Propagation delay							
t_{CKO}	Clock	Output ±	CK +		15	30	ns
t_{OE}	Output enable	Output –	OE –		20	30	
t_{OD}	Output disable	Output +	OE +		20	30	
t_{PR}	Preset	Output +	PR +		18	30	
t_{PPR}	Power-on preset	Output +	V_{CC} +		0	10	
Frequency of operation[3]							
$f_{MAX}C$	Without Complement Array					13.9	MHz
$f_{MAX}C$	With Complement Array					9.8	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% – 90%) ⩽ 30ns.
3. See "Speed vs. OR Loading" diagrams.

TIMING DIAGRAMS


I0-11
1.5V
1.5V
+3V
0V
tIH
tIS
1.5V
1.5V
1.5V
+3V
CLK
0V
tIS
tCKH
tCKL
tCKP
F0-3/P0-3
VOH
1.5V
1.5V
tCKO
VOL
tOD
OE
+3V
1.5V
1.5V
0V
tOE
WF05354S

Sequential Mode


I0-11
1.5V
+3V
0V
tCKP
+3V
1.5V
1.5V
1.5V
1.5V
CLK
0V
tIS
tCKO
tCKH
tCKL
VOH
1.5V
1.5V
1.5V
F0-3/P0-3
VOL
tPR
tPRS
tCKO
+3V
1.5V
1.5V
1.5V
PR
0V
tPRH
WF05364S

Asynchronous Preset


+5V
4.5V
VCC
0V
tPPR
VOH
1.5V
(Fn) = 1
1.5V
(Fn = 1)
F0-3/P0-3
VOL
tCKO
tCKP
+3V
1.5V
1.5V
1.5V
CLK
0V
tCKH
tVS
+3V
1.5V
1.5V
I0-11
0V
tIS
tIH
WF05404S

Power-On Preset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP1}	Clock period – when not using Complement array.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{CKP2}	Clock period – when using complement array.
t_{IS2}	Required delay between beginning of valid input and positive transition of clock, when using optional Complement Array (two passes necessary through the AND array).
t_{VS}	Required delay between V_{CC} (after power-on) and negative transition of clock preceding first reliable clock pulse.
t_{PRS}	Required delay between negative transition of asynchronous Preset and negative transition of clock preceding first reliable clock pulse.
t_{IH}	Required delay between positive transition of clock and end of valid input data.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with PR/$\overline{OE}$ Low).
t_{OE}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{SRE}	Delay between input I_0 transition to Diagnostic mode and when the Outputs reflect the contents of the State Register.
t_{SRD}	Delay between input I_0 transition to Logic mode and when the Outputs reflect the contents of the Output Register.
t_{PR}	Delay between positive transition of Preset and when Outputs become valid "1".
t_{PPR}	Delay between V_{CC} (after power-on) and when Outputs become preset at "1".
t_{PRH}	Width of preset input pulse.
f_{MAX}	Maximum clock frequency.

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

TIMING DIAGRAMS (Continued)


I
1.5V
+3V
0V
+10V
8.0V
8.0V
I_O
1.5V
1.5V
+3V
0V
t_{IH}
+3V
1.5V
1.5V
CLK
0V
t_{IS}
t_{CKH}
INTERNAL STATE REG.
(P_S)
(N_S)
V_{OH}
V_{OL}
t_{SRE}
t_{SRD}
OUTPUT P, F
(F_n)
1.5V
(F_{n+1})
(N_S)
1.5V
$(F_n + 1)$
V_{OH}
V_{OL}
t_{CKO}
$\overline{OE}$
0V
WF05381S

Diagnostic Mode

TEST LOAD CIRCUIT


V_{CC}
I_O
P_3
P_0
F_0
F_3
I_{11}
CK
PR/$\overline{OE}$
TC01570S
+5V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01580S

VOLTAGE WAVEFORM


+3.0V
90%
10%
0V
5ns
t_r
t_f
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and output, unless otherwise specified.

Input Pulses

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

SPEED VS. "OR" LOADING

The maximum frequency at which the FPLS can be clocked while operating in *sequential mode* is given by:

$$(1/f_{MAX}) = t_{CY} = t_{IS} + t_{CKO}$$

This frequency depends on the number of transition terms T_n used. Having all 48 terms connected in the AND array does not appreciably impact performance; but the number of terms connected to each OR line affects t_{IS}, due to capacitive loading. The effect of this loading can be seen in Figure 1, showing the variation of t_{IS1} with the number of terms connected per OR.

The AC electrical characteristics contain three limits for the parameters t_{IS1} and t_{IS2}. The first, t_{IS1A} is guaranteed for a device with 48 terms connected to any OR line. t_{IS1B} is guaranteed for a device with 32 terms connected to any OR line. And t_{IS1C} is guaranteed for a device with 24 terms connected to any OR line.



Figure 1. t_{IS1} vs. Terms/OR Connected

The three other entries in the AC table, t_{IS2} A, B and C are corresponding 48, 32 and 24 term limits when using the on-chip Complement Array.

The worst case of t_{IS} for a given application can be determined by identifying the OR line with the maximum number of T_n connections. This can be done by referring to the interconnect pattern in the FPLS logic diagram, typically illustrated in Figure 2, or by counting the maximum number of "H" or "L" entries in one of the columns of the device Program Table.

This number plotted on the curve in Figure 1 will yield the worst case t_{IS} and, by implication, the maximum clocking frequency for reliable operation.

Note that for maximum speed all UNUSED transition terms should be disconnected from the OR array.



Figure 2. Typical OR Array Interconnect Pattern

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table on the following page.

In this table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

PRESET/$\overline{OE}$ OPTION – (P/E)


PR/$\overline{OE}$
P
E = 1
LS01810S

OPTION	CODE
PRESET[1]	H


PR/$\overline{OE}$
P = 1
E
LS01820S

OPTION	CODE
$\overline{OE}$	L

PROGRAMMING:

The PLS168 has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (state and output register) at a logic High (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all Highs (H) as the present state.

"AND" ARRAY – (I), (P)


I,P
i,p
$\overline{i,p}$
T_n
LS01850S

STATE	CODE
INACTIVE[1,2]	O


I,P
i,p
$\overline{i,p}$
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\overline{i,p}$
T_n
LS01830S

STATE	CODE
$\overline{I}$, $\overline{P}$	L


I,P
i,p
$\overline{i,p}$
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – (N), (F)


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01890S

ACTION	CODE
INACTIVE[1,3]	O


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01900S

ACTION	CODE
SET	H


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01870S

ACTION	CODE
RESET	L


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01880S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)


$\overline{c}$
c
T_n
LS01930S

ACTION	CODE
INACTIVE[1,4]	O


$\overline{c}$
c
T_n
LS01940S

ACTION	CODE
GENERATE	A


$\overline{c}$
c
T_n
LS01910S

ACTION	CODE
PROPAGATE	●


$\overline{c}$
c
T_n
LS01920S

ACTION	CODE
TRANSPARENT	–

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate T_n will be unconditionally inhibited if both the true and complement of any input (I or P) are left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

FPLS PROGRAM TABLE PLS168

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # CF (XXXX) ____________
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ____________
REV ____________
DATE ____________

AND

INACTIVE	O	C_n
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	
INACTIVE	O	I_m P_s
I, P	H	
$\bar{I}, \bar{P}$	L	
DON'T CARE	—	

OR

INACTIVE	O	N_s, F_r
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

PRESET	H	P/E
$\overline{OE}$	L	

AND																									OPTION (P/E) OR													
TERM	C_n	INPUT(Im)												PRESENT STATE (Ps) (Px)										REMARKS	NEXT STATE (Ns) (Px)										OUTPUT (Fr)			
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	3	2	1	0
0																																						
1																																						
2																																						
3																																						
4																																						
5																																						
6																																						
7																																						
8																																						
9																																						
10																																						
11																																						
12																																						
13																																						
14																																						
15																																						
16																																						
17																																						
18																																						
19																																						
20																																						
21																																						
22																																						
23																																						
24																																						
25																																						
26																																						
27																																						
28																																						
29																																						
30																																						
31																																						
32																																						
33																																						
34																																						
35																																						
36																																						
37																																						
38																																						
39																																						
40																																						
41																																						
42																																						
43																																						
44																																						
45																																						
46																																						
47																																						
PIN NO.		18	19	20	21	22	23	2	3	4	5	6	7																		16	15	14	13	11	10	9	8
VARIABLE NAME																																						

TB02030S

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168

TEST ARRAY

The FPLS may be subjected to AC and DC parametric tests prior to programming via an on-chip test array.

The array consists of test transition terms 48 and 49, factory programmed as shown below.

Testing is accomplished by clocking the FPLS and applying the proper input sequence to I_{0-11} as shown in the test circuit timing diagram.


0
1023
$(I_n + F_n)/\bar{F}_n$
$(I_n \cdot F_n)/F_n$
$(\bar{I} \cdot \bar{F}_n)/F_n$
$(\bar{I}_n + \bar{F}_n)/F_n$
AF01820S

State Diagram


V_{CC} +5V
V_{CC}
I_n
CLOCK
I_{0-11}
CK
PR/$\overline{OE}$
P_{0-9}
P_{0-3}
F_{0-3}
F_r
GND
TC01593S

FPLS Under Test

TERM	AND																								OPTION (P E)													H
																									OR													
	Cn	INPUT(Im)												PRESENT STATE (Ps) (Px)										REMARKS	NEXT STATE (Ns) (Px)										OUTPUT (Fr)			
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	3	2	1	0
48	A	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H		L	L	L	L	L	L	L	L	L	L	L	L	L	L
49	•	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L		H	H	H	H	H	H	H	H	H	H	H	H	H	H

Test Array Program

Both terms 48 and 49 must be deleted during user programming to avoid interfering with the desired logic function. This is accomplished automatically by any of Signetics' qualified programming equipment.


V_{CC}
4.75V
+5V
0V
t_{VS}
t_{CKH}
t_{CKL}
CK
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
t_{IS1}
t_{IH}
t_{IS2}
t_{IH}
I_{0-11}
1.5V
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
t_{PPR}
t_{CKO}
t_{CKO}
F_{0-3}
1.5V
1.5V
1.5V
3V
0V
STATE REGISTER
HIGH
LOW

Test Circuit Timing Diagram

TERM	AND																								OPTION (P E)													H
																									OR													
	Cn	INPUT(Im)												PRESENT STATE (Ps) (Px)										REMARKS	NEXT STATE (Ns) (Px)										OUTPUT (Fr)			
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	3	2	1	0
48	–	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H		–	–	–	–	–	–	–	–	–	–	–	–	–	–
49	•	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L		–	–	–	–	–	–	–	–	–	–	–	–	–	–

Test Array Deleted

Signetics

PLS168A
Field-Programmable Logic Sequencer (12 × 48 × 8)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 24**

DESCRIPTION

The PLS168A is a bipolar, programmable state machine of the Mealy type. It contains logic AND-OR gate arrays with user programmable connections which control the inputs of on-chip State and Output Registers. These consist respectively of 10 Q_p, and 4 Q_f edge-triggered, clocked S/R flip-flops, with an Asynchronous Preset option.

All flip-flops are unconditionally preset to "1" during power turn-on.

The AND array combines 12 external inputs, I_{0-11}, with 10 internal inputs, P_{0-9}, fed back from the State Register to form up to 48 transition terms (AND terms). In addition, P_0-P_3 of the internal State Register are brought off-chip to allow extending the Output Register to 8 bits, if so desired.

All transition terms can include True, False, or Don't Care states of the controlling variables, and are merged in the OR array to issue next-state and next-output commands to their respective registers on the Low-to-High transition of the Clock pulse.

Both True and Complement transition terms can be generated by optional use of the internal variable (C) from the Complement Array. Also, if desired, the Preset input can be converted to output-enable function, as an additional user programmable option.

Order codes for this device are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **12 True/Complement buffered inputs**
- **48 programmable AND gates**
- **29 programmable OR gates**
- **10-bit State Register**
- **4-bit shared State/Output Register**
- **4-bit Output Register**
- **Transition Complement Array**
- **Programmable Asynchronous Preset/Output Enable**
- **Positive edge-triggered clock**
- **Power-on preset to logic "1" of all registers**
- **Automatic logic "HOLD" state via S/R flip-flops**
- **On-chip Test Array**
- **f_{MAX}: 20MHz**
- **Power: 600mW (typ.)**
- **TTL compatible**
- **Tri-state outputs**
- **Single +5V supply**
- **300mil-wide 24-pin DIP**

PIN CONFIGURATIONS

N Package


CK 1
I5 2
I4 3
I3 4
I2 5
I1 6
I0 7
F0 8
F1 9
F2 10
F3 11
GND 12
24 VCC
23 I6
22 I7
21 I8
20 I9
19 I10
18 I11
17 PR/OE
16 P3
15 P2
14 P1
13 P0
CD03281S

N = Plastic

A Package


N/C 11
F1 10
F0 9
I0 8
I1 7
I2 6
N/C 5
F2 12
F3 13
GND 14
P0 15
P1 16
P2 17
P3 18
4 I3
3 I4
2 I5
1 CK
28 VCC
27 I6
26 I7
19 N/C
20 PR/OE
21 I11
22 I10
23 I9
24 I8
25 N/C
CD04461S

A = Plastic Leaded Chip Carrier

FUNCTIONAL DIAGRAM


IM
C̄
C
STATE REG.
S Q
(6)
R P
S Q
(4)
R P
S Q
(4)
R P
OUTPUT REG.
PR/OE
P
E
P
F
CK
T47
T0
LD01150S

APPLICATIONS

- **Interface protocols**
- **Sequence detectors**
- **Peripheral controllers**
- **Timing generators**
- **Sequential circuits**
- **Elevator controllers**
- **Security locking systems**
- **Counters**
- **Shift registers**

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168A

PIN DESCRIPTION

PIN NO.	SYMBOL	NAME AND FUNCTION	POLARITY
1	CK	**Clock:** The Clock input to the State and Output Registers. A Low-to-High transition on this line is necessary to update the contents of both registers.	Active-High
2 – 6 18 – 23	I_{1-11}	**Logic Inputs:** The 11 external inputs to the AND array used to program jump conditions between machine states, as determined by a given logic sequence.	Active-High/Low
7	I_0	**Logic/Diagnostic Input:** A 12th external logic input to the AND array, as above, when exercised with standard TTL levels. When I_0 is held at +10V, device outputs $F_2 - F_3$ and $P_0 - P_3$ reflect the contents of State Register bits P_{4-9} (see Diagnostic Output Mode diagram). The contents of flip-flops P_{0-1} and F_{0-3} remain unaltered.	Active-High/Low
13 – 16	P_{0-3}	**Logic/Diagnostic Outputs:** Four device outputs which normally reflect the contents of State Register bits P_{0-3}. When I_0 is held at +10V these pins reflect ($P_6 - P_9$).	Active-High
10 – 11	$F_2 - F_3$	**Logic/Diagnostic Outputs:** Two register bits ($F_2 - F_3$) which reflect Output Register bits ($Q_2 - Q_3$). When I_0 is held at +10V these pins reflect ($P_4 - P_5$).	Active-High
17	PR/$\overline{\text{OE}}$	**Preset or $\overline{\textbf{Output Enable}}$ Input:** A user programmable function: • **Preset:** Provides an Asynchronous Preset to logic "1" of all State and Output Register bits. Preset overrides Clock, and when held high, clocking is inhibited and P_{0-9} and F_{0-3} are high. Normal clocking resumes with the first full clock pulse following a High-to-Low clock transition, after Preset goes low.	Active-High (H)
		• $\overline{\textbf{Output Enable}}$: Provides an Output Enable function to all output buffers.	Active-Low (L)
8, 9	$F_0 - F_1$	**Logic Output:** Two device outputs which reflect Output Registers $Q_0 - Q_1$. When I_0 is held at +10V $F_0 - F_1$ = Logic "1"	

LOGIC FUNCTION

Typical State Transition:



SET Q_0: $S_0 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$R_0 = 0$

RESET Q_1: $S_1 = 0$
$R_1 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $S_2 = 0$
$R_2 = 0$

TB00900S

TRUTH TABLE[1, 2, 3, 4, 5, 6]

V_{CC}	OPTION		I_0	CK	S	R	$Q_{P/F}$	F
	PR	$\overline{\text{OE}}$						
+5V	H		*	X	X	X	H	H
	L		+10V	X	X	X	Q_n	$(Q_P)_n$
	L		X	X	X	X	Q_n	$(Q_F)_n$
		H	*	X	X	X	Q_n	Hi-Z
		L	+10V	X	X	X	Q_n	$(Q_P)_n$
		L	X	X	X	X	Q_n	$(Q_F)_n$
		L	X	↑	L	L	Q_n	$(Q_F)_n$
		L	X	↑	L	H	L	L
		L	X	↑	H	L	H	H
		L	X	↑	H	H	IND.	IND.
↑	X	X	X	X	X	X	H	

NOTES:

1. Positive Logic:
   $S/R = T_0 + T_1 + T_2 + \ldots + T_{47}$
   $T_n = C(I_0\ I_1\ I_2 \ldots)\ (P_0\ P_1 \ldots P_9)$
2. Either Preset (Active-High) or $\overline{\text{Output Enable}}$ (Active-Low) are available, but not both. The desired function is a user programmable option.
3. ↑ denotes transition from Low to High level.
4. R = S = High is an illegal input condition.
5. * = H/L/+10V
6. X = Don't Care (⩽5.5V)

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. PR/$\overline{\text{OE}}$ option is set to PR. Thus, all outputs will be at "1", as preset by initial power-up procedure.
2. All transition terms are disabled (0).
3. All S/R flip-flop inputs are disabled (0).
4. The device can be clocked via a Test Array pre-programmed with a standard test pattern.

   NOTE: The Test Array pattern MUST be deleted before incorporating a user program.

Field-Programmable Logic Sequencer (12 × 48 × 8)

PLS168A

FPLS LOGIC DIAGRAM


(LOGIC TERMS—T)
I0 7
I1 6
I2 5
I3 4
I4 3
I5 2
I6 23
I7 22
I8 21
I9 20
I10 19
I11 18
I
P
P0
P1
P2
P3
P9
P8
P7
P6
P5
P4
C̄
C
N
F
OPTION
17 PR/OE
P
E
S Q
R P
P9
P8
P7
P6
P5
P4
16 P3
15 P2
14 P1
13 P0
Q3 11 F3
Q2 10 F2
Q1 9 F1
Q0 8 F0
1 CK
47
0
TB00882S

NOTES:
1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. ▨ Programmable connection.

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS168AN
28-pin Plastic Leaded Chip Carrier	PLS168AA

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{IN}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

THERMAL RATING

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High[5]	I_{OH} = −2mA	2.4			V
V_{OL}	Low[6]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	25	μA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
I_{IL}	Low (CK input)	V_{IN} = 0.45V		−50	−250	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[7]	V_{OUT} = 5.5V		1	40	μA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[4,8]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[9]	V_{CC} = Max		120	180	mA
Capacitance[7]						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		10		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = + 25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IL} applied to $\overline{OE}$ and a logic high stored, or with V_{IH} applied to PR.
6. Measured with a programmed logic condition for which the output is at a low logic level, and V_{IL} applied to PR/$\overline{OE}$ Output sink current is supplied through a resistor to V_{CC}.
7. Measured with V_{IH} applied to PR/$\overline{OE}$.
8. Duration of short circuit should not exceed 1 second.
9. I_{CC} is measured with the PR/$\overline{OE}$ input grounded, all other inputs at 4.5V and the outputs open.

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[1]	Max	
Pulse width[3]							
t_{CKH}	Clock[2] high	CK –	CK +	25	15		ns
t_{CKL}	Clock low	CK +	CK –	25	15		
$t_{CKP1}B$	Period (without Complement Array)	CK +	CK +	50	40		
$t_{CKP2}B$	Period (with Complement Array)	CK +	CK +	80	50		
t_{PRH}	Preset pulse	PR –	PR +	25	15		
Setup time[3]							
$t_{IS1}A$	Input	CK +	Input ±	40			ns
$t_{IS1}B$	Input	CK +	Input ±	30			
$t_{IS2}A$	Input (through Complement Array)	CK +	Input ±	70			
$t_{IS2}B$	Input (through Complement Array)	CK +	Input	60			
t_{VS}	Power-on preset	CK –	V_{CC} +	0	–10		
t_{PRS}	Preset	CK –	PR –	0	–10		
Hold time							
t_{IH}	Input	Input ±	CK +	5	–10		ns
Propagation delay							
t_{CKO}	Clock	Output ±	CK +		15	20	ns
t_{OE}	Output enable	Output –	OE –		20	30	
t_{OD}	Output disable	Output +	OE +		20	30	
t_{PR}	Preset	Output +	PR +		18	30	
t_{PPR}	Power-on preset	Output +	V_{CC} +		0	10	
Frequency of operation[3]							
$f_{MAX}B$	Without Complement Array					20	MHz
$f_{MAX}B$	With Complement Array					12.5	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% – 90%) ⩽ 30ns.
3. See ''Speed vs. OR Loading'' diagrams.

TIMING DIAGRAMS


I0-11
1.5V
+3V
0V
tIH
tIS
CLK
tCKH
tCKL
tCKP
F0-3/P0-3
VOH
VOL
tCKO
tOD
OE
tOE
WF05354S

Sequential Mode


I0-11
1.5V
+3V
0V
CLK
tIS
tCKO
tCKP
tCKH
tCKL
F0-3/P0-3
VOH
VOL
tPR
tPRS
PR
tPRH
WF05364S

Asynchronous Preset


VCC
4.5V
+5V
0V
tPPR
F0-3/P0-3
1.5V
(Fn) = 1
(Fn = 1)
VOH
VOL
tCKO
tCKP
CLK
tCKH
tVS
+3V
I0-11
tIS
tIH
WF05404S

Power-On Preset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP1}	Clock period – when not using Complement array.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{CKP2}	Clock period – when using complement array.
t_{IS2}	Required delay between beginning of valid input and positive transition of clock, when using optional Complement Array (two passes necessary through the AND array).
t_{VS}	Required delay between V_{CC} (after power-on) and negative transition of clock preceding first reliable clock pulse.
t_{PRS}	Required delay between negative transition of asynchronous Preset and negative transition of clock preceding first reliable clock pulse.
t_{IH}	Required delay between positive transition of clock and end of valid input data.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with PR/$\overline{OE}$ Low).
t_{OE}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{SRE}	Delay between input I_0 transition to Diagnostic mode and when the Outputs reflect the contents of the State Register.
t_{SRD}	Delay between input I_0 transition to Logic mode and when the Outputs reflect the contents of the Output Register.
t_{PR}	Delay between positive transition of Preset and when Outputs become valid "1".
t_{PPR}	Delay between V_{CC} (after power-on) and when Outputs become preset at "1".
t_{PRH}	Width of preset input pulse.
f_{MAX}	Maximum clock frequency.

TIMING DIAGRAMS (Continued)


I
1.5V
+3V
0V
+10V
8.0V
8.0V
I_O
1.5V
1.5V
+3V
0V
t_{IH}
1.5V
1.5V
+3V
CLK
0V
t_{IS}
t_{CKH}
INTERNAL STATE REG.
(P_S)
(N_S)
V_{OH}
V_{OL}
t_{SRE}
t_{SRD}
(F_n)
1.5V
(F_{n+1})
(N_S)
1.5V
(F_n + 1)
V_{OH}
V_{OL}
OUTPUT P, F
t_{CKO}
$\overline{OE}$
0V
WF05381S

Diagnostic Mode

TEST LOAD CIRCUIT


V_{CC}
I_O
P_3
P_0
F_0
F_3
I_{11}
CK
PR/$\overline{OE}$
TC01570S


+5V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01580S

VOLTAGE WAVEFORM


+3.0V
90%
10%
0V
5ns
t_r
t_f
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and output, unless otherwise specified.

Input Pulses

SPEED VS. "OR" LOADING

The maximum frequency at which the FPLS can be clocked while operating in *sequential mode* is given by:

$$(1/f_{MAX}) = t_{CY} = t_{IS} + t_{CKO}$$

This frequency depends on the number of transition terms T_n used. Having all 48 terms connected in the AND array does not appreciably impact performance; but the number of terms connected to each OR line affects t_{IS}, due to capacitive loading. The effect of this loading can be seen in Figure 1, showing the variation of t_{IS1} with the number of terms connected per OR.

The AC electrical characteristics contain two limits for the parameters t_{IS1} and t_{IS2}. The first, t_{IS1A} is guaranteed for a device with 24 terms connected to any OR line. t_{IS1B} is guaranteed for a device with 16 terms connected to any OR line.



Figure 1. t_{IS1} vs. Terms/OR Connected

The three other entries in the AC table, t_{IS2} A and B are corresponding 24 and 16 term limits when using the on-chip Complement Array.

The worst case of t_{IS} for a given application can be determined by identifying the OR line with the maximum number of T_n connections. This can be done by referring to the interconnect pattern in the FPLS logic diagram, typically illustrated in Figure 2, or by counting the maximum number of "H" *or* "L" entries in one of the columns of the device Program Table.

This number plotted on the curve in Figure 1 will yield the worst case t_{IS} and, by implication, the maximum clocking frequency for reliable operation.

Note that for maximum speed all UNUSED transition terms should be disconnected from the OR array.



Figure 2. Typical OR Array Interconnect Pattern

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168A

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table on the following page.

In this table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

PRESET/$\overline{\text{OE}}$ OPTION – (P/E)


PR/$\overline{\text{OE}}$
P
E = 1
LS01810S

OPTION	CODE
PRESET[1]	H


PR/$\overline{\text{OE}}$
P = 1
E
LS01820S

OPTION	CODE
$\overline{\text{OE}}$	L

PROGRAMMING:

The PLS168A has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (state and output register) at a logic High (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all Highs (H) as the present state.

"AND" ARRAY – (I), (P)


I,P
i,p
$\bar{i}$,p
T_n
LS01850S

STATE	CODE
INACTIVE^{1,2}	O


I,P
i,p
$\bar{i}$,p
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\bar{i}$,p
T_n
LS01830S

STATE	CODE
$\bar{\text{I}}$, $\bar{\text{P}}$	L


I,P
i,p
$\bar{i}$,p
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – (N), (F)


T_n
n,f
$\bar{n}$,f
S
R
Q
LS01890S

ACTION	CODE
INACTIVE^{1,3}	O


T_n
n,f
$\bar{n}$,f
S
R
Q
LS01900S

ACTION	CODE
SET	H


T_n
n,f
$\bar{n}$,f
S
R
Q
LS01870S

ACTION	CODE
RESET	L


T_n
n,f
$\bar{n}$,f
S
R
Q
LS01880S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)


$\bar{c}$
c
T_n
LS01930S

ACTION	CODE
INACTIVE^{1,4}	O


$\bar{c}$
c
T_n
LS01940S

ACTION	CODE
GENERATE	A


$\bar{c}$
c
T_n
LS01910S

ACTION	CODE
PROPAGATE	•


$\bar{c}$
c
T_n
LS01920S

ACTION	CODE
TRANSPARENT	–

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates T_n.
2. Any gate T_n will be unconditionally inhibited if any one of its I or P link pairs is left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.

FPLS PROGRAM TABLE PLS168A

CUSTOMER NAME ____________________
PURCHASE ORDER # ____________________
SIGNETICS DEVICE # CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________________
TOTAL NUMBER OF PARTS ____________________
PROGRAM TABLE # ____________________
REV ____________________
DATE ____________________

AND

INACTIVE	O	C_n
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	
INACTIVE	O	I_m P_s
I, P	H	
$\bar{I}, \bar{P}$	L	
DON'T CARE	—	

OR

INACTIVE	O	N_s, F_r
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

PRESET	H	P/E
$\overline{OE}$	L	

AND																									OPTION (P/E)													
																									OR													
TERM	C_n	INPUT(Im)												PRESENT STATE (Ps) (Px)										REMARKS	NEXT STATE (Ns) (Px)										OUTPUT (Fr)			
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	3	2	1	0
0																																						
1																																						
2																																						
3																																						
4																																						
5																																						
6																																						
7																																						
8																																						
9																																						
10																																						
11																																						
12																																						
13																																						
14																																						
15																																						
16																																						
17																																						
18																																						
19																																						
20																																						
21																																						
22																																						
23																																						
24																																						
25																																						
26																																						
27																																						
28																																						
29																																						
30																																						
31																																						
32																																						
33																																						
34																																						
35																																						
36																																						
37																																						
38																																						
39																																						
40																																						
41																																						
42																																						
43																																						
44																																						
45																																						
46																																						
47																																						
PIN NO.		18	19	20	21	22	23	2	3	4	5	6	7																		16	15	14	13	11	10	9	8
VARIABLE NAME																																						

TB02031S

Field-Programmable Logic Sequencer (12 × 48 × 8) PLS168A

TEST ARRAY

The FPLS may be subjected to AC and DC parametric tests prior to programming via an on-chip test array.

The array consists of test transition terms 48 and 49, factory programmed as shown below.

Testing is accomplished by clocking the FPLS and applying the proper input sequence to I_{0-11} as shown in the test circuit timing diagram.



0
1023
$(I_n + F_n)/\bar{F}_n$
$(I_n \cdot F_n)/F_n$
$(\bar{I} \cdot \bar{F}_n)/F_n$
$(\bar{I}_n + \bar{F}_n)/F_n$
AF01822S

State Diagram



V_{CC} +5V
V_{CC}
I_n
CLOCK
I_{0-11}
CK
PR/$\overline{OE}$
P_{0-9}
P_{0-3}
F_{0-3}
F_r
GND
TC01593S

FPLS Under Test

AND																									OPTION (P E)													H
																									OR													
TERM	Cn	INPUT (Im)												PRESENT STATE (Ps) (Px)										REMARKS	NEXT STATE (Ns) (Px)										OUTPUT (Fr)			
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	3	2	1	0
48	A	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H		L	L	L	L	L	L	L	L	L	L	L	L	L	L
49	•	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L		H	H	H	H	H	H	H	H	H	H	H	H	H	H

Test Array Program



V_{CC}
4.75V
+5V
0V
t_{VS}
t_{CKH}
t_{CKL}
CK
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
t_{IS1}
t_{IH}
t_{IS2}
t_{IH}
I_{0-11}
1.5V
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
t_{PPR}
t_{CKO}
t_{CKO}
F_{0-3}
1.5V
1.5V
1.5V
3V
0V
STATE REGISTER
HIGH
LOW
WF05376S

Test Circuit Timing Diagram

Both terms 48 and 49 must be deleted during user programming to avoid interfering with the desired logic function. This is accomplished automatically by any of Signetics' qualified programming equipment.

AND																									OPTION (P E)													H
																									OR													
TERM	Cn	INPUT (Im)												PRESENT STATE (Ps) (Px)										REMARKS	NEXT STATE (Ns) (Px)										OUTPUT (Fr)			
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	3	2	1	0
48	-	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H		-	-	-	-	-	-	-	-	-	-	-	-	-	-
49	•	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L		-	-	-	-	-	-	-	-	-	-	-	-	-	-

Test Array Deleted

Signetics

PLS173

Field-Programmable Logic Array (22 × 42 × 10)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 24

DESCRIPTION

The PLS173 is a two-level logic element consisting of 42 AND gates and 10 OR gates with fusible link connections for programming I/O polarity and direction.

All AND gates are linked to 12 inputs (I) and 10 bidirectional I/O lines (B). These yield variable I/O gate configurations via 10 direction control gates (D), ranging from 22 inputs to 10 outputs.

On chip T/C buffers couple either True (I, B) or Complement ($\overline{I}$, $\overline{B}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. Their output polarity, in turn, is individually programmable through a set of EX-OR gates for implementing AND/OR or AND/NOR logic functions.

The PLS173 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes for this device are contained in the pages following.

FEATURES

- Field-Programmable (Ni-Cr links)
- 12 inputs
- 42 AND gates
- 10 OR gates
- 10 bidirectional I/O lines
- Active-High or -Low outputs
- 42 product terms:
  - 32 logic terms
  - 10 control terms
- I/O propagation delay: 30ns (max.)
- Input loading: −100µA (max.)
- Power dissipation: 750mW (typ.)
- Tri-state outputs
- TTL compatible

APPLICATIONS

- Random logic
- Code converters
- Fault detectors
- Function generators
- Address mapping
- Multiplexing

FUNCTIONAL DIAGRAM



P_{31}
P_0
D_0
D_9
I_0
I_{11}
B_0
B_9
S_9
S_0
X_9
X_0
B_9
B_0
AF01831S

PIN CONFIGURATIONS

N Package



I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
I_8 9
I_9 10
I_{10} 11
GND 12
24 V_{CC}
23 B_9
22 B_8
21 B_7
20 B_6
19 B_5
18 B_4
17 B_3
16 B_2
15 B_1
14 B_0
13 I_{11}
CD03290S

N = Plastic

A Package



N/C 11
I_8 10
I_7 9
I_6 8
I_5 7
I_4 6
N/C 5
I_9 12
I_{10} 13
GND 14
I_{11} 15
B_0 16
B_1 17
B_2 18
4 I_3
3 I_2
2 I_1
1 I_0
28 V_{CC}
27 B_9
26 B_8
19 N/C
20 B_3
21 B_4
22 B_5
23 B_6
24 B_7
25 N/C
CD03390S

NOTE:
A = Plastic Leaded Chip Carrier

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
$P_n = A \cdot \overline{B} \cdot C \cdot D \cdot \ldots$

TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
$Z = P0 + P1 + P2 \ldots$

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +} \ldots$
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot \ldots$

NOTES:
1. For each of the 10 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I), and bidirectional pins (B).

Field-Programmable Logic Array (22 × 42 × 10) PLS173

FPLA LOGIC DIAGRAM


(LOGIC TERMS—P)
(CONTROL TERMS)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
I_8 9
I_9 10
I_{10} 11
I_{11} 13
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
B_9
D_9 D_8 D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
S_9 S_8 S_7 S_6 S_5 S_4 S_3 S_2 S_1 S_0
X_9 X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
23 B_9
22 B_8
21 B_7
20 B_6
19 B_5
18 B_4
17 B_3
16 B_2
15 B_1
14 B_0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
TB00941S

NOTES:

1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. ● Programmable connection.

Field-Programmable Logic Array (22 × 42 × 10) PLS173

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS173N
28-pin Plastic Leaded Chip Carrier	PLS173A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			°C
T_A	Operating	0	+75	
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			0.8	V
V_{IH}	High	V_{CC} = Max	2.0			
V_{IC}	Clamp[3,4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage						
V_{OL}	Low[3,5]	V_{CC} = Min I_{OL} = 15mA			0.5	V
V_{OH}	High[3,6]	I_{OH} = −2mA	2.4			
Input current[11]						
I_{IL}	Low	V_{CC} = Max V_{IN} = 0.45V			−100	µA
I_{IH}	High	V_{IN} = 5.5V			40	
Output current						
$I_{O(OFF)}$	Hi-Z state[10]	V_{CC} = Max V_{OUT} = 5.5V V_{OUT} = 0.45V			80 −140	µA
I_{OS}	Short circuit[4,6,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		150	170	mA
Capacitance						
I_{IN}	Input	V_{CC} = 5V V_{IN} = 2.0V		8		pF
C_B	I/O	V_B = 2.0V		15		

AC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$, $R_1 = 470\Omega$, $R_2 = 1k\Omega$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ	Max	
t_{PD}	Propagation delay	Output±	Input±	$C_L = 30pF$		20	30	ns
t_{OE}	Output enable	Output–	Input±	$C_L = 30pf$		20	30	ns
t_{OD}	Output disable[9]	Output+	Input±	$C_L = 5pF$		20	30	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IL} applied to I_{11}. Pins 1 – 5 = 0V, Pins 6 – 10 = 4.5V, Pin 11 = 0V and Pin 13 = 10V.
6. Same conditions as Note 5 except Pin 11 = +10V.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with I_0 and $I_1 = 0V$ and $I_2 - I_{11}$ and $B_0 - B_9 = 4.5V$. Part in Virgin State.
9. Measured at $V_T = V_{OL} + 0.5V$.
10. Leakage values are a combination of input and output leakage.
11. I_{IL} and I_{IH} limits are for dedicated inputs only ($I_0 - I_{11}$).

TEST LOAD CIRCUIT


VCC
I0
I11
BW
BX
DUT
GND
BY
BZ
+5V
R1
R2
CL
INCLUDES SCOPE AND JIG CAPACITANCE
TC01601S

TIMING DIAGRAM


I, B
1.5V
1.5V
1.5V
+3V
0V
B
1.5V
VT
1.5V
VOH
VOL
tPD
tOD
tOE
WF05412S

TIMING DEFINITIONS

t_{PD}	Propagation delay between input and output.
t_{OD}	Delay between input change and when output is off (Hi-Z or High).
t_{OE}	Delay between input change and when output reflects specified output level.

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Array (22 × 42 × 10) PLS173

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this table, the logic state of variables I, P, and B associated with each Sum Term S is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

OUTPUT POLARITY – (B)


S
X
B
LS01950S

ACTIVE LEVEL	CODE
HIGH^{1}	H


S
X
$\overline{B}$
LS01960S

ACTIVE LEVEL	CODE
LOW	L

"AND" ARRAY – (I, B)


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01990S

STATE	CODE
INACTIVE^{1,2}	O


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS02000S

STATE	CODE
I, B	H


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01970S

STATE	CODE
$\overline{I}$, $\overline{B}$	L


I,B
I,B
$\overline{I},\overline{B}$
P,D
LS01980S

STATE	CODE
DON'T CARE	–

OR ARRAY – (B)


P
S
LS02010S

P_n STATUS	CODE
ACTIVE^{1}	A


P
S
LS02020S

P_n STATUS	CODE
INACTIVE	•

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates P_n, D_n.
2. Any gate P_n, D_n will be unconditionally inhibited if both the true and complement of any input (I, B) are left intact.

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. All outputs at "H" polarity.
2. All P_n terms are disabled.
3. All P_n terms are active on all outputs.

CAUTION: PLS173 TEST COLUMNS

The PLS173 incorporates two columns not shown in the logic block diagram. These columns are used for in-house testing of the device in the unprogrammed state. These columns must be disabled prior to using the PLS173 in your application. If you are using a Signetics-approved programmer, the disabling is accomplished during the device programming sequence. If these columns are not disabled, abnormal operation is possible.

Field-Programmable Logic Array (22 × 42 × 10) PLS173

FPLA PROGRAM TABLE


CUSTOMER NAME
SIGNETICS DEVICE #
PROGRAM TABLE # REV DATE
Notes
1. The FPLA is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table. (Shown BLANK for clarity.)
2. Unused I and B bits in the AND array must be programmed Don't Care (–).
3. Unused product terms can be left blank.
OR
ACTIVE A
INACTIVE •
B(O)
CONTROL
HIGH H
LOW L
(POL)
AND
INACTIVE 0
I, B H
Ī, B̄ L
DON'T CARE –
I, B (I)
POLARITY
AND
B(I)
OR
B(O)
TERM
PIN
VARIABLE NAME
D9
D8
D7
D6
D5
D4
D3
D2
D1
D0

TB00956S

Signetics

PLS179
Field-Programmable Logic Sequencer (20 × 45 × 12)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 24

DESCRIPTION

The PLS179 is a Tri-state output, registered logic element combining AND/OR gate arrays with clocked J-K flip-flops. These J-K flip-flops are dynamically convertible to D-type via a "foldback" inverting buffer and control gate F_C. It features 8 registered I/O outputs (F) in conjunction with 4 bidirectional I/O lines (B). There are 8 dedicated inputs. These yield variable I/O gate and register configurations via control gates (D, L) ranging from 20 inputs to 12 outputs.

The AND/OR arrays consist of 32 logic AND gates, 13 control AND gates, and 21 OR gates with fusible link connections for programming I/O polarity and direction. All AND gates are linked to 8 inputs (I), bidirectional I/O lines (B), internal flip-flop outputs (Q), and Complement Array output ($\overline{C}$). The Complement Array consists of a NOR gate optionally linked to all AND gates for generating and propagating complementary AND terms.

FEATURES

- Field-Programmable (Ni-Cr link)
- 8 dedicated inputs
- 13 control gates
- 32 AND gates
- 21 OR gates
- 45 product terms:
  - 32 logic terms
  - 13 control terms
- 4 bidirectional I/O lines
- 8 bidirectional registers
- J/K, T, or D-type flip-flops
- Asynchronous Preset/Reset
- Complement Array
- Active-High or -Low outputs
- Programmable $\overline{OE}$ control
- Positive edge-triggered clock
- Power-on reset on flip-flop (F_n = "1")
- Clock frequency: PLS179: 18MHz (max.)
- Input loading: PLS179: – 100μA (max.)
- Power dissipation: 750mW (typ.)
- TTL compatible
- Tri-state option

PIN CONFIGURATIONS

N Package


CLK 1
I0 2
I1 3
I2 4
I3 5
I4 6
I5 7
I6 8
I7 9
B0 10
B1 11
GND 12
24 VCC
23 B3
22 F7
21 F6
20 F5
19 F4
18 F3
17 F2
16 F1
15 F0
14 B2
13 O.E.
CD04520S

N = Plastic

A Package*


N/C 11
I7 10
I6 9
I5 8
I4 7
I3 6
N/C 5
B0 12
B1 13
GND 14
O.E. 15
B2 16
F0 17
F1 18
4 I2
3 I1
2 I0
1 CLK
28 VCC
27 B3
26 F7
19 N/C
20 F2
21 F3
22 F4
23 F5
24 F6
25 N/C
CD04530S

A = Plastic Leaded Chip Carrier

APPLICATIONS

- Random sequential logic
- Synchronous up/down counters
- Shift registers
- Bidirectional data buffers
- Timing function generators
- System controllers/synchronizers
- Priority encoder/registers

FUNCTIONAL DIAGRAM


(LOGIC TERMS)
(CONTROL TERMS)
P R L D
E
a
b
a
ā
b
b̄
O.E.
Q
Q̄
C̄
C
S
X
M
J P
R Q
(n)
K
CK
B
F
T31
T0
FC
AF01880S

Field-Programmable Logic Sequencer (20 × 45 × 12) PLS179

On-chip T/C buffers couple either True (I, B, Q) or Complement ($\overline{I}$, $\overline{B}$, $\overline{Q}$, $\overline{C}$) input polarities to all AND gates, whose outputs can be optionally linked to all OR gates. One group of AND gates drives bidirectional I/O lines (B), whose output polarity is individually programmable through a set of EX-OR gates for implementing AND-OR or AND-NOR logic functions. Another group drives the J-K inputs of all flip-flops, as well as asynchronous Preset and Reset lines (P, R).

All flip-flops are positive edge-triggered and can be used as input, output or I/O (for interfacing with a bidirectional data bus) in conjunction with load control gates (L), steering inputs (I), (B), (Q) and programmable output select lines (E).

The PLS179 is field programmable, enabling the user to quickly generate custom patterns using standard programming equipment.

Order codes are contained on the pages following.

LOGIC FUNCTION



SET Q_0: $J_0 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_0 = 0$

RESET Q_1: $J_1 = 0$
$K_1 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $J_2 = 0$
$K_2 = 0$

TOGGLE Q_3: $J_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$K_3 = (Q_3 \bullet \overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

TB00901S

NOTES:
Similar logic functions are applicable for D and T mode flip-flops.

FLIP-FLOP TRUTH TABLE

$\overline{OE}$	L	CK	P	R	J	K	Q	F
H	■	■	■	■	■	■	■	H/Hi-Z
L	X	X	X	X	X	X	L	H
L	X	X	H	L	X	X	H	L
L	X	X	L	H	X	X	L	H
L	L	↑	L	L	L	L	Q	$\overline{Q}$
L	L	↑	L	L	L	H	L	H
L	L	↑	L	L	H	L	H	L
L	L	↑	L	L	H	H	$\overline{Q}$	Q
H	H	↑	L	L	L	H	L	H*
H	H	↑	L	L	H	L	H	L*
+10V	X	↑	X	X	L	H	L	H**
	X	↑	X	X	H	L	H	L**

NOTES:

1. Positive Logic:
   $J/K = T_0 + T_1 + T_2 + \ldots + T_{31}$
   $T_n = \overline{C} \cdot (I_0 \cdot I_1 \cdot I_2 \ldots) \cdot (Q_0 \cdot Q_1 \ldots) \cdot (B_0 \cdot B_1 \ldots)$
2. ↑ denotes transition from Low to High level.
3. X = Don't Care
4. * = Forced at F_n pin for loading J/K flip-flop in I/O mode. L must be enabled, and other active T_n disabled via steering input(s) I, B, or Q.
5. At P = R = H, Q = H. The final state of Q depends on which is released first.
6. ** = Forced at F_n pin to load J/K flip-flop independent of program code (Diagnostic mode), Tri-state B outputs.

VIRGIN STATE

The factory shipped virgin device contains all fusible links intact, such that:

1. $\overline{OE}$ is always enabled.
2. Preset and Reset are always disabled.
3. All transition terms are disabled.
4. All flip-flops are in D-mode unless otherwise programmed to J/K only or J/K or D (controlled).
5. All B pins are inputs and all F pins are outputs unless otherwise programmed.

Field-Programmable Logic Sequencer (20 × 45 × 12)

PLS179

FPLS LOGIC DIAGRAM


(LOGIC TERMS — T)
(CONTROL TERMS)
I0 2
I1 3
I2 4
I3 5
I4 6
I5 7
I6 8
I7 9
F0
F1
F2
F3
F4
F5
F6
F7
B0
B1
B2
B3
C̄
C
OE 13
PB RB PA RA LB LA D3 D2 D1 D0
EA EB
S3
S2
S1
S0
X3
X2
X1
X0
M7
M6
M5
M4
M3
M2
M1
M0
P R
J Q
K
CK'
23 B3
14 B2
11 B1
10 B0
22 F7
21 F6
20 F5
19 F4
18 F3
17 F2
16 F1
15 F0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0 FC
CK' 1 CLK
LD01672S

1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.
4. ▨ Programmable connection.

Field-Programmable Logic Sequencer (20 × 45 × 12) PLS179

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLS179N
28-pin Plastic Leaded Chip Carrier	PLS179A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp	V_{CC} = Min, $I_{IN} = -12mA$		−0.8	−1.2	
Output voltage[3]						
V_{OH}	High	V_{CC} = Min, $I_{OH} = -2mA$	2.4			V
V_{OL}	Low	I_{OL} = 10mA		0.35	0.5	
Input current						
I_{IH}	High	V_{CC} = Max, V_{IN} = 5.5V		< 1	40	μA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
$I_{O(OFF)}$	Hi-Z state[5,8]	V_{CC} = Max, V_{OUT} = 5.5V		1	80	μA
		V_{OUT} = 0.45V			−140	
I_{OS}	Short circuit[4,6]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[7]	V_{CC} = Max		150	210	mA
Capacitance						
C_{IN}	Input	V_{CC} = 5.0V, V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		15		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at V_{CC} = 5V, T_A = +25°C.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IH} applied to $\overline{OE}$.
6. Duration of short circuit should not exceed 1 second.
7. I_{CC} is measured with the $\overline{OE}$ input grounded, all other inputs at 4.5V, and the outputs open.
8. Leakage values are a combination of input and output leakage.

Field-Programmable Logic Sequencer (20 × 45 × 12) PLS179

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS Min[5]	LIMITS Typ[1]	LIMITS Max	UNIT
Pulse width								
t_{CKH}	Clock[2] high	CK –	CK +	$C_L = 30pF$	20	15		ns
t_{CKL}	Clock low	CK +	CK –		20	15		
t_{CKP}	Period	CK +	CK +		55	45		
t_{PRH}	Preset/Reset pulse	(I,B) +	(I,B) –		35	30		
Setup time								
t_{IS1}	Input	CK +	(I,B) ±		35	30		ns
t_{IS2}	Input (through F_n)	CK +	F ±		15	10		
t_{IS3}	Input (through Complement Array)[4]	CK +	(I,B) ±		55	45		
Hold time								
t_{IH1}	Input	CK +	(I,B) ±		0	–5		ns
t_{IH2}	Input (through F_n)	CK +	F ±		15	10		
Propagation delay								
t_{CKO}	Clock	F ±	CK ±			15	20	ns
t_{OE1}	Output enable	F –	$\overline{OE}$ –			20	30	
t_{OD1}	Output disable[3]	F +	$\overline{OE}$ +	$C_L = 5pF$		20	30	
t_{PD}	Output	B ±	(I,B) ±	$C_L = 30pF$		25	35	
t_{OE2}	Output enable	B ±	(I,B) +			20	30	
t_{OD2}	Output disable[3]	B +	(I,B) –	$C_L = 5pF$		20	30	
t_{PRO}	Preset/Reset	F ±	(I,B) +	$C_L = 30pF$		35	45	
t_{PPR}	Power-on preset	F –	V_{CC} +			0	10	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% – 90%) ⩽ 10ns.
3. Measured at $V_T = V_{OL} + 0.5V$.
4. When using the Complement Array $T_{CKP} = 75ns$ (min).
5. Limits are guaranteed with 12 product terms maximum connected to each sum term line.

TEST LOAD CIRCUIT


VCC
I0
In
BW
BX
CK
DUT
GND
BY
BZ
F0
FN
OE
TC01611S
+5V
R1
R2
CL
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01621S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05460S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Sequencer (20 × 45 × 12) PLS179

TIMING DIAGRAMS


I, B (INPUTS)
1.5V
1.5V
+3V
0V
t_{IH1}
t_{IS1}
1.5V
1.5V
1.5V
+3V
CK
0V
t_{IS1}
t_{CKH}
t_{CKL}
t_{CKP}
F (OUTPUTS)
V_{OH}
1.5V
V_T
t_{CKO}
V_{OL}
t_{OD1}
$\overline{OE}$
1.5V
1.5V
+3V
0V
t_{OE1}
WF05471S

Flip-Flop Outputs


I, B (INPUTS)
1.5V
+3V
0V
t_{PD}
B (OUTPUTS)
1.5V
V_T
V_{OH}
V_{OL}
t_{OE2}
t_{OD2}
I, B (OUTPUT ENABLE)
+1.5V
+1.5V
+3V
0V
WF05481S

Gate Outputs


VCC
4.5V
+5V
0V
t_{PPR}
F (OUTPUTS)
1.5V
1.5V
V_{OH}
V_{OL}
t_{CKO}
I, B (INPUTS)
1.5V
1.5V
+3V
0V
t_{IH1}
t_{IS1}
CK
1.5V
1.5V
1.5V
+3V
0V
t_{IS1}
t_{CKH}
t_{CKL}
t_{CKP}
WF06872S

Power-On Reset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP}	Clock period.
t_{PRH}	Width of preset input pulse.
t_{IS1}	Required delay between beginning of valid input and positive transition of clock.
t_{IS2}	Required delay between beginning of valid input forced at flip-flop output pins, and positive transition of clock.
t_{IH1}	Required delay between positive transition of clock and end of valid input data.
t_{IH2}	Required delay between positive transition of clock and end of valid input data forced at flip-flop output pins.
t_{CKO}	Delay between positive transition of clock and when Outputs become valid (with $\overline{OE}$ Low).
t_{OE1}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD1}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{PPR}	Delay between V_{CC} (after power-on) and when flip-flop outputs become preset at "1" (internal Q outputs at "0").
t_{PD}	Propagation delay between combinational inputs and outputs.
t_{OE2}	Delay between predefined Output Enable High, and when combinational Outputs become valid.
t_{OD2}	Delay between predefined Output Enable Low and when combinational Outputs are in the off state.
t_{PRO}	Delay between positive transition of predefined Preset/Reset input, and when flip-flop outputs become valid.

TIMING DIAGRAMS (Continued)


I,B
(INPUTS)
+3V
1.5V
0V
CK
+3V
1.5V
0V
tIS1*
tIS1
tCKO
PRESET/RESET
(I, B INPUTS)
+3V
1.5V
1.5V
0V
tPRH
Q
(PRESET)
(RESET)
tPRO
F
(OUTPUTS)
VOH
1.5V
(RESET)
(PRESET)
1.5V
VOL
WF17071S

*Preset and Reset functions override Clock. However, F outputs may glitch with the first positive Clock Edge if T_{IS1} cannot be guaranteed by the user.

Asynchronous Preset/Reset


I,B
(LOAD SELECT)
1.5V
1.5V
+3V
0V
$\overline{OE}$
1.5V
1.5V
+3V
0V
tOE1
L
F
(INPUTS)
VT
(FORCED DIN)
1.5V
+3V VOH
0V VOL
tOD1
tIS2
tIH2
CK
+3V
0V
tCKH
tIH1
Q
($\overline{D_{IN}}$)
WF05501S

Flip-Flop Input Mode

Field-Programmable Logic Sequencer (20 × 45 × 12) PLS179

The FPLS can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/OR-EX-OR input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Tables on the following pages.

In these Tables, the logic state or action of all I/O, control, and state variables is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

"AND" ARRAY – (I), (B), (Qp)


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
INACTIVE^{1,2}	O

LS02030S


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
I, B, Q	H

LS02040S


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
$\overline{I}, \overline{B}, \overline{Q}$	L

LS02050S


I, B, Q
I, B, Q
$\overline{I}, \overline{B}, \overline{Q}$
$(T, F_C, L, P, R, D)_n$

STATE	CODE
DON'T CARE	–

LS02060S

"COMPLEMENT" ARRAY – (C)


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
INACTIVE^{1,3,5}	O

LS02070S


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
GENERATE^{5}	A

LS02080S


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
PROPAGATE	●

LS02090S


$\overline{C}$
C
(T_n, F_C)

ACTION	CODE
TRANSPARENT	–

LS02100S


$\overline{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
PROPAGATE	●

LS02110S


$\overline{C}$
C
(D_n, L_n, P_n, R_n)

ACTION	CODE
TRANSPARENT	–

LS02120S

"OR" ARRAY — (MODE)



ACTION	CODE
J/K OR D (CONTROLLED)	A

LS02130S



ACTION	CODE
J·K	●

LS02140S

Notes on following page.

"OR" ARRAY — (Q_N = D – Type)


Tn
M = ENABLED
J
K
Q

T_n STATUS	CODE
ACTIVE (Set)	A

LS02150S


Tn
M = ENABLED
J
K
Q

T_n STATUS	CODE
INACTIVE (Reset)	●

LS02160S

"AND" ARRAY — (Q_N = J – K Type)


Tn
M = DISABLED
J
K
Q

ACTION	CODE
TOGGLE	O

LS02170S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
SET	H

LS02180S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
RESET	L

LS02190S


Tn
M = DISABLED
J
K
Q

ACTION	CODE
HOLD	–

LS02200S

"OR" ARRAY — (S or B),(P),(R)



T_n STATUS	CODE
ACTIVE	A

LS02210S



T_n STATUS	CODE
INACTIVE	●

LS02220S

"EX-OR" ARRAY — (B)



POLARITY	CODE
LOW	L

LS02230S



POLARITY	CODE
HIGH	H

LS02240S

"OE " ARRAY — (E)



ACTION	CODE
IDLE[4]	O

LS02250S



ACTION	CODE
CONTROL	A

LS02260S



ACTION	CODE
ENABLE[4]	●

LS02270S



ACTION	CODE
DISABLE	–

LS02280S

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates.
2. Any gate (T, F_C, L, P, R, D)$_n$ will be unconditionally inhibited if any one of the I, B, or Q link pairs is left intact.
3. To prevent oscillations, this state is not allowed for C link, pairs coupled to active gates T_n, F_C.
4. E_n = O and E_n = • are logically equivalent states, since both cause F_n outputs to be unconditionally enabled.
5. These states are not allowed for control gates (L, P, R, D)$_n$ due to their lack of "OR" array links.

Field-Programmable Logic Sequencer (20 × 45 × 12) PLS179

FPLS PROGRAM TABLE

AND

INACTIVE	0	I, B, (I), Q (P)
I, B, Q	H	
$\overline{I}, \overline{B}, \overline{Q}$	L	
DON'T CARE	—	

INACTIVE	0	C
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	

OR

ACTIVE	A	P, R, B (O) (Q = D)
INACTIVE	•	

TOGGLE	0	(Q = J/K)
SET	H	
RESET	L	
HOLD	—	

CONTROL

J/K	•	F/F MODE
J/K or D (CONTROLLED)	A	

IDLE	0	E_A, B
CONTROL	A	
ENABLE	•	
DISABLE	—	

HIGH	H	(POL.)
LOW	L	

NOTES

1. The FPLS is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Program unused C, I, B, and O bits in the AND array as (—). Program unused Q, B, R, and P bits in the OR array as (—) or (A), as applicable.
3. Unused Terms can be left blank.
4. Q (P) and Q (N) are respectively the present and next states of flip-flops Q.

THIS PORTION TO BE COMPLETED BY SIGNETICS

CF (XXXX) ________

CUSTOMER SYMBOLIZED PART # ________

DATE RECEIVED ________

COMMENTS ________

CUSTOMER NAME ________

PURCHASE ORDER # ________

SIGNETICS DEVICE # ________

TOTAL NUMBER OF PARTS ________

PROGRAM TABLE # ________ REV ________ DATE ________

														F/F MODE								E_B				E_A				POLARITY			
		AND																				(OR)											
	C	I								B (I)				Q (P)								Q (N)								B (O)			
TERM		7	6	5	4	3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0	3	2	1	0
0																																	
1																																	
2																																	
3																																	
4																																	
5																																	
6																																	
7																																	
8																																	
9																																	
10																																	
11																																	
12																																	
13																																	
14																																	
15																																	
16																																	
17																																	
18																																	
19																																	
20																																	
21																																	
22																																	
23																																	
24																																	
25																																	
26																																	
27																																	
28																																	
29																																	
30																																	
31																																	
F_C																																	
P_B																																	
R_B																																	
L_B																																	
P_A																																	
R_A																																	
L_A																																	
D3																																	
D2																																	
D1																																	
D0																																	
PIN		9	8	7	6	5	4	3	2	23	14	11	10	22	21	20	19	18	17	16	15												

TB01711S

Signetics

PLHS473

Field-Programmable Logic Array (20 × 24 × 11)

Signetics Programmable Logic
Preliminary Specification

Application Specific Products
• Series 24

DESCRIPTION

The PLHS473 is a two level logic device consisting of 24 AND gates and 22 OR gates with fusible link connections for programming I/O polarity and direction. The Signetics state of the art Oxide-Isolated Bipolar process is used to produce performance not yet achieved in devices of this complexity.

All AND gates are linked to 11 input pins, 9 bidirectional I/O pins, and 2 dedicated output pins. The bidirectional pins are controlled via the OR array. Using these features, the PLHS473 can be configured with up to 20 inputs and as many as 11 outputs.

The AND array input buffers provide both the True and Complement of the inputs (I_X) and the bidirectional signals (B_X) as programmable connections to the AND gates. All 24 AND gates can then be optionally linked to all 22 OR gates (a feature known as Product Term sharing not found in PALs[1] or most macrocell architectures). The OR array drives 11 output buffers which can be programmed as Active-High for AND-OR functions or Active-Low for AND-NOR functions. In addition, the I/O configuration of each bidirectional pin is individually controlled by a sum-of-products (AND-OR) function which may also contain any of the 24 AND gate outputs. This allows dynamic I/O configuration of all 9 bidirectional pins.

The PLHS473 contains two new features of significance. A code verification lock has been incorporated to improve user security. The addition of three test columns and one test row enables the user to test the device in an unprogrammed state.

The PLHS473 is field programmable using Vertical Avalanche Migration Programmed (VAMP^{TM}) fuses to program the cells. This enables the generation of custom logic patterns using standard programming equipment.

Order codes for this device are contained in the pages following.

FEATURES

- **Field-Programmable**
- **11 dedicated inputs**
- **2 dedicated outputs**
- **9 bidirectional I/O lines**
- **24 product terms**
- **22 OR gates**
- **I/O direction decoded in OR array**
- **Output Enable decoded in OR array**
- **I/O propagation delay: 20ns (max.)**
- **Input loading: −100μA (max.)**
- **Power dissipation: 700mW (typ.)**
- **Security fuse**
- **Testable in unprogrammed state**
- **Programmable as Tri-state or Open-Collector outputs**
- **TTL compatible**

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

PIN CONFIGURATIONS

N Package



N = Plastic

A Package



A = Plastic Leaded Chip Carrier

FUNCTIONAL DIAGRAM



---

[1] PAL is a trademark of MMI.

Field-Programmable Logic Array (20 × 24 × 11)

PLHS473

FPLA LOGIC DIAGRAM


(LOGIC TERMS–P)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
I9 10
I10 11
B0
B1
B2
B3
B4
B5
B6
B7
B8
D8
S8
D7
S7
D6
S6
D5
S5
D4
S4
D3
S3
D2
S2
D1
S1
D0
S0
EB
SB
EA
SA
X8
X7
X6
X5
X4
X3
X2
X1
X0
XB
XA
23 B8
22 B7
21 B6
20 B5
17 B4
16 B3
15 B2
14 B1
13 B0
19 OB
18 OA
23 • • • • • • 16
15 • • • • • • 8
7 • • • • • • 0
LD02630S

NOTES:

1. All unprogrammed or virgin "AND" gate locations are pulled to logic "1".
2. All unprogrammed or virgin "OR" gate locations are pulled to logic "0".
3. ▨ Programmable connection.

Field-Programmable Logic Array (20 × 24 × 11) PLHS473

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-pin Plastic DIP 300mil-wide	PLHS473N
28-pin Plastic Leaded Chip Carrier	PLHS473A

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING Min	RATING Max	UNIT
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

LOGIC FUNCTION

TYPICAL PRODUCT TERM:

$Pn = A \cdot \overline{B} \cdot C \cdot D \cdot \ ...$

TYPICAL LOGIC FUNCTION:

AT OUTPUT POLARITY = H

$Z = P0 + P1 + P2\ ...$

AT OUTPUT POLARITY = L

$Z = \overline{P0 + P1 + P2 +}\ ...$

$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot \ ...$

NOTES:

1. For each of the 11 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I), fixed output pins (0) and bidirectional pins (B).

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

DC ELECTRICAL CHARACTERISTICS $0°C \leq T_A \leq +75°C$, $4.75 \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS Min	LIMITS Typ[2]	LIMITS Max	UNIT
Input voltage[3]						
V_{IL}	Low	V_{CC} = Min			0.8	V
V_{IH}	High	V_{CC} = Max	2.0			
V_{IC}	Clamp[4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OL}	Low[5]	I_{OL} = 15mA			0.5	V
V_{OH}	High[6]	I_{OH} = −2mA	2.4			
Input current						
		V_{CC} = Max				
I_{IL}	Low	V_{IN} = 0.45V			−100	µA
I_{IH}	High	V_{IN} = 5.5V			40	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[10]	V_{OUT} = 5.5V			40	µA
		V_{OUT} = 0.45V			−100	
I_{OS}	Short circuit[4,6,7]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		140	155	mA
Capacitance						
		V_{CC} = 5V				
I_{IN}	Input	V_{IN} = 2.0V		8		pF
C_B	I/O	V_B = 2.0V		15		

Field-Programmable Logic Array (20 × 24 × 11) PLHS473

AC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant +75°C$, $4.75 \leqslant V_{CC} \leqslant 5.25V$, $R_1 = 470\Omega$, $R_2 = 1k\Omega$

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	LIMITS			UNIT
					Min	Typ	Max	
t_{PD}	Propagation delay	Output±	Input±	$C_L = 30pF$		15	20	ns
t_{OE}	Output enable	Output–	Input±	$C_L = 30pF$		15	20	ns
t_{OD}	Output disable[9]	Output+	Input±	$C_L = 5pF$		15	20	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with Pins 1 – 5 = 0V, Pins 6, 8 = 4.5V, and Pins 7, 9 – 11 = 10V.
6. Same conditions as Note 5 except Pin 9 = 4.5V.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with all inputs and bidirectional pins at 4.5V. Part in Virgin State.
9. Measured at $V_T = V_{OL} + 0.5V$.
10. Leakage values are a combination of input and output leakage.

TEST LOAD CIRCUIT



VCC
I0
I10
DUT
BW
BX
GND
BY
BZ
OX
+5V
R1
R2
CL
INCLUDES SCOPE AND JIG CAPACITANCE
TC02681S

TIMING DIAGRAM



I, B
1.5V
1.5V
1.5V
+3V
0V
B
1.5V
VT
1.5V
VOH
VOL
tPD
tOD
tOE
WF05412S

TIMING DEFINITIONS

t_{PD}	Propagation delay between input and output.
t_{OD}	Delay between input change and when output is off (Hi-Z or High).
t_{OE}	Delay between input change and when output reflects specified output level.

VOLTAGE WAVEFORM



+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this table, the logic state of variables I, P, and B associated with each Sum Term S is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:

OUTPUT POLARITY – (O, B)



ACTIVE LEVEL	CODE
LOW[1]	L

TC02560S



ACTIVE LEVEL	CODE
HIGH	H

TC02570S

"AND" ARRAY – (I, B)



STATE	CODE
DON'T CARE[1]	–

TC02600S



STATE	CODE
INACTIVE[2]	O

TC02630S



STATE	CODE
I, B	H

TC02610S



STATE	CODE
$\overline{I}, \overline{B}$	L

TC02620S

OR ARRAY – (O, B)



P_n STATUS	CODE
INACTIVE[1]	•

TC02580S



P_n STATUS	CODE
ACTIVE	A

TC02591S

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. All outputs at "L" polarity.
2. All P_n terms are enabled. (Don't Cares).
3. All P_n terms are inactive on all outputs.

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate P_n will be unconditionally inhibited if the true and complement of either input (I or B) are both programmed for a connection.

Field-Programmable Logic Array (20 × 24 × 11) PLHS473

FPLA PROGRAM TABLE

CUSTOMER NAME ____________________
PURCHASE ORDER # ____________________
SIGNETICS DEVICE # __________ CF (XXXX) __________
CUSTOMER SYMBOLIZED PART # ____________________
TOTAL NUMBER OF PARTS ____________________
PROGRAM TABLE # __________ REV __________ DATE __________

AND

INACTIVE	0	I,B(I)
I, B	H	
$\bar{I}$, $\bar{B}$	L	
DON'T CARE	—	

OR

ACTIVE	A	B(O)
INACTIVE	•	

CONTROL

HIGH	H	(POL)
LOW	L	

																																	POLARITY										
TERM	AND																				TERM	OR																					
	I											B (I)										E		D									O		B (O)								
	10	9	8	7	6	5	4	3	2	1	0	8	7	6	5	4	3	2	1	0		B	A	8	7	6	5	4	3	2	1	0	B	A	8	7	6	5	4	3	2	1	0
0																					0																						
1																					1																						
2																					2																						
3																					3																						
4																					4																						
5																					5																						
6																					6																						
7																					7																						
8																					8																						
9																					9																						
10																					10																						
11																					11																						
12																					12																						
13																					13																						
14																					14																						
15																					15																						
16																					16																						
17																					17																						
18																					18																						
19																					19																						
20																					20																						
21																					21																						
22																					22																						
23																					23																						
PIN	11	10	9	8	7	6	5	4	3	2	1	23	22	21	20	17	16	15	14	13													19	18	23	22	21	20	17	16	15	14	13
VARIABLE NAME																																											

Notes
1. The FPLA is shipped with all links open.
2. Unused I and B bits in the AND array exist as Don't Care (–) in the virgin state.
3. All P-terms are inactive on all outputs (B, O) in the virgin array.
4. Unused product terms can be left blank.

TB01980S

Signetics

PLC473

Erasable-Programmable Logic Array (20 × 24 × 11)

Signetics Programmable Logic
Preliminary Specification

Application Specific Products
• Series 24

DESCRIPTION

The PLC473 is a two-level logic CMOS Erasable Programmable Logic Device (EPLD) consisting of 24 AND gates and 22 OR gates with EPROM cell connections for programming I/O polarity and direction. The Signetics state-of-the-art Floating Gate CMOS process is used to produce performance not yet achieved in devices of this complexity.

All AND gate inputs are linked to 11 dedicated input pins ($I_0 - I_{10}$) and 9 bidirectional I/O pins ($B_0 - B_8$). These bidirectional pins are controlled via the OR array. Employing the 2 dedicated outputs ($O_A - O_B$) and the programmable I/O direction feature, the PLC473 can be configured with up to 20 inputs — and as many as 11 outputs.

The AND array input buffers provide both the True and Complement of the inputs (I_X) and the bidirectional signals (B_X) as programmable connections to the AND gates. All 24 AND gates can then be optionally linked to all 22 OR gates (a feature known as Product Term sharing not found in PALs[1] or most macrocell architectures). The OR array drives 11 output buffers which can be programmed as Active-High for AND-OR functions or Active-Low for AND-NOR functions. In addition, the I/O configuration of each bidirectional pin is individually controlled by a sum-of-products (AND-OR) function which may also contain any of the 24 AND gate outputs. This allows dynamic I/O configuration of all 9 bidirectional pins.

The PLC473 contains two new features of significance. Additional testing capability includes stress test mode, whereby all cells can be stressed to ensure reliability. In another test mode, the threshold voltage of each cell can be individually checked to ensure charge retention.

The PLC473 is field programmable using Floating Gate Ultraviolet Erasable Cells. This enables the generation of custom logic patterns using standard programming equipment.

FUNCTIONAL DIAGRAM



PIN CONFIGURATION



FA = Ceramic with window

FEATURES

- **Electrically Programmable; UV erasable**
- **11 dedicated inputs**
- **2 dedicated outputs**
- **9 bidirectional I/O lines**
- **24 product terms**
- **I/O direction decoded in OR array**
- **I/O propagation delay: 35ns (max.)**
- **Input loading: $-10\mu A$ (max.)**
- **Power dissipation at 10MHz**
  CMOS: 210mW
  TTL: 270mW
- **Threshold voltage test mode for individual cells**
- **Stress test mode for individual cells**
- **Output: Tri-state condition decoded in OR array**
- **TTL compatible**

APPLICATIONS

- **Random logic**
- **Code converters**
- **Fault detectors**
- **Function generators**
- **Address mapping**
- **Multiplexing**

---

[1] Pal is a trademark of MMI.

FPLA LOGIC DIAGRAM


(LOGIC TERMS–P)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
I9 10
I10 11
B0
B1
B2
B3
B4
B5
B6
B7
B8
D8
S8
D7
S7
D6
S6
D5
S5
D4
S4
D3
S3
D2
S2
D1
S1
D0
S0
EB
SB
EA
SA
X8
X7
X6
X5
X4
X3
X2
X1
X0
XB
XA
23 B8
22 B7
21 B6
20 B5
17 B4
16 B3
15 B2
14 B1
13 B0
19 OB
18 OA
23 • • • • • • 16
15 • • • • • • • 8
7 • • • • • • 0
LD02630S

NOTES:

1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. ▨ Programmable connection.

Erasable-Programmable Logic Array (20 × 24 × 11) PLC473

ORDERING CODE

DESCRIPTION	ORDER CODE
24-pin Ceramic DIP with Window 300mil-wide	PLC473-35FA PLC473-45FA PLC473-60FA

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING Min	RATING Max	UNIT
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		V_{CC} + 0.5	V_{DC}
V_{OUT}	Output voltage		V_{CC} + 0.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
$Pn = A \cdot \overline{B} \cdot C \cdot D \cdot \ldots$

TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
$Z = P0 + P1 + P2 \ldots$

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +} \ldots$
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot \ldots$

NOTES:
1. For each of the 11 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I), fixed output pins (O) and bidirectional pins (B).

DC ELECTRICAL CHARACTERISTICS 0°C ≤ T_A ≤ +75°C, 4.75 ≤ V_{CC} ≤ 5.25V

SYMBOL	PARAMETER	TEST CONDITIONS		LIMITS Min	LIMITS Typ[2]	LIMITS Max	UNIT
Input voltage[3]							
V_{IL}	Low	V_{CC} = Min		−0.3		0.8	
V_{IH}	High	V_{CC} = Max		2.0		V_{CC} + 0.3	V
Output voltage[3]							
V_{OL}	Low	V_{CC} = Min I_{OL} = 8mA				0.45	V
V_{OH}	High	I_{OH} = −3mA		2.4			
Input current							
I_{IL}	Low	V_{IN} = GND				−10	µA
I_{IH}	High	V_{IN} = V_{CC}				10	
Output current							
$I_{O(OFF)}$	Hi-Z state[8]	V_{OUT} = V_{CC} V_{OUT} = GND				10 −10	µA µA
I_{OS}	Short circuit[4,7]	V_{OUT} = GND		−15		−70	mA
I_{CC}	V_{CC} supply current (Active)[5,6]	No load f = 1MHz	CMOS inputs			40	mA
			TTL inputs			50	mA
Capacitance							
I_{IN}	Input	V_{CC} = 5V V_{IN} = 2.0V			6		
C_B	I/O	V_B = 2.0V			12		pF

AC ELECTRICAL CHARACTERISTICS 0°C ≤ T_A ≤ +75°C, 4.75 ≤ V_{CC} ≤ 5.25V, R_1 = 470Ω, R_2 = 1kΩ

SYMBOL	PARAMETER	TO	FROM	TEST CONDITIONS	PLC473-35 MIN	PLC473-35 MAX	PLC473-45 MIN	PLC473-45 MAX	PLC473-60 MIN	PLC473-60 MAX	UNIT
t_{PD}	Propagation delay	Output±	Input±	C_L = 30pF		35		45		60	ns
t_{OE}	Output enable	Output−	Input±	C_L = 30pF		35		45		60	ns
t_{OD}	Output disable[9]	Output+	Input±	C_L = 30pF		35		45		60	ns

Notes on following page.

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$. $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. CMOS inputs: $V_{IL} = GND$, $V_{IH} = V_{CC}$
   TTL inputs: $V_{IL} = 0.45V$, $V_{IH} = 2.4V$
6. Measured with all inputs and outputs switching.
7. Duration of short circuit should not exceed 1 second.
8. Leakage values are a combination of input and output leakage.
9. Measured at $V_T = V_{OL} + 0.5V$.

TEST LOAD CIRCUIT



V_{CC}
I0
I10
BW
BX
GND
BY
BZ
OX
+5V
R1
R2
CL
INCLUDES SCOPE AND JIG CAPACITANCE
TC02680S

TIMING DIAGRAM



I, B
1.5V
1.5V
1.5V
+3V
0V
B
1.5V
VT
VOH
1.5V
VOL
tPD
tOD
tOE
WF05412S

TIMING DEFINITIONS

t_{PD}	Propagation delay between input and output.
t_{OD}	Delay between input change and when output is off (Hi-Z or High).
t_{OE}	Delay between input change and when output reflects specified output level.

VOLTAGE WAVEFORM



+3.0V
90%
0V
10%
5ns
tr
tf
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Erasable-Programmable Logic Array (20 × 24 × 11) PLC473

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table on the following page.

In this table, the logic state of variables I, P, and B associated with each Sum Term S is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

OUTPUT POLARITY – (O, B)


S
X
$\overline{O}$, $\overline{B}$

ACTIVE LEVEL	CODE
LOW	L

TC02561S



ACTIVE LEVEL	CODE
HIGH[1]	H

TC02571S

"AND" ARRAY – (I, B)


I,B
I,B
$\overline{I}$,$\overline{B}$
P

STATE	CODE
DON'T CARE	–

TC02601S


I,B
I,B
$\overline{I}$,$\overline{B}$
P

STATE	CODE
INACTIVE[1]	O

TC02632S


I,B
I,B
$\overline{I}$,$\overline{B}$
P

STATE	CODE
I, B	H

TC02610S


I,B
I,B
$\overline{I}$,$\overline{B}$
P

STATE	CODE
$\overline{I}$, $\overline{B}$	L

TC02620S

OR ARRAY – (O, B)



P_n STATUS	CODE
INACTIVE	•

TC02581S



P_n STATUS	CODE
ACTIVE[1]	A

TC02590S

NOTES:

1. This is the initial unprogrammed state of all link pairs.
2. Any Product Term (P_n) will always be False (logic low) if at least one of its (I,B) link pairs is unprogrammed as shown.

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. All outputs at "H" polarity.
2. All P_n terms are disabled.
3. All P_n terms are active on all outputs.

Erasable-Programmable Logic Array (20 × 24 × 11)

PLC473

FPLA PROGRAM TABLE

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # ________ CF (XXXX) ________
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ________ REV ________ DATE ________

AND

INACTIVE	0	I,B(I)
I, B	H	
$\bar{I}$, $\bar{B}$	L	
DON'T CARE	—	

OR

ACTIVE	A	B(O)
INACTIVE	•	

CONTROL

HIGH	H	(POL)
LOW	L	

TERM	AND																			
	I											B (I)								
	10	9	8	7	6	5	4	3	2	1	0	8	7	6	5	4	3	2	1	0
0																				
1																				
2																				
3																				
4																				
5																				
6																				
7																				
8																				
9																				
10																				
11																				
12																				
13																				
14																				
15																				
16																				
17																				
18																				
19																				
20																				
21																				
22																				
23																				
PIN	11	10	9	8	7	6	5	4	3	2	1	23	22	21	20	17	16	15	14	13
VARIABLE NAME																				

												POLARITY										
TERM	OR																					
	E		D									O		B (O)								
	B	A	8	7	6	5	4	3	2	1	0	B	A	8	7	6	5	4	3	2	1	0
0																						
1																						
2																						
3																						
4																						
5																						
6																						
7																						
8																						
9																						
10																						
11																						
12																						
13																						
14																						
15																						
16																						
17																						
18																						
19																						
20																						
21																						
22																						
23																						
PIN												19	18	23	22	21	20	17	16	15	14	13
VARIABLE NAME																						

Notes
1. The FPLA is shipped with all links open.
2. Unused I and B bits in the AND array exist as Don't Care (–) in the virgin state.
3. All P-terms are inactive on all outputs (B, O) in the virgin array.
4. Unused product terms can be left blank.

TB01980S

Section 6
PLD Data Sheets

INDEX

Section 6 – PLD Data Sheets

Series 28

PLS100/PLS101 Field-Programmable Logic Array (16 × 48 × 8) 6-3
PLS103 Field-Programmable Gate Array (16 × 9 × 9) 6-10
PLS105 Field-Programmable Logic Sequencer (16 × 48 × 8) ... 6-16
PLS105A Field-Programmable Logic Sequencer (16 × 48 × 8) ... 6-27
PLUS405A Field-Programmable Logic Sequencer (16 × 64 × 8) ... 6-38

Signetics

PLS100/PLS101

Field-Programmable Logic Array (16 × 48 × 8)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 28

DESCRIPTION

The PLS100 (Tri-state) and PLS101 (Open Collector) are bipolar, fuse Programmable Logic Arrays (FPLAs). Each device utilizes the standard AND/OR/Invert architecture to directly implement custom sum of product logic equations.

Each device consists of 16 dedicated inputs and 8 dedicated outputs. Each output is capable of being actively controlled by any or all of the 48 product terms. The True, Complement, or Don't Care condition of each of the 16 inputs can be ANDed together to comprise one P-term. All 48 P-terms can be selectively ORed to each output.

The PLS100 and PLS101 are fully TTL compatible, and chip enable control for expansion of input variables and output inhibit. They feature either Open Collector or Tri-state outputs for ease of expansion of product terms and application in bus-organized systems.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **Input variables: 16**
- **Output functions: 8**
- **Product terms: 48**
- **I/O propagation delay: 50ns (max.)**
- **Power dissipation: 600mW (typ.)**
- **Input loading: −100μA (max.)**
- **Chip Enable input**
- **Output option:**
  - **PLS100: Tri-state**
  - **PLS101: Open-Collector**
- **Output disable function:**
  - **Tri-state: Hi-Z**
  - **Open-Collector: High**

APPLICATIONS

- **CRT display systems**
- **Code conversion**
- **Peripheral controllers**
- **Function generators**
- **Look-up and decision tables**
- **Microprogramming**
- **Address mapping**
- **Character generators**
- **Data security encoders**
- **Fault detectors**
- **Frequency synthesizers**
- **16-bit to 8-bit bus interface**
- **Random logic replacement**

PIN CONFIGURATIONS

N Package


FE† 1
I7 2
I6 3
I5 4
I4 5
I3 6
I2 7
I1 8
I0 9
F7 10
F6 11
F5 12
F4 13
GND 14
28 VCC
27 I8
26 I9
25 I10
24 I11
23 I12
22 I13
21 I14
20 I15
19 CE
18 F0
17 F1
16 F2
15 F3
CD04281S

N = Plastic
†Open or grounded during normal operation.

A Package


F6 11
F7 10
I0 9
I1 8
I2 7
I3 6
I4 5
F5 12
F4 13
GND 14
F3 15
F2 16
F1 17
F0 18
4 I5
3 I6
2 I7
1 FE
28 VCC
27 I8
26 I9
19 CE
20 I15
21 I14
22 I13
23 I12
24 I11
25 I10
TOP VIEW
CD04271S

A = Plastic Leaded Chip Carrier

FUNCTIONAL DIAGRAM


I0
I1
I15
TYPICAL CONNECTION
TYPICAL CONNECTION
S0
S6
S7
F0
F6
F7
P0
P1
P47
CE
LD01480S

LOGIC FUNCTION

TYPICAL PRODUCT TERM:
$Pn = A \cdot \overline{B} \cdot C \cdot D \cdot \ ...$

TYPICAL LOGIC FUNCTION:
AT OUTPUT POLARITY = H
$Z = P0 + P1 + P2 \ ...$

AT OUTPUT POLARITY = L
$Z = \overline{P0 + P1 + P2 +} \ ...$
$Z = \overline{P0} \cdot \overline{P1} \cdot \overline{P2} \cdot \ ...$

NOTES:
1. For each of the 8 outputs, either function Z (Active-High) or $\overline{Z}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. Z, A, B, C, etc. are user defined connections to fixed inputs (I) and output pins (O).

Field-Programmable Logic Array (16 × 48 × 8)

PLS100/PLS101

FPLA LOGIC DIAGRAM


(LOGIC TERMS—P)
I0 9
I1 8
I2 7
I3 6
I4 5
I5 4
I6 3
I7 2
I8 27
I9 26
I10 25
I11 24
I12 23
I13 22
I14 21
I15 20
S0 X0 18 F0
S1 X1 17 F1
S2 X2 16 F2
S3 X3 15 F3
S4 X4 13 F4
S5 X5 12 F5
S6 X6 11 F6
S7 X7 10 F7
19 CE
47 • • • • • • 40 39 • • • • • • 32 31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
LD01450S

NOTES:

1. All AND gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown fuse float to logic "0".
3. ▨ Programmable connection.

ORDERING INFORMATION

DESCRIPTION	TRI-STATE	OPEN-COLLECTOR
28-pin Plastic DIP 600mil-wide	PLS100N	PLS101N
28-pin Plastic Leaded Chip Carrier	PLS100A	PLS101A

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

The PLS100 device is also processed to military requirements for operation over the military temperature range. For specifications and ordering information consult the Signetics Military Data Book.

DC ELECTRICAL CHARACTERISTICS $0°C \leq T_A \leq +75°C$, $4.75V \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[3,4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High (PLS100)[5]	I_{OH} = −2mA	2.4			V
V_{OL}	Low[6]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	25	µA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
$I_{O(OFF)}$	Hi-Z state (PLS100)	$\overline{CE}$ = High, V_{CC} = Max				
		V_{OUT} = 5.5V		1	40	µA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit (PLS100)[4,7]	$\overline{CE}$ = Low, V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[8]	V_{CC} = Max		120	170	mA
Capacitance						
		$\overline{CE}$ = High, V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		17		

Notes on following page.

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[2]	Max	
Propagation delay							
t_{PD}	Input	Output	Input		35	50	ns
t_{CE}	Chip enable	Output	Chip enable		15	30	ns
Disable time							
t_{CD}	Chip disable	Output	Chip enable		15	30	ns

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other conditions above those indicated in the operational and programming specification of the device is not implied.
2. All values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one pin at a time.
5. Measured with V_{IL} applied to $\overline{CE}$ and a logic high stored.
6. Measured with a programmed logic condition for which the output test is at a low logic level. Output sink current is applied through a resistor to V_{CC}.
7. Duration of short circuit should not exceed 1 second.
8. I_{CC} is measured with the chip enable input grounded, all other inputs at 4.5V and the outputs open.

Field-Programmable Logic Array (16 × 48 × 8)

PLS100/PLS101

LOGIC PROGRAMMING

The FPLA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table.

In this Table the logic state or action of variables I, P, and F, associated with each Sum Term S_n, is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

OUTPUT POLARITY – (F)


S
$\overline{F}$

ACTIVE LEVEL	CODE
LOW	L

LS02293S


S
F

ACTIVE LEVEL	CODE
HIGH^{1}	H

LS02304S

"AND" ARRAY – (I)


I
i
$\overline{i}$
P

STATE	CODE
INACTIVE^{1,2}	O

LS02311S


I
i
$\overline{i}$
P

STATE	CODE
I	H

LS02321S


I
i
$\overline{i}$
P

STATE	CODE
$\overline{I}$	L

LS02331S


I
i
$\overline{i}$
P

STATE	CODE
DON'T CARE	—

LS02341S

"OR" ARRAY – (F)


P
S
LS02010S

P_n STATUS	CODE
ACTIVE^{1}	A


P
S
LS02020S

P_n STATUS	CODE
INACTIVE	•

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates P_n.
2. Any gate P_n will be unconditionally inhibited if any one of its (I) link pairs is left intact.

Field-Programmable Logic Array (16 × 48 × 8)

PLS100/PLS101

TEST LOAD CIRCUIT


I_0
V_{CC}
DUT
F_0
F_7
I_{15}
$\overline{CE}$
GND
TC01651S


+5 V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01661S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
t_r
t_f
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the + 1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

TIMING DIAGRAM


INPUT
1.5V
+3.0V
0V
$\overline{CE}$
1.5V
1.5V
+3.0V
0V
t_{CE}
t_{CD}
F_0-F_7
1.5V
1.5V
V_{OH}
V_{OL}
t_{PD}
WF06502S

Read Cycle

TIMING DEFINITIONS

t_{CE}	Delay between beginning of Chip Enable low (with Input valid) and when Data Output becomes valid.
t_{CD}	Delay between when Chip Enable becomes High and Data Output is in off state (Hi-Z or High).
t_{PD}	Delay between beginning of valid Input (with Chip Enable Low) and when Data Output becomes valid.

VIRGIN STATE

The PLS100/101 virgin devices are factory shipped in an unprogrammed state, with all fuses intact, such that:

1. All P_n terms are disabled (inactive).
2. All P_n terms are active on all outputs.
3. All outputs are Active-High.

Field-Programmable Logic Array (16 × 48 × 8)

PLS100/PLS101

FPLA PROGRAM TABLE

PROGAM TABLE ENTRIES

INPUT VARIABLE			OUTPUT FUNCTION		OUTPUT ACTIVE LEVEL	
Im	Im	Don't Care	Prod. Term Present in F_P	Prod. Term Not Present in F_P	Active High	Active Low
H	L	— (dash)	A	• (period)	H	L

NOTE
Enter (—) for unused inputs of used P-terms.

NOTES
1. Entries independent of output polarity.
2. Enter (A) for unused outputs of used P-terms.

NOTES
1. Polarity programmed once only.
2. Enter (H) for all unused outputs.

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # ____________ CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ____________ REV ______ DATE ______

	AND																POLARITY							
	INPUT (I_m)																OR							
																	OUTPUT (F_P)							
TERM	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0																								
1																								
2																								
3																								
4																								
5																								
6																								
7																								
8																								
9																								
10																								
11																								
12																								
13																								
14																								
15																								
16																								
17																								
18																								
19																								
20																								
21																								
22																								
23																								
24																								
25																								
26																								
27																								
28																								
29																								
30																								
31																								
32																								
33																								
34																								
35																								
36																								
37																								
38																								
39																								
40																								
41																								
42																								
43																								
44																								
45																								
46																								
47																								
PIN NO.	20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9	10	11	12	13	15	16	17	18
VARIABLE NAME																								

TB01560S

Signetics

PLS103
Field-Programmable Gate Array (16 × 9 × 9)

Signetics Programmable Logic
Product Specification

Application Specific Products
- **Series 28**

DESCRIPTION

The PLS103 is a bipolar, fuse Programmable Gate Array. The device consists of nine AND/NAND gates which share 16 common inputs. The type of gate is selected by programming the output as Active-High (H) or Active-Low (L). Each of the 16 inputs $I_0 - I_{15}$ can be programmed to provide the True (H), Complement (L), or Don't Care (—) state to each of the nine AND/NAND gates. OR/NOR logic functions can also be implemented by complementing the inputs and outputs via on-chip inverting buffers.

The device is field programmable, which means that custom patterns are immediately available.

The PLS103 includes chip-enable control for output strobing and inhibit. It features Tri-state outputs for ease of expansion of input variables and application in bus-organized systems.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **16 input variables**
- **9 output functions**
- **Chip Enable input**
- **I/O propagation delay: 35ns (max.)**
- **Power dissipation: 600mW (typ.)**
- **Input loading: $-100\mu A$ (max.)**
- **Tri-state outputs**
- **Output disable function: Hi-Z**
- **Fully TTL compatible**

APPLICATIONS

- **Random logic**
- **Address decoders**
- **Code detectors**
- **Peripheral selectors**
- **Fault monitors**
- **Machine state decoders**

PIN CONFIGURATIONS

N Package



I_7 1
I_6 2
I_5 3
I_4 4
I_3 5
I_2 6
I_1 7
I_0 8
F_8 9
F_7 10
F_6 11
F_5 12
F_4 13
GND 14
28 V_{CC}
27 I_8
26 I_9
25 I_{10}
24 I_{11}
23 I_{12}
22 I_{13}
21 I_{14}
20 I_{15}
19 $\overline{CE}$
18 F_0
17 F_1
16 F_2
15 F_3
CD04280S

N = Plastic

A Package



F_6 11
F_7 10
F_8 9
I_0 8
I_1 7
I_2 6
I_3 5
F_5 12
F_4 13
GND 14
F_3 15
F_2 16
F_1 17
F_0 18
4 I_4
3 I_5
2 I_6
1 I_7
28 V_{CC}
27 I_8
26 I_9
19 $\overline{CE}$
20 I_{15}
21 I_{14}
22 I_{13}
23 I_{12}
24 I_{11}
25 I_{10}
TOP VIEW
CD04270S

A = Plastic Leaded Chip Carrier

FUNCTIONAL DIAGRAM



8
7
0
Typical Connection
I_0
I_1
I_{15}
F_0
F_7
F_8
$\overline{CE}$
LD01460S

Fusible Ni-Cr links are initially intact at all array cross-points.

LOGIC FUNCTION

TYPICAL OUTPUT FUNCTIONS:

ACTIVE-HIGH

$X = A \cdot \overline{B} \cdot C \cdot \ldots$

ACTIVE-LOW

$X = \overline{A \cdot \overline{B} \cdot C \cdot \ldots}$

$X = \overline{A} + B + \overline{C} + \ldots$

NOTES:
1. For each of the 9 outputs, either function X (Active-High) or $\overline{X}$ (Active-Low) is available, but not both. The desired output polarity is programmed via the EX-OR gates.
2. X, A, B, C, etc. are user defined connections to fixed inputs (I) and output pins (O).

Field-Programmable Gate Array (16 × 9 × 9)

PLS103

FPGA LOGIC DIAGRAM


(LOGIC GATES—G)
I_0 8
I_1 7
I_2 6
I_3 5
I_4 4
I_5 3
I_6 2
I_7 1
I_8 27
I_9 26
I_{10} 25
I_{11} 24
I_{12} 23
I_{13} 22
I_{14} 21
I_{15} 20
8 7 6 5 4 3 2 1 0
X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
$\overline{CE}$ 19
9 10 11 12 13 15 16 17 18
F_8 F_7 F_6 F_5 F_4 F_3 F_2 F_1 F_0
LD01471S

NOTES:
1. All gate inputs when a blown link float to a logic "1".
2. ▨ Programmable connection.

Field-Programmable Gate Array (16 × 9 × 9)

PLS103

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
28-pin Plastic DIP 600mil-wide	PLS103N
28-pin Plastic Leaded Chip Carrier	PLS103A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input current	−30	+30	mA
I_{OUT}	Output current		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leq T_A \leq +75°C$, $4.75V \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[1]						
V_{IH}	High	V_{CC} = Max	2.0			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[3]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[1]						
		V_{CC} = Min				
V_{OH}	High[5]	I_{OH} = −2mA	2.4			V
V_{OL}	Low[4]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	25	μA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
Output current						
		$\overline{CE}$ = High, V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state	V_{OUT} = 5.5V		1	40	μA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[3,6]	$\overline{CE}$ = Low, V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[7]	V_{CC} = Max		120	170	mA
Capacitance						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		15		

Notes on following page.

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[2]	Max	
Propagation delay							
t_{PD}	Input	Output	Input		20	35	ns
t_{CE}	Chip enable	Output	Chip enable		15	30	ns
Disable time							
t_{CD}	Chip disable	Output	Chip enable		15	30	ns

NOTES:

1. All voltage values are with respect to network ground terminal.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. Test one pin at a time.
4. Measure with a programmed logic condition for which the output under test is at a low logic level. Output sink current is supplied through a resistor to V_{CC}.
5. Measured with V_{IL} applied to $\overline{CE}$ and a logic high at the output.
6. Duration of short circuit should not exceed 1 second.
7. I_{CC} is measured with the outputs open.
8. Stresses above those listed under "Absolute Maximum Ratings " may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other conditions above those listed in the operational and programming specification of the device is not implied.

TEST LOAD CIRCUIT


I_0
VCC
DUT
F_0
F_8
I_{15}
$\overline{CE}$
GND
TC1631SS
VCC
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC01640S

VOLTAGE WAVEFORM


INPUT
1.5V
+3.0V
0V
$\overline{CE}$
1.5V
1.5V
+3.0V
0V
t_{CE}
t_{CD}
$F_0 \sim F_8$
1.5V
1.5V
V_{OH}
V_{OL}
t_{PD}
WF05511S

All inputs: $t_r = t_f = 5ns$ (10% to 90%)

LOGIC PROGRAMMING

In a virgin device all Ni-Cr links are intact.

The FPGA can be programmed by means of Logic programming equipment.

With Logic programming, the AND/EX-OR gate input connections necessary to implement the desired logic function are coded directly from logic equations using the Program Table.

In this table, the logic state of variables I and F associated with each P-term P_n is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

OUTPUT POLARITY – (F)



ACTIVE LEVEL	CODE
HIGH	H

LS02290S


G
$\overline{F}$

ACTIVE LEVEL	CODE
LOW[1]	L

LS02303S

"AND" ARRAY – (I), (P)


I
i
$\overline{i}$
G

STATE	CODE
INACTIVE[1,2]	O

LS02310S


I
i
$\overline{i}$
G

STATE	CODE
I	H

LS02320S


I
i
$\overline{i}$
G

STATE	CODE
I	L

LS02330S


I
i
$\overline{i}$
G

STATE	CODE
DON'T CARE	—

LS02340S

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate G_n will be unconditionally inhibited if both the true and complement fuses of any input (I) are left intact.

VIRGIN STATE

The PLS103 virgin device is factory shipped in an unprogrammed state, with all fuses intact, such that:

1. All P_n terms are disabled (inactive).
2. All P_n terms are active on all outputs.
3. All outputs are Active-Low.

FPGA PROGRAM TABLE

CUSTOMER NAME ______________________

PURCHASE ORDER # ______________________

SIGNETICS DEVICE # ______________________

TOTAL NUMBER OF PARTS ______________________

PROGRAM TABLE # ______________________

THIS PORTION TO BE COMPLETED BY SIGNETICS

CF (XXXX) ______________________

CUSTOMER SYMBOLIZED PART # ______________________

DATE RECEIVED ______________________

COMMENTS ______________________

F_0 (18) __________ = ______________________

F_1 (17) __________ = ______________________

F_2 (16) __________ = ______________________

F_3 (15) __________ = ______________________

F_4 (13) __________ = ______________________

F_5 (12) __________ = ______________________

F_6 (11) __________ = ______________________

F_7 (10) __________ = ______________________

F_8 (9) __________ = ______________________

GATE		**INPUT**															
POLARITY		I_{15}	I_{14}	I_{13}	I_{12}	I_{11}	I_{10}	I_9	I_8	I_7	I_6	I_5	I_4	I_3	I_2	I_1	I_0
F_0																	
F_1																	
F_2																	
F_3																	
F_4																	
F_5																	
F_6																	
F_7																	
F_8																	
PIN NO.		20	21	22	23	24	25	26	27	1	2	3	4	5	6	7	8
VARIABLE NAME																	

NOTES:
1. The FPGA is shipped with all links intact. Thus a background of entries corresponding to states of virgin links exists in the table, shown BLANK for clarity.
2. Unused Inputs are normally programmed Don't Care (—).
3. Unused Gates can be left blank.

PROGRAM TABLE ENTRIES

AND

INACTIVE	0
I	H
$\overline{I}$	L
Don't Care	—

(I)

CONTROL

HIGH	H
LOW	L

(POL.)

LD02260S

Signetics

PLS105
Field-Programmable Logic Sequencer (16 × 48 × 8)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 28

DESCRIPTION

The PLS105 is a bipolar programmable state machine of the Mealy type. It contains logic AND-OR gate arrays with user programmable connections which control the inputs of on-chip State and Output Registers. These consist respectively of 6 Q_P, and 8 Q_F edge-triggered, clocked S/R flip-flops, with an Asynchronous Preset option. All flip-flops are unconditionally preset to "1" during power turn on.

The AND array combines 16 external inputs I_{0-15} with six internal inputs P_{0-5}, which are fed back from the State Registers to form up to 48 transition terms (AND terms). All transition terms can include True, False, or Don't Care states of the controlling variables, and are merged in the OR array to issue next-state and next-output commands to their respective registers on the Low-to-High transition of the Clock pulse. Both True and Complement transition terms can be generated by optional use of the internal input variable (C) from the Complement Array. Also, if desired, the $\overline{\text{Preset}}$ input can be converted to $\overline{\text{Output Enable}}$ function, as an additional user-programmable option.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ni-Cr link)**
- **16 input variables**
- **8 output functions**
- **48 transition terms**
- **6-bit State Register**
- **8-bit Output Register**
- **Transition Complement Array**
- **Positive edge-triggered clocked flip-flops**
- **Programmable Asynchronous Preset or Output Enable**
- **Power-on preset to all "1" of internal registers**
- **f_{MAX} = 13.9MHz**
- **Power dissipation: 600mW (typ.)**
- **TTL compatible**
- **Single +5V supply**
- **Tri-state outputs**

APPLICATIONS

- **Interface protocols**
- **Sequence detectors**
- **Peripheral controllers**
- **Timing generators**
- **Sequential circuits**
- **Elevator controllers**
- **Security locking systems**
- **Counters**
- **Shift registers**

PIN CONFIGURATIONS

N Package


CLK 1
I7 2
I6 3
I5 4
I4 5
I3 6
I2 7
I1 8
I0 9
F7 10
F6 11
F5 12
F4 13
GND 14
28 VCC
27 I8
26 I9
25 I10
24 I11
23 I12
22 I13
21 I14
20 I15
19 PR/OE
18 F0
17 F1
16 F2
15 F3
CD04961S

N = Plastic

A Package


F6 F7 I0 I1 I2 I3 I4
11 10 9 8 7 6 5
F5 12
F4 13
GND 14
F3 15
F2 16
F1 17
F0 18
4 I5
3 I6
2 I7
1 CLK
28 VCC
27 I8
26 I9
19 20 21 22 23 24 25
PR/OE I15 I14 I13 I12 I11 I10
CD04970S

A = Plastic Leaded Chip Carrier

FUNCTIONAL DIAGRAM


LOGIC TERMS
I0
IM
C̄
C
STATE REG.
S Q
(6)
R P
S Q
(8)
R P
P
E
PR/OE
F
CK
OUTPUT REG.
T47
T0
LD02230S

LOGIC FUNCTION

Typical State Transition:


Q2 Q1 Q0
0 1 0
STATE REGISTER
0 0 1
SR
PRESENT STATE
Ā • B̄ • C • . . .
Sn+1
NEXT STATE

SET Q_0: $S_0 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$
$R_0 = 0$

RESET Q_1: $S_1 = 0$
$R_1 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $S_2 = 0$
$R_2 = 0$

TB00900S

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105

PIN DESCRIPTION

PIN NO.	SYMBOL	NAME AND FUNCTION	POLARITY
1	CK	**Clock:** The Clock input to the State and Output Registers. A Low-to-High transition on this line is necessary to update the contents of both registers.	Active-High
2 – 8 20 – 27	I_{1-15}	**Logic Inputs:** The 15 external inputs to the AND array used to program jump conditions between machine states, as determined by a given logic sequence.	Active-High/Low
9	I_0	**Logic/Diagnostic Input:** A 16th external logic input to the AND array, as above, when exercised with standard TTL levels. When I_0 is held at +10V, device outputs F_{0-5} reflect the contents of State Register bits P_{0-5}. The contents of each Output Register remains unaltered.	Active-High/Low
10 – 13 15 – 18	F_{0-7}	**Logic/Diagnostic Outputs:** Eight device outputs which normally reflect the contents of Output Register bits Q_{0-7}, when enabled. When I_0 is held at +10V, $F_{0-5} = (P_{0-5})$, and $F_{6,7}$ = Logic "1".	Active-High
19	PR/$\overline{\text{OE}}$	**Preset or $\overline{\textbf{Output Enable}}$ Input:** A user programmable function:	
		• **Preset:** Provides an Asynchronous Preset to logic "1" of all State and Output Register bits. Preset overrides Clock, and when held High, clocking is inhibited and F_{0-7} are High. Normal clocking resumes with the first full clock pulse following a High-to-Low clock transition, after Preset goes Low.	Active-High (H)
		• $\overline{\textbf{Output Enable}}$**:** Provides an Output Enable function to all output buffers F_{0-7} from the Output Register.	Active-Low (L)

TRUTH TABLE [1, 2, 3, 4, 5, 6]

V_{CC}	OPTION		I_0	CK	S	R	$Q_{P/F}$	F
	PR	$\overline{\text{OE}}$						
+5V	H	■	*	X	X	X	H	H
	L	■	+10V	X	X	X	Q_n	$(Q_P)_n$
	L	■	X	X	X	X	Q_n	$(Q_F)_n$
	■	H	*	X	X	X	Q_n	Hi-Z
	■	L	+10V	X	X	X	Q_n	$(Q_P)_n$
	■	L	X	X	X	X	Q_n	$(Q_F)_n$
	■	L	X	↑	L	L	Q_n	$(Q_F)_n$
	■	L	X	↑	L	H	L	L
	■	L	X	↑	H	L	H	H
	■	L	X	↑	H	H	IND.	IND.
↑	X	X	X	X	X	X	H	■

NOTES:

1. Positive Logic:
   $S/R = T_0 + T_1 + T_2 + \ldots + T_{47}$
   $T_n = C(I_0\ I_1\ I_2 \ldots)\ \overline{(P_0\ P_1 \ldots P_5)}$
2. Either Preset (Active-High) or $\overline{\text{Output Enable}}$ (Active-Low) are available, but not both. The desired function is a user-programmable option.
3. ↑ denotes transition from Low to High level.
4. R = S = High is an illegal input condition.
5. * = H/L/+10V
6. X = Don't Care ($\leqslant$5.5V)

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. PR/$\overline{\text{OE}}$ option is set to PR. Thus, all outputs will be at "1", as preset by initial power-up procedure.
2. All transition terms are disabled (0).
3. All S/R flip-flop inputs are disabled (0).
4. The device can be clocked via a Test Array pre-programmed with a standard test pattern.

   NOTE: The Test Array pattern MUST be deleted before incorporating a user program. This is accomplished automatically when using Signetics qualified programming equipment.

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105

FPLS LOGIC DIAGRAM


(LOGIC TERMS - T)
(OPTION)
19 PR/OE
P
E
I0 9
I1 8
I2 7
I3 6
I4 5
I5 4
I6 3
I7 2
I8 27
I9 26
I10 25
I11 24
I12 23
I13 22
I14 21
I15 20
I
P0
P1
P2
P3
P4
P5
P
C̄
C
C
N
F
S Q R P
18 F0
17 F1
16 F2
15 F3
13 F4
12 F5
11 F6
10 F7
1 CK
47 • • • • • • 40 39 • • • • • • 32 31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
LD02240S

NOTES:
1. All AND inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown link float to logic "0".
3. ▨ Programmable connection.

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
28-pin Plastic DIP 600mil-wide	PLS105N
28-pin Plastic Leaded Chip Carrier	PLS105A

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, $I_{IN} = -12mA$		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				V
V_{OH}	High[5]	$I_{OH} = -2mA$	2.4			
V_{OL}	Low[6]	$I_{OL} = 9.6mA$		0.35	0.45	
Input current						
I_{IH}	High	$V_{IN} = 5.5V$		< 1	25	µA
I_{IL}	Low	$V_{IN} = 0.45V$		−10	−100	
I_{IL}	Low (CK input)	$V_{IN} = 0.45V$		−50	−250	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[7]	$V_{OUT} = 5.5V$		1	40	µA
		$V_{OUT} = 0.45V$		−1	−40	
I_{OS}	Short circuit[4,8]	$V_{OUT} = 0V$	−15		−70	mA
I_{CC}	V_{CC} supply current[9]	V_{CC} = Max		120	180	mA
Capacitance[7]						
		$V_{CC} = 5.0V$				pF
C_{IN}	Input	$V_{IN} = 2.0V$		8		
C_{OUT}	Output	$V_{OUT} = 2.0V$		10		

See Notes on following page.

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IL} applied to $\overline{OE}$ and a logic high stored, or with V_{IH} applied to PR.
6. Measured with a programmed logic condition for which the output is at a low logic level, and V_{IL} applied to PR/$\overline{OE}$ Output sink current is supplied through a resistor to V_{CC}.
7. Measured with V_{IH} applied to PR/$\overline{OE}$.
8. Duration of short circuit should not exceed 1 second.
9. I_{CC} is measured with the PR/$\overline{OE}$ input grounded, all other inputs at 4.5V and the outputs open.

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TO	FROM	LIMITS			UNIT
				Min	Typ[1]	Max	
Pulse width							
t_{CKH}	Clock[2] high	CK −	CK +	25	15		ns
t_{CKL}	Clock low	CK +	CK −	25	15		
$t_{CKP1}B$	Period (without Complement Array)	CK +	CK +	80	40		
$t_{CKP2}B$	Period (with Complement Array)	CK +	CK +	120	60		
t_{PRH}	Preset pulse	PR −	PR +	25	15		
Setup time[3]							
$t_{IS1}A$	Input	CK +	Input ±	60			ns
$t_{IS1}B$	Input	CK +	Input ±	50			
$t_{IS1}C$	Input	CK +	Input ±	42			
$t_{IS2}A$	Input (through Complement Array)	CK +	Input ±	90			
$t_{IS2}B$	Input (through Complement Array)	CK +	Input	80			
$t_{IS2}C$	Input (through Complement Array)	CK +	Input	72			
t_{VS}	Power-on preset	CK −	V_{CC} +	0	−10		
t_{PRS}	Preset	CK −	PR −	0	−10		
Hold time							
t_{IH}	Input	Input ±	CK +	5	−10		ns
Propagation delay							
t_{CKO}	Clock	Output ±	CK +		15	30	ns
t_{OE}	Output enable	Output −	OE −		20	30	
t_{OD}	Output disable	Output +	OE +		20	30	
t_{PR}	Preset	Output +	PR +		18	30	
t_{PPR}	Power-on preset	Output +	V_{CC} +		0	10	
Frequency of operation[3]							
$f_{MAX}C$	Without Complement Array					13.9	MHz
$f_{MAX}C$	With Complement Array					9.8	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% − 90%) ⩽ 30ns.
3. See "Speed vs. OR Loading" diagrams.

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105

TIMING DIAGRAMS


I0-15
1.5V
1.5V
+3V
0V
tIH
tIS
CLK
1.5V
1.5V
1.5V
+3V
0V
tIS
tCKH
tCKL
tCKP
F0-7
1.5V
1.5V
VOH
VOL
tCKO
tOD
OE
1.5V
1.5V
+3V
0V
tOE
WF06851S

Sequential Mode


I0-15
1.5V
+3V
0V
CLK
1.5V
1.5V
1.5V
1.5V
tCKP
+3V
0V
tIS
tCKO
tCKH
tCKL
F0-7
1.5V
1.5V
1.5V
VOH
VOL
tPR
tPRS
tCKO
PR
1.5V
1.5V
1.5V
+3V
0V
tPRH
WF06861S

Asynchronous Preset


VCC
4.5V
+5V
0V
tPPR
F0-7
1.5V
[Fn] = 1
1.5V
[Fn+1]
VOH
VOL
tCKP
tCKO
CLK
1.5V
1.5V
1.5V
+3V
0V
tCKH
tVS
I0-15
1.5V
1.5V
+3V
0V
tIS
tIH
WF06871S

Power-On Preset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP1}	Clock period – when not using Complement Array.
t_{IS1}	Required delay between beginning of valid input and positive transition of Clock.
t_{CKP2}	Clock period – when using Complement Array.
t_{IS2}	Required delay between beginning of valid input and positive transition of Clock, when using optional Complement Array (two passes necessary through the AND Array).
t_{VS}	Required delay between V_{CC} (after power-on) and negative transition of Clock preceding first reliable clock pulse.
t_{PRS}	Required delay between negative transition of Asynchronous Preset and negative transition of Clock preceding first reliable clock pulse.
t_{IH}	Required delay between positive transition of Clock and end of valid Input data.
t_{CKO}	Delay between positive transition of clock and when outputs become valid (with PR/$\overline{OE}$ low).
t_{OE}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{SRE}	Delay between input I_0 transition to Diagnostic Mode and when the Outputs reflect the contents of the State Register.
t_{SRD}	Delay between input I_0 transition to Logic mode and when the Outputs reflect the contents of the Output Register.
t_{PR}	Delay between positive transition of Preset and when Outputs become valid at "1".
t_{PPR}	Delay between V_{CC} (after power-on) and when Outputs become preset at "1".
t_{PRH}	Width of preset input pulse.
f_{MAX}	Maximum clock frequency.

TIMING DIAGRAMS (Continued)


I1-15
1.5V
+3V
0V
+10V
8.0V
8.0V
I0
1.5V
1.5V
+3V
0V
tIH
+3V
1.5V
1.5V
CLK
0V
tIS
tCKH
INTERNAL STATE REG Q0-5
(PS)
(NS)
VOH
VOL
tSRE
tSRD
VOH
(Fn)
1.5V
(Fn+1)
(NS)
1.5V
(Fn+1)
F0-5
VOL
tCKO
OE
0V
WF06881S

Diagnostic Mode

TEST LOAD CIRCUIT


I0
VCC
F0
DUT
F7
I15
CK
GND
PR/OE
TC02341S
+5V
R1
R2
CL
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC02350S

VOLTAGE WAVEFORM


+3.0V
90%
0V
10%
5ns
tr
tf
5ns
+3.0V
90%
10%
0V
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

SPEED VS. "OR" LOADING

The maximum frequency at which the FPLS can be clocked while operating in *sequential mode* is given by:

$$(1/f_{MAX}) = t_{CY} = t_{IS} + t_{CKO}$$

This frequency depends on the number of transition terms T_n used. Having all 48 terms connected in the AND array does not appreciably impact performance; but the number of terms connected to each OR line affects t_{IS}, due to capacitive loading. The effect of this loading can be seen in Figure 1, showing the variation of t_{IS1} with the number of terms connected per OR.

The AC electrical characteristics contain three limits for the parameters t_{IS1} and t_{IS2}. The first, t_{IS1A} is guaranteed for a device with 48 terms connected to any OR line. t_{IS1B} is guaranteed for a device with 32 terms connected to any OR line. And t_{IS1C} is guaranteed for a device with 24 terms connected to any OR line.



OP01261S

Figure 1. t_{IS1} vs. Terms/OR Connected

The three other entries in the AC table, t_{IS2} A, B, and C are corresponding 48, 32, and 24 term limits when using the on-chip Complement Array.

The worst case t_{IS} for a given application can be determined by identifying the OR line with the maximum number of t_n connections. This can be done by referring to the interconnect pattern in the FPLS logic diagram, typically illustrated in Figure 2, or by counting the maximum number of "H" *or* "L" entries in one of the columns of the device Program Table.

This number plotted on the curve in Figure 1 will yield the worst case t_{IS} and, by implication, the maximum clocking frequency for reliable operation.

Note that for maximum speed all UNUSED transition terms should be disconnected from the OR array.



AF01810S

Figure 2. Typical OR Array Interconnect Pattern

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table on the following page.

In this Table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding links, defined as follows:

PRESET/$\overline{OE}$ OPTION – (P/E)


PR/$\overline{OE}$
P
E = 1
LS01810S

OPTION	CODE
PRESET^1	H


PR/$\overline{OE}$
P = 1
E
LS01820S

OPTION	CODE
$\overline{OE}$	L

PROGRAMMING THE PLS105:

The PLS105 has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (state and output register) at a logic High (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all Highs (H) as the present state.

"AND" ARRAY – (I), (P)


I,P
i,p
$\overline{i,p}$
T_n
LS01850S

STATE	CODE
INACTIVE^{1,2}	O


I,P
i,p
$\overline{i,p}$
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\overline{i,p}$
T_n
LS01830S

STATE	CODE
$\overline{I}$, $\overline{P}$	L


I,P
i,p
$\overline{i,p}$
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – (N), (F)


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01890S

ACTION	CODE
INACTIVE^{1,3}	O


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01900S

ACTION	CODE
SET	H


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01870S

ACTION	CODE
RESET	L


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01880S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)


$\overline{c}$
c
T_n
LS01930S

ACTION	CODE
INACTIVE^{1,4}	O


$\overline{c}$
c
T_n
LS01940S

ACTION	CODE
GENERATE	A


$\overline{c}$
c
T_n
LS01910S

ACTION	CODE
PROPAGATE	●


$\overline{c}$
c
T_n
LS01920S

ACTION	CODE
TRANSPARENT	–

NOTES:

1. This is the initial unprogrammed state of all links.
2. Any gate T_n will be unconditionally inhibited if both the true and complement fuses of any input (I,P) are left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105

FPLS PROGRAM TABLE

CUSTOMER NAME ____________________
PURCHASE ORDER # ____________________
SIGNETICS DEVICE # CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________________
TOTAL NUMBER OF PARTS ____________________
PROGRAM TABLE ____________________
REV ____________________
DATE ____________________

PROGRAM TABLE ENTRIES

AND

INACTIVE	0	Cn
GENERATE	A	
PROPAGATE	●	
TRANSPARENT	—	

INACTIVE	0	Im, Ps
I, P	H	
$\overline{I}$, $\overline{P}$	L	
DON'T CARE	—	

OR

INACTIVE	0	Ns, Fr
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

PRESET	H	P/E
$\overline{OE}$	L	

	AND																								OPTION (P/E)													
																									OR													
TERM	Cn	INPUT (Im)																PRESENT STATE (Ps)						REMARKS	NEXT STATE (Ns)						OUTPUT (Fr)							
		15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0		5	4	3	2	1	0	7	6	5	4	3	2	1	0
0																																						
1																																						
2																																						
3																																						
4																																						
5																																						
6																																						
7																																						
8																																						
9																																						
10																																						
11																																						
12																																						
13																																						
14																																						
15																																						
16																																						
17																																						
18																																						
19																																						
20																																						
21																																						
22																																						
23																																						
24																																						
25																																						
26																																						
27																																						
28																																						
29																																						
30																																						
31																																						
32																																						
33																																						
34																																						
35																																						
36																																						
37																																						
38																																						
39																																						
40																																						
41																																						
42																																						
43																																						
44																																						
45																																						
46																																						
47																																						
PIN NO.		20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9														10	11	12	13	15	16	17	18
VARIABLE NAME																																						

LD02251S

NOTES:
1. The FPLS is shipped with all links initially intact. Thus, a background of "0" for all Terms, and an "H" for the P/E option, exits in the table, shown BLANK instead for clarity.
2. Unused Cn Im, and Ps bits are normally programmed Don't Care (–).
3. Unused Transition Terms can be left blank for future code modification, or programmed as (–) for maximum speed.
4. Letters in variable fields are used as identifiers by logic type programmed.

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105

TEST ARRAY

The FPLS may be subjected to AC and DC parametric tests prior to programming via an on-chip test array.

The array consists of test transition terms 48 and 49, factory programmed as shown below.

Testing is accomplished by clocking the FPLS and applying the proper input sequence to I_{0-15} as shown in the test circuit timing diagram.



0
63
$(I_n + F_n)/\bar{F}_n$
$(I_n \cdot F_n)/\bar{F}_n$
$(\bar{I} \cdot \bar{F}_n)/F_n$
$(\bar{I}_n + \bar{F}_n)/F_n$
AF01820S

State Diagram



V_{CC}
+5V
V_{CC}
I_n
CLOCK
I_{0-15}
CK
PR/$\overline{OE}$
P_{0-5}
F_{0-7}
F_r
GND
TC01597S

FPLS Under Test

TEST ARRAY PROGRAM

																								OPTION (P/E)													H
		AND																						OR													
TERM	C	INPUT (Im)																PRESENT STATE (Ps)						NEXT STATE (Ns)						OUTPUT (Fr)							
		15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	A	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	L	L
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H

TB01760S

Test Array Program

Both terms 48 and 49 must be deleted during user programming to avoid interfering with the desired logic function. This is accomplished automatically by any of Signetics' qualified programming equipment.



V_{CC}
4.75V
+5V
0V
T_{VS}
T_{CKH}
T_{CKL}
CK
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
T_{IS1}
T_{IH}
T_{IS2}
T_{IH}
I_{0-15}
1.5V
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
T_{PPR}
T_{CKO}
T_{CKO}
F_{0-7}
1.5V
1.5V
1.5V
3V
0V
STATE REGISTER
HIGH
LOW
WF05377S

Test Circuit Timing Diagram

TEST ARRAY DELETED

																								OPTION (P/E)													H
		AND																						OR													
TERM	C	INPUT (Im)																PRESENT STATE (Ps)						NEXT STATE (Ns)						OUTPUT (Fr)							
		15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	—	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—

TB01750S

Test Array Deleted

Signetics

PLS105A
Field-Programmable Logic Sequencer (16 × 48 × 8)

Signetics Programmable Logic
Product Specification

Application Specific Products
• Series 28

DESCRIPTION

The PLS105A is a bipolar programmable state machine of the Mealy type. It contains logic AND-OR gate arrays with user programmable connections which control the inputs of on-chip State and Output Registers. These consist respectively of 6 Q_P, and 8 Q_F edge-triggered, clocked S/R flip-flops, with an Asynchronous Preset option. All flip-flops are unconditionally preset to "1" during power turn on.

The AND array combines 16 external inputs I_{0-15} with 6 internal inputs P_{0-5}, which are fed back from the State Registers to form up to 48 Transition terms (AND terms). All Transition terms can include True, False, or Don't Care states of the controlling variables, and are merged in the OR array to issue next-state and next-output commands to their respective registers on the Low-to-High transition of the Clock pulse. Both True and Complement Transition terms can be generated by optional use of the internal input variable (C) from the Complement Array. Also, if desired, the Preset input can be converted to $\overline{\text{Output-Enable}}$ function, as an additional user programmable option.

Order codes are contained on the pages following.

FEATURES

- Field-Programmable (Ni-Cr link)
- 16 input variables
- 8 output functions
- 48 transition terms
- 6-bit State Register
- 8-bit Output Register
- Transition complement array
- Positive edge-triggered clocked flip-flops
- Programmable Asynchronous Preset or Output Enable
- Power-on preset to all "1" of internal registers
- f_{MAX} = 20MHz
- Power dissipation: 600mW (typ.)
- TTL compatible
- Single +5V supply
- Tri-state outputs

APPLICATIONS

- Interface protocols
- Sequence detectors
- Peripheral controllers
- Timing generators
- Sequential circuits
- Elevator controllers
- Security locking systems
- Counters
- Shift registers

PIN CONFIGURATIONS

N Package


CLK 1
I7 2
I6 3
I5 4
I4 5
I3 6
I2 7
I1 8
I0 9
F7 10
F6 11
F5 12
F4 13
GND 14
28 VCC
27 I8
26 I9
25 I10
24 I11
23 I12
22 I13
21 I14
20 I15
19 PR/OE
18 F0
17 F1
16 F2
15 F3
CD04960S

N = Plastic

A Package


F6 F7 I0 I1 I2 I3 I4
11 10 9 8 7 6 5
F5 12
F4 13
GND 14
F3 15
F2 16
F1 17
F0 18
4 I5
3 I6
2 I7
1 CLK
28 VCC
27 I8
26 I9
19 20 21 22 23 24 25
PR/OE I15 I14 I13 I12 I11 I10
CD04970S

A = Plastic Leaded Chip Carrier

FUNCTIONAL DIAGRAM


LOGIC TERMS
I0
IM
C̄
C
STATE REG.
S Q
(6)
R P
S Q
(8)
R P
OUTPUT REG.
P
E
PR/OE
F
CK
T47
T0
LD02231S

LOGIC FUNCTION

Typical State Transition:


Q2 Q1 Q0
0 1 0
S_R
PRESENT STATE
STATE REGISTER
A̅ • B̅ • C • . . .
0 0 1
S_n+1
NEXT STATE

SET Q_0: $S_0 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$R_0 = 0$

RESET Q_1: $S_1 = 0$
$R_1 = (\overline{Q}_2 \bullet Q_1 \bullet \overline{Q}_0) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $S_2 = 0$
$R_2 = 0$

TB00900S

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105A

PIN DESCRIPTION

PIN NO.	SYMBOL	NAME AND FUNCTION	POLARITY
1	CK	**Clock:** The Clock input to the State and Output Registers. A Low-to-High transition on this line is necessary to update the contents of both registers.	Active-High
2 – 8 20 – 27	I_{1-15}	**Logic Inputs:** The 15 external inputs to the AND array used to program jump conditions between machine states, as determined by a given logic sequence.	Active-High/Low
9	I_0	**Logic/Diagnostic Input:** A 16th external logic input to the AND array, as above, when exercised with standard TTL levels. When I_0 is held at +10V, device outputs F_{0-5} reflect the contents of State Register bits P_{0-5}. The contents of each Output Register remains unaltered.	Active-High/Low
10 – 13 15 – 18	F_{0-7}	**Logic/Diagnostic Outputs:** Eight device outputs which normally reflect the contents of Output Register bits Q_{0-7}, when enabled. When I_0 is held at +10V, $F_{0-5} = (P_{0-5})$, and $F_{6,7}$ = Logic "1".	Active-High
19	PR/$\overline{\text{OE}}$	**Preset or $\overline{\text{Output Enable}}$ Input:** A user programmable function:	
		• **Preset:** Provides an Asynchronous Preset to logic "1" of all State and Output Register bits. Preset overrides Clock, and when held High, clocking is inhibited and F_{0-7} are High. Normal clocking resumes with the first full clock pulse following a High-to-Low clock transition, after Preset goes Low.	Active-High (H)
		• **$\overline{\text{Output Enable}}$:** Provides an output enable function to buffers F_{0-7} from the Output Register.	Active-Low (L)

TRUTH TABLE [1, 2, 3, 4, 5, 6]

V_{CC}	OPTION		I_0	CK	S	R	$Q_{P/F}$	F
	PR	$\overline{\text{OE}}$						
+5V	H		*	X	X	X	H	H
	L		+10V	X	X	X	Q_n	$(Q_P)_n$
	L		X	X	X	X	Q_n	$(Q_F)_n$
		H	*	X	X	X	Q_n	Hi-Z
		L	+10V	X	X	X	Q_n	$(Q_P)_n$
		L	X	X	X	X	Q_n	$(Q_F)_n$
		L	X	↑	L	L	Q_n	$(Q_F)_n$
		L	X	↑	L	H	L	L
		L	X	↑	H	L	H	H
		L	X	↑	H	H	IND.	IND.
↑	X	X	X	X	X	X	H	

NOTES:

1. Positive Logic:
   $S/R = T_0 + T_1 + T_2 + \ldots + T_{47}$
   $T_n = C(I_0\ I_1\ I_2 \ldots)\ (P_0\ P_1 \ldots P_5)$
2. Either Preset (Active-High) or $\overline{\text{Output Enable}}$ (Active-Low) are available, but not both. The desired function is a user-programmable option.
3. ↑ denotes transition from Low to High level.
4. R = S = High is an illegal input condition.
5. * = H/L/+10V
6. X = Don't Care (⩽5.5V)

VIRGIN STATE

A factory shipped virgin device contains all fusible links intact, such that:

1. PR/$\overline{\text{OE}}$ option is set to PR. Thus, all outputs will be at "1", as preset by initial power-up procedure.
2. All transition terms are disabled (0).
3. All S/R flip-flop inputs are disabled (0).
4. The device can be clocked via a Test Array pre-programmed with a standard test pattern.

   NOTE: The Test Array pattern MUST be deleted before incorporating a user program. This is accomplished automatically when using any of Signetics' qualified programming equipment.

Field-Programmable Logic Sequencer (16 × 48 × 8)

PLS105A

FPLS LOGIC DIAGRAM


(LOGIC TERMS - T)
(OPTION)
19 PR/$\overline{OE}$
P
E
I_0 9
I_1 8
I_2 7
I_3 6
I_4 5
I_5 4
I_6 3
I_7 2
I_8 27
I_9 26
I_{10} 25
I_{11} 24
I_{12} 23
I_{13} 22
I_{14} 21
I_{15} 20
P
P_0
P_1
P_2
P_3
P_4
P_5
C
$\overline{C}$
C
N
F
S Q
R P
18 F_0
17 F_1
16 F_2
15 F_3
13 F_4
12 F_5
11 F_6
10 F_7
1 CK
47 • • • • • • 40 39 • • • • • • 32 31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
LD02240S

NOTES:
1. All AND gate inputs with a blown link float to a logic "1".
2. All OR gate inputs with a blown fuse float to logic "0".
3. ▨ Programmable connection.

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
28-pin Plastic DIP 600mil-wide	PLS105AN
28-pin Plastic Leaded Chip Carrier	PLS105AA

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leqslant T_A \leqslant 75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, I_{IN} = −12mA		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High[5]	I_{OH} = −2mA	2.4			V
V_{OL}	Low[6]	I_{OL} = 9.6mA		0.35	0.45	
Input current						
I_{IH}	High	V_{IN} = 5.5V		< 1	25	µA
I_{IL}	Low	V_{IN} = 0.45V		−10	−100	
I_{IL}	Low (CK input)	V_{IN} = 0.45V		−50	−250	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state[7]	V_{OUT} = 5.5V		1	40	µA
		V_{OUT} = 0.45V		−1	−40	
I_{OS}	Short circuit[4,8]	V_{OUT} = 0V	−15		−70	mA
I_{CC}	V_{CC} supply current[9]	V_{CC} = Max		120	180	mA
Capacitance[7]						
		V_{CC} = 5.0V				
C_{IN}	Input	V_{IN} = 2.0V		8		pF
C_{OUT}	Output	V_{OUT} = 2.0V		10		

See Notes on following page.

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Measured with V_{IL} applied to $\overline{OE}$ and a logic high stored, or with V_{IH} applied to PR.
6. Measured with a programmed logic condition for which the output is at a low logic level, and V_{IL} applied to PR/$\overline{OE}$ Output sink current is supplied through a resistor to V_{CC}.
7. Measured with V_{IH} applied to PR/$\overline{OE}$.
8. Duration of short circuit should not exceed 1 second.
9. I_{CC} is measured with the PR/$\overline{OE}$ input grounded, all other inputs at 4.5V and the outputs open.

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0°C \leqslant T_A \leqslant +75°C$, $4.75V \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETERS	TO	FROM	LIMITS			UNIT
				Min	Typ[1]	Max	
Pulse width							
t_{CKH}	Clock[2] high	CK −	CK +	25	15		ns
t_{CKL}	Clock low	CK +	CK −	25	15		
$t_{CKP1}B$	Period (without Complement Array)	CK +	CK +	50	40		
$t_{CKP2}B$	Period (with Complement Array)	CK +	CK +	80	50		
t_{PRH}	Preset pulse	PR −	PR +	25	15		
Setup time[3]							
$t_{IS1}A$	Input	CK +	Input ±	40			ns
$t_{IS1}B$	Input	CK +	Input ±	30			
$t_{IS2}A$	Input (through Complement Array)	CK +	Input ±	70			
$t_{IS2}B$	Input (through Complement Array)	CK +	Input	60			
t_{VS}	Power-on preset	CK −	V_{CC} +	0	−10		
t_{PRS}	Preset	CK −	PR −	0	−10		
Hold time							
t_{IH}	Input	Input ±	CK +	5	−10		ns
Propagation delay							
t_{CKO}	Clock	Output ±	CK +		15	20	ns
t_{OE}	Output enable	Output −	OE −		20	30	
t_{OD}	Output disable	Output +	OE +		20	30	
t_{PR}	Preset	Output +	PR +		18	30	
t_{PPR}	Power-on preset	Output +	V_{CC} +		0	10	
Frequency of operation							
$f_{MAX}B$	Without Complement Array					20	MHz
$f_{MAX}B$	With Complement Array					12.5	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
2. To prevent spurious clocking, clock rise time (10% − 90%) ⩽ 30ns.
3. See "Speed vs. OR Loading" diagrams.

TIMING DIAGRAMS


I0-15
1.5V
1.5V
+3V
0V
tIH
tIS
CLK
1.5V
1.5V
1.5V
tIS
tCKH
tCKL
tCKP
F0-7
1.5V
1.5V
VOH
VOL
tCKO
tOD
OE
1.5V
1.5V
tOE
WF06851S

Sequential Mode


I0-15
1.5V
+3V
0V
tCKP
CLK
1.5V
1.5V
1.5V
1.5V
tIS
tCKO
tCKH
tCKL
F0-7
1.5V
1.5V
1.5V
VOH
VOL
tPR
tPRS
tCKO
PR
1.5V
1.5V
1.5V
tPRH
WF06861S

Asynchronous Preset


VCC
4.5V
+5V
0V
tPPR
F0-7
1.5V
[Fn]= 1
1.5V
[Fn+1]
VOH
VOL
tCKP
tCKO
CLK
1.5V
1.5V
1.5V
+3V
0V
tCKH
tVS
I0-15
1.5V
1.5V
tIS
tIH
WF06871S

Power-On Preset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP}	Clock period — when not using Complement Array.
t_{IS1}	Required delay between beginning of valid input and positive transition of Clock.
t_{CKP2}	Clock period — when using Complement Array.
t_{IS2}	Required delay between beginning of valid Input and positive transition of Clock, when using optional Complement Array (two passes necessary through the AND Array).
t_{VS}	Required delay between V_{CC} (after power-on) and negative transition of Clock preceding first reliable clock pulse.
t_{PRS}	Required delay between negative transition of Asynchronous Preset and negative transition of Clock preceding first reliable clock pulse.
t_{IH}	Required delay between positive transition of Clock and end of valid Input data.
t_{CKO}	Delay between positive transition of Clock and when Outputs become valid (with PR/$\overline{OE}$ low).
t_{OE}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{SRE}	Delay between input I_0 transition to Diagnostic Mode and when the Outputs reflect the contents of the State Register.
t_{SRD}	Delay between input I_0 transition to Logic mode and when the Outputs reflect the contents of the Output Register.
t_{PR}	Delay between positive transition of Preset and when Outputs become valid at "1".
t_{PPR}	Delay between V_{CC} (after power-on) and when Outputs become preset at "1".
t_{PRH}	Width of preset input pulse.
f_{MAX}	Maximum clock frequency.

TIMING DIAGRAMS (Continued)


I1-15
1.5V
+3V
0V
+10V
8.0V
8.0V
I0
1.5V
1.5V
+3V
0V
tIH
+3V
1.5V
1.5V
CLK
0V
tIS
tCKH
INTERNAL STATE REG Q0-5
(PS)
(NS)
VOH
VOL
tSRE
tSRD
VOH
(Fn)
1.5V
(Fn+1)
(NS)
1.5V
(Fn+1)
F0-5
VOL
tCKO
OE
0V
WF06881S

Diagnostic Mode

TEST LOAD CIRCUIT


I0
VCC
F0
DUT
F7
I15
CK
GND
PR/OE
TC02341S


+5V
R1
R2
CL
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC02350S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
5ns
tr
tf
5ns
+3.0V
0V
90%
10%
5ns
5ns
WF05390S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

SPEED VS. "OR" LOADING

The maximum frequency at which the FPLS can be clocked while operating in *sequential mode* is given by:

$$(1/f_{MAX}) = t_{CY} = t_{IS} + t_{CKO}$$

This frequency depends on the number of transition terms T_n used. Having all 48 terms connected in the AND array does not appreciably impact performance; but the number of terms connected to each OR line affects $t_{IS,}$ due to capacitive loading. The effect of this loading can be seen in Figure 1, showing the variation of t_{IS1} with the number of terms connected per OR.

The AC electrical characteristics contain two limits for the parameters t_{IS1} and t_{IS2}. The first, t_{IS1A} is guaranteed for a device with 24 terms connected to any OR line. t_{IS1B} is guaranteed for a device with 16 terms connected to any OR line.

The two other entries in the AC table, t_{IS2} A and B are corresponding 24 and 16 term limits when using the on-chip Complement array.



OP01251S

Figure 1. t_{IS1} vs. Terms/OR Connected

The worst case of t_{IS} for a given application can be determined by identifying the OR line with the maximum number of T_n connections. This can be done by referring to the interconnect pattern in the FPLS logic diagram, typically illustrated in Figure 2, or by counting the maximum number of "H" *or* "L" entries in one of the columns of the device Program Table.

This number plotted on the curve in Figure 1 will yield the worst case t_{IS} and, by implication, the maximum clocking frequency for reliable operation.

Note that for maximum speed all UNUSED transition terms should be disconnected from the OR array.



AF01810S

Figure 2. Typical OR Array Interconnect Pattern

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table of the following page.

In this Table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding links, defined as follows:

PRESET/$\overline{OE}$ OPTION – (P/E)


PR/$\overline{OE}$
P
E = 1
LS01810S

OPTION	CODE
PRESET^{1}	H


PR/$\overline{OE}$
P = 1
E
LS01820S

OPTION	CODE
$\overline{OE}$	L

PROGRAMMING THE PLS105A:

The PLS105A has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (state and output register) at a logic High (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all Highs (H) as the present state.

"AND" ARRAY – (I), (P)


I,P
i,p
$\overline{i,p}$
T_n
LS01850S

STATE	CODE
INACTIVE^{1,2}	O


I,P
i,p
$\overline{i,p}$
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\overline{i,p}$
T_n
LS01830S

STATE	CODE
$\overline{I}$, $\overline{P}$	L


I,P
i,p
$\overline{i,p}$
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – (N), (F)


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01890S

ACTION	CODE
INACTIVE^{1,3}	O


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01900S

ACTION	CODE
SET	H


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01870S

ACTION	CODE
RESET	L


T_n
n,f
$\overline{n,f}$
S
R
Q
LS01880S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)


$\overline{c}$
c
T_n
LS01930S

ACTION	CODE
INACTIVE^{1,4}	O


$\overline{c}$
c
T_n
LS01940S

ACTION	CODE
GENERATE	A


$\overline{c}$
c
T_n
LS01910S

ACTION	CODE
PROPAGATE	•


$\overline{c}$
c
T_n
LS01920S

ACTION	CODE
TRANSPARENT	–

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates T_n.
2. Any gate T_n will be unconditionally inhibited if both the true and complement fuses of any input (I,P) are left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105A

FPLS PROGRAM TABLE

CUSTOMER NAME ____________________
PURCHASE ORDER # ____________________
SIGNETICS DEVICE # CF (XXXX)
CUSTOMER SYMBOLIZED PART # ____________________
TOTAL NUMBER OF PARTS ____________________
PROGRAM TABLE ____________________
REV ____________________
DATE ____________________

PROGRAM TABLE ENTRIES

AND

INACTIVE	0	Cn
GENERATE	A	
PROPAGATE	●	
TRANSPARENT	—	

INACTIVE	0	Im, Ps
I, P	H	
$\bar{I}$, $\bar{P}$	L	
DON'T CARE	—	

OR

INACTIVE	0	Ns, Fr
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

PRESET	H	P/E
$\overline{OE}$	L	

AND																									OPTION (P/E)													
																									OR													
TERM	Cn	INPUT (Im)																PRESENT STATE (Ps)						REMARKS	NEXT STATE (Ns)						OUTPUT (Fr)							
		15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0		5	4	3	2	1	0	7	6	5	4	3	2	1	0
0																																						
1																																						
2																																						
3																																						
4																																						
5																																						
6																																						
7																																						
8																																						
9																																						
10																																						
11																																						
12																																						
13																																						
14																																						
15																																						
16																																						
17																																						
18																																						
19																																						
20																																						
21																																						
22																																						
23																																						
24																																						
25																																						
26																																						
27																																						
28																																						
29																																						
30																																						
31																																						
32																																						
33																																						
34																																						
35																																						
36																																						
37																																						
38																																						
39																																						
40																																						
41																																						
42																																						
43																																						
44																																						
45																																						
46																																						
47																																						
PIN NO.		20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9														10	11	12	13	15	16	17	18
VARIABLE NAME																																						

LD02251S

NOTES:
1. The FPLS is shipped with all links initially intact. Thus, a background of "0" for all Terms, and an "H" for the P/E option, exits in the table, shown BLANK instead for clarity.
2. Unsed C_n, I_m, and P_s bits are normally programmed Don't Care (–).
3. Unused Transition Terms can be left blank for future code modification, or programmed as (–) for maximum speed.
4. Letters in variable fields are used as identifiers by logic type programmers.

Field-Programmable Logic Sequencer (16 × 48 × 8) PLS105A

TEST ARRAY

The FPLS may be subjected to AC and DC parametric tests prior to programming via an on-chip test array.

The array consists of test transition terms 48 and 49, factory programmed as shown below.

Testing is accomplished by clocking the FPLS and applying the proper input sequence to I_{0-15} as shown in the test circuit timing diagram.


0
63
$(I_n + F_n)/\bar{F}_n$
$(I_n \cdot F_n)/\bar{F}_n$
$(\bar{I} \cdot \bar{F}_n)/F_n$
$(\bar{I}_n + \bar{F}_n)/F_n$
AF01820S

State Diagram


V_{CC} +5V
V_{CC}
I_n
CLOCK
I_{0-15}
CK
PR/$\overline{OE}$
P_{0-5}
F_{0-7}
F_r
GND
TC01597S

FPLS Under Test

TEST ARRAY PROGRAM

TERM	C	AND																						OPTION (P/E): H OR													
		INPUT (Im)																PRESENT STATE (Ps)						NEXT STATE (Ns)						OUTPUT (Fr)							
		15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	A	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	L	L
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H

TB01760S

Test Array Program

Both terms 48 and 49 must be deleted during user programming to avoid interfering with the desired logic function. This is accomplished automatically by any of Signetics' qualified programming equipment.


V_{CC}
4.75V
+5V
0V
CK
T_{VS}
T_{CKH}
T_{CKL}
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
I_{0-15}
T_{IS1}
T_{IH}
T_{IS2}
T_{IH}
1.5V
1.5V
1.5V
1.5V
V_{IH}
V_{IL}
F_{0-7}
T_{PPR}
T_{CKO}
T_{CKO}
1.5V
1.5V
1.5V
3V
0V
STATE REGISTER
HIGH
LOW
WF05377S

Test Circuit Timing Diagram

TEST ARRAY DELETED

TERM	C	AND																						OPTION (P/E): H OR													
		INPUT (Im)																PRESENT STATE (Ps)						NEXT STATE (Ns)						OUTPUT (Fr)							
		15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	7	6	5	4	3	2	1	0
48	—	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—
49	●	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—

TB01750S

Test Array Deleted

Signetics

PLUS405A
Field-Programmable Logic Sequencer (16 × 64 × 8)

Signetics Programmable Logic
Preliminary Specification

Application Specific Products
• Series 28

DESCRIPTION

The PLUS405A is a bipolar, programmable state machine of the Mealy type. Both the AND and the OR array are user programmable. All 64 AND gates are connected to the 16 external dedicated inputs ($I_0 - I_{15}$) and to the feedback paths of the 8 on-chip State Registers ($Q_{P0} - Q_{P7}$). Both true and complement transition terms can be generated via optional use of the two internal Complement Arrays (input variables C_0, C_1).

All transition terms can include True, False and Don't Care states of the controlling state variables. All AND gates are merged into the programmable OR array to issue the next-state and next-output commands to their respective registers. Because the OR array is programmable, any one or all of the 64 transition terms can be connected to any or all of the State and Output Registers.

All state ($Q_{P0} - Q_{P7}$) and output ($Q_{F0} - Q_{F7}$) registers are edge-triggered, clocked J-K flip-flops, with Asynchronous Preset and Reset options. The PLUS405A architecture provides the added flexibility of the J-K toggle function which is indeterminate on S-R flip-flops. Each register may be individually programmed such that a specific Preset-Reset pattern is initialized when the initialization pin is raised to a logic level "1". (Note: Upon power-up, all registers are unconditionally preset to "1"). If desired, the initialization input pin (INIT) can be converted to an Output Enable ($\overline{OE}$) function as an additional user programmable feature.

Availability of two user programmable clocks allows the user to design an independent counter or state machine function that can be used to control the bank of output registers.

Order codes are contained on the pages following.

FEATURES

- **Field-Programmable (Ti-W fusible link)**
- **16 input variables**
- **8 output functions**
- **64 transition terms**
- **8-bit State Register**
- **8-bit Output Register**
- **2 Transition complement array term**
- **Multiple clocks**
- **Programmable Asynchronous Preset/Reset or $\overline{\text{Output Enable}}$**
- **Power-on preset to "1" of registers**
- **f_{MAX} = 40MHz**
- **950mW power dissipation (typ.)**
- **TTL compatible**
- **J-K or S-R flip-flop functions**
- **Tri-state outputs**
- **Functional superset of PLS105/105A**

APPLICATIONS

- **Interface protocols**
- **Sequence detectors**
- **Peripheral controllers**
- **Timing generators**
- **Sequential circuits**
- **Elevator controllers**
- **Security locking systems**
- **Counters**
- **Shift registers**

LOGIC FUNCTION

Typical State Transition:


Q2 Q1 Q0
0 1 0
STATE REGISTER
0 0 1
S_R
PRESENT STATE
$\overline{A} \bullet \overline{B} \bullet C \bullet \ldots$
S_{n+1}
NEXT STATE

SET Q_0: $S_0 = (\overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

$R_0 = 0$

RESET Q_1: $S_1 = 0$
$R_1 = (\overline{Q_2} \bullet Q_1 \bullet \overline{Q_0}) \bullet \overline{A} \bullet \overline{B} \bullet C \ldots$

HOLD Q_2: $S_2 = 0$
$R_2 = 0$

TB00900S

PIN CONFIGURATIONS

N Package


CLK 1
I_7 2
I_6/CLK 3
I_5 4
I_4 5
I_3 6
I_2 7
I_1 8
I_0 9
F_7 10
F_6 11
F_5 12
F_4 13
GND 14
28 V_{CC}
27 I_8
26 I_9
25 I_{10}
24 I_{11}
23 I_{12}
22 I_{13}
21 I_{14}
20 I_{15}
19 INIT/$\overline{OE}$
18 F_0
17 F_1
16 F_2
15 F_3
TOP VIEW
CD11462S

NOTE:
N = Plastic

A Package


F_6 F_7 I_0 I_1 I_2 I_3 I_4
11 10 9 8 7 6 5
F_5 12
F_4 13
GND 14
F_3 15
F_2 16
F_1 17
F_0 18
4 I_5
3 I_6/CLK
2 I_7
1 CLK
28 V_{CC}
27 I_8
26 I_9
19 20 21 22 23 24 25
INIT/$\overline{OE}$ I_{15} I_{14} I_{13} I_{12} I_{11} I_{10}
CD04972S

NOTE:
A = Plastic Leaded Chip Carrier

Field-Programmable Logic Sequencer (16 × 64 × 8)

PLUS405A

PIN DESCRIPTION

PIN NO.	SYMBOL	NAME AND FUNCTION	POLARITY
1	CK	**Clock:** The Clock input to the State and Output Registers. A Low-to-High transition on this line is necessary to update the contents of both registers.	Active – High (H)
2, 4 – 9, 26 – 27 21 – 22	$I_0 - I_5$, I_7 $I_8 - I_9$ $I_{13} - I_{14}$	**Logic Inputs:** The 11 external inputs to the AND array used to program jump conditions between machine states, as determined by a given logic sequence.	Active – High/Low (H/L)
3	I_6/CK	**Logic Input/Clock:** A user programmable function: • **Logic Input:** A 12th external logic input to the AND array, as above.	Active – High/Low (H/L)
		• **Clock:** A 2nd clock for the State Registers, as above. The Output Registers continue to be clocked off of Pin 1. If two separate State Machines are designed, setup and hold times must be adhered to in order to synchronize both banks of registers. Note that input buffer I_6 must be deleted from the AND array (i.e. all fuse locations "Don't Care") when using Pin 3 as a Clock.	Active – High (H)
20	I_{15}	**High Fan-Out Logic Input:** A 13th external logic input to the AND array, as above. I_{15} is capable of pulling down all 64 Product Terms by itself.	Active – High/Low (H/L)
23	I_{12}	**Logic/Diagnostic Input:** A 14th external logic input to the AND array, as above, when exercising standard TTL levels. When I_{12} is held at +10V, device outputs $F_0 - F_7$ reflect the contents of State Register bits $P_0 - P_7$. The contents of each Output Register remains unaltered.	Active – High/Low (H/L)
24	I_{11}	**Logic/Diagnostic Input:** A 15th external logic input to the AND array, as above, when exercising standard TTL levels. When I_{11} is held at +10V, device outputs $F_0 - F_7$ become direct inputs for State Register bits $P_0 - P_7$; a Low-to-High transition on the appropriate clock line loads the values on pins $F_0 - F_7$ into the State Register bits $P_0 - P_7$. The contents of each Output Register remains unaltered.	Active – High/Low (H/L)
25	I_{10}	**Logic/Diagnostic Input:** A 16th external logic input to the AND array, as above, when exercising standard TTL levels. When I_{10} is held at +10V, device outputs $F_0 - F_7$ become direct inputs for Output Register bits $Q_0 - Q_7$; a Low-to-High transition on the appropriate clock line loads the values on pins $F_0 - F_7$ into the Output Register bits $Q_0 - Q_7$. The contents of each State Register remains unaltered.	Active – High/Low (H/L)
10 – 13 15 – 18	$F_0 - F_7$	**Logic Outputs/Diagnostic Outputs/Diagnostic Inputs:** Eight device outputs which normally reflect the contents of Output Register Bits $Q_0 - Q_7$, when enabled. When I_{12} is held at +10V, $F_0 - F_7 = (P_0 - P_7)$. When I_{11} is held at +10V, $F_0 - F_7$ become inputs to State Register bits $P_0 - P_7$. When I_{10} is held at +10V, $F_0 - F_7$ become inputs to Output Register bits $Q_0 - Q_7$.	Active – High (H)
19	INIT/$\overline{\text{OE}}$	**Initialization or $\overline{\textbf{Output Enable}}$ Input:** **A user programmable function:** • **Initialization:** Provides an asynchronous preset to logic "1" or reset to logic "0" of all State and Output Register bits, determined individually for each register bit through user programming. INIT overrides Clock, and when held HIGH, clocking is inhibited and $F_0 - F_7$ are in their initialization state. Normal clocking resumes with the first full clock pulse following a High-to-Low clock transition, after INIT goes low.	Active – High (H)
		• **Output Enable:** Provides an output enable function to buffers $F_0 - F_7$ from the Output Registers.	Active – Low (L)

Field-Programmable Logic Sequencer (16 × 64 × 8)

PLUS405A

TRUTH TABLE 1, 2, 3, 4, 5, 6, 7

V_{CC}	OPTION		I_{10}	I_{11}	I_{12}	CK	J	K	Q_P	Q_F	F
	INIT	$\overline{OE}$									
+5V	H		*	*	*	X	X	X	H/L	H/L	Q_F
	L		+10V	X	X	↑	X	X	Q_P	L	L^9
	L		+10V	X	X	↑	X	X	Q_P	H	H^9
	L		X	+10V	X	↑	X	X	L	Q_F	L^9
	L		X	+10V	X	↑	X	X	H	Q_F	H^9
	L		X	X	+10V	X	X	X	Q_P	Q_F	Q_P
	L		X	X	X	X	X	X	Q_P	Q_F	Q_F
		H	X	X	*	X	X	X	Q_P	Q_F	Hi-Z
		X	+10V	X	X	↑	X	X	Q_P	L	L^9
		X	+10V	X	X	↑	X	X	Q_P	H	H^9
		X	X	+10V	X	↑	X	X	L	Q_F	L^9
		X	X	+10V	X	↑	X	X	H	Q_F	H^9
		L	X	X	+10V	X	X	X	Q_P	Q_F	Q_P
		L	X	X	X	X	X	X	Q_P	Q_F	Q_F
		L	X	X	X	↑	L	L	Q_P	Q_F	Q_F
		L	X	X	X	↑	L	H	L	L	L
		L	X	X	X	↑	H	L	H	H	H
		L	X	X	X	↑	H	H	$\overline{Q_P}$	$\overline{Q_F}$	$\overline{Q_F}$
↑	X	X	X	X	X	X	X	X	X	X	H

NOTES:

1. Positive Logic:
   $S/R \text{ (or } J/K) = T_0 + T_1 + T_2 + \ldots T_{63}$
   $T_n = (C_0, C_1)(I_0, I_1, I_2, \ldots) (P_0, P_1, \ldots P_7)$
2. Either Initialization (Active – High) or $\overline{\text{Output Enable}}$ (Active – Low) are available, but not both. The desired function is a user-programmable option.
3. ↑ denotes transition from Low-to-High level.
4. * = H/L/+10V
5. X = Don't Care (≤ 5.5V)
6. H/L implies that either a High or a Low can occur, depending upon user programmed selection (each State and Output Register individually programmable).
7. When using the F_n pins as inputs to the State and Output Registers in diagnostic mode, the F buffers are tri-stated and the indicated levels on the output pins are forced by the user.

VIRGIN STATE

A factory-shipped virgin device contains all fusible links intact, such that:

1. INIT/$\overline{OE}$ option is set to INIT. In order to use the INIT function, the user must select either the PRESET or the RESET option for each flip-flop. Note that regardless of the user programmed initialization, or even if the INIT function is not used, all registers are preset to "1" by the power-up procedure.
2. All transition terms are disabled (0).
3. All S/R (or J/K) flip-flop inputs are disabled (0).
4. The device can be clocked via a Test Array preprogrammed with a standard test pattern. NOTE: The Test Array pattern must be deleted before incorporating a user program.

Field-Programmable Logic Sequencer (16 × 64 × 8)

PLUS405A

FUNCTIONAL DIAGRAM


P63
P0
I
15
I/CK
X2
S or J Q
X8
R or K
P R
8
8
CK
S or J
X8
R or K Q
P R
F
8
8
8
INIT/OE
LD06860S

Field-Programmable Logic Sequencer (16 × 64 × 8)

PLUS405A

FPLS LOGIC DIAGRAM


I0 9
I1 8
I2 7
I3 6
I4 5
I5 4
I6/CLK 3
I7 2
I8 27
I9 26
I10 25
I11 24
I12 23
I13 22
I14 21
I15 20
19 INIT/$\overline{OE}$
DETAIL A
P0
P1
P2
P3
P4
P5
P6
P7
$\overline{C}_1$
$\overline{C}_0$
C0
C1
DETAIL B
DETAIL C
18 F0
17 F1
16 F2
15 F3
13 F4
12 F5
11 F6
10 F7
1 CLK
DETAIL D
LD06872S

DETAILS FOR REGISTERS FOR PLUS405A


19
INIT/OE
LD06880S

Detail A



Detail D


TO INIT LINE
TO AND ARRAY
STATE REGISTERS
P_s
S or J
Q
Pre
R or K
Re
CLK
LD06890S

Detail B


TO INIT LINE
OUTPUT REGISTERS
S or J
Q
F_n
Pre
R or K
Re
CLK
LD06900S

Detail C

ORDERING INFORMATION

DESCRIPTION	ORDER CODE
28-Pin Plastic DIP 600mil-wide	PLUS405AN
28-Pin Plastic Leaded Chip Carrier	PLUS405AA

THERMAL RATINGS

TEMPERATURE	
Maximum junction	150°C
Maximum ambient	75°C
Allowable thermal rise ambient to junction	75°C

ABSOLUTE MAXIMUM RATINGS[1]

SYMBOL	PARAMETER	RATING		UNIT
		Min	Max	
V_{CC}	Supply voltage		+7	V_{DC}
V_{IN}	Input voltage		+5.5	V_{DC}
V_{OUT}	Output voltage		+5.5	V_{DC}
I_{IN}	Input currents	−30	+30	mA
I_{OUT}	Output currents		+100	mA
	Temperature range			
T_A	Operating	0	+75	°C
T_{STG}	Storage	−65	+150	

DC ELECTRICAL CHARACTERISTICS $0°C \leq T_A \leq +75°C$, $4.75 \leq V_{CC} \leq 5.25V$

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Min	Typ[2]	Max	
Input voltage[3]						
V_{IH}	High	V_{CC} = Max	2			V
V_{IL}	Low	V_{CC} = Min			0.8	
V_{IC}	Clamp[4]	V_{CC} = Min, $I_{IN} = -12mA$		−0.8	−1.2	
Output voltage[3]						
		V_{CC} = Min				
V_{OH}	High	$I_{OH} = -2mA$	2.4			V
V_{OL}	Low	$I_{OL} = 9.6mA$		0.35	0.45	
Input current						
I_{IH}	High	$V_{IN} = 5.5V$		< 1	25	µA
I_{IL}	Low	$V_{IN} = 0.45V$		−10	−100	
I_{IL}	Low (CK input)	$V_{IN} = 0.45V$		−50	−250	
Output current						
		V_{CC} = Max				
$I_{O(OFF)}$	Hi-Z state	$V_{OUT} = 5.5V$		1	40	µA
		$V_{OUT} = 0.45V$		−1	−40	
I_{OS}	Short circuit[4,5]	$V_{OUT} = 0V$	−15		−70	mA
I_{CC}	V_{CC} supply current[6]	V_{CC} = Max		190	225	mA
Capacitance						
		$V_{CC} = 5.0V$				
C_{IN}	Input	$V_{IN} = 2.0V$		8		pF
C_{OUT}	Output	$V_{OUT} = 2.0V$		10		

NOTES:

1. Stresses above those listed under "Absolute Maximum Ratings" may cause malfunction or permanent damage to the device. This is a stress rating only. Functional operation at these or any other condition above those indicated in the operational and programming specification of the device is not implied.
2. All typical values are at $V_{CC} = 5V$, $T_A = +25°C$.
3. All voltage values are with respect to network ground terminal.
4. Test one at a time.
5. Duration of short circuit should not exceed 1 second.
6. I_{CC} is measured with the INIT/$\overline{OE}$ input grounded, all other inputs at 4.5V and the outputs open.

AC ELECTRICAL CHARACTERISTICS $R_1 = 470\Omega$, $R_2 = 1k\Omega$, $C_L = 30pF$, $0^\circ C \leqslant T_A \leqslant +75^\circ C$, $4.75^\circ CV \leqslant V_{CC} \leqslant 5.25V$

SYMBOL	PARAMETERS	TO	FROM	LIMITS			UNIT
				Min	Typ[1]	Max	
Pulse width							
t_{CKH}	Clock high	CK−	CK+	10	8		ns
t_{CKL}	Clock low	CK+	CK−	10	8		
t_{CKP1}	Period (without Complement Array)	CK+	CK+	20	15		
t_{CKP2}	Period (with Complement Array)	CK+	CK+	30	25		
t_{INITH}	Initialization pulse	INIT+	INIT−	10	8		
Setup time[2]							
t_{IS1}	Input	CK+	Input±	15	12		ns
t_{IS2}	Input (through Complement Array)	CK+	Input±	25	20		
t_{VS}	Power-on preset	CK−	V_{CC}+	0	−10		
t_{INITS}	Initialization	CK−	INIT−	0	−10		
Hold time							
t_{IH}	Input	Input±	CK+	0	−5		ns
Propagation delay							
t_{CKO}	Clock	Output±	CK+		8	10	ns
t_{OE}	Output enable	Output−	OE−		12	15	
t_{OD}	Output disable	Output+	OE+		12	15	
t_{INIT}	Initialization	Output+	INIT+		15	20	
t_{PPR}	Power-on preset	Output+	V_{CC}+		0	10	
Frequency of operation							
f_{MAX}	Without Complement Array					40	MHz
f_{MAX}	With Complement Array					28.5	

NOTES:

1. All typical values are at $V_{CC} = 5V$, $T_A = +25^\circ C$.
2. Product term loading considerations: Connecting more than 8 toggle-mode registers to only one product term by itself may compromise the setup time performance. Product term loading restrictions do not apply if toggle mode functions are not used.

Field-Programmable Logic Sequencer (16 × 64 × 8)

PLUS405A

TIMING DIAGRAMS


I0-15
1.5V
1.5V
+ 3V
0V
tIH
tIS
1.5V
1.5V
1.5V
+3V
CLK
0V
tIS
tCKH
tCKL
tCKP
VOH
F0-7
1.5V
1.5V
tCKO
VOL
tOD
+3V
OE
1.5V
1.5V
0V
tOE
WF06851S

Sequential Mode


I0 - I15
1.5V
+3V
0V
tCKP
+3V
CLK
1.5V
1.5V
1.5V
1.5V
0V
tIS
tCKO
tCKH
tCKL
VOH
F0-7
1.5V
1.5V
1.5V
VOL
tINIT
tINITS
tCKO
+3V
INIT
1.5V
1.5V
1.5V
0V
tINITH
WF18181S

Asynchronous Initialization


4.5V
+5V
VCC
0V
tPPR
VOH
1.5V
(Fn) = 1
1.5V
(Fn+1)
F0-7
VOL
tCKO
tCKP
+3V
1.5V
1.5V
1.5V
CLK
0V
tCKH
tVS
+3V
1.5V
1.5V
I0-15
0V
tIS
tIH
WF06871S

Power-On Preset

TIMING DEFINITIONS

t_{CKH}	Width of input clock pulse.
t_{CKL}	Interval between clock pulses.
t_{CKP}	Clock period — when not using Complement Array.
t_{IS1}	Required delay between beginning of valid input and positive transition of Clock.
t_{CKP2}	Clock period — when using Complement Array.
t_{IS2}	Required delay between beginning of valid Input and positive transition of Clock, when using optional Complement Array (two passes necessary through the AND Array).
t_{VS}	Required delay between V_{CC} (after power-on) and negative transition of Clock preceding first reliable clock pulse.
t_{INITS}	Required delay between negative transition of Asynchronous Initialization and negative transition of Clock preceding first reliable clock pulse.
t_{IH}	Required delay between positive transition of Clock and end of valid Input data.
t_{CKO}	Delay between positive transition of Clock and when Outputs become valid (with INIT/$\overline{OE}$ low).
t_{OE}	Delay between beginning of Output Enable Low and when Outputs become valid.
t_{OD}	Delay between beginning of Output Enable High and when Outputs are in the off state.
t_{SRE}	Delay between input I_{12} transition to Diagnostic Mode and when the Outputs reflect the contents of the State Register.
t_{SRD}	Delay between input I_{12} transition to Logic mode and when the Outputs reflect the contents of the Output Register.
t_{INIT}	Delay between positive transition of Initialization and when Outputs become valid.
t_{PPR}	Delay between V_{CC} (after power-on) and when Outputs become preset at "1".
t_{INITH}	Width of initialization input pulse.
t_{RH}	Required delay between positive transition of Clock and end of valid Input data when jaming data into State or Output Registers in diagnostic mode.
t_{RJS}	Required delay between inputs I_{11} or I_{10} transition to State and Output Register Input Jam Diagnostic Modes, respectively, and when the ouput pins become available as inputs.
t_{RJH}	Required delay between positive transition of Clock and end of inputs I_{11} or I_{10} transition to State and Output Register Input Jam Diagnostic Modes, respectively.
f_{MAX}	Maximum clock frequency.

TIMING DIAGRAMS (Continued)


$I_0 - I_{11}$, $I_{13} - I_{15}$
1.5V
+3V
0V
+10V
I_{12}
1.5V
1.5V
8.0V
8.0V
+3V
0V
t_{IH}
CLK
1.5V
1.5V
+3V
0V
t_{IS}
t_{CKH}
INTERNAL STATE REG.
$Q_0 - Q_7$
(P_S)
(N_S)
V_{OH}
V_{OL}
t_{SRE}
t_{SRD}
$F_0 - F_7$
(F_n)
1.5V
(F_{n+1})
1.5V
(N_S)
1.5V
(F_{n+1})
V_{OH}
V_{OL}
t_{CKO}
$\overline{OE}$
0V
WF18191S

Diagnostic Mode — State Register Outputs


I_{11}
8.0V
8.0V
+10V
+3V
0V
t_{RJS}
t_{RJH}
$F_0 - F_7$ (INPUTS)
1.5V (FORCED D_{IN}) 1.5V
+3V
0V
t_{RH}
CLK
1.5V
1.5V
+3V
0V
t_{IS}
t_{CKH}
Q_P STATE REG.
(D_{IN})
V_{OH}
V_{OL}
t_{CKO}
WF18200S

Diagnostic Mode — State Register Input Jam


I_{10}
8.0V
8.0V
+10V
+3V
0V
t_{RJS}
t_{RJH}
$F_0 - F_7$ (INPUTS)
1.5V (FORCED D_{IN}) 1.5V
+3V
0V
t_{RH}
CLK
1.5V
1.5V
+3V
0V
t_{IS}
t_{CKH}
Q_F STATE REG.
(D_{IN})
V_{OH}
V_{OL}
t_{CKO}
WF18210S

Diagnostic Mode — Output Register Input Jam

TEST LOAD CIRCUIT


I_0
V_{CC}
F_0
DUT
F_7
I_{15}
CK
GND PR/$\overline{OE}$
TC02340S
+5V
R_1
R_2
C_L
(INCLUDES SCOPE AND JIG CAPACITANCE)
TC02350S

VOLTAGE WAVEFORM


+3.0V
0V
90%
10%
t_r
t_f
2.5ns
2.5ns
+3.0V
0V
90%
10%
2.5ns
2.5ns
WF05391S

MEASUREMENTS:
All circuit delays are measured at the +1.5V level of inputs and outputs, unless otherwise specified.

Input Pulses

Field-Programmable Logic Sequencer (16 × 64 × 8)

PLUS405A

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table of the following page.

In this table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

INITIALIZATION/$\overline{OE}$ OPTION – (IN/E)


INIT/$\overline{OE}$
INIT
E=1
LS01812S

OPTION	CODE
INITIALIZATION[1]	H


INIT/$\overline{OE}$
INIT=1
E
LS01822S

OPTION	CODE
$\overline{OE}$	L

PROGRAMMING THE PLUS405A:

The PLUS405A has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (State and Output Register) at a logic High (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all Highs (H) as the present state.

PRESET/RESET OPTION – (P/R)


P R
INIT
LD06910S

ACTION	CODE
INDETERMINATE[5]	O


P R
INIT
LD06911S

ACTION	CODE
PRESET	H


P R
INIT
LD06912S

ACTION	CODE
RESET	L


P R
INIT
LD06913S

ACTION	CODE
INDETERMINATE[5]	–

"AND" ARRAY – (I), (P)


I,P
i,p
$\overline{i},p$
T_n
LS01850S

STATE	CODE
INACTIVE[1,2]	O


I,P
i,p
$\overline{i},p$
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\overline{i},p$
T_n
LS01830S

STATE	CODE
$\overline{I}$, $\overline{P}$	L


I,P
i,p
$\overline{i},p$
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – J-K FUNCTION – (N), (F)


T_n
N,F
$\overline{N},F$
J Q
K
LD06920S

ACTION	CODE
TOGGLE [7]	O


T_n
N,F
$\overline{N},F$
J Q
K
LD06921S

ACTION	CODE
SET	H


T_n
N,F
$\overline{N},F$
J Q
K
LD06922S

ACTION	CODE
RESET	L


T_n
N,F
$\overline{N},F$
J Q
K
LD06923S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)



ACTION	CODE
INACTIVE[1,4]	O



ACTION	CODE
GENERATE	H



ACTION	CODE
PROPAGATE	•



ACTION	CODE
TRANSPARENT	–

CLOCK OPTION – (CLK1/CLK2)



OPTION	CODE
CLK1	L



OPTION	CODE
CLK2[6]	H

NOTES:

1. This is the initial unprogrammed state of all links. It is normally associated with all unused (inactive) AND gates T_n.
2. Any gate T_n will be unconditionally inhibited if any one of its I or P link pairs is left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.
5. These states are not allowed when using PRESET/RESET option.
6. Input buffer I_6 must be deleted from the AND array (i.e. all fuse locations "Don't Care") when using second clock option.
7. A single product term cannot drive more than 8 registers by itself when used in TOGGLE mode.

Field-Programmable Logic Sequencer (16 × 64 × 8)

PLUS405A

PLUS405A FPLS PROGRAM TABLE

CUSTOMER NAME ____________________

SIGNETICS DEVICE # CF (XXXX)

CUSTOMER SYMBOLIZED PART # ____________________

REV ______________ DATE ______________

PROGRAM TABLE ____________________

AND

INACTIVE	0	Cn
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	

INACTIVE	0	Im, Ps
I, P	H	
$\overline{I}$, $\overline{P}$	L	
DON'T CARE	—	

OR

INACTIVE OR TOGGLE	0	Ns, Fr
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

INIT	H	INIT/$\overline{OE}$
$\overline{OE}$	L	

	AND																										OR															
																			CLOCK 1/2								INITIALIZATION/OUTPUT ENABLE															
	COMP ARRAY		INPUT (Im)																PRESENT STATE (Ps)								NEXT STATE (Ns)								OUTPUT (Fr)							
	C1	C0	I15	I14	I13	I12	I11	I10	I9	I8	I7	I6	I5	I4	I3	I2	I1	I0	P7	P6	P5	P4	P3	P2	P1	P0	N7	N6	N5	N4	N3	N2	N1	N0	F7	F6	F5	F4	F3	F2	F1	F0
0																																										
1																																										
2																																										
3																																										
4																																										
5																																										
6																																										
7																																										
8																																										
9																																										
10																																										
11																																										
12																																										
13																																										
14																																										
15																																										
16																																										
17																																										
18																																										
19																																										
20																																										
21																																										
22																																										
23																																										
24																																										
25																																										
26																																										
27																																										
28																																										
29																																										
30																																										
31																																										
32																																										
33																																										
34																																										
35																																										
36																																										
37																																										
38																																										
39																																										
40																																										
41																																										
42																																										
43																																										
44																																										
45																																										
46																																										
47																																										
48																																										
49																																										
50																																										
51																																										
52																																										
53																																										
54																																										
55																																										
56																																										
57																																										
58																																										
59																																										
60																																										
61																																										
62																																										
63																																										
PIN NO.			20	21	22	23	24	25	26	27	2	3	4	5	6	7	8	9																	10	11	12	13	15	16	17	18
PIN LABELS																																										

TB03141S

NOTES:
1. The FPLS is shipped with all links initially intact. Thus, a background of "0" for all Terms, and an "H" for the IN/E and H for the clock option, exits in the table, shown BLANK instead for clarity.
2. Unused C_n I_m, and P_s bits are normally programmed Don't Care (—).
3. Unused Transition Terms can be left blank for future code modification, or programmed as (—) for maximum speed.

Signetics

Application Specific Products

Section 7
Military Errata

Effective October 1986, this section has been superseded by the Military Products Data Manual. Information regarding this manual can be obtained from the Military Division in Sacramento, (916) 925-6700.

Electrical specifications herein do not necessarily describe the performance characterization of military processed products.

Signetics

Application Specific Products

Section 8

INDEX

Section 8 – Development Software

AMAZE – Automatic Map and Zap Equations Design Software 8-3

AMAZE

Programmable Logic Development Software

SOFTWARE SUPPORT FOR USER PROGRAMMABLE LOGIC

Computer Aided Design (CAD) support is becoming necessary to address the time-consuming details required by the more complex programmable logic devices available today. The design effort can include the manipulation of Boolean equations, truth tables, state diagrams, flowcharts etc, to create the binary fuse map required to program such devices.

For many years, design engineers have used programmable read-only memories (PROM's) to replace conventional logic. The architecture of the PROM can be described as a programmable logic device containing a **fixed** AND array followed by a **programmable** OR array. The fixed structure of the PROM requires a full assignment of output words to be programmed for every input combination. Therefore, little use can be made of programmable logic software programs for logic minimization or other compiling efforts when using PROM's.

Signetics Programmable Logic Devices are the most advanced approach to solving the inherent limitations of PROM's. Their architecture consists of a **programmable** AND array, followed by a **programmable** OR array - with the addition of a **programmable** invert function for flexible output control.

A Signetics PLD device can implement **any** set of Boolean expressions, provided that they are first put into the standard sum of products form. The logical AND's are implemented at the first gate level of the programmable logic device and the logical OR's are implemented by the second gate level within the PLD. The only limitations on the expressions are those imposed by the number of inputs, outputs, and internal product terms provided by the particular PLD circuit selected. The efficiency of implementing the set of equations can be increased significantly by applying DeMorgan's theorem, and utilizing the programmable invert function on each output.

If there seems to be too few product terms to handle a relatively large equation set, one of several minimization methods can be pursued.

The probability of reducing such equations to manageable size is enhanced through the flexibility of shared AND terms for each output function, the accessibility of all AND terms to each output, and having a programmable invert function on each output. All of these features can be utilized by applying the manual manipulation of Venn Diagrams or Karnaugh Maps. However, the time and effort to accomplish these tasks as well as document the effort for procurement specification purposes increase the need and desire to have software programs to automatically perform such manipulations.

Many types of software programs are being developed to provide this assistance for operation on a wide range of computer hardware. This list of software is expanding rapidly, consisting of both Signetics generated software and some independent software houses' contributions.

This discussion is intended to outline the Signetics developed software program called AMAZE (**A**utomatic **M**ap **A**nd **Z**ap **E**quation **E**ntry) The AMAZE software program currently consists of five modules, BLAST ('**B**oolean **L**ogic **A**nd **S**tate **T**ransfer' entry program), PTP ('**P**AL **T**o **P**LD' conversion program), DPI ('**D**evice **P**rogrammer **I**nterface' program), PLD SIM ('**PLD Sim**ulator'' program) and the PTE ('**P**rogram **T**able **E**ditor' program). Other modules will be added when product developments require additional software tools.

It must be noted that the AMAZE program is not by any means the total extent of software available for use in designing with PLD (Programmable Logic Devices). Please contact your local Signetics representative for the latest word on the most currently available software.

Programmable Logic Development Software

AMAZE

Description

Automatic **M**ap **A**nd **Z**ap **E**quation **E**ntry software program. The AMAZE software program consists of the following five modules:

- **BLAST** ('**B**oolean **L**ogic **A**nd **S**tate **T**ransfer' entry program)
- **PTE** ('**P**rogram **T**able **E**ditor')
- **PTP** ('**P**AL **T**o **P**LD' conversion program)
- **DPI** ('**D**evice **P**rogrammer **I**nterface' program)
- **PLD SIM** ('**PLD Sim**ulator' program)

Each module performs specific tasks as outlined in the following sections.

Features

- **Multiple modules allowing expansion for future requirements**
- **Each module designed to be user friendly**
- **Both HELP and ERROR messages**
- **Document printout: Header, Pin diagram, Boolean equation and Fuse map**
- **Interface with most commercial programmers**
- **SIMULATOR programs provide both test and applications assistance**

Equipment

- **The PC version of AMAZE is capable of operating on an IBM-PC with MS-DOS operating system and having 512K bytes of on-board RAM**
- **The VAX version of AMAZE is capable of operating on a VAX computer with VMS operating system**

Please contact your Signetics Sales Representative for availability and ordering information.

Products Supported

AMAZE will support the following products:

- **20-pin PLDs:**
  - **PLS151**
  - **PLS153**
  - **PLS153A**
  - **PLHS153**
  - **PLUS153**
  - **PLS155**
  - **PLS157**
  - **PLS159**
  - **PLS159A**
  - **PLHS18P8A**
- **24-pin PLDs:**
  - **PLS161**
  - **PLS162**
  - **PLS163**
  - **PLS167**
  - **PLS167A**
  - **PLS168**
  - **PLS168A**
  - **PLS173**
  - **PLUS173**
  - **PLS179**
  - **PLHS473**
  - **PLC473**
- **28-pin PLDs:**
  - **PLS100**
  - **PLS101**
  - **PLS103**
  - **PLS105**
  - **PLS105A**
  - **PLC105**
  - **PLUS405A**
- **52-pin PLDs:**
  - **PLHS501**
  - **PLHS502**

Programmable Logic Development Software

AMAZE

BLAST

Boolean **L**ogic **A**nd **S**tate **T**ransfer program is a menu driven software package that supports the engineer in implementing logic designs into Signetics Programmable Logic Devices. It checks design data and automatically compiles a program table from Boolean and State Machine equations. Data from the program table is then used to produce a **S**tandard **F**ile which contains the fusing codes in a form acceptable to all the AMAZE modules (i.e. PLD-SIM and DPI).

BLAST reports the logic and syntax errors, and lists the equations in a Sum of Products form, which can help the user to minimize the entered logic equations. It will automatically partition State machine designs into specified devices, and then delete redundant terms during compilation.

BLAST also provides the capability of modifying a current logic set programmed into a device by overlaying new data onto unused fuses.

BOOLEAN LOGIC AND STATE TRANSFER FEATURES

- **User friendly interactive pinlist editor**
- **Boolean equation or state vector entry**
- **Schematic entry (with external schematic capture package)****
- **On-line error checking, minimization, and design overlay**
- **Capable of partitioning single designs into multiple PLDs**
- **Generates standard PLD fusemap files**
- **Supports all Signetics' PLDs and PLEs**
- **User definable device files for support of PALs and other PLD devices**

PTE

Program **T**able **E**ntry is an interactive editor which allows the logic designer to enter data into AMAZE in the form of SIGNETICS APPROVED PROGRAM TABLES. Each Signetics PLD data sheet has the program table format which applies to that device. In addition, PTE can be used to document completed designs and to make changes in logic functions which have been previously defined in the BLAST module.

PROGRAM TABLE EDITOR FEATURES

- **Allows easy creation and editing of new and existing PLD designs**
- **Truth-table representation of PLD fusemap in High/Low format**
- **On-line editor provides automatic cursor control and prevents syntax errors**
- **On-line help screen and print facility**
- **Operates on standard PLD fusemap files**

PTP

PAL™ **T**o **P**LD is a conversion program to allow easy transfer of the various PAL 20 and 24 pin circuits to the Signetics PLD 20 and 24 pin series devices.

PTP can automatically upload the PAL™ pattern from a Commercial programmer, convert the pattern into a PLD pattern, and then download the PLD pattern into the programmer. The PAL™ pattern and it's corresponding PLD pattern are documented, and the PLD pattern can be directed to other AMAZE modules.

PTP can also convert the PAL™ fuse file in a HEXPLOT format.

PAL-TO-PLD CONVERSION FEATURES

- **Menu-driven fusemap conversion of 20- and 24-pin PALs to pin and functional equivalent Signetics' PLDs**
- **Automatic assembler removes duplicated p-terms providing efficient PLD mapping**
- **Accepts JEDEC, fuseplot files or direct PAL master input via commercial PLD programmer**
- **User selectable RS-232 programmable interface parameters**
- **Provides fusemap conversion documentation**
- **Generates standard PLD fusemap files compatible with other AMAZE modules**

DPI

Device **P**rogrammer **I**nterface is the software module that provides the interface between the Standard File created by the AMAZE modules and a commercial programmer. This module allows both download (Sending from Host to programmer) and upload (Sending from programmer into the host) operations.

DPI supports both JEDEC and Signetics H & L formats to convey fusing information to and from several commercial programmers.

DEVICE PROGRAMMER INTERFACE FEATURES

- **Supports standard JEDEC and Signetics High/Low fusemap file formats**
- **RS-232 interface to commercial PLD programmers**
- **Screen menus for easy upload and download of fusemaps**
- **User selectable RS-232 parameters for programmer flexibility**
- **Test vectors automatically transferred to programmer along with fusemap file**
- **Operates with standard PLD fusemap files**

PLD SIMULATOR

The **PLD Simulator** program is a software package that simulates the operation of the logic that has been defined for Signetics PLD products. The input to the program is the Standard File generated by other AMAZE modules. The simulator has the capability of running manually or automatically. In the automatic mode the simulator creates a file of test vectors that can be used to test the programmed devices. In the manual mode the program will allow the operator to assigned an input vector and observe the resultant output.

PLD FUNCTIONAL SIMULATOR FEATURES

- **Functional simulation of designs created from equations, program tables, or existing programmed devices**
- **Automatic test vector generation from standard or JEDEC PLD fusemap files**
- **Interactive keyboard entry or batch file input of test vectors**
- **Detects illegal State Machine transitions and flags affected p-terms**
- **On-line help screen**

---

*PAL™ and PLE™ are trademarks of Monolithic Memories, Inc.

(** AMAZE accepts TTL schematics generated with DATA-I/O FUTURENET DASH)

AMAZE HARDWARE REQUIREMENTS

P/N	
82SOFT523-SS	IBM-PC or IBM-XT or compatible computer 512K Memory PC-DOS Operating System Version 2.0 or higher. 2 Floppy Disk Drives or 1 Floppy and 1 Hard disk
82SOFT211-SS	VAX Series Computer VMS operating system – all revisions.

AMAZE comes fully documented with appropriate magnetic media. Applications support is provided by Signetics Field Application Engineers in most areas. Contact the Sales Office in your area for information on AMAZE and Signetics Programmable Logic Products.

Section 9
Application Notes

INDEX

Section 9 – Application Notes

AN7	Single Chip Multiprocessor Arbiter	9-3
AN8	Introduction to Signetics Programmable Logic	9-15
AN10	4-Bit Binary-To-7 Segment Decoder	9-27
AN11	PLD Programmable Retriggerable One-Shot	9-51
AN12	Low Cost Programmer for PLD 20-Pin Series	9-55
AN13	Oscillator With PLS159	9-71
AN14	Latches and Flip-Flops With PLS153	9-76
AN15	PLS159 Primer	9-89
AN16	PLS159 as Modulo Counters	9-100
AN17	Electronic Combination Lock	9-107
AN18	Schmitt Trigger Using PLS153 and PLS159	9-110
AN19	Electronic Dice	9-118
AN20	Single Pin Debouncer Using PLS153/159	9-122
AN21	9-Bit Parity Generator/Checker With PLS153/153A	9-125
AN22	PLS151 Toolkit	9-131
AN23	PLS168/168A Primer	9-139
AN24	PLS173 as a 10-Bit Comparator, 74LS460	9-152
AN25	A Simple Entry/Exit Meeting Device (PLS157)	9-158
AN26	PLHS18P8A Primer	9-164
AN27	PLHS473 Primer	9-172
AN28	High-Speed 12-Bit Tracking A/D Converter Using PLS179	9-180
AN29	PLHS501 Programmable Macro Logic Primer	9-190

Signetics

AN7

Single Chip Multiprocessor Arbiter

Application Note

Application Specific Products

INTRODUCTION

In multiprocessor environments there is considerable savings to be made through sharing system resources. If each processor must support its own bus structure, I/O devices, and bulk storage medium, system cost could be very high. In the configuration shown in Figure 1, all processors share a common communication bus, and a number of system resources.

Since every processor must use the common system bus to communicate with its peripherals, a priority structure that resolves simultaneous processor bus requests into a single bus grant must be integrated into the system. In addition to making request-grant transactions, transient bus contention due to grant switching must be removed by inserting precise guard band times between bus grants.

Signetics' Field Programmable Logic Sequencer provides a convenient and cost-effective means for implementing a synchronous arbiter to perform these tasks within a single chip.

ARBITER STRUCTURE

Within a multiprocessor system, two general classes of processors can be recognized: Priority A and Priority b. Priority A processors have the highest request priority and must only compete with other Priority A processors for bus control. The arbiter must issue "A" grants in manner that prevents any high priority "A" processor from locking out another Priority A processor. To enable this, the Priority A rules implemented here use a Last Granted Lowest Priority (LGLP) ring structure. After an "A" processor has completed a bus-related task, its next arbitrated request priority will be lowest in the "A" request group. The previously second highest priority "A" processor will then become highest priority requester. The net effect of the "round robin" exchange is that every Priority A processor will have a turn at being highest priority processor. Priority A processors are typically ones that perform real-time operations or vital system tasks.

Priority b processors are lower in priority than the "A's" and may only be granted system control when no "A" requests are pending. "b" processors usually perform background tasks. Within the Priority b group, further priority ordering exists such that each "b" processor has a fixed priority position.

Plumber[1], Pearce[2], and Hojberg[3] present asynchronous techniques of arbiter implementation. These methods all have hardwired priority rules and imprecise guard band times during grant switching. As pointed out by Hojberg, a synchronous state machine can be configured as a Mealy-type controller to provide not only precise guard band times and programmable priority rules, but also programmable input/output polarity. The state machine in Figure 2 is made from a control PROM array and an edge-triggered latch. The "A" and "b" requests and the machine's present state are used by the control PROM to determine the next "A" and "b" grants and the next state.



Figure 1. Multiprocessor Structure

Single Chip Multiprocessor Arbiter

AN7



BD01490S

a. A and b service requests (R_N, r_N) plus the present state determine, through the control PROM, the next state and the next grant outputs (G_N, g_N).



WF05340S

b. Requests R_0, R_1, r_0, and r_1 are asserted low in the same clock sample period. The priority rules that determine the order in which the grants are issued and the shaded guard-band areas are programmed into the control PROM. Note that the A and b request lines and the present state input to the PROM must have a set-up time equal or greater than the latch set-up time plus the PROM access time.

Figure 2. Arbiter Constructed From A Mealy-Type State Machine

SYSTEM OPERATION

Two machine states can be identified by inspection: a wait state and a grant state. The state machine enters a grant state as a response to a system request on either R_N or r_N. The machine will remain in this state with a single grant line asserted as long as the request remains asserted. Upon releasing the request line, the machine will pass through a single wait state before considering other pending requests. This provides a single state guard band time. The requests received must meet the set-up requirement of the edge-triggered latch after propagating through the control PROM. If these time considerations do not fit within a given multiprocessor structure, an input latch may be added such that the R_N and r_N lines are clocked through the latch by the system clock, thereby removing asynchronous set-up time considerations. On the basis of a state machine approach, two techniques of implementation are feasible: 1) using an architecturally advanced single IC controller, the FPLS, and, 2) a traditional PROM/LATCH configuration.

Single Chip Multiprocessor Arbiter

AN7



BD01480S

a. FPLS Single Chip System

																								OPTION (P/$\overline{E}$)													
		TRANSITION TERM																						OUTPUT TERM													
		INPUT VARIABLE (Im)																PRESENT STATE (Ps)						NEXT STATE (Ns)						OUTPUT FUNCTION (Fn)							
NO.	C	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0																																					
1																																					
2																																					
3																																					
4																																					
5																																					
46																																					
47																																					

TB00800S

b. FPLS Standard Program Table

CK	S	R	Q
↑	0	0	Q
↑	0	1	0
↑	1	0	1
↑	1	1	Undefined

NOTE:
(↑) denotes positive clock transition. S = R = 1 is an illegal input condition.

c. Transition Table of Clocked S/R Flip-Flop

Figure 3

FPLS ARBITER IMPLEMENTATION

A five Priority "A" and three Priority "b" arbiter will be constructed such that all grant outputs will be asserted low for grants and all request inputs will be asserted low for system requests.

Brief FPLS Description

The FPLS block diagram shown in Figure 3(a) consists of a control PLA and 14 clocked S/R flip-flops. The control PLA is actually an AND-OR logic array that functions as a Content Addressable PROM. The PLA is organized as 48 words of 28 bits with 16 external input lines, and six internal inputs fed back from the State Register. The 28 PLA outputs drive the S/R inputs of the six-bit State Register and eight-bit Output Register. Note that the state feedback path is made inside the FPLS.

I_N and present state inputs, P_S, represent 2^{22} possible input codes; 48 of these codes may be mapped in the PLA to provide a 14 bit register control word. As shown in Figure 3(b) each input code may be specified by assigning to the variables either Low "L", High "H", or Don't Care "-" logic states. If any input code falls logically outside the programmed codes, the PLA asserts a Low on all its 28 internal outputs, thereby issuing a "no change" command to the R/S flip-flops.

This is an important architectural feature because it requires that only state or output transition terms be programmed. Looping terms that change neither state nor output need not be programmed in the FPLS, owing to the functional characteristics of S/R flip-flops tabulated in Figure 3(c). An example of this is shown in Figure 4.

The S/R inputs of both state and output registers are specified by using PLA outputs ("AND" functions of request inputs and present state) in the program table of Figure 3(c).

The corresponding next state of each bit will be set to 0 for "L", 1 for "H", and No Change for "-". The FPLS's PR/OE line may be assigned either Asynchronous Preset or Output Enable functions, via a user programmable option.

The entire function is integrated into a single 28-pin package designated as PLS105.

State Algorithm

Figure 5(a) displays the circular state form and all possible state transitions of the LGLP priority structure. Hex states 3F, 3E, 3D, 3C, and 3B are arbiter wait states W_{0-4}. In these states, processor "A" and "b" requests are monitored. Figure 5(b) illustrates a typical grant to processor A_1 in hex state 07. As long as A_1 asserts its request line low, the next state will be 07_{16} and the next output will remain with G_1 asserted low and all the other grant outputs asserted high. Since no change in state or grant output results from this transition, no PLA resources are required.

As soon as processor A_1 returns its request line, R_1, to 1, a state transition is made to 3D, and an output transition is made to set all grant outputs to 1. Since processor A_1 was the last to be granted system resources, it will now have the lowest A level request priority (LGLP). In wait state W_2, the highest priority processor will be A_2, second A_3, third A_4, and fourth A_0. To maintain the LGLP rule, grant transitions must follow the state rule $G_N \rightarrow W_{(N+1)}$, and wait states, W_M, must set their "A" priorities so that processor A_M is highest priority. Priority decreases as one proceeds clockwise around the state ring to the lowest priority processor, $A_{(m-1)}$.

When no "A" requests are pending, "b" requests may be granted. To avoid upsetting the LGLP priority rule, a "b" grant must leave and return to the same wait state. Since the "b" priority structure is the same regardless of the wait state, only a single set of "b" transition terms are required.



NOTE:
T_N/F_N = Inputs/outputs.
The FPLS requires that only two out of the three transition terms be programmed.

Figure 4. FPLS State and Output Transitions

For example, a grant transition to g_2 (Hex 20 – 25) can be issued only if there are no "A", "b_0", or "b_1" requests pending. Given the binary wait state code 111XXX, where "X's" represent Don't Cares, a request code of 01111111 will transfer the arbiter to the grant state g_2 from any of the wait states, W_{0-4}.

It is important to realize that in making this transition, the lower three-state bits will not be changed — they provide the wait state return address. When r_2 returns high, 1XXXXXXX, a transition back to the previously exited wait state is made by forcing a "1" in the three most significant state bits and leaving the lower three-state bits unchanged.

All output and state bits are initially preset to "1" through the use of the optional preset function. Grant output lines are only forced low when transitions are made to grant states and are returned to "1" when jumping back to a wait state.

Table 1 provides the complete arbiter program. The complete arbiter circuit diagram is shown in Figure 6. The AMAZE equations are shown in Figure 7.

PROM/LATCH IMPLEMENTATION

The same five "A" processor and three "b" processor arbiter can be implemented with discrete PROM's and Latches using the same state diagrams for the FPLS, except that now looping transition terms must be programmed. Coding of all state and output transitions requires programming of two memory fields: the "A" request PROM's (2KX6) and the "b" request PROM (64 × 3). The complete circuit diagram is shown in Figure 6(b).

The "A" request PROM's determine the next machine state (N_{0-5}) at all times, except when there are no "A" requests pending and there is a "b" request, or if the machine is presently in a "b" grant state. In these cases, the "b" request PROM controls the machine's next state.

The grant control lines are decoded from the next state lines and latched in two quad output latches. This PROM/LATCH organization is conceptually the same as that shown in Figure 2.


100XXX
g_2
110XXX
g_1
101XXX
g_0
W_{0-4}
111XXX
TYPICAL TRANSITION TERM
$r_2\ r_1\ r_0\ R_4\ R_3\ R_2\ R_1\ R_0$
0XXXXXXX
01111111
1XXXXXXX
r_2
R_0
11111111
AF01780S
a.
3F 111111
W_0
16 010110
G_4
06 000110
G_0
3B 111011
W_4
3E 111110
W_1
0F 001111
G_3
07 000111
G_1
3C 111100
W_3
3D 111101
W_2
0E 001110
G_2
111111
010110
000110
111011
111110
XXX011XX
XXX111X0
XXXXX1X
001111
07 000111
XXXX01XX
XXX11101
111100
001110
3D 111101
XXXXX0XX
AF01770S
b.

Figure 5. Arbiter State Transition Diagram


PRESET
PLS105
FPLS
P
CK
SYSTEM CLOCK
I_7 I_6 I_5 I_4 I_3 I_2 I_1 I_0
F_7 F_6 F_5 F_4 F_3 F_2 F_1 F_0
$\overline{r_2}$ $\overline{r_1}$ $\overline{r_0}$
$\overline{R_4}$ $\overline{R_3}$ $\overline{R_2}$ $\overline{R_1}$ $\overline{R_0}$
$\overline{g_2}$ $\overline{g_1}$ $\overline{g_0}$
$\overline{G_4}$ $\overline{G_3}$ $\overline{G_2}$ $\overline{G_1}$ $\overline{G_0}$
LS01690S
N/C
256X4
"b"
REQUEST
PROM
A_7 A_6 A_5 A_4 A_3 A_2 A_1 A_0
CE
NOTE: ALL RANDOM LOGIC MUST BE SCHOTTKY
+5P
P_5 P_4 P_3 P_2 P_1 P_0
LOW FOR "b" · "$\overline{A}$" REQUEST
HIGH FOR "b" GRANT STATE
G1
G2A
G2B
74S138
Y_7 Y_6 Y_5 Y_4 Y_3 Y_2 Y_1 Y_0
C
B
A
+5V
1K
LD R CK
D C B A
QD QC QB QA
74S161
"A"
REQUEST
PROMS
2KX4
A_{10} A_9 A_8 A_7 A_6 A_5 A_4 A_3 A_2 A_1 A_0
O_4 O_3 O_2 O_1
N_5 N_4 N_3 N_2 N_1 N_0
$\overline{RESET}$
SYSTEM CLOCK
T
P
BD01470S

a.

b.

Figure 6. Arbiter Circuit Diagram Summary

Single Chip Multiprocessor Arbiter

Table 1. FPLS Program Table for Priority Arbiter

No.	TRANSITION TERM																						OUTPUT TERM															
	INPUT VARIABLE (Im)																PRESENT STATE (Ps)						NEXT STATE (Ns)						OUTPUT FUNCTION (Fn)								
	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0	7	6	5	4	3	2	1	0	
0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	L	L	L	H	H	L	H	H	H	H	H	H	H	L	W_0
1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	H	L	L	L	H	H	H	H	H	H	H	H	H	L	H	
2	—	—	—	—	—	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	H	H	L	L	H	H	H	L	H	H	H	H	H	L	H	H	
3	—	—	—	—	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	H	H	H	L	L	H	H	H	H	H	H	H	H	L	H	H	H	
4	—	—	—	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	H	H	H	H	L	H	L	H	H	L	H	H	H	L	H	H	H	H	
5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	L	—	H	H	H	H	H	L	L	L	L	H	H	H	H	H	H	H	H	H	L	H	W_1
6	—	—	—	—	—	—	—	—	—	—	—	—	—	L	H	—	H	H	H	H	H	L	L	L	H	H	H	L	H	H	H	H	H	L	H	H	
7	—	—	—	—	—	—	—	—	—	—	—	—	L	H	H	—	H	H	H	H	H	L	L	L	H	H	H	H	H	H	H	H	L	H	H	H	
8	—	—	—	—	—	—	—	—	—	—	—	L	H	H	H	—	H	H	H	H	H	L	L	H	L	H	H	L	H	H	H	L	H	H	H	H	
9	—	—	—	—	—	—	—	—	—	—	—	H	H	H	H	L	H	H	H	H	H	L	L	L	L	H	H	L	H	H	H	H	H	H	H	L	
10	—	—	—	—	—	—	—	—	—	—	—	—	—	L	—	—	H	H	H	H	L	H	L	L	H	H	H	L	H	H	H	H	H	L	H	H	W_2
11	—	—	—	—	—	—	—	—	—	—	—	—	L	H	—	—	H	H	H	H	L	H	L	L	H	H	H	H	H	H	H	H	L	H	H	H	
12	—	—	—	—	—	—	—	—	—	—	—	L	H	H	—	—	H	H	H	H	L	H	L	H	L	H	H	L	H	H	H	L	H	H	H	H	
13	—	—	—	—	—	—	—	—	—	—	—	H	H	H	—	L	H	H	H	H	L	H	L	L	L	H	H	L	H	H	H	H	H	H	H	L	
14	—	—	—	—	—	—	—	—	—	—	—	H	H	H	L	H	H	H	H	H	L	H	L	L	L	H	H	H	H	H	H	H	H	H	L	H	
15	—	—	—	—	—	—	—	—	—	—	—	—	L	—	—	—	H	H	H	H	L	L	L	L	H	H	H	H	H	H	H	H	L	H	H	H	W_3
16	—	—	—	—	—	—	—	—	—	—	—	L	H	—	—	—	H	H	H	H	L	L	L	H	L	H	H	L	H	H	H	L	H	H	H	H	
17	—	—	—	—	—	—	—	—	—	—	—	H	H	—	—	L	H	H	H	H	L	L	L	L	L	H	H	L	H	H	H	H	H	H	H	L	
18	—	—	—	—	—	—	—	—	—	—	—	H	H	—	L	H	H	H	H	H	L	L	L	L	L	H	H	H	H	H	H	H	H	H	L	H	
19	—	—	—	—	—	—	—	—	—	—	—	H	H	L	H	H	H	H	H	H	L	L	L	L	H	H	H	L	H	H	H	H	H	L	H	H	
20	—	—	—	—	—	—	—	—	—	—	—	L	—	—	—	—	H	H	H	L	H	H	L	H	L	H	H	L	H	H	H	L	H	H	H	H	W_4
21	—	—	—	—	—	—	—	—	—	—	—	H	—	—	—	L	H	H	H	L	H	H	L	L	L	H	H	L	H	H	H	H	H	H	H	L	
22	—	—	—	—	—	—	—	—	—	—	—	H	—	—	L	H	H	H	H	L	H	H	L	L	L	H	H	L	H	H	H	H	H	H	L	H	
23	—	—	—	—	—	—	—	—	—	—	—	H	—	L	H	H	H	H	H	L	H	H	L	L	H	H	H	H	H	H	H	H	H	L	H	H	
24	—	—	—	—	—	—	—	—	—	—	—	H	L	H	H	H	H	H	H	L	H	H	L	L	H	H	H	H	H	H	H	H	L	H	H	H	
25	—	—	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	H	H	—	—	—	H	L	H	—	—	—	H	H	L	H	H	H	H	H	W_{0-4}
26	—	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	H	H	H	—	—	—	H	H	L	—	—	—	H	L	H	H	H	H	H	H	
27	—	—	—	—	—	—	—	—	L	H	H	H	H	H	H	H	H	H	H	—	—	—	H	L	L	—	—	—	L	H	H	H	H	H	H	H	
28	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	H	L	L	L	H	H	L	H	H	H	H	H	L	H	H	H	H	H	H	H	H	G_0
29	—	—	—	—	—	—	—	—	—	—	—	—	—	—	H	—	L	L	L	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	G_1
30	—	—	—	—	—	—	—	—	—	—	—	—	—	H	—	—	L	L	H	H	H	L	H	H	H	H	L	L	H	H	H	H	H	H	H	H	G_2
31	—	—	—	—	—	—	—	—	—	—	—	—	H	—	—	—	L	L	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	G_3
32	—	—	—	—	—	—	—	—	—	—	—	H	—	—	—	—	L	H	L	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	G_4
33	—	—	—	—	—	—	—	—	—	—	H	—	—	—	—	—	H	L	H	—	—	—	H	H	H	—	—	—	H	H	H	H	H	H	H	H	g_0
34	—	—	—	—	—	—	—	—	—	H	—	—	—	—	—	—	H	H	L	—	—	—	H	H	H	—	—	—	H	H	H	H	H	H	H	H	g_1
35	—	—	—	—	—	—	—	—	H	—	—	—	—	—	—	—	H	L	L	—	—	—	H	H	H	—	—	—	H	H	H	H	H	H	H	H	g_2
36																																					
									$\overline{r}_2$	$\overline{r}_1$	$\overline{r}_0$	$\overline{R}_4$	$\overline{R}_3$	$\overline{R}_2$	$\overline{R}_1$	$\overline{R}_0$													$\overline{g}_2$	$\overline{g}_1$	$\overline{g}_0$	$\overline{G}_4$	$\overline{G}_3$	$\overline{G}_2$	$\overline{G}_1$	$\overline{G}_0$	

TB00790S

```
 ********************* ARBITERS *********************
@DEVICE SELECTION
ARBITERB/82S105
@STATE VECTORS
[ FF5, FF4, FF3, FF2, FF1, FF0 ]
W0  = 03Fh ;
W1  = 03Eh ;
W2  = 03Dh ;
W3  = 03Ch ;
W4  = 03Bh ;
W04 = 111---b ;
GA0 = 06h ;
GA1 = 07h ;
GA2 = 0Eh ;
GA3 = 0Fh ;
GA4 = 16h ;
GB0 = 101---b ;
GB1 = 110---b ;
GB2 = 100---b ;

@INPUT VECTORS
@OUTPUT VECTORS
[OB2, OB1, OB0, OA4, OA3, OA2, OA1, OA0]
QA0'  = FEh ;
QA1'  = FDh ;
QA2'  = FBh ;
QA3'  = F7h ;
QA4'  = EFh ;
QB0'  = DFh ;
QB1'  = BFh ;
QB2'  = 7Fh ;
NOGRANT'  = FFh ;

@TRANSITIONS
WHILE [W0]
  CASE
    [/RA0] :: [GA0] WITH [QA0']
    [/RA1 * RA0] :: [GA1] WITH [QA1']
    [/RA2 * RA1 * RA0] :: [GA2] WITH [QA2']
    [/RA3 * RA2 * RA1 * RA0] :: [GA3] WITH [QA3']
    [/RA4 * RA3 * RA2 * RA1 * RA0] :: [GA4] WITH [QA4']
  ENDCASE

WHILE [W1]
  CASE
    [/RA1] :: [GA1] WITH [QA1']
    [/RA2 * RA1] :: [GA2] WITH [QA2']
    [/RA3 * RA2 * RA1] :: [GA3] WITH [QA3']
    [/RA4 * RA3 * RA2 * RA1] :: [GA4] WITH [QA4']
    [/RA0 * RA4 * RA3 * RA2 * RA1] :: [GA0] WITH [QA0']
  ENDCASE
```

TB00750S

a. Arbiter State Equations

Figure 7

```
WHILE [W2]
  CASE
    [/RA2] :: [GA2] WITH [QA2']
    [/RA3 * RA2] :: [GA3] WITH [QA3']
    [/RA4 * RA3 * RA2] :: [GA4] WITH [QA4']
    [/RA0 * RA4 * RA3 * RA2] :: [GA0] WITH [QA0']
    [/RA1 * RA0 * RA4 * RA3 * RA2] :: [GA1] WITH [QA1']
  ENDCASE

WHILE [W3]
  CASE
    [/RA3] :: [GA3] WITH [QA3']
    [/RA4 * RA3] :: [GA4] WITH [QA4']
    [/RA0 * RA4 * RA3] :: [GA0] WITH [QA0']
    [/RA1 * RA0 * RA4 * RA3] :: [GA1] WITH [QA1']
    [/RA2 * RA1 * RA0 * RA4 * RA3] :: [GA2] WITH [QA2']
  ENDCASE

WHILE [W4]
  CASE
    [/RA4] :: [GA4] WITH [QA4']
    [/RA0 * RA4] :: [GA0] WITH [QA0']
    [/RA1 * RA0 * RA4] :: [GA1] WITH [QA1']
    [/RA2 * RA1 * RA0 * RA4] :: [GA2] WITH [QA2']
    [/RA3 * RA2 * RA1 *RA1 * RA4] :: [GA3] WITH [QA3']
  ENDCASE

WHILE [W04]
  CASE
    [/RB0 * RA4 * RA3 * RA2 * RA1 * RA0] :: [GB0] WITH [QB0']
    [/RB1 * RB0 * RA4 * RA3 * RA2 * RA1 * RA0] :: [GB1] WITH [QB1']
    [/RB2 * RB1 * RB0 * RA4 * RA3 * RA2 * RA1 * RA0] :: [GB2] WITH [QB2']
  ENDCASE

WHILE [GA0]
  IF [RA0] THEN [W1] WITH [NOGRANT']

WHILE [GA1]
  IF [RA1] THEN [W2] WITH [NOGRANT']

WHILE [GA2]
  IF [RA2] THEN [W3] WITH [NOGRANT']

WHILE [GA3]
  IF [RA3] THEN [W4] WITH [NOGRANT']

WHILE [GA4]
  IF [RA4] THEN [W0] WITH [NOGRANT']

WHILE [GB0]
  IF [RB0] THEN [GB1] WITH [NOGRANT']

WHILE [GB1]
  IF [RB1] THEN [GB2] WITH [NOGRANT']

WHILE [GB2]
  IF [RB2] THEN [GB0] WITH [NOGRANT']
```

TB00751S

a. Arbiter State Equations (Continued)

Figure 7 (Continued)



```
 ********************* ARBITERB *********************
####################### P I N   L I S T #######################

   LABEL      ** FNC **PIN ---------- PIN** FNC **     LABEL
CLOCK         ** CK  **   1-|         |-28 ** +5V **VCC
RB2           ** I   **   2-|         |-27 ** I   **N/C
RB1           ** I   **   3-|         |-26 ** I   **N/C
RB0           ** I   **   4-|    8    |-25 ** I   **N/C
RA4           ** I   **   5-|    2    |-24 ** I   **N/C
RA3           ** I   **   6-|    S    |-23 ** I   **N/C
RA2           ** I   **   7-|    1    |-22 ** I   **N/C
RA1           ** I   **   8-|    0    |-21 ** I   **N/C
RA0           ** I   **   9-|    5    |-20 ** I   **N/C
OB2           ** O   **  10-|         |-19 ** PR  **PRESET
OB1           ** O   **  11-|         |-18 ** O   **OA0
OB0           ** O   **  12-|         |-17 ** O   **OA1
OA4           ** O   **  13-|         |-16 ** O   **OA2
GND           ** OV  **  14-|         |-15 ** O   **OA3
                             ----------
```

TB00760S

b. Arbiter Pin List



```
 ********************* ARBITERB *********************
@DEVICE TYPE
82S105
@DRAWING
************* MULTI-PROCESSOR BUS ARBITOR
@REVISION
************* ARBITERB REV. 0
@DATE
************* JULY 26, 1985
@SYMBOL
************* ARBITERB
@COMPANY
************* SIGNETICS
@NAME
************* DAVID K. WONG
@DESCRIPTION
@INTERNAL SR FLIP FLOP LABELS
FF0 FF1 FF2 FF3 FF4 FF5

@COMMON PRODUCT TERM
@COMPLEMENT ARRAY
@LOGIC EQUATION
```

TB00770S

c. Arbiter Boolean Equations

Figure 7 (Continued)

Table 2. Arbiter Program Table

```
 ********************* ARBITERB *********************
Cust/Project - ************* DAVID K. WONG
Date         - ************* JULY 26, 1985
Rev/I. D.    - ************* ARBITERB REV. 0

82S105

---                                              -----------------------------
 T !                                             !           OPTION P/E    !H!
 E !--------------------------------------------------------------------------
 R ! !            INPUT VARIABLE     !PRESENT ST ! NEXT ST   !    OUTPUT     !
 M !C!1 1 1 1 1 1 ------------------------------------------------------------
___!_!5_4_3_2_1_0_9_8_7_6_5_4_3_2_1_0!5_4_3_2_1_0!5_4_3_2_1_0!7_6_5_4_3_2_1_0!
  0!A!- - - -,- - - -,- - - -,- - - L!H H,H H H H!L L,L H H L!H H H H,H H H L!
  1!A!- - - -,- - - -,- - - -,- - L H!H H,H H H H!L L,L H H H!H H H H,H H L H!
  2!A!- - - -,- - - -,- - - -,- L H H!H H,H H H H!L L,H H H L!H H H H,H L H H!
  3!A!- - - -,- - - -,- - - -,L H H H!H H,H H H H!L L,H H H H!H H H H,L H H H!
  4!A!- - - -,- - - -,- - - L,H H H H!H H,H H H H!L H,L H H L!H H H L,H H H H!
  5!A!- - - -,- - - -,- - - -,- - L -!H H,H H H L!L L,L H H H!H H H H,H H L H!
  6!A!- - - -,- - - -,- - - -,- L H -!H H,H H H L!L L,H H H L!H H H H,H L H H!
  7!A!- - - -,- - - -,- - - -,L H H -!H H,H H H L!L L,H H H H!H H H H,L H H H!
  8!A!- - - -,- - - -,- - - L,H H H -!H H,H H H L!L H,L H H L!H H H L,H H H H!
  9!A!- - - -,- - - -,- - - H,H H H L!H H,H H H L!L L,L H H L!H H H H,H H H L!
 10!A!- - - -,- - - -,- - - -,- L - -!H H,H H L H!L L,H H H L!H H H H,H L H H!
 11!A!- - - -,- - - -,- - - -,L H - -!H H,H H L H!L L,H H H H!H H H H,L H H H!
 12!A!- - - -,- - - -,- - - L,H H - -!H H,H H L H!L H,L H H L!H H H L,H H H H!
 13!A!- - - -,- - - -,- - - H,H H - L!H H,H H L H!L L,L H H L!H H H H,H H H L!
 14!A!- - - -,- - - -,- - - H,H H L H!H H,H H L H!L L,L H H H!H H H H,H H L H!
 15!A!- - - -,- - - -,- - - -,L - - -!H H,H H L L!L L,H H H H!H H H H,L H H H!
 16!A!- - - -,- - - -,- - - L,H - - -!H H,H H L L!L H,L H H L!H H H L,H H H H!
 17!A!- - - -,- - - -,- - - H,H - - L!H H,H H L L!L L,L H H L!H H H H,H H H L!
 18!A!- - - -,- - - -,- - - H,H - L H!H H,H H L L!L L,L H H H!H H H H,H H L H!
 19!A!- - - -,- - - -,- - - H,H L H H!H H,H H L L!L L,H H H L!H H H H,H L H H!
 20!A!- - - -,- - - -,- - - L,- - - -!H H,H L H H!L H,L H H L!H H H L,H H H H!
 21!A!- - - -,- - - -,- - - H,- - - L!H H,H L H H!L L,L H H L!H H H H,H H H L!
 22!A!- - - -,- - - -,- - - H,- - L H!H H,H L H H!L L,L H H H!H H H H,H H L H!
 23!A!- - - -,- - - -,- - - H,- L H H!H H,H L H H!L L,H H H L!H H H H,H L H H!
 24!A!- - - -,- - - -,- - - H,L H H -!H H,H L H H!L L,H H H H!H H H H,L H H H!
 25!A!- - - -,- - - -,- - L H,H H H H!H H,H - - -!H L,H - - -!H H L H,H H H H!
 26!A!- - - -,- - - -,- L H H,H H H H!H H,H - - -!H H,L - - -!H L H H,H H H H!
 27!A!- - - -,- - - -,L H H H,H H H H!H H,H - - -!H L,L - - -!L H H H,H H H H!
 28!A!- - - -,- - - -,- - - -,- - - H!L L,L H H L!H H,H H H L!H H H H,H H H H!
 29!A!- - - -,- - - -,- - - -,- - H -!L L,L H H H!H H,H H L H!H H H H,H H H H!
 30!A!- - - -,- - - -,- - - -,- H - -!L L,H H H L!H H,H H L L!H H H H,H H H H!
 31!A!- - - -,- - - -,- - - -,H - - -!L L,H H H H!H H,H L H H!H H H H,H H H H!
 32!A!- - - -,- - - -,- - - H,- - - -!L H,L H H L!H H,H H H H!H H H H,H H H H!
 33!A!- - - -,- - - -,- - H -,- - - -!H L,H - - -!H H,L - - -!H H H H,H H H H!
 34!A!- - - -,- - - -,- H - -,- - - -!H H,L - - -!H L,L - - -!H H H H,H H H H!
 35!A!- - - -,- - - -,H - - -,- - - -!H L,L - - -!H L,H - - -!H H H H,H H H H!
 36!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 37!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 38!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 39!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 40!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 41!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 42!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 43!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 44!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 45!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 46!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!
 47!0!0 0 0 0,0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0 0 0,0 0 0 0!

      N N N N N N N N R R R R R R R R F F F F F F F F F F F F 0 0 0 0 0 0 0 0
      / / / / / / / / B B B A A A A A F F F F F F F F F F F F B B B A A A A A
      C C C C C C C C 2 1 0 4 3 2 1 0 5 4 3 2 1 0 5 4 3 2 1 0 2 1 0 4 3 2 1 0
```

TB00780S

Single Chip Multiprocessor Arbiter AN7

SUMMARY

As can be seen from the circuit diagrams, the FPLS can offer significant advantages over discrete MSI arrays in the design of state machines. The tradeoff in both design alternatives for the Priority Arbiter is shown in Table 2. Clearly, the FPLS approach uses fewer parts, with savings in PC board space and power requirements.

Table 3. Design Alternatives for the Priority Arbiter

PARAMETER	F.P.L.S.	PROM/LATCH
Parts count	1 IC	≈19IC's
PCB space	.84 in^2	7.92 in^2
Power	.65W	2.85W
Voltage	+5V	+5V

REFERENCES

1. W.W. Plumber: "Asynchronous Arbiters"; *IEEE Transactions on Computers,* January 1972, pp. 37 – 42.
2. R.C. Pearce, J.A. Field, and W.D. Little: "Asynchronous Arbiter Module"; *IEEE Transactions on Computers,* September 1975, pp. 931 – 933.
3. K. Soe Hojberg: "An Asynchronous Arbiter Resolves Resource Allocation Conflicts on a Random Priority Basis"; *Computer Design,* August 1977, pp. 120 – 123.
4. K. Soe Hojberg: "One-Step Programmable Arbiter for Multiprocessors"; *Computer Design,* April 1978, pp. 154 – 158.

AN8

Introduction To Signetics Programmable Logic

Application Note

Application Specific Products

Author: K. A. H. Noach

INTRODUCTION

Custom logic is expensive – too expensive if your production run is short. 'Random logic' is cheaper but occupies more sockets and board space. Signetics Programmable Logic bridges the gap. Using PLD, you can configure an off-the-shelf chip to perform just the logic functions you need. Design and development times are much shorter, and risk much lower than for custom logic. Connections are fewer than for random logic, and, for all but the simplest functions, propagation delay is usually shorter. Yet another advantage that PLD has over custom logic is that it allows you to redesign the functions without redesigning the chip – giving you an invaluable margin not only for cut-and-try during system development, but also for later revision of system design. You're not tied down by the need to recover capital invested in a custom chip.

A PLD chip is an array of logic elements – gates, inverters, and flip-flops, for instance. In the virgin state, everything is connected to everything else by nichrome fuses, and although the chip has the capacity to perform an extensive variety of logic functions, it doesn't have the ability to. What gives it that is programming: selectively blowing undesired fuses so that those that remain provide the interconnections necessary for the required functions.

Signetics Series 20 PLD, named for the number of pins, supplements the well-known Series 28. The package is smaller – little more than a third the size, in fact – but the improved architecture, with user-programmable shared I/O. compensates for the fewer pins. The series comprises the following members, in order of increasing complexity:

- **PLS151 – field-programmable gate array**
- **PLS153 – field-programmable logic array**
- **PLS155 – field-programmable logic sequencer**
- **PLS157 – field-programmable logic sequencer**
- **PLS159 – field-programmable logic sequencer**

Entry to all the devices is via a product matrix, an array of input and shared I/O lines fuse-connected to the multiple inputs of an array of AND gates (see Figures 1, 2 and 5). To exploit the capacity of any device, it is important to make the most economical use of the AND gates it has available. Application of de Morgan's theorem can help in this. For example, inputs for the function

$$F = A + B + C + D$$

would occupy four of the AND gates of the product matrix. However, the same function rewritten as

$$\overline{F} = \overline{A}\ \overline{B}\ \overline{C}\ \overline{D}$$

would occupy only one. Moreover, the second function could be done on the simplest of the Series 20 devices (*and* leave eleven gates over for other functions), whereas the first could not. The fact that all inputs of the Series 20 devices, including the shared ones, incorporate double buffers that make the true and complement forms of all input variables equally accessible, greatly facilitates the use of de Morgan's theorem for logic minimization.

To convert the minimized logic equations to the pattern of fuses to be blown, you can use either a programming sheet (see e.g. Table 1) or Boolean equation program-entry software that lets you enter the equations via the keyboard of a terminal. The direct programmability of logic equations makes system design with PLD simple and sure. Functional changes can be made by replacing one PLD chip by another differently programmed. In many cases you can even remove the original one, reprogram it on the spot, and re-insert it. Programming machines qualified for the Series 20 are at present available from DATA I/O, KONTRON, and STAG.

FPGA PLS151

The field-programmable gate array is the simplest of the Series 20 PLD devices; Figure 1 shows the functional diagram. The array can accept up to 18 inputs. There are six dedicated input pins (A) and twelve (A') that can be programmed as inputs, outputs, or bidirectional I/O. All input variables, whether on dedicated or programmed input pins, are available in both true and complement form in the product matrix (B), and both forms are buffered: either form can drive all 12 product lines if required. In the virgin state, all the input variables and their complements are connected to all the product lines via a diode and a fuse (C), and the product matrix is effectively inoperative. To enable it to generate the required functions, unrequired connections between individual input lines and product lines are severed by blowing the connecting fuses.

At the output of the product matrix are 12 NAND gates, each with 36 inputs to accommodate the 18 possible input variables and their complements. Each of the product terms is normally active-Low, but a unique feature of Signetics PLD is that any or all of them can be independently programmed active-High. This is done by means of an array of exclusive-OR gates (D) at the NAND-gate outputs; when the fuse that grounds the second input of each OR gate is blown, the output of that gate is inverted.

The product matrix and exclusive OR-gate connections shown in Figure 1 illustrate the flexibility conferred by having buffered complements of all input variables internally available, together with independently programmable output polarities. Output B_{11}, shown with its exclusive OR-gate fuse intact, is programmed

$$\overline{B_{11}} = I_0 I_1 \overline{I_5}$$

Introduction To Signetics Programmable Logic

AN8


LOGIC GATES G
CONTROL GATES
11
10
9
8
7
6
5
4
3
2
1
0
D_2
D_1
D_0
fixed inputs
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
A
fuse
C
B_{11}
B_{10}
B_9
B_8
B_7
B_6
B_5
B_4
B_3
B_2
B_1
B_0
B
F
A'
D
E
shared I/O pins
7 B_0
8 B_1
9 B_2
11 B_3
12 B_4
13 B_5
14 B_6
15 B_7
16 B_8
17 B_9
18 B_{10}
19 B_{11}
LD01341S

NOTE:
A, dedicated inputs; A', programmable I/O. B, product (NAND) matrix with fused connections C; each of the vertical lines in the matrix represents 36 inputs to the terminating NAND gated. D, exclusive-OR array with inputs grounded via fuses for polarity control. E, programmable Tri-state output buffers. F, fuse-programmable control matrix. Square dots (■) represent permanent connections; round dots (●) intact fuse connections. Connected as shown, the array is programmed for the functions $\overline{B}_{11} = I_0\ I_1\ \overline{I_5}$ and $B_{10} = \overline{I_0}\ \overline{I_1}\ \overline{I_5}$.

Figure 1. Field-Programmable Gate Array PLS151A


LOGIC TERMS P
CONTROL TERMS
31 30 29 28 27 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0
D_9 D_8 D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
fixed inputs
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
B
F
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
B_9
A'
D
E
G
fuse
shared I/O pins
19 B_9
18 B_8
17 B_7
16 B_6
15 B_5
14 B_4
13 B_3
12 B_2
11 B_1
9 B_0
LD01380S

NOTE:
A to F, as in Figure 1. G, sum (OR) matrix. Connected as shown, the array is programmed as a single-bit adder with Carry Enable.

Figure 2. Field-Programmable Logic Array PLS153

At the same time, and without using any additional inputs, output B_{10} (fuse blown) is programmed

$$B_{10} = \overline{I_0}\,\overline{I_1}\,\overline{I_5}$$

Each of the exclusive-OR gates drives a three-state output buffer. In the virgin state all the buffers (E) are disabled and therefore in the high-impedance state. The function of the programmable I/O pins (A') is then determined by the I/O control matrix (F). The three AND gates at the control-matrix output are Active-High, and when one of them is in the High state, the four output buffers it controls are enabled; the corresponding I/O pins then act as outputs. conversely, when a control-matrix AND-gate output is Low and the control fuse for the corresponding Tri-state buffer is intact, the pins controlled by that gate act as inputs. Thus, these pins can be programmed in groups of up to four to act as inputs or outputs according to the state of selected input variables. If required, any of the programmable I/O pins can be made a dedicated output by blowing the control fuse of the output buffer associated with it.

The speed of the FPGA compares favorably with TTL, although its propagation delay is longer than the individual gate delay of TTL. When the number of inputs required is large, however, the FPGA more than makes up for this. When more than eight inputs are required, for example, the FPGA has a distinct advantage. Then, the overall propagation delay of TTL often amounts to two or three gate delays, but that of the FPGA to only one.

FPLA PLS153

Architecture

With two levels of logic embodied in a product matrix terminating in 32 AND gates coupled to a ten-output OR matrix (Figure 2), the FPLA is a step up in complexity from the FPGA. Again, there is provision for 18 input variables, internally complemented and buffered, but here divided between eight dedicated input pins and ten individually programmable I/O pins. As before, exclusive-OR gates grounded by fuses provide output polarity control, and any of the programmable I/O pins can be made a dedicated output by blowing the control fuse of the output buffer associated with it.

Programming

When the required functions have been defined, corresponding programming instructions are entered in a programming table, the layout of which reflects the FPLA architecture. (A Signetics computer program named AMAZE, which accepts Boolean equations as input and generates an FPLA programming table as output, is also available.) The programming machine blows the FPLA fuses in the pattern prescribed by the table.

As an illustration of FPLA programming, consider a full adder. Figure 3 shows a TTL version (74LS80) and the corresponding logic equations. Note that the feedback of $\overline{C}_{n+1}$ introduces a second propagation delay. In the FPLA this is eliminated by redefining Σ in terms of A, B, and C_n, as shown in Figure 4, and using the right side of the equation for $\overline{C}_{n+1}$ instead of the term itself. At first glance this would appear to require a minimum of three product terms for $\overline{C}_{n+1}$ plus four for Σ, or a total of seven. The Karnaugh maps, however, show considerable overlap between the two functions: the map for $\overline{C}_{n+1}$ differs from that for Σ only by having $A\ B\ C_n$ instead of $\overline{A}\ \overline{B}\ \overline{C_n}$. Rewriting the equation for $\overline{C}_{n+1}$ to introduce $\overline{A}\ \overline{B}\ \overline{C_n}$ and eliminate $A\ B\ C_n$,

$$\overline{C}_{n+1} = A\ \overline{B}\ \overline{C_n} + \overline{A}\ B\ \overline{C_n} + \overline{A}\ \overline{B}\ C_n + \overline{A}\ \overline{B}\ \overline{C_n}$$

increases the number of product terms by one, but now $\overline{C}_{n+1}$ and Σ have three terms in common. Therefore, since the FPLA allows multiple use of product terms, it is sufficient to program each of the common terms only once; thus, the original seven product terms are effectively reduced to five.

To fill in the programming table (Table 1), first allocate inputs and outputs.


FULL ADDER
A
B
C_n
Σ
$\overline{\Sigma}$
$\Sigma = A\overline{C}_{n+1} + B\overline{C}_{n+1} + C_n\overline{C}_{n+1} + ABC_n$
$\overline{C}_{n+1}$
$\overline{C}_{n+1} = \overline{AC_n + BC_n + AB}$
LD01370S

Figure 3. Single-Bit Full Adder in TTL (e.g. 74LS80)



$$\Sigma = A\overline{C}_{n+1} + B\overline{C}_{n+1} + \overline{C}_n\overline{C}_{n+1} + ABC_n$$
$$= A\overline{B}\overline{C}_n + \overline{A}B\overline{C}_n + \overline{A}\overline{B}C_n + ABC_n$$

$$\overline{C}_{n+1} = \overline{AC_n + BC_n + AB}$$
$$= \overline{A}\overline{B} + \overline{A}\overline{C}_n + \overline{B}\overline{C}_n$$
$$= A\overline{B}\overline{C}_n + \overline{A}B\overline{C}_n + \overline{A}\overline{B}C_n + \overline{A}\overline{B}\overline{C}_n$$

Figure 4. Karnaugh Maps and Logic Equations for the Full Adder of Figure 3, Illustrating how the Equations are Reduced for the FPLA Implementation Shown in Figure 2 and Table 1

Inputs: $A = I_0$ Outputs: $\overline{C}_{n+1} = B_7$
$B = I_1$ $\overline{\Sigma} = B_8$
$C_n = I_2$ $\Sigma = B_9$

Next, enter the product terms of Σ in the product-matrix (AND) part of the table, using H to indicate a true input and L a false one.

- Term 0 is $A\ \overline{B}\ \overline{C_n}$: mark H, L, L in columns I_0, I_1, I_2 of row 0
- Term 1 is $\overline{A}\ B\ \overline{C_n}$: mark L, H, L in columns I_0, I_1, I_2 of row 1
- Term 2 is $\overline{A}\ \overline{B}\ C_n$: mark L, L, H in columns I_0, I_1, I_2 of row 2
- Term 3 is $A\ B\ C_n$: mark H, H, H in columns I_0, I_1, I_2 of row 3.

Fill the rest of rows 0, 1, 2, and 3 with dashes to indicate that all other inputs are to be disconnected from Terms 0, 1, 2, and 3 (fuses blown).

The product terms of Σ must be added to form the sum-of-products required at output B_9. Indicate the required addition by putting an A (for Attached, i.e. fuse unblown) in the Term 0, 1, 2, and 3 spaces of column $B(O)_9$; Term 4 is not required for Σ, so put a dot in the Term 4 space to indicate that it is to be disconnected (fuse blown). To indicate that the output is to be Active-High, put an H in the polarity square above the $B(O)_9$ column. Finally, fill row D_9 with dashes to indicate that all fuses on line D_9 of the control matrix are to be blown and B_9 is to be a dedicated output. This completes the programming of Σ.

The $\overline{\Sigma}$ output on B_8 is programmed in just the same way, except that the polarity square above the $B(O)_8$ column is marked L to indicate Active-Low. (Note that in the FPLA, the Σ and $\overline{\Sigma}$ outputs change simultaneously, because all output signals traverse the exclusive-OR array (D), whether they are Active-High or Active-Low. In the TTL full adder shown in Figure 3, the output inverter delays the change of Σ with respect to $\overline{\Sigma}$.)

Table 1. FPLA Programming Table Filled in for the Full Adder of Figure 2

PROGRAM TABLE ENTRIES:

I, B(I)	
INACTIVE	0
I, B	H
$\overline{I}$, $\overline{B}$	L
DON'T CARE	—

(AND)

B(O)	
ACTIVE	A
INACTIVE	•

B(O)	
HIGH	H
LOW	L

(POL.)

TERM	AND																		OR									
	I								B(I)										B(O)									
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0
POLARITY																			H	L	L							
0	—	—	—	—	—	L	L	H	—	—	—	—	—	—	—	—	—	—	A	A	A							
1	—	—	—	—	—	L	H	L	—	—	—	—	—	—	—	—	—	—	A	A	A							
2	—	—	—	—	—	H	L	L	—	—	—	—	—	—	—	—	—	—	A	A	A							
3	—	—	—	—	—	H	H	H	—	—	—	—	—	—	—	—	—	—	A	A	•							
4	—	—	—	—	—	L	L	L	—	—	—	—	—	—	—	—	—	—	•	•	A							
5																												
6																												
7																												
8																												
9																												
10																												
11																												
12																												
13																												
14																												
15																												
16																												
17																												
18																												
19																												
20																												
21																												
22																												
23																												
24																												
25																												
26																												
27																												
28																												
29																												
30																												
31																												
D9	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—										
D7	—	—	—	—	H	—	—	—	—	—	—	—	—	—	—	—	—	—										
D6																												
D5																												
D4																												
D3																												
D2																												
D1																												
D0																												
PIN NO.	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9										
VARIABLE NAME					ENABLE	C_n	B	A	Σ	$\overline{\Sigma}$	$\overline{C_{n+1}}$																	

TB01480S

Introduction To Signetics Programmable Logic

The output C_{n+1} on B_7 contains three of the same terms as Σ, plus the term $\overline{A}\ \overline{B}\ \overline{C_n}$. Only this last term needs to be additionally programmed in the product matrix: mark L, L, L in columns I_0, I_1, I_2 of the Term 4 row. Indicate the addition

$$A\ \overline{B}\ \overline{C_n} + \overline{A}\ B\ \overline{C_n} + \overline{A}\ \overline{B}\ C_n + \overline{A}\ \overline{B}\ \overline{C_n}$$

by putting an A in rows 0, 1, 2, and 4 of column $B(O)_7$, and show that Term 3 ($A\ B\ C_n$) is not required by putting a dot in the Term 3 row to indicate disconnection (fuse blown). Put an L in the $B(O)_7$ polarity square to indicate Active-Low.

Identifying B_7 as a dedicated output by indicating that all the fuses to control term D_7 are to be blown, would now complete the programming of the full adder. However, a useful supplementary feature would be a Carry Enable function to keep the B_7 output buffer in the high-impedance state except when the enable input I_3 is true. The output buffer is enabled when both the fuses of a control term are blown, or when one is blown and the term that controls the output buffer is true. Thus, a Carry Enable can be provided via the I_3 input by leaving intact the fuse for Active-High operation of the enable signal to control term D_7. To indicate this, put an H in the I_3 column of row D_7 and fill the rest of the row with dashes.

The full adder with output Carry Enable uses only four of the eight dedicated inputs, three of the ten programmable I/O pins, and five of the 32 AND gates. The remaining capacity can be used for programming other functions which may, if required, also make use of AND-gate outputs already programmed for the full adder.

All fuses not indicated as blown in the programming table are normally left intact to preserve capacity for later program revisions or the addition of supplementary functions. If it is essential to minimize propagation delay, however, the finalized program should include instructions for blowing all unused fuses to minimize load capacitance.

FPLS PLS155 – PLS157 – PLS159

Architecture

The FPLS (Figure 5) is the most complex of the Series 20 PLD devices. Like the FPLA, it has a 32-term product matrix followed by an OR matrix. In the FPLS, however, the OR matrix is larger and comprises three distinct parts, with architecture differing in detail from type to type. In the PLS155, for instance, the first part consists of eight 32-input gates coupled, like those of the FPLA, to an output-polarity-controlling exclusive-OR array. The second consists of twelve additional gates which control four flip-flops. These are what give the FPLS its sequential character, enabling it to dictate its next state as a function of its present state. The third part is the deceptively simple Complement Array (I in Figure 5): a single OR gate with its output inverted and fed back into the product matrix. This enables a chosen sum-of-products to become a common factor of any or all the product terms and makes it possible to work factored sum-of-products equations. it is also useful for handshaking control when interfacing with a processor and for altering the sequence of a state machine without resorting to a large number of product terms.

PLS155 has four dedicated inputs and eight programmable I/O pins that can be allocated in the same way as in the FPLA. It also has four shared I/O pins (L) whereby the flip-flops can be interfaced with a bidirectional data bus. Two product terms, L_A and L_B in the control matrix F, control the loading of the flip-flops, in pairs, synchronized with the clock.

Figure 6 shows the architecture of the flip-flop circuitry in the PLS155. The flip-flops are positive-edge–triggered and can be dynamically changed to J-K, T, or D types according to the requirements of the function being performed; this considerably lessens the demands on the logic. The Tri-state inverter between the J and K inputs governs the mode of operation, under the control of the product term F:

- When the inverter is in the high-impedance state, the flip-flop is a J-K type, or a T type when $J = K$.
- When the inverter is active, $K = \overline{J}$ and the flip-flop is a D type; the K input must then be disconnected from the OR matrix.

All the product terms from the product matrix (T_0 to T_{31} in Figure 5) are fuse-connected to the J and K input OR gates. if both fuses of any one product term are left intact, $J = K$ and the flip-flop is a T type.

The flip-flops of the PLS155 have asynchronous Preset and Reset controlled by terms in the OR matrix that take priority over the clock. Their three-state output buffers can be controlled from the enable pin OE or permanently enabled or disabled by blowing fuses or leaving them intact in the enable array (K in Figure 5).

The PLS157 and PLS159 sequencers have, respectively, six and eight flip-flops. The architecture differs in detail but is similar in principle to that of PLS155.

Programming

The FPLS is programmed in much the same way as the FPLA, using a table to instruct the machine that blows the undesired fuses. It is not necessary to work with a circuit diagram; in fact, it is even undesirable to do so, since applying the necessary logic reduction techniques would in most cases make the diagram difficult to read and more a hindrance than a help. An example of how to program the FPLS as a universal counter/shift-register is given in the Appendix.

DEVELOPMENT AND PRODUCTION ECONOMY WITH PLD

Underlying the design philosophy of the Signetics Series 20 PLD is the concept of programmable arrays whose architecture emulates logic equation formats rather than mere aggregations of gates. The unique combination of features which support this philosophy includes:

- double-buffered true and complement inputs
- programmable-polarity outputs
- programmable I/O for internal feedback and maximum freedom in allocating inputs and outputs
- truth-table programming format

These features are common to all the PLD devices. In the field-programmable logic sequencers they are further supported by:

- flip-flops with dynamically alterable operating modes
- a complement array for simplified handshaking control

From the development engineer's point of view an important advantage of PLD is that it eliminates breadboarding. Once the functions required in terms of minimized logic equations are worked out, a PLD can be programmed accordingly. Once programmed, it will perform those functions.

Loading the instructions into the programming machine usually takes no more than a couple of hours; after that, the machine can program the devices at a rate of 100 an hour. Moreover, since any PLD can be programmed in many different ways, PLD has considerable potential for simplifying purchasing and stock control. One type of device can be programmed to perform a diversity of tasks for which it would otherwise be necessary to purchase and stock many different devices.

Series 20 PLD is second-sourced by Harris Semiconductor.

Introduction To Signetics Programmable Logic

AN8


(LOGIC TERMS - T)
(CONTROL TERMS)
F
I_0 2
I_1 3
I_2 4
I_3 5
A
F_0
F_1
F_2
F_3
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B
C
$\overline{C}$
I
L_B L_A D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
E_B E_A
11 $\overline{O.E.}$
K
X_7 S_7
X_6 S_6
X_5 S_5
X_4 S_4
X_3 S_3
X_2 S_2
X_1 S_1
X_0 S_0
D
E
H
19 B_7
18 B_6
13 B_5
12 B_4
9 B_3
8 B_2
7 B_1
6 B_0
R_B
P_B
R_A
P_A
P R
J Q
K CK'
M_3
M_2
M_1
M_0
G
L
17 F_3
16 F_2
15 F_1
14 F_0
31 • • • • • • 24 23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0 F_C
CK
J
1 CK
LD01930S

NOTE:
A to G, As In Figure 2. H, Flip-Flops And Bus-Load Buffer. J, Clock Input. K, Output-Buffer Enable. L, Tri-state Flip-Flop Output Buffers.

Figure 5. Field-Programmable Logic Sequencer PLS155



Figure 6. Architecture of the PLS155 Flip-Flop Circuitry

APPENDIX

Programming an FPLS as a Counter/Shift-Register

Objective: to program a PLS155 FPLS as a count-up, count-down, shift-right, shift-left machine governed by three control terms – COUNT/$\overline{\text{SHIFT}}$, RIGHT/UP, LEFT/DOWN. Direct implementation would result in a machine with 64 state transitions (see Table A-1), which is beyond the scope of the PLS155 or even the 28-pin PLS105. Logic reduction is therefore necessary.

As there are only four feedback variables (D, C, B, A), you can do the reduction by hand, one mode at a time; the control terms need not be included till the summary equations are written. Using the transition mapping method suggested here, you can examine the excitation equations for all types of flip-flops (R-S, J-K, D, T) and choose those types that will perform the required functions using the fewest product terms. Table A-2 summarizes the rules for flip-flop implementation using transition maps; the transition symbols used in the table mean:

PRESENT STATE	NEXT STATE	TRANSITION SYMBOL
0	0	0
0	1	α
1	0	β
1	1	1

Using these symbols, construct Table A-3 from Table A-1 to enable you to examine the excitation equations for all types of flip-flops. Proceeding one mode at a time, transfer the state conditions from Table A-3 to Karnaugh maps, as in Figure A-1. Following the rules in Table A-2, derive the excitation equations for the different types of flip-flops (the examples shown in Figure A-1 omit the T type because it is the same as the J-K type when J = K). In deciding which types of flip-flop to use, remember that logic minimization with PLD is different from logic minimization with 'random logic': with random logic you seek to reduce the number of standard packages required; with PLD you seek to reduce the number of product terms.

From Figure A-1 it is evident that you should choose J-K or T flip-flops for the counter mode and D flip-flops for the shift mode, for you then require only one product term per flip-flop per mode. Table A-4 summarizes the number of product terms per mode the various types of flip-flops would require.

Table A-5 shows the completed programming table for the counter/shift-register. The programming of Terms 0 to 15 reflects the flip-flop excitation equations and illustrates the value of being able to switch the flip-flops dynamically from one type of operation to another. Terms 16, 17 and 18, respectively, provide for INITIALIZE, asynchronous RESET, and STOP functions.

The programming of the two additional inputs $\overline{\text{HALT}}$ and $\overline{\text{BUSY}}$ illustrates the value of the complementary, which is made active when $\overline{\text{HALT}}$ and $\overline{\text{BUSY}}$ are Low (A in the Complement square of Term 18) and propagated into all the other terms (dot in the Complement squares of Terms 0 to 17). This means that unless the $\overline{\text{HALT}}$ and $\overline{\text{BUSY}}$ inputs are High, none of the product terms will be true and the state of the machine will not change. If the Complement Array were not used, twice the number of product terms would be required, even if one of the additional inputs were omitted.

As it is, the design uses only 19 of the 32 product terms available, so there is ample capacity for extending its capabilities. For example, the shift-left function can be augmented by a binary multiplication capability, using a D type flip-flop to make it shift one, two, or three places according to the state of two extra inputs, X and Y. Table A-6 shows the revised programming table. The binary multiplication function occupies nine additional product terms.

ACKNOWLEDGEMENT

Electronic Components and Applications; Vol. 4, No. 2, February 1982. Reprinted with the permission of PHILIPS.

Table A-1. Present-State/Next-State Table for Counter/Shift-Register

STATE NO.	PRESENT STATE				NEXT STATE															
					Count Down				Count Up				Shift Left				Shift Right			
	D	C	B	A	D	C	B	A	D	C	B	A	D	C	B	A	D	C	B	A
0	0	0	0	0	1	1	1	1	0	0	0	1	0	0	0	0	0	0	0	0
1	0	0	0	1	0	0	0	0	0	0	1	0	0	0	1	0	1	0	0	0
2	0	0	1	0	0	0	0	1	0	0	1	1	0	1	0	0	0	0	0	1
3	0	0	1	1	0	0	1	0	0	1	0	0	0	1	1	0	1	0	0	1
4	0	1	0	0	0	0	1	1	0	1	0	1	1	0	0	0	0	0	1	0
5	0	1	0	1	0	1	0	0	0	1	1	0	1	0	1	0	1	0	1	0
6	0	1	1	0	0	1	0	1	0	1	1	1	1	1	0	0	0	0	1	1
7	0	1	1	1	0	1	1	0	1	0	0	0	1	1	1	0	1	0	1	1
8	1	0	0	0	0	1	1	1	1	0	0	1	0	0	0	1	0	1	0	0
9	1	0	0	1	1	0	0	0	1	0	1	0	0	0	1	1	1	1	0	0
10	1	0	1	0	1	0	0	1	1	0	1	1	0	1	0	1	0	1	0	1
11	1	0	1	1	1	0	1	0	1	1	0	0	0	1	1	1	1	1	0	1
12	1	1	0	0	1	0	1	1	1	1	0	1	1	0	0	1	0	1	1	0
13	1	1	0	1	1	1	0	0	1	1	1	0	1	0	1	1	1	1	1	0
14	1	1	1	0	1	1	0	1	1	1	1	1	1	1	0	1	0	1	1	1
15	1	1	1	1	1	1	1	0	0	0	0	0	1	1	1	1	1	1	1	1
CONTROL TERMS																				
COUNT/$\overline{\text{SHIFT}}$					1				1				0				0			
RIGHT/UP					0				1				0				1			
LEFT/DOWN					1				0				1				0			

Table A-2. Rules for Flip-Flop Implementation Using Transition Maps

FLIP-FLOP TYPE	INPUT	MUST INCLUDE	MUST EXCLUDE	REDUNDANT
R-S	S	α	β,0	1,x
	R	β	α,1	0,x
D	D	α,1	β,0	x
T	T	α,β	0,1	x
J-K	J	α	0	1,β,x
	K	β	1	0,α,x

Table A-3. Transition Table for Counter/Shift-Register

STATE NO.	PRESENT STATE				TRANSITION															
					Count Down				Count Up				Shift Left				Shift Right			
	D	C	B	A	D	C	B	A	D	C	B	A	D	C	B	A	D	C	B	A
0	0	0	0	0	α	α	α	α	0	0	0	α	0	0	0	0	0	0	0	0
1	0	0	0	1	0	0	0	β	0	0	α	β	0	0	α	β	α	0	0	β
2	0	0	1	0	0	0	β	α	0	0	1	α	0	α	β	0	0	0	β	α
3	0	0	1	1	0	0	1	β	0	α	β	β	0	α	1	β	α	0	β	1
4	0	1	0	0	0	β	α	α	0	1	0	α	α	β	0	0	0	β	α	0
5	0	1	0	1	0	1	0	β	0	1	α	β	α	β	α	β	α	β	α	β
6	0	1	1	0	0	1	β	α	0	1	1	α	α	1	β	0	0	β	1	α
7	0	1	1	1	0	1	1	β	α	β	β	β	α	1	1	β	α	β	1	1
8	1	0	0	0	β	α	α	α	1	0	0	α	β	0	0	α	β	α	0	0
9	1	0	0	1	1	0	0	β	1	0	α	β	β	0	α	1	1	α	0	β
10	1	0	1	0	1	0	β	α	1	0	1	α	β	α	β	α	β	α	β	α
11	1	0	1	1	1	0	1	β	1	α	β	β	β	α	1	1	1	α	β	1
12	1	1	0	0	1	β	α	α	1	1	0	α	1	β	0	α	β	1	α	0
13	1	1	0	1	1	1	0	β	1	1	α	β	1	β	α	1	1	1	α	β
14	1	1	1	0	1	1	β	α	1	1	1	α	1	1	β	α	β	1	1	α
15	1	1	1	1	1	1	1	β	β	β	β	β	1	1	1	1	1	1	1	1

Table A-4. Number of Product Terms Required for Counter/Shift-Register Flip-Flop Excitation

FLIP-FLOP TYPE	COUNT UP	COUNT DOWN	SHIFT RIGHT	SHIFT LEFT	TOTAL
SR only	8	8	8	8	32
JK only	4	4	8	8	24
D only	10	10	4	4	28
FPLS	4(J-K)	4(J-K)	4(D)	4(D)	16

COUNT UP

Ⓐ

			B	B
	α	β	β	α
C	α	β	β	α
C D	α	β	β	α
D	α	β	β	α
		A	A	

Ⓑ

0	α	β	1
0	α	β	1
0	α	β	1
0	α	β	1

Ⓒ

0	0	α	0
1	1	β	1
1	1	β	1
0	0	α	0

Ⓓ

0	0	0	0
0	0	α	0
1	1	β	1
1	1	1	1

S	$\bar{A}$	$A\bar{B}$	$AB\bar{C}$	$ABC\bar{D}$
R	A	AB	ABC	ABCD
J	1	A	AB	ABC
K	1	A	AB	ABC
D	$\bar{A}$	$A\bar{B} + \bar{A}B$	$AB\bar{C} + \bar{B}C + \bar{A}C$	$ABC\bar{D} + \bar{C}D + \bar{B}D + \bar{A}D$

TB01430S

COUNT DOWN

Ⓐ

			B	B
	α	β	β	α
	α	β	β	α
D	α	β	β	α
D	α	β	β	α
		A	A	

Ⓑ

α	0	1	β
α	0	1	β
α	0	1	β
α	0	1	β

Ⓒ

α	0	0	0
β	1	1	1
β	1	1	1
α	0	0	0

Ⓓ

α	0	0	0
0	0	0	0
1	1	1	1
β	1	1	1

S	$\bar{A}$	$\bar{A}\bar{B}$	$\bar{A}\bar{B}\bar{C}$	$\bar{A}\bar{B}\bar{C}\bar{D}$
R	A	$\bar{A}B$	$\bar{A}\bar{B}C$	$\bar{A}\bar{B}\bar{C}D$
J	1	$\bar{A}$	$\bar{A}\bar{B}$	$\bar{A}\bar{B}\bar{C}$
K	1	$\bar{A}$	$\bar{A}\bar{B}$	$\bar{A}\bar{B}\bar{C}$
D	$\bar{A}$	$A\bar{B} + AB$	$\bar{A}\bar{B}\bar{C} + AC + BC$	$\bar{A}\bar{B}\bar{C}\bar{D} + CD + AD + BD$

TB01440S

SHIFT RIGHT

Ⓐ

			B	B
	0	β	1	α
C	0	β	1	α
C D	0	β	1	α
D	0	β	1	α
		A	A	

Ⓑ

0	0	β	β
α	α	1	1
α	α	1	1
0	0	β	β

Ⓒ

0	0	0	0
β	β	β	β
1	1	1	1
α	α	α	α

Ⓓ

0	α	α	0
0	α	α	0
β	1	1	β
β	1	1	β

S	B	C	D	A
R	$\bar{B}$	$\bar{C}$	$\bar{D}$	$\bar{A}$
J	B	C	D	A
K	$\bar{B}$	$\bar{C}$	$\bar{D}$	$\bar{A}$
D	B	C	D	A

TB01490S

SHIFT LEFT

Ⓐ

			B	B
	0	β	β	0
C	0	β	β	0
C D	α	1	1	α
D	α	1	1	α
		A	A	

Ⓑ

0	α	1	β
0	α	1	β
0	α	1	β
0	α	1	β

Ⓒ

0	0	α	α
β	β	1	1
β	β	1	1
0	0	α	α

Ⓓ

0	0	0	0
α	α	α	α
1	1	1	1
β	β	β	β

S	D	A	B	C
R	$\bar{D}$	$\bar{A}$	$\bar{B}$	$\bar{C}$
J	D	A	B	C
K	$\bar{D}$	$\bar{A}$	$\bar{B}$	$\bar{C}$
D	D	A	B	C

TB01450S

Figure A-1 Karnaugh Maps and Flip-Flop Excitation Functions for the Counter/Shift-Register

Table A-5. PLS155 FPLS Programming Table for the Counter/Shift-Register

PROGRAM TABLE ENTRIES

I, B(I), Q(P)

INACTIVE	O
I, B, Q	H
$\overline{I}, \overline{B}, \overline{Q}$	L
DON'T CARE	–

(AND)

C

INACTIVE	O
GENERATE	A
PROPAGATE	•
TRANSPARENT	–

AND

P, R, B(O), (Q = D)

ACTIVE	A
INACTIVE	•

(OR)

(Q = J/K)

TOGGLE	O
SET	H
RESET	L
HOLD	–

(OR)

HIGH	H
LOW	L

(POL.)

E_A, E_B

IDLE	O
CONTROL	A
ENABLE	•
DISABLE	–

F/F TYPE

J/K	•
D OR J/K	A

(OR)

														F/F TYPE				$E_B = A$		$E_A = A$						POLARITY							
														A	A	A	A	A	A	A	A												H
	AND																	OR															
TERM	C	I				B(I)								Q(P)				Q(N)				P				B(O)							
		3	2	1	0	7	6	5	4	3	2	1	0	3	2	1	0	3	2	1	0	B	A	B	A	7	6	5	4	3	2	1	0
0	•	L	H	L	H	L		–	–	–	–	–	–	–	–	–	–	–	–	–	O	–	–	–	–	–	–	–	–	–	–	–	A
1	•	L	H	L	H	L	}	C	O	UN	T	–	–	–	–	–	L	–	–	O	–	–	–	–	–	–	–	–	–	–	–	–	A
2	•	L	H	L	H	L		–	D	O	W	N	–	–	–	L	L	–	O	–	–	–	–	–	–	–	–	–	–	–	–	–	A
3	•	L	H	L	H	L		–	–	–	–	–	–	–	L	L	L	O	–	–	–	–	–	–	–	–	–	–	–	–	–	–	A
4	•	L	L	H	H	L		–	–	–	–	–	–	–	–	–	–	–	–	–	O	–	–	–	–	–	–	–	–	–	–	–	A
5	•	L	L	H	H	L	}	CO	UN	T	–	–	–	–	–	–	H	–	–	O	–	–	–	–	–	–	–	–	–	–	–	–	A
6	•	L	L	H	H	L			U	P	–	–	–	–	–	H	H	–	O	–	–	–	–	–	–	–	–	–	–	–	–	–	A
7	•	L	L	H	H	L		–	–	–	–	–	–	–	H	H	H	O	–	–	–	–	–	–	–	–	–	–	–	–	–	–	A
8	•	L	H	L	L	L		–	–	–	–	–	–	H	–	–	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	A
9	•	L	H	L	L	L	}	SH	IF	T	–	–	–	–	–	–	H	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	A
10	•	L	H	L	L	L		–	LE	FT	–	–	–	–	–	H	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	A
11	•	L	H	L	L	L		–	–	–	–	–	–	–	H	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	–	A
12	•	L	L	H	L	L		–	–	–	–	–	–	–	–	H	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	A
13	•	L	L	H	L	L	}	SH	IF	T	–	–	–	–	H	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	A
14	•	L	L	H	L	L		–	RIG	HT	–	–	–	H	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	A
15	•	L	L	H	L	L		–	–	–	–	–	–	–	–	–	H	H	–	–	–	–	–	–	–	–	–	–	–	–	–	–	A
16	•	H	–	–	–	L	–	INI	TIA	LI	ZE	–	–	–	–	–	–	L	L	L	L	–	–	–	–	–	–	–	–	–	–	–	•
17	•	–	–	–	–	H	–	R	E	SE	T	–	–	–	–	–	–	–	–	–	–	–	–	A	A	–	–	–	–	–	–	–	•
18	A	–	–	–	–	–	L	L	–	S	TO	P	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	•
19																																	
20																																	
21																																	
22																																	
23																																	
24																																	
25																																	
26																																	
27																																	
28																																	
29																																	
30																																	
31																																	
F_C	–	–	–	–	L	–	–	–	–	–	–	–	–	–	–	–	–																
L_B																																	
L_A																																	
D_7	•	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O																
D_6	•	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O																
D_5	•	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O																
D_4																																	
D_3																																	
D_2																																	
D_1																																	
D_0	–	–	–	–	–	–	–	L	–	–	–	–	–	–	–	–	–																
		5	4	3	2	19	18	13	12	9	8	7	6	17	16	15	14																
VARIABLE NAME		$\overline{\text{INIT}}$	LEFT\DOWN	RIGHT\UP	$\overline{\text{COUNT}}$\SHIFT	RESET	$\overline{\text{HALT}}$	$\overline{\text{BUSY}}$					ACTIVE	D	C	B	A																

TB01470S

Table A-6. Modified PLS155 FPLS Programming Table for the Counter/Shift-Register With the Addition of a Binary Multiplier

PROGRAM TABLE ENTRIES

I, B(I), Q(P)	
INACTIVE	0
I, B, Q	H
I, B, Q	L
DON'T CARE	-

(AND)

C	
INACTIVE	0
GENERATE	A
PROPAGATE	•
TRANSPARENT	-

AND

P, R, B(O), (Q = D)	
ACTIVE	A
INACTIVE	•

(OR)

(Q = J/K)	
TOGGLE	0
SET	H
RESET	L
HOLD	-

(OR)

HIGH	H
LOW	L

(POL.)

E_A, E_B	
IDLE	0
CONTROL	A
ENABLE	•
DISABLE	-

F/F TYPE	
J/K	•
D OR J/K	A

(OR)

														F/F TYPE				E_B = A		E_A = A						POLARITY							
														A	A	A	A	A	A	A	A												H
TERM	AND																	OR															
	C	I				B(I)								Q(P)				Q(N)				P				B(O)							
		3	2	1	0	7	6	5	4	3	2	1	0	3	2	1	0	3	2	1	0	B	A	B	A	7	6	5	4	3	2	1	0
0	•	L	H	L	H	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0	-	-	-	-	-	-	-	-	-	-	-	A
1	•	L	H	L	H	L	-	-	-	-	-	-	-	-	-	-	L	-	-	0	-	-	-	-	-	-	-	-	-	-	-	-	A
2	•	L	H	L	H	L	-	-	-	-	-	-	-	-	-	L	L	-	0	-	-	-	-	-	-	-	-	-	-	-	-	-	A
3	•	L	H	L	H	L	-	-	-	-	-	-	-	-	L	L	L	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A
4	•	L	L	H	H	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0	-	-	-	-	-	-	-	-	-	-	-	A
5	•	L	L	H	H	L	-	-	-	-	-	-	-	-	-	-	H	-	-	0	-	-	-	-	-	-	-	-	-	-	-	-	A
6	•	L	L	H	H	L	-	-	-	-	-	-	-	-	-	H	H	-	0	-	-	-	-	-	-	-	-	-	-	-	-	-	A
7	•	L	L	H	H	L	-	-	-	-	-	-	-	-	H	H	H	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A
8	•	L	H	L	L	L	-	-	L	H	-	-	-	H	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	A
9	•	L	H	L	L	L	-	-	H	L	-	-	-	-	H	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	A
10	•	L	H	L	L	L	-	-	H	H	-	-	-	-	-	H	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	A
11	•	L	H	L	L	L	-	-	L	H	-	-	-	-	-	-	H	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	A
12	•	L	H	L	L	L	-	-	H	L	-	-	-	H	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	A
13	•	L	H	L	L	L	-	-	H	H	-	-	-	-	H	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	A
14	•	L	H	L	L	L	-	-	L	H	-	-	-	-	-	H	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	A
15	•	L	H	L	L	L	-	-	H	L	-	-	-	-	-	-	H	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	A
16	•	L	H	L	L	L	-	-	H	H	-	-	-	H	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	A
17	•	L	H	L	L	L	-	-	L	H	-	-	-	-	H	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A
18	•	L	H	L	L	L	-	-	H	L	-	-	-	-	-	H	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A
19	•	L	H	L	L	L	-	-	H	H	-	-	-	-	-	-	H	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A
20	•	L	L	H	L	L	-	-	-	-	-	-	-	-	-	H	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	A
21	•	L	L	H	L	L	-	-	-	-	-	-	-	-	H	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	A
22	•	L	L	H	L	L	-	-	-	-	-	-	-	H	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	A
23	•	L	L	H	L	L	-	-	-	-	-	-	-	-	-	-	H	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A
24	•	H	-	-	-	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	•
25	•	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	•
26	A	-	-	-	-	-	L	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	•
27																																	
28																																	
29																																	
30																																	
31																																	
F_C	-	-	-	-	L	-	-	-	-	-	-	-	-	-	-	-	-																
L_B																																	
L_A																																	
D_7	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																
D_6	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																
D_5	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																
D_4	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																
D_3	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																
D_2																																	
D_1																																	
D_0	-	-	-	-	-	-	-	L	-	-	-	-	-	-	-	-	-																
		5	4	3	2	19	18	13	12	9	8	7	6	17	16	15	14																
VARIABLE NAME		INIT	LEFT\DOWN	RIGHT\UP	COUNT\$\overline{\text{SHIFT}}$	RESET	$\overline{\text{HALT}}$	$\overline{\text{BUSY}}$					ACTIVE	D	C	B	A																

TB01460S

Signetics

Application Specific Products

AN10

4-Bit Binary-To-7 Segment Decoder

Application Note

INTRODUCTION

Using the PLS153 or PLS153A, a 4-bit binary-to-7 segment decoder may be easily constructed. This paper will cover Hex-to-7 segment decoder, BCD-to-7 segment decoder, decoder with latches, and decoder with multiplexer. The architecture of PLS153/153A is basically an AND-OR matrix. The large number of inputs of each AND term is ideal for decoder applications, and the ability to drive the entire OR array makes possible the efficient use of AND terms such that, together with the programmable output polarity, a minimum number of AND terms is needed to implement the decoder function. Another important feature of the PLS153/153A architecture is the 10 bidirectional I/O pins. The bidirectionality of these pins provides internal feedback to the AND matrix, which eliminates the need for external wiring and, more importantly, it saves I/O pin requirements. All I/O pins of the PLS153/153A have tri-state output buffers, each may be enabled or disabled by its own controlling AND terms. In applications where high current drive is necessary but low power consumption is still desirable, the AND term controlled tri-state buffers are ideal for multiplexing. The LED display may be driven at a higher current and lower duty cycle to get better brightness/current efficiency and reduce the overall power dissipation.

DESCRIPTION

Hex-To-7 Segment Decoder

A 7 segment display (Figure 1) may be used to represent a hexadecimal number as shown in Table 1. The format serves merely as an example. Some designers may prefer other configurations, particularly for letters B and D. Before implementing the truth table with programmable logic devices, one has to decide whether the outputs should be Active-High or Active-Low. If a moderate drive current of 15mA or less is needed, and if a common anode LED display is used, then an Active-Low output configuration is sufficient. On the other hand, if only a common cathode LED display is available and the current drive requirement is not very critical, an Active-High output configuration may be used. The change of output polarity may be easily affected by putting in the POLARITY section 'H' for Active-High and 'L' for Active-Low. Since the output polarity is programmable, one may choose to describe the logic in terms of outputs equal to '1's or outputs equal to '0's.



AF01841S

Figure 1. 7 Segment Decoder Driving a Common Anode LED Display

```
A>######################## P I N   L I S T ########################

   LABEL      ** FNC **PIN ---------- PIN** FNC **     LABEL
W             ** I    **  1-¦        ¦-20 ** +5V **VCC
X             ** I    **  2-¦        ¦-19 ** B   **N/C
Y             ** I    **  3-¦        ¦-18 ** B   **N/C
Z             ** I    **  4-¦   8    ¦-17 ** B   **/SEG_A
N/C           ** I    **  5-¦   2    ¦-16 ** B   **/SEG_B
N/C           ** I    **  6-¦   S    ¦-15 ** B   **/SEG_C
N/C           ** I    **  7-¦   1    ¦-14 ** B   **/SEG_D
/OE           ** I    **  8-¦   5    ¦-13 ** B   **/SEG_E
N/C           ** B    **  9-¦   3    ¦-12 ** B   **/SEG_F
GND           ** OV   ** 10-¦        ¦-11 ** B   **/SEG_G
                          ----------
```

TB00981S

Figure 2. Pin List of Binary-to-7 Segment Decoder

NOTE:
PLSXXX and 82SXXX are interchangeable part numbers.

4-Bit Binary-To-7 Segment Decoder

Table 1. Truth Table of Hex-to-7-Segment Decoder


0000
0001
0010
0011
0100
0101
0110
0111
1000
1001
1010
1011
1100
1101
1110
1111

Z Y X W	a	b	c	d	e	f	g
0 0 0 0	1	1	1	1	1	1	0
0 0 0 1	0	1	1	0	0	0	0
0 0 1 0	1	1	0	1	1	0	1
0 0 1 1	1	1	1	1	0	0	1
0 1 0 0	0	1	1	0	0	1	1
0 1 0 1	1	0	1	1	0	1	1
0 1 1 0	1	0	1	1	1	1	1
0 1 1 1	1	1	1	0	0	0	0
1 0 0 0	1	1	1	1	1	1	1
1 0 0 1	1	1	1	1	0	1	1
1 0 1 0	1	1	1	0	1	1	1
1 0 1 1	0	0	1	1	1	1	1
1 1 0 0	1	0	0	1	1	1	0
1 1 0 1	0	1	1	1	1	0	1
1 1 1 0	1	0	0	1	1	1	1
1 1 1 1	1	0	0	0	1	1	1

TB00990S

4-Bit Binary-To-7 Segment Decoder

Table 2. H/L Programming Table for Binary-to-7-Segment Decoder

82S153/153A PROGRAMMING TABLE DRAWING ID: B TO 7 SEG DECODER REV. –
DESIGNER: D.K. WONG DATE: 12/15/84

																			POLARITY											
																			H	H	L	L	L	L	L	L	L	H	COMMENTS	
	AND																		OR											
	I								B(I)										B(O)											
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	INPUT	OUTPUT
0	–	–	–	–	L	L	L	L	–	–	–	–	–	–	–	–	–	–	•	•	A	A	A	A	A	A	•	•	0	0
1	–	–	–	–	L	L	L	H	–	–	–	–	–	–	–	–	–	–	•	•	•	A	A	•	•	•	•	•	1	1
2	–	–	–	–	L	L	H	L	–	–	–	–	–	–	–	–	–	–	•	•	A	A	•	A	A	•	A	•	2	2
3	–	–	–	–	L	L	H	H	–	–	–	–	–	–	–	–	–	–	•	•	A	A	A	A	•	•	A	•	3	3
4	–	–	–	–	L	H	L	L	–	–	–	–	–	–	–	–	–	–	•	•	•	A	A	•	•	A	A	•	4	4
5	–	–	–	–	L	H	L	H	–	–	–	–	–	–	–	–	–	–	•	•	A	•	A	A	•	A	A	•	5	5
6	–	–	–	–	L	H	H	L	–	–	–	–	–	–	–	–	–	–	•	•	A	•	A	A	A	A	A	•	6	6
7	–	–	–	–	L	H	H	H	–	–	–	–	–	–	–	–	–	–	•	•	A	A	A	•	•	•	•	•	7	7
8	–	–	–	–	H	L	L	L	–	–	–	–	–	–	–	–	–	–	•	•	A	A	A	A	A	A	A	•	8	8
9	–	–	–	–	H	L	L	H	–	–	–	–	–	–	–	–	–	–	•	•	A	A	A	A	•	A	A	•	9	9
10	–	–	–	–	H	L	H	L	–	–	–	–	–	–	–	–	–	–	•	•	A	A	A	•	A	A	A	•	10	A
11	–	–	–	–	H	L	H	H	–	–	–	–	–	–	–	–	–	–	•	•	•	•	A	A	A	A	A	•	11	b
12	–	–	–	–	H	H	L	L	–	–	–	–	–	–	–	–	–	–	•	•	A	•	•	A	A	A	A	•	12	C
13	–	–	–	–	H	H	L	H	–	–	–	–	–	–	–	–	–	–	•	•	•	A	A	A	A	•	A	•	13	d
14	–	–	–	–	H	H	H	L	–	–	–	–	–	–	–	–	–	–	•	•	A	•	•	A	A	A	A	•	14	E
15	–	–	–	–	H	H	H	H	–	–	–	–	–	–	–	–	–	–	•	•	A	•	•	•	A	A	A	•	15	F
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	ENABLE B7 FOR OUTPUT (SEG A)											
D6	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	" B6 " " " B											
D5	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	" B5 " " " C											
D4	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	" B4 " " " D											
D3	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	" B3 " " " E											
D2	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	" B2 " " " F											
D1	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	" B1 " " " G											
D0																														
NAME	/OE				Z	Y	X	W													A	B	C	D	E	F	G			

TB01001S

4-Bit Binary-To-7 Segment Decoder

AN10

Table 3. H/L Programming Table for Binary-to-7 Segment Decoder

82S153/153A PROGRAMMING TABLE   DRAWING ID: B TO 7SEG DECODER   REV. A
DESIGNER: D. K. WONG   DATE: 12/15/84

	AND																		OR										
	I								B(I)										B(O)										
POLARITY																			H	H	H	H	H	H	H	H	H	H	
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	COMMENTS
0	-	-	-	-	L	L	L	L	-	-	-	-	-	-	-	-	-	-	·	·	·	·	·	·	·	·	A	·	0
1	-	-	-	-	L	L	L	H	-	-	-	-	-	-	-	-	-	-	·	·	A	·	·	A	A	A	A	·	1
2	-	-	-	-	L	L	H	L	-	-	-	-	-	-	-	-	-	-	·	·	·	·	A	·	·	A	·	·	2
3	-	-	-	-	L	L	H	H	-	-	-	-	-	-	-	-	-	-	·	·	·	·	·	·	A	A	·	·	3
4	-	-	-	-	L	H	L	L	-	-	-	-	-	-	-	-	-	-	·	·	A	·	·	A	A	·	·	·	4
5	-	-	-	-	L	H	L	H	-	-	-	-	-	-	-	-	-	-	·	·	·	A	·	·	A	·	·	·	5
6	-	-	-	-	L	H	H	L	-	-	-	-	-	-	-	-	-	-	·	·	·	A	·	·	·	·	·	·	6
7	-	-	-	-	L	H	H	H	-	-	-	-	-	-	-	-	-	-	·	·	·	·	·	A	A	A	A	·	7
8	-	-	-	-	H	L	L	L	-	-	-	-	-	-	-	-	-	-	·	·	·	·	·	·	·	·	·	·	8 (*)
9	-	-	-	-	H	L	L	H	-	-	-	-	-	-	-	-	-	-	·	·	·	·	·	·	A	·	·	·	9
10	-	-	-	-	H	L	H	L	-	-	-	-	-	-	-	-	-	-	·	·	·	·	·	A	·	·	·	·	A
11	-	-	-	-	H	L	H	H	-	-	-	-	-	-	-	-	-	-	·	·	A	A	·	·	·	·	·	·	b
12	-	-	-	-	H	H	L	L	-	-	-	-	-	-	-	-	-	-	·	·	·	A	A	·	·	·	A	·	C
13	-	-	-	-	H	H	L	H	-	-	-	-	-	-	-	-	-	-	·	·	A	·	·	·	·	A	·	·	d
14	-	-	-	-	H	H	H	L	-	-	-	-	-	-	-	-	-	-	·	·	·	A	A	·	·	·	·	·	E
15	-	-	-	-	H	H	H	H	-	-	-	-	-	-	-	-	-	-	·	·	·	A	A	A	·	·	·	·	F
16																													
17																													
18																													
19																													
20																													
21																													
22																													
23																													
24																													
25																													
26																													
27																													
28																													
29																													
30																													
31																													
D9																													
D8																													
D7	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D6	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D5	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D4	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D3	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D2	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D1	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D0																													
NAME	OE				Z	Y	X	W													A	B	C	D	E	F	G		

(*) SINCE THIS TERM IS "INACTIVE", IT MAY BE DELETED. THEREFORE, THE TOTAL # OF TERMS REQUIRED IS 15.

TB01011S

4-Bit Binary-To-7 Segment Decoder

AN10

```
@DEVICE TYPE
82S153
@DRAWING
************************ BINARY-TO-7 SEGMENT DECODER
@REVISION
************************ REV. -
@DATE
************************ OCT 1, 1984
@SYMBOL
************************ FILE ID: 7deco
@COMPANY
************************ SIGNETICS
@NAME
************************ DAVID K. WONG
@DESCRIPTION
***************************************************************************
*   This circuit converts a 4-bit binary code ( HEX ) into                *
*   a 7-segment display. The display is a common anode 7-segment LED.     *
*   The output of the 82S153 goes LOW for each segment that is ON.        *
***************************************************************************

                                    TRUTH TABLE
         a                ZYXW          a  b  c  d  e  f  g
      -------           ------------------------------------
   f :       : b          0 0 0 0       0  0  0  0  0  0  1
     :   g   :            0 0 0 1       1  0  0  1  1  1  1
      -------             0 0 1 0       0  0  1  0  0  1  0
   e :       : c          0 0 1 1       0  0  0  0  1  1  0
     :       :            0 1 0 0       1  0  0  1  1  0  0
      -------             0 1 0 1       0  1  0  0  1  0  0
         d                0 1 1 0       0  1  0  0  0  0  0
                          0 1 1 1       0  0  0  1  1  1  1
                          1 0 0 0       0  0  0  0  0  0  0
                          1 0 0 1       0  0  0  0  1  0  0
                          1 0 1 0       0  0  0  1  0  0  0
                          1 0 1 1       1  1  0  0  0  0  0
                          1 1 0 0       0  1  1  0  0  0  1
                          1 1 0 1       1  0  0  0  0  1  0
                          1 1 1 0       0  1  1  0  0  0  0
                          1 1 1 1       0  1  1  1  0  0  0

@COMMON PRODUCT TERM
ZER = /z * /y * /x * /w  ;
ONE = /z * /y * /x *  w  ;
TWO = /z * /y *  x * /w  ;
THR = /z * /y *  x *  w  ;
FOU = /z *  y * /x * /w  ;
FIV = /z *  y * /x *  w  ;
SIX = /z *  y *  x * /w  ;
SEV = /z *  y *  x *  w  ;
EIG =  z * /y * /x * /w  ;
NIN =  z * /y * /x *  w  ;
AAA =  z * /y *  x * /w  ;
BBB =  z * /y *  x *  w  ;
CCC =  z *  y * /x * /w  ;
DDD =  z *  y * /x *  w  ;
EEE =  z *  y *  x * /w  ;
FFF =  z *  y *  x *  w  ;
```

TB01020S

Figure 3. Boolean Equation for Binary-to-7 Segment Decoder

```
@LOGIC EQUATION
/SEG_A =  ONE + FOU + BBB + DDD                  ;
/SEG_B =  FIV + SIX + BBB + CCC + EEE + FFF      ;
/SEG_C =  TWO + CCC + EEE + FFF                  ;
/SEG_D =  ONE + FOU + SEV + AAA + FFF            ;
/SEG_E =  ONE + THR + FOU + FIV + SEV + NIN      ;
/SEG_F =  ONE + TWO + THR + SEV + DDD            ;
/SEG_G =  ZER + ONE + SEV + CCC                  ;

@I/O DIRECTION 150/1, 152/3, 154-9
"
**************************************************************************
*             OUTPUTS ARE ENABLED WHEN /OE GOES LOW.                     *
*             THEREFORE, D1...D7 = /(/OE)  =  OE      ;                  *
**************************************************************************
"
D1 = OE  ;
D2 = OE  ;
D3 = OE  ;
D4 = OE  ;
D5 = OE  ;
D6 = OE  ;
D7 = OE  ;

"
**************************************************************************
*                        END OF LOGIC EQUATIONS                          *
**************************************************************************
"
```

TB01030S

Figure 3 (Continued)

In this example, an Active-Low output goes Low when a segment is to be turned on. The truth table shown in Table 1 is translated into an H/L programming table as shown in Table 2. Since the LED display used here is common anode, the output polarity of each output pin is programmed "L" so that an output goes low when a segment is to be turned on. The decoder takes 16 AND terms. Notice that all outputs go Low when input equals "8". If the logic is written for "0s" instead of "1s", one AND term could be saved. Table 3 shows that the same circuit may be implemented by using only 15 AND terms. Notice that the polarity is the reverse of that of Table 2. The outputs may be turned on and off by I_7, /OE, which controls the 7 tri-state output buffers through control terms (AND terms D_1 to D_7). The same design is also implemented using Boolean equations with AMAZE. Figures 2 through 4 are, respectively, pin list, logic equations, and logic simulation results of the hex-to-7 segment decoder circuit generated by AMAZE. Table 4 is the H/L table generated by AMAZE. In the process of generating Boolean equations for the decoder, common product terms are used to economize the usage of AND terms.

Table 4. H/L Table Generated by AMAZE for Binary-to-7 Segment Decoder

```
Cust/Project - *********************** DAVID K. WONG
Date         - *********************** OCT 1, 1984
Rev/I. D.    - *********************** REV. -

82S153                                 !     POLARITY      !
---                                    _____________________
 T !                                   !H:H:H:H:H:H:H:H:H:H!
 E !--------------------------------------------------------
 R !       I       !        B(i)       !        B(o)       !
 M !--------------------------------------------------------
___!7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!
  0!- - - -,L L L H!- -,- - - -,- - - -!A A,A . . A,A A A A!
  1!- - - -,L H L L!- -,- - - -,- - - -!A A,A . . A,A . . A!
  2!- - - -,H L H H!- -,- - - -,- - - -!A A,A A . .,. . . A!
  3!- - - -,H H L H!- -,- - - -,- - - -!A A,A . . .,. A . A!
  4!- - - -,L H L H!- -,- - - -,- - - -!A A,. A . .,A . . A!
  5!- - - -,L H H L!- -,- - - -,- - - -!A A,. A . .,. . . A!
  6!- - - -,H H L L!- -,- - - -,- - - -!A A,. A A .,. . A A!
  7!- - - -,H H H L!- -,- - - -,- - - -!A A,. A A .,. . . A!
  8!- - - -,H H H H!- -,- - - -,- - - -!A A,. A A A,. . . A!
  9!- - - -,L L H L!- -,- - - -,- - - -!A A,. . A .,. A . A!
 10!- - - -,L H H H!- -,- - - -,- - - -!A A,. . . A,A A A A!
 11!- - - -,H L L H!- -,- - - -,- - - -!A A,. . . .,A . . A!
 12!- - - -,H L H L!- -,- - - -,- - - -!A A,. . . A,. . . A!
 13!- - - -,L L H H!- -,- - - -,- - - -!A A,. . . .,A A . A!
 14!- - - -,L L L L!- -,- - - -,- - - -!A A,. . . .,. . A A!
 15!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 16!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 17!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 18!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 19!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 23!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D8!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D7!L - - -,- - - -!- -,- - - -,- - - -!
 D6!L - - -,- - - -!- -,- - - -,- - - -!
 D5!L - - -,- - - -!- -,- - - -,- - - -!
 D4!L - - -,- - - -!- -,- - - -,- - - -!
 D3!L - - -,- - - -!- -,- - - -,- - - -!
 D2!L - - -,- - - -!- -,- - - -,- - - -!
 D1!L - - -,- - - -!- -,- - - -,- - - -!
 D0!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!

    / N N N Z Y X W N N / / / / / / / N N N / / / / / / / N
    O / / /         / / S S S S S S S / / / S S S S S S S /
    E C C C         C C E E E E E E E C C C E E E E E E E C
                        G G G G G G G       G G G G G G G

                        _ _ _ _ _ _ _       _ _ _ _ _ _ _
                        A B C D E F G       A B C D E F G
```

TB01040S

```
82S153    A:7deco153.STD
" 4-bit binary to 7-segment decoder simulation
"
"  INPUTS  <=B(I/O)=>   TRACE TERMS
" 76543210 9876543210
"
  00000000 ..LLLLLLH. ;
  00000001 ..HLLHHHH. ;
  00000010 ..LLHLLHL. ;
  00000011 ..LLLLHHL. ;
  00000100 ..HLLHHLL. ;
  00000101 ..LHLLHLL. ;
  00000110 ..LHLLLLL. ;
  00000111 ..LLLHHHH. ;
  00001000 ..LLLLLLL. ;
  00001001 ..LLLLHLL. ;
  00001010 ..LLLHLLL. ;
  00001011 ..HHLLLLL. ;
  00001100 ..LHHLLLH. ;
  00001101 ..HLLLLHL. ;
  00001110 ..LHHLLLL. ;
  00001111 ..LHHHLLL. ;
  10001111 .......... ;
  10000000 .......... ;
"
" X------- ----------   I/O CONTROL LINES
"          IIBBBBBBBI   DESIGNATED I/O USAGE
"          IIBBBBBBBI   ACTUAL I/O USAGE
"
" PIN LIST...
" 08 07 06 05 04 03 02 01 19 18 17 16 15 14 13 12 11 09 ;
```

TB01050S

Figure 4

```
####################### P I N   L I S T #######################

   LABEL      ** FNC **PIN --------- PIN** FNC **    LABEL
W             ** I   **  1-:         :-20 ** +5V **VCC
X             ** I   **  2-:         :-19 ** B   **N/C
Y             ** I   **  3-:         :-18 ** B   **N/C
Z             ** I   **  4-:    8    :-17 ** B   **/SEG_A
N/C           ** I   **  5-:    2    :-16 ** B   **/SEG_B
N/C           ** I   **  6-:    S    :-15 ** B   **/SEG_C
N/C           ** I   **  7-:    1    :-14 ** /B  **/SEG_D
/OE           ** I   **  8-:    5    :-13 ** /B  **/SEG_E
N/C           ** B   **  9-:    3    :-12 ** /B  **/SEG_F
GND           ** OV  ** 10-:         :-11 ** /B  **/SEG_G
                             ---------
```

TB01060S

Figure 5. Pin List of Binary-to-7 Segment Decoder Generated by AMAZE

BCD-To-7 Segment Decoder

Using the same principle as in the previous example, a BCD input may be converted to a 7 segment display. If the input will always be within the range of 0000B to 1001B, the design will take ten AND terms to implement the decoding function. But if the display of an error message is desired when input exceeds 1001B, the design shown in Figures 5 and 6 and Table 5, may be used. Alternatively, the error message ''E'' will be displayed if the input does not equal anything between 0000B and 1001B inclusively. The circuit used to detect that none of the ten AND terms being true is shown in Figure 7 where if the input is outside of the range of 0000B to 1001B, none of the terms ZER to NIN will be active, which in turn causes the output of the NOR term to be High. The High output then causes the ''E'' term to be active and thus an output ''E'' is displayed. This scheme takes two propagation delays before ''E'' is displayed but only one delay for ''0'' to ''9'' to be displayed. The circuit shown in Figure 7 is implemented as shown in Table 4, column $B(O)_0$ of terms 0 to 9, and term #11. The output $B(O)_0$ becomes High when terms 0 to 9 are inactive, $(T_0 + T_1 + T_2 + T_3 + T_4 + T_5 + T_6 + T_7 + T_8 + T_9) = 0$ where T_0 is term #0, T_1 is term #1, T_2 is . . ., etc. $B(O)_0$ is then fed back to the input of term #11 which, when active, causes outputs B and C to be High, segments B and C to turn off and the other segments to turn on. Term #10 is left blank to separate the main decoding function and the feedback function for the sake of clarity of this demonstration. A similar feature (the COMPLEMENT ARRAY) may be found in PLS155/157/159 where the feedback path is buried inside the chip without having to use up one I/O pin. Notice that this feature greatly reduces the number of AND terms needed. But for device architectures which do not allow common AND terms, this logic minimization will not be possible. Figure 8 and Table 6 implement design with AMAZE. The circuit is then simulated as shown in Figure 9.

4-Bit Binary-To-7 Segment Decoder

```
N@DEVICE TYPE
82S153
@DRAWING
*********************** BCD-TO-7 SEGMENT DECODER
@REVISION
*********************** REV. -
@DATE
*********************** OCT 1, 1984
@SYMBOL
*********************** FILE ID: BCD-7153
@COMPANY
*********************** SIGNETICS
@NAME
*********************** DAVID K. WONG
@DESCRIPTION
*************************************************************************
*   This circuit converts a 4-bit BCD code into a 7-segment display.    *
*   The display is a common anode 7-segment LED.                        *
*   The output of the 82S153 goes LOW for each segment that is ON.      *
*************************************************************************

                                    TRUTH TABLE
         a             Z Y X W         a  b  c  d  e  f  g
      --------        ------------------------------------
   f :       : b       0 0 0 0         0  0  0  0  0  0  1
     :   g   :         0 0 0 1         1  0  0  1  1  1  1
      --------         0 0 1 0         0  0  1  0  0  1  0
   e :       : c       0 0 1 1         0  0  0  0  1  1  0
     :       :         0 1 0 0         1  0  0  1  1  0  0
      --------         0 1 0 1         0  1  0  0  1  0  0
          d            0 1 1 0         0  1  0  0  0  0  0
                       0 1 1 1         0  0  0  1  1  1  1
                       1 0 0 0         0  0  0  0  0  0  0
                       1 0 0 1         0  0  0  0  1  0  0

                       1 0 1 0         1  0  0  1  1  1  1  Display E (error)
                       1 0 1 1         1  0  0  1  1  1  1      "
                       1 1 0 0         1  0  0  1  1  1  1      "
                       1 1 0 1         1  0  0  1  1  1  1      "
                       1 1 1 0         1  0  0  1  1  1  1      "
                       1 1 1 1         1  0  0  1  1  1  1      "


@COMMON PRODUCT TERM
ZER = /z * /y * /x * /w  ;
ONE = /z * /y * /x *  w  ;
TWO = /z * /y *  x * /w  ;
THR = /z * /y *  x *  w  ;
FOU = /z *  y * /x * /w  ;
FIV = /z *  y * /x *  w  ;
SIX = /z *  y *  x * /w  ;
SEV = /z *  y *  x *  w  ;
EIG =  z * /y * /x * /w  ;
NIN =  z * /y * /x *  w  ;
AAA =  z * /y *  x * /w  ;
BBB =  z * /y *  x *  w  ;
CCC =  z *  y * /x * /w  ;
DDD =  z *  y * /x *  w  ;
EEE =  z *  y *  x * /w  ;
FFF =  z *  y *  x *  w  ;
```

TB01071S

Figure 6. Boolean Equations for BCD-to-7 Segment Decoder for AMAZE

4-Bit Binary-To-7 Segment Decoder

AN10



```
@LOGIC EQUATION
/SEG_A =      ONE + FOU + AAA
/SEG_B =      FIV + SIX
/SEG_C =      TWO
/SEG_D =   /( ZER + TWO + THR
/SEG_E =   /( ZER + TWO + SIX
/SEG_F =   /( ZER + FOU + FIV
/SEG_G =   /( TWO + THR + FOU

@I/O DIRECTION 150/1, 152/3,
"
******************************
*             OUTPUTS ARE ENA
*             THEREFORE, D1..
******************************
"
D1  = OE  ;
D2  = OE  ;
D3  = OE  ;
D4  = OE  ;
D5  = OE  ;
D6  = OE  ;
D7  = OE  ;

"
******************************
*                         END
******************************
"
```

TB01081S

Figure 6 (Continued)



$\overline{\text{ZER + ONE + ... NIN}}$
E
NIN
ONE
ZER
ZER + ONE + ... NIN

LD01160S

Figure 7. Complement Array — "None of the Above" Detection Circuit

Table 5. H/L Table for BCD-to-7 Segment Decoder Generated by AMAZE

```
Cust/Project - ************************ DAVID K. WONG
Date         - ************************ OCT 1, 1984
Rev/I. D.    - ************************ REV. -

82S153                                 !     POLARITY       !
___                                    _____________________
 T !                                   !H:H:H:H:H:L:L:L:L:H!
 E !--------------------------------------------------------
 R !       I       !        B(i)       !        B(o)       !
 M !--------------------------------------------------------
___!7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!
  0!- - - -,L L L H!- -,- - - -,- - - -!A A,A . . .,. . . A!
  1!- - - -,L H L L!- -,- - - -,- - - -!A A,A . . .,. A A A!
  2!- - - -,H L H L!- -,- - - -,- - - -!A A,A . . .,. . . A!
  3!- - - -,H L H H!- -,- - - -,- - - -!A A,A . . .,. . . A!
  4!- - - -,H H L L!- -,- - - -,- - - -!A A,A . . .,. . . A!
  5!- - - -,H H L H!- -,- - - -,- - - -!A A,A . . .,. . . A!
  6!- - - -,H H H L!- -,- - - -,- - - -!A A,A . . .,. . . A!
  7!- - - -,H H H H!- -,- - - -,- - - -!A A,A . . .,. . . A!
  8!- - - -,L H L H!- -,- - - -,- - - -!A A,. A . A,. A A A!
  9!- - - -,L H H L!- -,- - - -,- - - -!A A,. A . A,A A A A!
 10!- - - -,L L H L!- -,- - - -,- - - -!A A,. . A A,A . A A!
 11!- - - -,L L L L!- -,- - - -,- - - -!A A,. . . A,A A . A!
 12!- - - -,L L H H!- -,- - - -,- - - -!A A,. . . A,. . A A!
 13!- - - -,H L L L!- -,- - - -,- - - -!A A,. . . A,A A A A!
 14!- - - -,H L L H!- -,- - - -,- - - -!A A,. . . A,. A A A!
 15!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 16!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 17!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 18!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 19!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 23!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D8!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D7!L - - -,- - - -!- -,- - - -,- - - -!
 D6!L - - -,- - - -!- -,- - - -,- - - -!
 D5!L - - -,- - - -!- -,- - - -,- - - -!
 D4!L - - -,- - - -!- -,- - - -,- - - -!
 D3!L - - -,- - - -!- -,- - - -,- - - -!
 D2!L - - -,- - - -!- -,- - - -,- - - -!
 D1!L - - -,- - - -!- -,- - - -,- - - -!
 D0!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!

    / N N N Z Y X W N N / / / / / / / N N N / / / / / / / N
    O / / /         / / S S S S S S S / / / S S S S S S S /
    E C C C         C C E E E E E E E C C C E E E E E E E C
                        G G G G G G G       G G G G G G G

                        _ _ _ _ _ _ _       _ _ _ _ _ _ _
                        A B C D E F G       A B C D E F G
```

TB01090S

4-Bit Binary-To-7 Segment Decoder

AN10

```
@DEVICE TYPE
************************ 82S153
@DRAWING
************************ BINARY-TO-7 SEGMENT DECODER
@REVISION
************************ REV. -
@DATE
************************ OCT 1, 1984
@SYMBOL
************************ FILE ID: BCD77153
@COMPANY
************************ SIGNETICS
@NAME
************************ DAVID K. WONG
@DESCRIPTION
**************************************************************************
*   This circuit converts a 4-bit BCD code into a 7-segment display.     *
*   The display is a common anode 7-segment LED.                         *
*   The output of the 82S153 goes LOW for each segment that is ON.       *
**************************************************************************

                                                TRUTH TABLE
             a                 Z Y X W        a  b  c  d  e  f  g
          -------             -------------------------------------
      f :         : b          0 0 0 0        0  0  0  0  0  0  1
        :    g    :            0 0 0 1        1  0  0  1  1  1  1
          -------              0 0 1 0        0  0  1  0  0  1  0
      e :         : c          0 0 1 1        0  0  0  0  1  1  0
        :         :            0 1 0 0        1  0  0  1  1  0  0
          -------              0 1 0 1        0  1  0  0  1  0  0
             d                 0 1 1 0        0  1  0  0  0  0  0
                               0 1 1 1        0  0  0  1  1  1  1
                               1 0 0 0        0  0  0  0  0  0  0
                               1 0 0 1        0  0  0  0  1  0  0

           Over Range          1 0 1 0        0  1  1  0  0  0  0  Display E (error)
                "              1 0 1 1        0  1  1  0  0  0  0         "
                "              1 1 0 0        0  1  1  0  0  0  0         "
                "              1 1 0 1        0  1  1  0  0  0  0         "
                "              1 1 1 0        0  1  1  0  0  0  0         "
                "              1 1 1 1        0  1  1  0  0  0  0         "


@COMMON PRODUCT TERM
ZER = /z * /y * /x * /w  ;
ONE = /z * /y * /x *  w  ;
TWO = /z * /y *  x * /w  ;
THR = /z * /y *  x *  w  ;
FOU = /z *  y * /x * /w  ;
FIV = /z *  y * /x *  w  ;
SIX = /z *  y *  x * /w  ;
SEV = /z *  y *  x *  w  ;
EIG =  z * /y * /x * /w  ;
NIN =  z * /y * /x *  w  ;
```

TB01101S

Figure 8. Boolean Equation for BCD-to-7 Segment Decoder

```
@LOGIC EQUATION

"
****************************************************************************
*  When input is greater than 9, OVR ( Over Range ) will go HIGH, WHICH    *
*  will be fed-back to the AND array to control the segments.              *
*  Here the OVR pin and the feedback loop is used as COMPLEMENT ARRAY.     *
*  The COMPLEMENT ARRAY saves 5 P-terms but loses one I/O pin.             *
****************************************************************************
"

OVR = /( ZER + ONE + TWO + THR + FOU + FIV + SIX + SEV + EIG + NIN  ) ;
/SEG_A =     ONE + FOU                                             ;
/SEG_B =     FIV + SIX + OVR                                       ;
/SEG_C =     TWO + OVR                                             ;
/SEG_D =     ONE + FOU + SEV                                       ;
/SEG_E =   /( ZER + TWO + SIX + EIG + OVR                        ) ;
/SEG_F =     ONE + TWO + THR + SEV                                 ;
/SEG_G =     ZER + ONE + SEV                                       ;

@I/O DIRECTION 150/1, 152/3, 154-9
"
****************************************************************************
*             OUTPUTS ARE ENABLED WHEN /OE GOES LOW.                       *
*             THEREFORE, D1...D7 = /(/OE)   =  OE      ;                   *
****************************************************************************
"
D1 = OE  ;
D2 = OE  ;
D3 = OE  ;
D4 = OE  ;
D5 = OE  ;
D6 = OE  ;
D7 = OE  ;

"
****************************************************************************
*                        END OF LOGIC EQUATIONS                            *
****************************************************************************
"
```

TB01111S

Figure 8 (Continued)

4-Bit Binary-To-7 Segment Decoder

Table 6. H/L Table of BCD-to-7 Segment Decoder Generated by AMAZE

```
Cust/Project  - ************************ DAVID K. WONG
Date          - ************************ OCT 1, 1984
Rev/I. D.     - ************************ REV. -

82S153                                 !     POLARITY      !
___                                    _____________________
 T !                                   !H:H:H:H:H:H:L:H:H:L!
 E !--------------------------------------------------------
 R !      I        !       B(i)        !       B(o)        !
 M !--------------------------------------------------------
___!7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!
  0!- - - -,L L L L!- -,- - - -,- - - -!A A,. . . .,A . A A!
  1!- - - -,L L L H!- -,- - - -,- - - -!A A,A . . A,. A A A!
  2!- - - -,L L H L!- -,- - - -,- - - -!A A,. . A .,A A . A!
  3!- - - -,L L H H!- -,- - - -,- - - -!A A,. . . .,. A . A!
  4!- - - -,L H L L!- -,- - - -,- - - -!A A,A . . A,. . . A!
  5!- - - -,L H L H!- -,- - - -,- - - -!A A,. A . .,. . . A!
  6!- - - -,L H H L!- -,- - - -,- - - -!A A,. A . .,A . . A!
  7!- - - -,L H H H!- -,- - - -,- - - -!A A,. . . A,. A A A!
  8!- - - -,H L L L!- -,- - - -,- - - -!A A,. . . .,A . . A!
  9!- - - -,H L L H!- -,- - - -,- - - -!A A,. . . .,. . . A!
 10!- - - -,- - - -!- -,- - - -,- - - H!A A,. A A .,A . . .!
 11!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 12!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 13!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 14!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 15!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 16!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 17!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 18!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 19!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 23!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D8!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D7!L - - -,- - - -!- -,- - - -,- - - -!
 D6!L - - -,- - - -!- -,- - - -,- - - -!
 D5!L - - -,- - - -!- -,- - - -,- - - -!
 D4!L - - -,- - - -!- -,- - - -,- - - -!
 D3!L - - -,- - - -!- -,- - - -,- - - -!
 D2!L - - -,- - - -!- -,- - - -,- - - -!
 D1!L - - -,- - - -!- -,- - - -,- - - -!
 D0!- - - -,- - - -!- -,- - - -,- - - -!

    / N N N Z Y X W N N / / / / / / / O N N / / / / / / / O
    O / / /         / / S S S S S S S V / / S S S S S S S V
    E C C C         C C E E E E E E E R C C E E E E E E E R
                        G G G G G G G       G G G G G G G

                        - - - - - - -       - - - - - - -
                        A B C D E F G       A B C D E F G
```

TB01120S



```
82S153   A:bcd77153.STD
" yhgfikuhyfouiy
"
"  INPUTS  <=B(I/O)=>   TRACE TERMS
" 76543210 9876543210
"
  00000000 ..LLLLLLHL ;
  00001111 ..LHHLLLLH ;
  10001111 .........H ;
  00000000 ..LLLLLLHL ;
  01000001 ..HLLHHHHL ;
  01000010 ..LLHLLHLL ;
  01000011 ..LLLLHHLL ;
  01000100 ..HLLHHLLL ;
  01000101 ..LHLLHLLL ;
  01000110 ..LHLLLLLL ;
  01000111 ..LLLHHHHL ;
  01001000 ..LLLLLLLL ;
  01001001 ..LLLLHLLL ;
  01001010 ..LHHLLLLH ;
  01001011 ..LHHLLLLH ;
  01001100 ..LHHLLLLH ;
  01001101 ..LHHLLLLH ;
  01001110 ..LHHLLLLH ;
  01001111 ..LHHLLLLH ;
  11001111 .........H ;
  10000000 .........L ;
"
" X------- ----------   I/O CONTROL LINES
"          IIBBBBBBBO   DESIGNATED I/O USAGE
"          IIBBBBBBBO   ACTUAL I/O USAGE
"
" PIN LIST...
" 08 07 06 05 04 03 02 01 19 18 17 16 15 14 13 12 11 09 ;
```

TB01130S

Figure 9. Simulation Results of H/L Table

BCD-To-7 Segment Decoder with Output Latches

Output latches may be constructed by using the bidirectional I/Os of PLS153/153A as shown in Figure 10. When /LE (latch enable) is High, the output equals the input. But when /LE is Low, the output is latched. Changing the input will not effect the output. Segments a and e are used to illustrate the decoding and latch circuit as shown in Figures 11 and 12 which are expressed in H/L format as shown in Table 8. The complete design of the decoder is shown in Figures 13 and 14 and Table 7. With the output latches, the circuit cannot be tri-stated since the tri-state condition will interrupt the feedback path. An alternative approach is shown in Figure 15 where the display is a common cathode, the segment drivers are always on and the duty cycling is implemented with a digit driver which pulls the common cathode of the display to ground as the input "Duty Cycle" goes High. A common practice is to drive the segments with 10 time the desired DC current and drive the digit with a 10% duty cycle pulse. The H/L implementation is as shown in Tables 9 and 10. The "Duty Cycle" control input is generated externally.


INPUT
OUTPUT
/LE
LD01170S

Figure 10. Block Diagram Of A Simple D-Latch


W
X
Y
Z
/LE
ONE
FOU
AL
SEG_A
LD01180S

Figure 11. Segment-A Latch Circuit



Figure 12. Segment-E Latch



```
####################### P I N   L I S T #######################

   LABEL      ** FNC **PIN ---------- PIN** FNC **     LABEL
W             ** I    **   1-¦         ¦-20 ** +5V **VCC
X             ** I    **   2-¦         ¦-19 ** B   **N/C
Y             ** I    **   3-¦         ¦-18 ** B   **N/C
Z             ** I    **   4-¦    8    ¦-17 ** O   **/SEG_A
N/C           ** I    **   5-¦    2    ¦-16 ** O   **/SEG_B
N/C           ** I    **   6-¦    S    ¦-15 ** O   **/SEG_C
/LE           ** I    **   7-¦    1    ¦-14 ** O   **/SEG_D
N/C           ** I    **   8-¦    5    ¦-13 ** /O  **/SEG_E
OVR           ** /O   **   9-¦    3    ¦-12 ** O   **/SEG_F
GND           ** OV   **  10-¦         ¦-11 ** O   **/SEG_G
                             ----------
```

TB01140S

Figure 13. Pin List of BCD-to-7 Segment Decoder with Latches

4-Bit Binary-To-7 Segment Decoder

AN10



```
@DEVICE TYPE
82S153
@DRAWING
************************ BCD-TO-7 SEGMENT DECODER
@REVISION
************************ REV. -
@DATE
************************ OCT 1, 1984
@SYMBOL
************************ FILE ID: BCD7L153
@COMPANY
************************ SIGNETICS
@NAME
************************ DAVID K. WONG
@DESCRIPTION
**************************************************************************
*   This circuit converts a 4-bit BCD code into a 7-segment display.     *
*   The display is a common anode 7-segment LED.                         *
*   The output of the 82S153 goes LOW for each segment that is ON.       *
*   The outputs are latched when /LE goes LOW.                           *
**************************************************************************

                                             TRUTH TABLE
          a                 Z Y X W        a  b  c  d  e  f  g
       -------             ---------------------------------------
    f |       | b           0 0 0 0        0  0  0  0  0  0  1
      |   g   |             0 0 0 1        1  0  0  1  1  1  1
       -------              0 0 1 0        0  0  1  0  0  1  0
    e |       | c           0 0 1 1        0  0  0  0  1  1  0
      |       |             0 1 0 0        1  0  0  1  1  0  0
       -------              0 1 0 1        0  1  0  0  1  0  0
          d                 0 1 1 0        0  1  0  0  0  0  0
                            0 1 1 1        0  0  0  1  1  1  1
                            1 0 0 0        0  0  0  0  0  0  0
                            1 0 0 1        0  0  0  0  1  0  0

         Over Range         1 0 1 0        0  1  1  0  0  0  0  Display E (error)
              "             1 0 1 1        0  1  1  0  0  0  0        "
              "             1 1 0 0        0  1  1  0  0  0  0        "
              "             1 1 0 1        0  1  1  0  0  0  0        "
              "             1 1 1 0        0  1  1  0  0  0  0        "
              "             1 1 1 1        0  1  1  0  0  0  0        "


@COMMON PRODUCT TERM
ZER = /z * /y * /x * /w * /LE  ;
ONE = /z * /y * /x *  w * /LE  ;
TWO = /z * /y *  x * /w * /LE  ;
THR = /z * /y *  x *  w * /LE  ;
FOU = /z *  y * /x * /w * /LE  ;
FIV = /z *  y * /x *  w * /LE  ;
SIX = /z *  y *  x * /w * /LE  ;
SEV = /z *  y *  x *  w * /LE  ;
EIG =  z * /y * /x * /w * /LE  ;
NIN =  z * /y * /x *  w * /LE  ;

"
**************************************************************************
*                  Feedback circuits to form D-latches.                  *
**************************************************************************
```

TB01150S

Figure 14. Boolean Equation of BCD-to-7 Segment Decoder with Latches

```
"
AL   =  LE * /SEG_A  ;
BL   =  LE * /SEG_B  ;
CL   =  LE * /SEG_C  ;
DL   =  LE * /SEG_D  ;
EL   =  LE *  SEG_E  ; "Note that in LOGIC EQUATION definition, SEG_E is
                        inverted. Therefore, the feedback for E has to
                        be inverted too."
FL   =  LE * /SEG_F  ;
GL   =  LE * /SEG_G  ;

@LOGIC EQUATION

"
****************************************************************************
*  When input is greater than 9, OVR ( Over Range ) will go HIGH, WHICH    *
*  will be fed-back to the AND array to control the segments.              *
*  Here the OVR pin and the feedback loop is used as COMPLEMENT ARRAY.     *
*  The COMPLEMENT ARRAY saves 5 P-terms but uses up one I/O pin.           *
****************************************************************************
"

OVR = /( ZER + ONE + TWO + THR + FOU + FIV + SIX + SEV + EIG + NIN + LE ) ;
/SEG_A =      ONE + FOU +  AL                                      ;
/SEG_B =      FIV + SIX + OVR + BL                                 ;
/SEG_C =      TWO + OVR +  CL                                      ;
/SEG_D =      ONE + FOU + SEV + DL                                 ;
/SEG_E =   /( ZER + TWO + SIX + EIG + OVR + EL                   ) ;
/SEG_F =      ONE + TWO + THR + SEV + FL                           ;
/SEG_G =      ZER + ONE + SEV + GL                                 ;

@I/O DIRECTION
"
****************************************************************************
*                          END OF LOGIC EQUATIONS                          *
****************************************************************************
"
```

TB01160S

Figure 14 (Continued)

Table 7. H/L Table of BCD-to-7 Segment Decoder with Latches

```
Cust/Project  - ************************ DAVID K. WONG
Date          - ************************ OCT 1, 1984
Rev/I. D.     - ************************ REV. -

82S153                                 !     POLARITY       !
---                                    ---------------------
 T !                                   !H:H:H:H:H:H:L:H:H:L!
 E !--------------------------------------------------------
 R !      I        !       B(i)        !       B(o)        !
 M !--------------------------------------------------------
___!7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!
  0!- H - -,L L L L!- -,- - - -,- - - -!A A,. . . .,A . A A!
  1!- H - -,L L L H!- -,- - - -,- - - -!A A,A . . A,. A A A!
  2!- H - -,L L H L!- -,- - - -,- - - -!A A,. . A .,A A . A!
  3!- H - -,L L H H!- -,- - - -,- - - -!A A,. . . .,. A . A!
  4!- H - -,L H L L!- -,- - - -,- - - -!A A,A . . A,. . . A!
  5!- H - -,L H L H!- -,- - - -,- - - -!A A,. A . .,. . . A!
  6!- H - -,L H H L!- -,- - - -,- - - -!A A,. A . .,A . . A!
  7!- H - -,L H H H!- -,- - - -,- - - -!A A,. . . A,. A A A!
  8!- H - -,H L L L!- -,- - - -,- - - -!A A,. . . .,A . . A!
  9!- H - -,H L L H!- -,- - - -,- - - -!A A,. . . .,. . . A!
 10!- L - -,- - - -!- -,- - - -,- - - -!A A,. . . .,. . . A!
 11!- L - -,- - - -!- -,H - - -,- - - -!A A,A . . .,. . . .!
 12!- - - -,- - - -!- -,- - - -,- - - H!A A,. A A .,A . . .!
 13!- L - -,- - - -!- -,- H - -,- - - -!A A,. A . .,. . . .!
 14!- L - -,- - - -!- -,- - H -,- - - -!A A,. . A .,. . . .!
 15!- L - -,- - - -!- -,- - - H,- - - -!A A,. . . A,. . . .!
 16!- L - -,- - - -!- -,- - - -,L - - -!A A,. . . .,A . . .!
 17!- L - -,- - - -!- -,- - - -,- H - -!A A,. . . .,. A . .!
 18!- L - -,- - - -!- -,- - - -,- - H -!A A,. . . .,. . A .!
 19!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 23!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D8!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!
 D7!- - - -,- - - -!- -,- - - -,- - - -!
 D6!- - - -,- - - -!- -,- - - -,- - - -!
 D5!- - - -,- - - -!- -,- - - -,- - - -!
 D4!- - - -,- - - -!- -,- - - -,- - - -!
 D3!- - - -,- - - -!- -,- - - -,- - - -!
 D2!- - - -,- - - -!- -,- - - -,- - - -!
 D1!- - - -,- - - -!- -,- - - -,- - - -!
 D0!- - - -,- - - -!- -,- - - -,- - - -!

    N / N N Z Y X W N N / / / / / / / O N N / / / / / / / O
    / L / /         / / S S S S S S S V / / S S S S S S S V
    C E C C         C C E E E E E E E R C C E E E E E E E R
                            G G G G G G G       G G G G G G G

                            - - - - - - -       - - - - - - -
                            A B C D E F G       A B C D E F G
```

TB01170S


TC01710S
Vcc
SEGMENT g
SEGMENT f
SEGMENT e
SEGMENT d
SEGMENT c
SEGMENT b
SEGMENT a
DUTY CYCLE

Figure 15. Segment Drivers and Digit Driver

4-Bit Binary-To-7 Segment Decoder

Table 8. BCD-to-7 Segment Decoder Using Complement Array

82S153/153A PROGRAMMING TABLE DRAWING ID: BCD TO 7SEG DECODER REV. –
DESIGNER: D.K. WONG DATE: 12/15/84

POLARITY																			H	H	H	H	H	H	H	H	H	L	
	AND																		OR										
	I								B(I)										B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	
0	-	-	-	-	L	L	L	L	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	•	•	•	A	A	
1	-	-	-	-	L	L	L	H	-	-	-	-	-	-	-	-	-	-	•	•	A	•	•	A	A	A	A	A	
2	-	-	-	-	L	L	H	L	-	-	-	-	-	-	-	-	-	-	•	•	•	•	A	•	•	A	•	A	
3	-	-	-	-	L	L	H	H	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	•	A	A	•	A	
4	-	-	-	-	L	H	L	L	-	-	-	-	-	-	-	-	-	-	•	•	A	•	•	A	A	•	•	A	
5	-	-	-	-	L	H	L	H	-	-	-	-	-	-	-	-	-	-	•	•	•	A	•	•	A	•	•	A	
6	-	-	-	-	L	H	H	L	-	-	-	-	-	-	-	-	-	-	•	•	•	A	•	•	•	•	•	A	
7	-	-	-	-	L	H	H	H	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	A	A	A	A	A	
8	-	-	-	-	H	L	L	L	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	•	•	•	•	A	(*)
9	-	-	-	-	H	L	L	H	-	-	-	-	-	-	-	-	-	-	•	•	•	•	•	•	A	•	•	A	
10																													
11	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	•	•	•	A	A	•	•	•	•	•	"E" FOR OVER-RANGE.
12																													B(O)0 AND TERM 11
13																													FORM A COMPLEMENT
14																													ARRAY.
15																													
16																													
17																													
18																													
19																													
20																													
21																													
22																													
23																													
24																													
25																													
26																													
27																													
28																													
29																													
30																													
31																													
D9																													(*) NOTICE THAT IN THIS PARTICULAR
D8																													APPLICATION, THIS TERM MUST BE
D7	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											PRESENT FOR THE COMPLEMENT
D6	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											ARRAY TO FUNCTION PROPERLY.
D5	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D4	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D3	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D2	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D1	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D0	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
NAME	/OE				Z	Y	X	W										/OVR			A	B	C	D	E	F	G	/OVR	

TB01180S

Table 9. Segments A and E with Latches

82S153/153A PROGRAMMING TABLE DRAWING ID:________ REV. ________

DESIGNER: ________ DATE: ________

	AND																		POLARITY										
																					H	H	H	H	L	H	H	L	
																			OR										
	I								B(I)										B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	
0	H	-	-	-	L	L	L	H	-	-	-	-	-	-	-	-	-	-			A								$\overline{A} = LE * w * \overline{X} * \overline{Y} * \overline{Z}$
1	H	-	-	-	L	H	L	L	-	-	-	-	-	-	-	-	-	-			A								$+ LE * \overline{w} * \overline{X} * Y * \overline{Z}$
2	L	-	-	-	-	-	-	-	-	-	H	-	-	-	-	-	-	-			A								$+ \overline{LE} * A$
3																													
4																													
5	H	-	-	-	L	L	L	L	-	-	-	-	-	-	-	-	-	-							A				$E = LE * \overline{W} * \overline{X} * \overline{Y} * \overline{Z}$
6	H	-	-	-	L	L	H	L	-	-	-	-	-	-	-	-	-	-							A				$+ LE * \overline{W} * \overline{X} * Y * \overline{Z}$
7	H	-	-	-	L	H	H	L	-	-	-	-	-	-	-	-	-	-							A				$+ LE * \overline{W} * X * Y * \overline{Z}$
8	H	-	-	-	H	L	L	L	-	-	-	-	-	-	-	-	-	-							A				$+ LE * W * \overline{X} * \overline{Y} * \overline{Z}$
9	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H							A				$+ LE * OVR$
10	L	-	-	-	-	-	-	-	-	-	-	-	-	-	L	-	-	-							A				$+ \overline{LE} * \overline{E}$
11																													
12																												A	OVR=1 IF INPUT≠0-9
13																													
14																													
15																													
16																													
17																													
18																													
19																													
20																													
21																													
22																													
23																													
24																													
25																													
26																													
27																													
28																													
29																													
30																													
31																													
D9																													
D8																													
D7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D6																													
D5																													
D4																													
D3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D2																													
D1																													
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
NAME	LE				Z	Y	X	W			A				E			OVR			A				E			OVR	

TB01191S

4-Bit Binary-To-7 Segment Decoder

Table 10. H/L Table of BCD-to-7 Segment Decoder with Latches with Outputs Active-High

82S153/153A PROGRAMMING TABLE DRAWING ID: BCD7LM REV. –
DESIGNER: D.K. WONG DATE: 12/26/84.

	AND																		OR										
	I								B(I)										B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	
POLARITY																					L	L	L	L	L	L	L	L	
0	-	H	-	-	L	L	L	L	-	-	-	-	-	-	-	-	-	-			·	·	·	·	·	·	A	A	0
1	-	H	-	-	L	L	L	H	-	-	-	-	-	-	-	-	-	-			A	·	·	A	A	A	A	A	1
2	-	H	-	-	L	L	H	L	-	-	-	-	-	-	-	-	-	-			·	·	A	·	·	A	·	A	2
3	-	H	-	-	L	L	H	H	-	-	-	-	-	-	-	-	-	-			·	·	·	·	A	A	·	A	3
4	-	H	-	-	L	H	L	L	-	-	-	-	-	-	-	-	-	-			A	·	·	A	A	·	·	A	4
5	-	H	-	-	L	H	L	H	-	-	-	-	-	-	-	-	-	-			·	A	·	·	A	·	·	A	5
6	-	H	-	-	L	H	H	L	-	-	-	-	-	-	-	-	-	-			·	A	·	·	·	·	·	A	6
7	-	H	-	-	L	H	H	H	-	-	-	-	-	-	-	-	-	-			·	·	·	A	A	A	A	A	7
8	-	H	-	-	H	L	L	L	-	-	-	-	-	-	-	-	-	-			·	·	·	·	·	·	·	A	8
9	-	H	-	-	H	L	L	H	-	-	-	-	-	-	-	-	-	-			·	·	·	·	A	·	·	A	9
10																													
11	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H			·	A	A	·	·	·	·	·	E (ERROR)
12																													
13	-	L	-	-	-	-	-	-	-	-	L	-	-	-	-	-	-	-			A	·	·	·	·	·	·	·	SEG A LATCH
14	-	L	-	-	-	-	-	-	-	-	-	L	-	-	-	-	-	-			·	A	·	·	·	·	·	·	" B "
15	-	L	-	-	-	-	-	-	-	-	-	-	L	-	-	-	-	-			·	·	A	·	·	·	·	·	" C "
16	-	L	-	-	-	-	-	-	-	-	-	-	-	L	-	-	-	-			·	·	·	A	·	·	·	·	" D "
17	-	L	-	-	-	-	-	-	-	-	-	-	-	-	L	-	-	-			·	·	·	·	A	·	·	·	" E "
18	-	L	-	-	-	-	-	-	-	-	-	-	-	-	-	L	-	-			·	·	·	·	·	A	·	·	" F "
19	-	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	L	-			·	·	·	·	·	·	A	·	" G "
20																													
21																													
22																													
23																													
24																													
25																													
26																													
27																													
28																													
29																													
30																													
31																													
D9																													ALL OUTPUT POLARITIES ARE INVERTED
D8																													SO THAT AN "A" CAUSES A "LOW" OUTPUT,
D7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											A "·" CAUSES A "HIGH" OUTPUT.
D6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											SINCE ALL OUTPUTS ARE INVERTED, THE
D4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											FEEDBACK CIRCUITS FOR THE LATCHES
D3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											ARE ALSO INVERTED
D2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											
D1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											THE OVR OUTPUT CREATES THE "ERROR"
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-											DISPLAY IF INPUT ≠ (0 TO 9)
NAME		/LE			Z	Y	X	W										OVR			A	B	C	D	E	F	G	OVR	

TB01200S

Signetics

Application Specific Products

AN11
PLD Programmable Retriggerable One-Shot

Application Note

Author: David Wong

FEATURES

- **Programmable pulse-width/delay**
- **Maximum 256 clock cycles**
- **Asynchronous TRIGGER input**
- **Active-High and Active-Low outputs**
- **Asynchronous RESET**
- **20-pin package**

THEORY OF OPERATION

The one-shot consists of an FPLS PLS159 and an external clock which may be part of the system in which this one-shot is to work. As shown in Figure 1 and Table 1 the FPLS is configured to have a latch and an eight-bit binary up counter which is presettable by input data to any number less than 256. Since the input data is inverted before it is loaded into the registers, counting from the complements of the input to FF will give the correct number of counts as counting from the input down to 00.

Pulse-width/delay inputs may be the outputs of another device or switches. When /RESET goes Low, flip-flops are set to all 1's (terms PB and PA). At the rising edge of the next clock, data is latched into the registers (terms LB and LA). When /TRIG goes Low, it is latched into the input latch formed by term # 0, 1, 2 and 13. The output O_1 of the latch goes High and O_2 goes Low which enables the 8-bit counting cycle. The O_1 and $/O_1$ will maintain their output levels until the end of the counting cycle at which time the counter reaches the count FF, resets the latch by term # 13, and sets O_2 High. At the rising edge of the next clock, terms LA and LB cause data to be loaded again into the registers, and the device is ready for another /TRIG input. The output wave-forms are illustrated in Figure 2.

If the /TRIG pulse-width is longer than the desired pulse-width of the one-shot, the device will react as mentioned above, and at the end of the count cycle new data will be loaded, another count cycle begins while the outputs remain set by the /TRIG input without changing throughout the change-over of one count cycle to another. O_{1a}, on the other hand, will go Low for one clock period at the change-over. As long as the /TRIG is Low, O_{1a} will continue to pulse Low for one clock period at the change-over of one count cycle to another. The output O_2 will pulse High for one clock cycle at the change-over. Figure 2 illustrates output wave-forms for both cases. The output wave-forms are as illustrated in Figure 2.

The one-shot is implemented by programming the PLS159 as shown in Table 1. The logic representation of the program is shown in Figure 3.



Figure 1. Programmable Retriggerable One-Shot

PLD Programmable Retriggerable One-Shot

Table 1. PLS159 FPLS Program Table

PROGRAMMABLE RETRIGGERABLE ONE-SHOT

											FF MODE									E_B				E_A				POLARITY				
											A	A	A	A	A	A	A	A		–				–				L	L	H	H	
	TERM	AND																	REMARK	(OR)												REMARK
		C	I				B(I)				Q(P)									Q(N)								B(O)				
			3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
	0	–	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	LATCH	–	–	–	–	–	–	–	–	A	●	●	A	$B_0 = \overline{B_3}$
	1	–	–	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	"	–	–	–	–	–	–	–	–	A	●	●	A	
	2	–	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	"	–	–	–	–	–	–	–	–	●	A	●		
	3																															
	4	–	–	–	H	–	–	H	–	–	–	–	–	–	–	–	–	–	COUNT CYCLE	–	–	–	–	–	–	–	O	●	●	●	●	
	5	–	–	–	H	–	–	H	–	–	–	–	–	–	–	–	–	H		–	–	–	–	–	–	O	–	●	●	●	●	
	6	–	–	–	H	–	–	H	–	–	–	–	–	–	–	–	H	H		–	–	–	–	–	O	–	–	●	●	●	●	
	7	–	–	–	H	–	–	H	–	–	–	–	–	–	–	H	H	H		–	–	–	–	O	–	–	–	●	●	●	●	
	8	–	–	–	H	–	–	H	–	–	–	–	–	–	H	H	H	H		–	–	–	O	–	–	–	–	●	●	●	●	
	9	–	–	–	H	–	–	H	–	–	–	–	–	H	H	H	H	H		–	–	O	–	–	–	–	–	●	●	●	●	
	0	–	–	–	H	–	–	H	–	–	–	–	H	H	H	H	H	H		–	O	–	–	–	–	–	–	●	●	●	●	
	11	–	–	–	H	–	–	H	–	–	–	H	H	H	H	H	H	H	↓	O	–	–	–	–	–	–	–	●	●	●	●	
	12																															
	13	–	–	–	–	–	–	–	–	–	H	H	H	H	H	H	H	H	LATCH	–	–	–	–	–	–	–	–	●	A	A	●	
	14																															
	15																															
	16																															
	17																															
	18																															
	19																															
	20																															
	21																															
	22																															
	23																															
	24																															
	25																															
	26																															
	27																															
	28																															
	29																															
	30																															
	31																															
2	F_C																															
3	P_B	–	–	–	L	–	–	–	–	–	–	–	–	–	–	–	–	–	SET Q4 TO Q7 HIGH													
4	R_B																															
5	L_B	–	–	–	–	–	–	–	–	–	H	H	H	H	H	H	H	H	LOAD DATA AT NEXT CK													
6	P_A	–	–	–	L	–	–	–	–	–	–	–	–	–	–	–	–	–	SET Q0 TO Q3 HIGH													
7	R_A																															
8	L_A	–	–	–	–	–	–	–	–	–	H	H	H	H	H	H	H	H	LOAD DATA AT NEXT CK													
9	D3	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
0	D2	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
1	D1	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
2	D0	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
	PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12														
	NAMES		/TRIG		/RESET		O1a	/O1	O2	O1																						

TB00421S

COMMENTS:
This one-shot will load data at the end of the count cycle. If $\overline{\text{TRIG}}$ pulse-width is longer than the count cycle, output B3 will go Low for one clock period and go High again for another count cycle. Outputs B_2 and B_0 stay Low and High respectively until $\overline{\text{TRIG}}$ goes High and count cycle is completed without interruption.


CLOCK
$\overline{\text{TRIG}}$
COUNT CYCLE
O_1, O_{1a}
$\overline{O}_1$
O_2
$\overline{\text{TRIG}}$
RETRIGGER MODE
COUNT CYCLE
COUNT CYCLE
O_{1a}
O_1
$\overline{O}_1$
O_2
WF04120S

PLS159 Programmable One-Shot


$\overline{\text{TRIG}}$
B3
B1
TRIG
B3
B1

Figure 2. Timing Diagram of Programmable Retriggerable One-Shot


TRIG
I3
"1"
B0 O1
B3 O1a
B2 $\bar{O}_1$
B1 O2
"1"
LA
LB
"O"
"O"
J
K
P
Q0
Q1
Q7
PA
PB
I1
RESET
F0
F1
F7
INPUTS
LS01390S

Figure 3. Logic Representation of Table 1

Signetics

Application Specific Products

AN12

Low Cost Programmer for PLD 20-Pin Series

Application Note

INTRODUCTION

The Low Cost Programmer (LCP) is designed to provide the user with a low cost alternative to program Signetics' PLD 20-pin series programmable logic devices. This system is a peripheral device which is to be controlled by a computer running Signetics software, AMAZE, or by a terminal. The LCP is connected to the host computer via the RS232 interface and will accept ASCII codes. The data transfer rate can be either 9600 or 4800 baud. The LCP system clock is 4800 baud. The basic measure of time in the system is in units of 13μs. After every fuse is programmed, the LCP will automatically perform a verification cycle and feed data back to the computer. The system can be set to TEST mode which causes the outputs to cycle through the fusing sequence in an endless loop.

THEORY OF OPERATION

A block diagram of the LCP is shown in Figure 1. U1 generates the 9600 baud clock for U3 (UART) and the 4800 baud clock for the rest of the system. When data is transferred into U3, it is put on the system bus. U1 generates IDAV which enables the rest of the system to react to the input. Since each device can decode the input instruction, very few controls are necessary.


ROW ADD. GEN.
U4
IDAV
7
7
PLD DEVICE
ROW ADDRESS (PIN 7 to 9 12 to 15)
RS232 INTERFACE
UART
Tx
Rx
U7
U8
SI
SO
CR
U3
7
INT/EXT
COLUMN ADD. GEN.
U5
IDAV
7
6
COLUMN ADDRESS (PIN 1 to 6)
BAUD RATE GEN./ SYSTEM CONTROL
9600
U1
IDAV
4800
SYSTEM CLOCK
INT/EXT
DATA STORAGE
U3
IDAV
4
4
1
OUTPUT (F) (PIN 16)
U9
5.0688 MHz OSCILLATOR
U6
5
IDAV
INT/EXT
FUSING SEQUENCER
V_P (PIN 18)
V_CCP (PIN 20)
P/V̄ (PIN 17)
STB (PIN 11)
IFL DEVICE
BD01760S

Figure 1. Block Diagram

C2 (D6)	C1 (D5)	C0 (D4)	D3	D2	D1	D0	FUNCTION
0	0	0	X	X	X	X	System internal use
0	0	1	X	X	X	X	System internal use
0	1	0	0	0	0	0	System reset
0	1	0	0	0	0	1	Set system ON-LINE
0	1	0	0	0	1	0	Set system OFF-LINE
0	1	1	4-bit data				Load fusing data
1	0	0	4-bit data				Load 4-bit lower TERM ADD.
1	0	1	2-bit data				Load 2-bit upper TERM ADD.
1	1	0	4-bit data				Load 4-bit upper VAR ADD.
1	1	1	3-bit data				Load 3-bit upper VAR ADD.

NOTE:
The upper and lower VARIABLE ADDRESSES will be reset to zero if upper or lower TERM ADDRESS is loaded into the LCP.

Figure 2. LCP Instruction Set

Figure 2 shows the system instruction set. Each consists of seven bits with the upper 3 bits being the instruction code and the lower 4 bits being data or finer resolution of the instruction code. Figures 2 and 3 of Appendix 1 show the fuse address tables of PLS153 and PLS159, respectively. Note that the Variable Addresses have seven bits (3 upper bits and 4 lower bits), whereas the Term Addresses have six bits (2 upper bits and 4 lower bits). Therefore, it takes up to four nibbles to define a fuse address. Once an address is defined, the Variable Address generator will increment automatically to generate the subsequent fuse addresses for the same Term Address. Loading a Term Address in the Term Address generator will always reset the Variable Address generator. Therefore, the Term Address should be entered first and then the Variable Address. The last entry is the fusing data in a 4-bit nibble. The system will automatically increment the Variable Address generator to program four fuses. Once the 4-bit fusing data is loaded, the system goes into an internal mode until the fusing cycle for the four fuses are completed.

The following illustrates the sequence of programming operation:

1. Switch LCP to ON-LINE
2. Input 010 0000 – reset LCP
3. Input 010 0001 – put LCP "ON-LINE"

Low Cost Programmer for PLD 20-Pin Series

4. Input 100 —-- load 4-bit lower TERM ADDRESS
5. Input 101 00-- load 2-bit upper TERM ADDRESS
6. Input 110—-- load 4-bit lower VARIABLE ADDRESS
7. Input 111 0—-- load 3-bit upper VARIABLE ADDRESS
8. Input 011—-- load 4-bit fusing data, a "1" causes a fuse to be blown
9. U6, the fusing sequencer, causes the system to go into INTERN mode
10. Fusing sequence starts. See Figures 3 and 4
11. Fusing cycle completed. Input next address:
    a. If next TERM ADDRESS is different from the previous one, go to (4)
    b. If next address is in sequence with the previous VARIABLE ADDRESS and in the same TERM, go to (8)
    c. The Variable Address generator will always reset to 0 if TERM ADDRESS is loaded.

Figure 3 shows the sequence of fusing operation while the system is in internal mode. Figure 4 shows the timing diagram and voltage waveform of the fusing sequence of four consecutive fuses.

Analog Drivers:

V_P — This signal is current limited to 325mA. It is 1.25V to 1.75V when not fusing (idle). During the fusing cycle it takes on a value of 14.25V to 14.75V for a short time. The leading edge is slew rate limited to about 10µs.

V_{CCP} — This signal is the programming power supply. It can source up to 1A. It has a value of 1.1V to 1.3V when not fusing (idle).


INITIALIZE + OFFLINE + RESET
31 29 30
WAIT (EXT MODE) EF
DATA NIBBLE
0
20
INT MODE VCCP ON 6F
CLEAR INT MODE EE
2
19
DELAY 6D
SEND CYCLE COMPLETE 6E
15
BSC
ZAP FUSE
3
18
SET PROG. MODE 4F
INCR VAR 6C
4
22
ZAP FUSE
17
BSC
VP ON 47
STROBE OFF 69
5
14
DELAY 46
INT. STROBE OFF 79
6
13
STROBE ON 53
INT. STROBE ON 3B
7
12
STROBE OFF 43
STROBE ON 7B
8
11
VP OFF 4B
10
SET VERIFY MODE 6B
PF00720S

NOTES:
1. State numbers in hex.
2. State changes on every clock.
3. 13µs cycle time.

Figure 3. State Diagram Fusing Sequence and Control PLD U6


P/V PIN 17
VIH
VIL
START
BIT 1
P1
V1
BIT 2
P2
V2
BIT 3
P3
V3
BIT 4
P4
V4
NEXT CYCLE
VCCP PIN 20
6.5
5.0
TR
18 µs
13µs
13µs
13 µs
13µs
VP PIN 18
1.4–1.5V
14-15V
13 µs
TR
20 µs
13 µs
13µs
STROBE PIN 11
VIL
13µs
TP1
TV1
TP2
TV2
TP3
TV3
TP4
TV4
VOH
SENSE PIN 16
VOL
1CLK
1CLK
F1
F2
F3
F4
INTERNAL STROBE
READ BACK SHIFT REG STB
WF06550S

Figure 4. Timing Diagram and Voltage Waveforms

Low Cost Programmer for PLD 20-Pin Series

AN12

During the fusing cycle it assumes a value of 8.25V to 8.75V for the duration of the entire cycle (four fusing pulses – See Figure 4).

V_P Driver Circuitry — The V_P signal is toggled by the Fusing Sequencer, U6, Pin 15. This TTL signal is buffered up by the switching transistor, Q3, and its associated resistors, R6 and R9. Transistor Q4 inverts the signal to achieve the correct phase relationship. It also performs the following circuit functions:

1. It clamps the base of the Darlington transistor, Q5, to near ground through the R10 resistor.
2. Transistor Q4 discharges the slew rate time constant capacitor, C1, through the resistor, R10, and shunts the current from the current source, VR2, to near ground. This prepares the circuit for the next controlled slew rate edge at the beginning of the next fuse blowing cycle.
3. It provides a current sinking path to pull current out of the fusing socket enable line, thus creating a rapidly falling V_{CCP} trailing edge. The diode, D2, provides sourcing isolation while the resistor, R11, limits inrush currents. A ferrite bead on the R11 lead slows down this path. This prevents large currents from flowing through transistor Q4 at the low level switching transition time.

The voltage regulator, VR1, forms the 325mA current limit circuit in conjunction with the voltage dropping resistor, R8.

The controlled slew rate of the leading edge and the final level of the enable high output voltage V_P are generated in the following manner:

1. A 10mA current source is formed by the voltage regulator, VR2, and the dropping resistor, R7.
2. This current is shunted to ground through Q4 when the enable pulse is low.
3. At the instant when Q4 turns off, the 10mA current is diverted into the slew rate control capacitor, C1. The capacitor, C1, will continue to charge linearly until the voltage across it reaches the value of the zener diode stack D1A and D1B.
4. The current is then shunted down the zener diodes until Q4 is turned back on.
5. The base of the Darlington transistor, Q5, follows the voltage across the capacitor, C1, and draws very little current due to its very high current gain. Since the Q5 transistor is configured as an emitter follower, the voltage seen on the fusing socket enable line will be about 1V lower than the base of transistor Q5. Resistor R12 stabilizes the value of the V_{BE} on transistor Q5 by pulling a small amount of current early in the ramp.

V_{CCP} Driver Circuitry — V_{CCP} is toggled by the internal/external signal from the Fusing Sequencer, U6. Again, the signal is buffered and inverted twice by transistors Q1 and Q2 along with resistors R4 and R3.

Low Voltage (Idle)
Resistor R2 is shorted to ground through transistor Q2 in order to generate the 1.1V to 1.3V low output level. This is an intrinsic value generated by the internal reference of the voltage regulator.

High Voltage (V_{CCP})
When transistor Q2 is turned off, the output voltage ramps to the 8.25V to 8.75V level. This value is determined by the ratio of resistors R1 and R2 in conjunction with the actual value of the voltage regulator's internal reference.

Power Supply Consideration

1. The Low Cost Programmer circuitry draws about 1A.
2. The Enable and V_{CCP} currents may reach about 1.4A.
3. The Enable signal is about 15V and needs at least 5V of head room.
4. The RS232 drivers require ± 12V at about 60mA.

In a bridge circuit, a rule of thumb says that the transformer's current rating should be from 1.2 to 1.6 times the load current. Using this rule, the secondary of the transformer that supplies V_{CC} and ± 12V should be rated at 18V center tapped at about 1.6A.

The transformer that supplies the Enable and V_{CCP} circuits should have an 18V secondary at about 2.2A.

PROGRAMMING THE LCP

The addresses and fusing data can be generated by the host computer using AMAZE or a terminal nibble by nibble. The fuse address of each PLD 20-pin device is available in the Signetics PLD data manual. Copies of the fuse address tables of PLS153 and PLS159 are included in Appendix A Tables A-1 and A-2. These fuse addresses, together with the 3-bit instruction code, form a 7-bit instruction which can be represented by a single ASCII character. Table 1 is a table of ASCII characters.

The following example illustrates the conversion of program table entries into fuse addresses and fusing data. Table 2 shows a simple entry in an PLS153 program table. To keep things simple, only four entries are made. The first entry is term 3, variable I7. The fuse of the non-inverting buffer is to remain intact, whereas the fuse to be blown is the inverting buffer, I7. For this entry, from Table A-1 of Appendix A, the Term Address is 03hex or 00 0011b, the Variable Addresses of the two buffers are 0Ehex or 000 1110b, and 0Fhex or 000 1111. The fusing data is 01. The second entry is Term 3, I6. The fuse of the inverting buffer is to be kept intact while that of the non-inverting buffer will be blown. The Term Address is the same as the previ-

Table 1. ASCII Character Table

		0000	0001	0010	0011	0100	0101	0110	0111
		0	**1**	**2**	**3**	**4**	**5**	**6**	**7**
0000	0	NUL	DLE	SP	0	●	P	•	p
0001	1	SOH	DC1	!	1	A	Q	a	q
0010	2	STX	DC2	''	2	B	R	b	r
0011	3	ETX	DC3	#	3	C	S	c	s
0100	4	EOT	DC4	$	4	D	T	d	t
0101	5	ENQ	NAK	%	5	E	U	e	u
0110	6	ACK	SYN	&	6	F	V	f	v
0111	7	BEL	ETB	'	7	G	W	g	w
1000	8	BS	CAN	(	8	H	X	h	x
1001	9	HT	EM	)	9	I	Y	i	y
1010	A	LF	SUB	*	:	J	Z	j	z
1011	B	VT	ESC	+	;	K	[	k	{
1100	C	FF	FS	,	<	L	^	l	:
1101	D	CR	GS	—	=	M	]	m	}
1110	E	SO	RS	.	>	N		n	~
1111	F	SI	US	/	?	O	÷	o	DEL

Table 2. FPLA Program Table

CODE NO.

POLARITY

TERM	AND																		REMARKS	OR										REMARKS
	I								B(I)											B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	
0																														
1																														
2																														
3	H	L	-	-																										
4																														
5																														
6																														
7																														
8																														
9																														
10																														
11																														
12																														
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5																														
D4																														
D3																														
D2																														
D1																														
D0																														
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS																														

PLS153

TB01650S

ous entry; the Variable Addresses of the two buffers are 0Chex or 000 1100b and 0Dhex or 000 1101b. The fusing data is 10. The four fusing data can be combined into one nibble (0110) since the two entries are in sequence. Only the first address has to be loaded (Term Address 03hex and Variable Address 0F). The next two entries are in sequence with the first two, therefore only fusing data nibble 1111 has to be loaded.

The instruction and data nibbles can be loaded into the LCP in ASCII characters (see Table 1).

LCP CHECK OUT AND CALIBRATION

This section deals with the check out and calibration of the Low Cost Programmer.

The voltage regulator, VR4, dissipates a lot of heat. It should be mounted on a metal chassis with an isolation mount.

Notice that the fusing socket, P1, has three columns of pads. Use the left set if the socket is to be mounted on the component side of the PCB. Use the right set if the socket is to be placed on the blank side of the PCB. The LEDs may also be mounted on the blank side, allowing for very easy panel mounting of the finished LCP.

Power Supplies

1. $+10V_{DC}$ to $+14V_{DC}$ at the positive side of C4.
2. $-10V_{DC}$ to $-14V_{DC}$ at the negative side of C3.
3. $+4.75V_{DC}$ to $+5.25V_{DC}$ at the $+5V_{DC}$ input pad of the PCB.
4. $+20V_{DC}$ to $+26V_{DC}$ at the positive side of C2.

Turn off the LCP and insert ICs U1 through U5, U7 and U8. Do not insert U6 yet.

Turn on the LCP and repeat steps 1 through 4 above.

Driver Calibration

The Fusing Sequencer, U6, must not be in the LCP for the following steps:

Measure $1.25V_{DC}$ to $1.75V_{DC}$ at Pin 18 of P1. (The fusing socket.)

2. Place a clip lead from the U6 Pin 15 end of resistor R6 to V_{CC} ($+5V_{DC}$).
3. Measure $14.0V_{DC}$ to $15.0V_{DC}$ at Pin 18 of P1.
4. Momentarily place a 75Ω 3W resistor from Pin 18 of P1 to ground and observe the voltage to still read $14.0V_{DC}$ to $15.0V_{DC}$.
5. Disconnect the clip lead between R6 and V_{CC}.
6. Measure the voltage at Pin 18 of P1 to once again be 1.25 to $1.75V_{DC}$.
7. Place a jumper from the U6 Pin 19 side of resistor R4 to ground.
8. Measure the voltage at Pin 20 of P1. It should be $1.10V_{DC}$ to $1.30V_{DC}$.
9. Place a jumper from the U6 Pin 19 side of resistor R4 to V_{CC}.
10. The voltage should be from $8.25V_{DC}$ to $8.75V_{DC}$ at Pin 20 of P1.
11. Place a 30Ω 3W load resistor momentarily from Pin 20 of P1 to ground and measure the voltage. It should remain within the $8.25V_{DC}$ to $8.75V_{DC}$ range. The value of R2 may have to be selected in order to give the correct voltage reading.
12. Reconnect the jumper from R4 to ground.
13. The voltage at Pin 20 of P1 should be $1.10V_{DC}$ to $1.30V_{DC}$.
14. Turn off power and insert U6 into its socket.

Baud Rate Generation

1. Using an oscilloscope, look at the waveform on Pin 17 of the Baud Rate Generator, U1. This signal should swing from <450mV to >2.4V and have about a 50% duty cycle.
2. The frequency at this pin should be 153.6kHz. This results in a period of 6.51μs.
3. Repeat Steps 1 and 2 for Pin 18 of U1. The frequency should be 76.8kHz, resulting in a period of 13.0μs.

Control Functions

Connect an ASCII RS232 terminal to the computer connector, C1, on the LCP. The set up should be:

1. 9600 baud.
2. 8 bits.
3. 1 Stop bit.
4. No parity.
5. Terminal Tx to Pin 3 of the LCP C1 connector.
6. Terminal Rx to Pin 2 of the LCP C1 connector.

The following steps send ASCII characters to the LCP, which it should interpret as instructions. It will not echo the characters sent, but it should perform the instructions. Refer to Figure 5 for the ASCII equivalent instruction characters.

1. Turn on the LCP.
2. Set the ON-LINE/OFF-LINE switch to ON-LINE.
3. Type ''.
4. Type !. The ON-LINE LED should illuminate. If the ON-LINE LED does not light at this point, check for the correct interfacing of Pins 2 and 3 on the RS232 terminal connector.
5. Type ''. The ON-LINE LED should go back off.

TERM ADDRESS GENERATION

The purpose of this section is to test the ability of the LCP to uniquely load the bits of the term address. This is done by sending ASCII characters to the LCP and then checking the term address pins of P1.

Send the following lines of characters and check the P1 pins after each.

CHAR	1	2	3	4	5	6
!	On-Line — Address at Previous State					
SO	H	H	H	H	H	H
space	L	L	L	L	L	L
A	L	L	L	L	L	L
B	L	L	L	L	H	H
D	L	L	L	H	L	L
H	L	L	H	L	L	L
@Q	L	H	L	L	L	L
R	H	L	L	L	L	L
SO	H	H	H	H	H	H
N	H	H	H	H	H	L
M	H	H	H	H	L	H
K	H	H	H	L	H	H
G	H	H	L	H	H	H
OR	H	L	H	H	H	H
Q	L	H	H	H	H	H
S	H	H	H	H	H	H
@ P	L	L	L	L	L	L
	Off-Line — Address Not Altered					

VARIABLE ADDRESS GENERATION

The purpose of this section is to test the ability of the LCP to uniquely load and increment the bits of the Variable Address. This is done by sending the appropriate ASCII characters to the LCP and then checking the Term Address pins of P1.

Send each line of characters and check the specified P1 pins after each.

Low Cost Programmer for PLD 20-Pin Series AN12

CHAR	7	8	9	12	13	14	15
!	On-Line — Address Same as Previous						
wo	H	H	H	H	H	H	H
space	L	L	L	L	L	L	L
a	L	L	L	L	L	L	H
b	L	L	L	L	L	H	L
d	L	L	L	L	H	L	L
h	L	L	L	H	L	L	L
space q	L	L	H	L	L	L	L
r	L	H	L	L	L	L	L
t	H	L	L	L	L	L	L
ow	H	H	H	H	H	H	H
n	H	H	H	H	H	H	L
m	H	H	H	H	H	L	H
k	H	H	H	H	L	H	H
g	H	H	H	L	H	H	H
ov	H	H	L	H	H	H	H
u	H	L	H	H	H	H	H
s	L	H	H	H	H	H	H
w	H	H	H	H	H	H	H
A	L	L	L	L	L	L	L
owQ	L	L	L	L	L	L	L
1	L	L	L	L	H	L	L
1	L	L	L	H	L	L	L
2	L	L	L	H	H	L	L
2	L	L	H	L	L	L	L
l2	L	H	L	L	L	L	L
ls2	H	L	L	L	L	L	L
	Off-Line — Address Not Altered						

Fusing Cycle/Test Mode

Place a jumper from U1 Pin 3 to ground. This enables test mode. Send any data character and the LCP will continuously loop through the fusing sequence. Verify the voltages and timing per Figure 4.

Remove the jumper.

Pass Through

Turn the LCP ON-LINE/OFF-LINE switch to OFF-LINE.

Connect the Host Computer to the C1 connector of the LCP and the Terminal to T1 of the LCP. Make certain the Tx and Rx signals of both are associated with the correct LCP RS232 pins on the respective connectors.



Figure A-1. Programming Pin Functions

Type on the terminal keyboard. The computer should behave normally – usually with an echo.

This completes the LCP calibration and checkout.

APPENDIX A

HOW TO PROGRAM PLD 20-PIN SERIES DEVICES

An PLD device is basically a group of logic functions interconnected to each other by fuses which can be blown to open a circuit, or left intact to make a connection. Each fuse can be identified by its own unique address which consists of a 7-bit Variable Address (ROW ADDRESS) and a 6-bit Term Address (COLUMN ADDRESS). The programming pin function is the same throughout the 20-pin series see Figure A-1). Tables A-1 and A-2 are fuse address tables of the PLS153 and PLS159, respectively.

The programming cycle can be separated into four stages:

Set-Up

1. Set Program Enable (V_P) to GND
2. Apply Column and Row Address to pins 1-6 and 7-9, 11-15
3. Set STROBE (STB) to V_{IH}
4. Set PROGRAM/VERIFY (P/V) to V_{IL}
5. Wait 1-50μs
6. Set V_{CCP} to 8.5V

To Blow a Fuse

1. Wait 1-10μs
2. Set P/V to V_{IH}
3. Wait 1-50μs
4. Set V_P to 14.5V
5. Wait 1-5μs
6. Pulse STB to V_{IL} for 10μs
7. Wait 1-5μs
8. Set V_P to GND
9. Wait 1-5μs
10. Set P/V to V_{IL}

To Verify

1. Wait 1-5μs
2. Pulse STB to V_{IL} for 1-10μs
3. While STB is LOW, OUTPUT (F) will be V_{IL} for a fuse intact and 2-8.75V for a blown fuse (note: F is an open-collector, a pull-up circuit may be needed)

Go To Set-Up for Next Fuse

Table A-1. Program Cycle Row/Column Fuse Addressing

PLS153

Variable Select Table[1]

ROW HEX ADDRESS		SELECTED VARIABLE	
$I_6I_7B_0$	$B_2B_3B_4B_5$		
0	0	AND Array	I_0
0	1		$\overline{I_0}$
0	2		I_1
0	3		$\overline{I_1}$
0	4		I_2
0	5		$\overline{I_2}$
0	6		I_3
0	7		$\overline{I_3}$
0	8		I_4
0	9		$\overline{I_4}$
0	A		I_5
0	B		$\overline{I_5}$
0	C		I_6
0	D		$\overline{I_6}$
0	E		I_7
0	F		$\overline{I_7}$
1	0		B_9
1	1		$\overline{B_9}$
1	2		B_8
1	3		$\overline{B_8}$
1	4		B_7
1	5		$\overline{B_7}$
1	6		B_6
1	7		$\overline{B_6}$
1	8		B_5
1	9		$\overline{B_5}$
1	A		B_4
1	B		$\overline{B_4}$
1	C		B_3
1	D		$\overline{B_3}$
1	E		B_2
1	F		$\overline{B_2}$
1	0		B_1
1	1		$\overline{B_1}$
1	2		B_0
1	3		$\overline{B_0}$

ROW HEX ADDRESS		SELECTED VARIABLE	
$I_6I_7B_0$	$B_2B_3B_4B_5$		
2	4	Empty Address Space	
↓	↓		
2	F		
3	0	OR Array	9
3	1		8
3	2		7
3	3		6
3	4		5
3	5		4
3	6		3
3	7		2
3	8		1
3	9		0
3	A	Polarity Enable	
3	B	Empty Address Space	
↓	↓		
3	F		

Term Select Table[2]

COLUMN HEX ADDRESS		SELECTED PRODUCT TERM	
I_0I_1	$I_2I_3I_4I_5$		
0	0	Logic Terms	0
0	1		1
0	2		2
0	3		3
0	4		4
0	5		5
0	6		6
0	7		7
0	8		8
0	9		9
0	A		10
0	B		11
0	C		12
0	D		13
0	E		14
0	F		15
1	0		16
1	1		17
1	2		18
1	3		19
1	4		20
1	5		21
1	6		22
1	7		23
1	8		24
1	9		25
1	A		26
1	B		27
1	C		28
1	D		29
1	E		30
1	F		31
2	0	Control Terms	0
2	1		1
2	2		2
2	3		3
2	4		4
2	5		5
2	6		6
2	7		7
2	8		8
2	9		9
2	A	Polarity Terms	0
2	B		1
2	C		2
2	D		3
2	E		4
2	F		5
3	0		6
3	1		1
3	2		8
3	3		9

NOTES:

1. A row address identifies a particular variable coupled to all product terms.
2. With a variable selected by the row address the column address further selects a coupling fuse for each term.

Low Cost Programmer for PLD 20-Pin Series

AN12

Table A-2. Program Cycle Row/Column Fuse Addressing (Continued)

PLS159

Variable Select Table[1]

ROW HEX ADDRESS		SELECTED VARIABLE	
$B_1B_2B_3$	$F_0F_1F_2F_3$		
0	0	AND Array	$\overline{B}_3$
0	1		B_3
0	2		$\overline{B}_2$
0	3		B_2
0	4		$\overline{B}_1$
0	5		B_1
0	6		$\overline{B}_0$
0	7		B_0
0	8		$\overline{I}_3$
0	9		I_3
0	A		$\overline{I}_2$
0	B		I_2
0	C		$\overline{I}_1$
0	D		I_1
0	E		$\overline{I}_0$
0	F		I_0
2	0		$\overline{F}_0$
2	1		F_0
2	2		$\overline{F}_1$
2	3		F_1
2	4		$\overline{F}_2$
2	5		F_2
2	6		$\overline{F}_3$
2	7		F_3
2	8		$\overline{F}_4$
2	9		F_4
2	A		$\overline{F}_5$
2	B		F_5
2	C		$\overline{F}_6$
2	D		F_6
2	E		$\overline{F}_7$
2	F		F_7
4	F		C_N

ROW HEX ADDRESS		SELECTED VARIABLE		
$B_1B_2B_3$	$F_0F_1F_2F_3$			
5	0	Flip-flop Control Terms	F_7	J
5	1			K
5	2		F_6	J
5	3			K
5	4		F_5	J
5	5			K
5	6		F_4	J
5	7			K
5	8		F_3	J
5	9			K
5	A		F_2	J
5	B			K
5	C		F_1	J
5	D			K
5	E		F_0	J
5	F			K
6	0	J-K/D Option	F_7	
6	1		F_6	
6	2		F_5	
6	3		F_4	
6	4		F_3	
6	5		F_2	
6	6		F_1	
6	7		F_0	
7	1	OR Array	B_3	
7	2		B_2	
7	3		B_1	
7	4		B_0	
7	5	C-Array	C_N	
7	6	OE	EA	
7	8	Polarity Terms	B_0	
7	A		B_1	
7	D		B_2	
7	F		B_3	

Term Select Table[2]

COLUMN HEX ADDRESS		SELECTED TERM		
$CLKI_0$	$I_1I_2I_3B_0$			
0	0	Transition Term		0
0	1			1
0	2			2
0	3			3
0	4			4
0	5			5
0	6			6
0	7			7
0	8			8
0	9			9
0	A			10
0	B			11
0	C			12
0	D			13
0	E			14
0	F			15
1	0			16
1	1			17
1	2			18
1	3			19
1	4			20
1	5			21
1	6			22
1	7			23
1	8			24
1	9			25
1	A			26
1	B			27
1	C			28
1	D			29
1	E			30
1	F			31
2	1	Control Term		PA
2	2			PB
2	3			RA
2	4			RB
2	5			LA
2	6			LB
2	7			FC
2	8	Output Enable	•	EA
2	9			EB
2	C		A	EA
2	A			EB
2	D		Polarity	
2	E	Direction Control		D_0
2	F			D_1
3	0			D_2
3	1			D_3
2	0			Test Col. 2
3	2			Test Col. 1

NOTES:

1. A row address identifies a particular variable coupled to all product terms.
2. With a variable selected by the row address the column address further selects a coupling fuse for each term.

APPENDIX B


VARIABLE SELECT
TERM SELECT
ON LINE
ON LINE INDICATOR
R15 270 10% 1/4W
D4
STROBE
P/V
SENSE
RTN
VP
VCCP
+12 RS232 U6 PIN 14
R14 270 5% 1/4W
D3 10mA
POWER IND
GND
C5 0.01μF
VFSP(H) = 14.0–15.0V
VFSP(L) = 1.25–1.75V
VCCP(H) = 8.25–8.75
VCCP(L) = 1.1–1.3V
VR4 7805
+5 VCC
DB2
4700μF @ 35V
C2
-12V
C3
220μF @ 16V
RS232 TO U6 PIN 1
BYPASS
C8 C9 C10 C11 C12 C13
T1 9 VAC 115 VAC
+23V
4700μF @ 35V
C4
DB1
18VAC
T2 115 VAC
CONTROL/DATA BUS
INC. VAR
SENSE
R13 10K
U1
U2
U3
U4
U5
U6
U9
OSC 5.0688 MHz
IDAV
SYS CLK
Q5
D2 IN4001
R12 1K 1/2W
R11 47 1/4W
R10 75 1/4W
Q4
2N2222
Q3
R9 120 1/4W
D1 18.2V
R6
R8 3.3 1/4W 1%
R7 39 1/4W 1%
LM317 VR1
LM317 VR2
C1 0.0047 μF
D1A = IN4739
D1B = IN4735
1.8K 1/4W
+5V
R3 1K 1/4W
R4 1.8K 1/4W
Q1 2N2222
Q2 2N2222
LM317 VR3
C14 0.005 μF
R1 100 1/2W 1%
R2 572 1/2W 5%
R5 1K 1/4W
SELECT TO GIVE 8.25–8.75V UNDER WITH Q2 OFF
COMPUTER
TERMINAL
RX TX
MC1488 = U6
U7 = MC1489A
PIN 14 = VCC
PIN 7 = GND
PIN 14 = +12VDC
PIN 7 = GND
PIN 1 = -12VDC
C6 400 pF
C7 400 pF
ON LINE
S2
9600
4800
INT/EXT
VFY STB
INCR VAR
RN1
12μs
BD01770S

Figure B-1. PLD 20 Programmer

Table B-1. Baud Rate Generation and UART Control PLD U1 Revision "B" Adds Test Mode

CODE NO. U1

FF MODE: • • • • • • • •

E_B: •

E_A: •

POLARITY: H H L L

TERM	C	AND																REMARKS	(OR)												REMARKS
		I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	•	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	–	–	–	–	–	0	•	•	•	•	
1	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	H		–	–	–	–	–	–	0	–	•	•	•	•	
2	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	H	H		–	–	–	–	–	0	–	–	•	•	•	•	GEN. BAUD RATE ×16
3	–	–	–	–	–	–	–	–	–	–	–	–	–	–	H	H	H		–	–	–	–	0	–	–	–	•	•	•	•	" "
4	–	–	–	–	–	–	–	–	–	–	–	L	–	H	H	H	H		–	–	0	–	–	–	–	–	•	•	•	•	" "
5	–	–	–	–	–	–	–	–	–	–	–	H	–	H	H	H	H		–	–	–	0	–	–	–	–	•	•	•	•	" "
6	A	–	–	–	–	–	–	–	–	–	–	H	H	L	L	L	L		–	0	0	0	–	–	–	–	•	•	•	•	" "
7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	" "
8	–	H	–	H	–	L	H	–	–	H	H	H	H	L	L	L	L		L	–	–	–	–	–	–	–	•	•	•	•	" "
9	–	–	–	–	–	L	–	–	–	L	H	H	H	L	L	L	L		H	–	–	–	–	–	–	–	•	•	•	•	SET IDAV (EXT)
10	–	–	–	–	–	L	–	–	–	L	–	–	–	–	–	–	–		–	–	–	–	–	–	–	–	•	•	•	A	RESET IDAV (EXT)
11	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
12	–	–	–	–	L	H	–	–	–	H	H	H	H	L	L	L	L		L	–	–	–	–	–	–	–	•	•	•	•	GEN IDAV (INT.)
13	–	–	–	–	H	H	–	–	–	L	H	H	H	L	L	L	L		H	–	–	–	–	–	–	–	•	•	•	•	RESET IDAV (INT)
14	–	–	–	–	H	H	–	–	–	–	–	–	–	–	–	–	–		–	–	–	–	–	–	–	–	•	•	A	•	
15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	TEST MODE
16	–	–	–	L	–	L	H	–	–	H	H	H	H	L	L	L	L		L	–	–	–	–	–	–	–	•	•	•	•	
17	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
18	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
19	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
20	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
21	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
22	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
23	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
24	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
26	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
28	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
29	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
31	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
FC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D3	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D2	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D1	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
D0	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS		DAV		$\overline{TEST}$	CO	INT/$\overline{EXT}$	TBMT	$\overline{DS}$	$\overline{RDAV}$	IDAV	4800 SYS CLK	9600	÷ 32	÷ 16	÷ 8	÷ 4	÷ 2														PLS159

TB01660S

Table B-2. Low Cost Programmer PLD #U4 Variable Address Generator

CODE NO. U4										FF MODE									E_B				E_A				POLARITY				
										•	•	•	•	•	•	•	•		•				•				H	H	H	H	
TERM	AND																	REMARKS	(OR)												REMARKS
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	H	L	L	–	–	H	–	–	H	–	–	–	–	–	–	–		–	–	–	–	–	–	–	O	•	•	•	•	INT MODE COUNT
1	–	H	L	L	–	–	H	–	–	H	–	–	–	–	–	–	L		–	–	–	–	–	–	O	–	•	•	•	•	" "
2	–	H	L	L	–	–	H	–	–	H	–	–	–	–	–	L	L		–	–	–	–	–	O	–	–	A	•	•	•	" "
3	–	H	L	L	–	–	H	–	–	H	–	–	–	–	L	L	L		–	–	–	–	O	–	–	–	•	•	•	•	" "
4	–	H	L	L	–	–	H	–	–	H	–	–	–	L	L	L	L		–	–	–	O	–	–	–	–	•	•	•	•	" "
5	–	H	L	L	–	–	H	–	–	H	–	–	L	L	L	L	L		–	–	O	–	–	–	–	–	•	•	•	•	" "
6	–	H	L	L	–	–	H	–	–	H	–	L	L	L	L	L	L		–	O	–	–	–	–	–	–	•	•	•	•	" "
7	–	H	L	L	–	–	H	–	–	H	L	L	L	L	L	L	L		–	–	–	–	–	–	–	–	•	•	•	A	TERM COUNT
8	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
9	–	H	H	H	L	–	–	–	H	H	–	–	–	–	–	–	–		–	–	–	–	–	–	–	L	•	•	•	•	LOAD RESET J/K
10	–	H	H	H	L	–	–	H	–	H	–	–	–	–	–	–	–		–	–	–	–	–	–	L	–	•	•	•	•	" "
11	–	H	H	H	L	–	H	–	–	H	–	–	–	–	–	–	–		–	–	–	–	–	L	–	–	•	•	•	•	" "
12	–	H	H	H	L	H	–	–	–	H	–	–	–	–	–	–	–		–	–	–	–	L	–	–	–	•	•	•	•	" "
13	–	H	H	H	H	–	–	–	H	H	–	–	–	–	–	–	–		–	–	–	L	–	–	–	–	•	•	•	•	" "
14	–	H	H	H	H	–	–	H	–	H	–	–	–	–	–	–	–		–	–	L	–	–	–	–	–	•	•	•	•	" "
15	–	H	H	H	H	–	H	–	–	H	–	–	–	–	–	–	–		–	L	–	–	–	–	–	–	•	•	•	•	" "
16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
17	–	H	L	H	L	L	L	L	H	–	–	–	–	–	–	–	–		H	–	–	–	–	–	–	–	•	•	•	•	ONLINE
18	–	H	L	H	L	L	L	H	L	–	–	–	–	–	–	–	–		L	–	–	–	–	–	–	–	•	•	•	•	OFFLINE
19	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
20	–	H	H	H	L	–	–	–	L	H	–	–	–	–	–	–	–		–	–	–	–	–	–	–	H	•	•	•	•	LOAD SET J/K
21	–	H	H	H	L	–	–	L	–	H	–	–	–	–	–	–	–		–	–	–	–	–	–	H	–	•	•	•	•	" "
22	–	H	H	H	L	–	L	–	–	H	–	–	–	–	–	–	–		–	–	–	–	–	H	–	–	•	•	•	•	" "
23	–	H	H	H	L	L	–	–	–	H	–	–	–	–	–	–	–		–	–	–	–	H	–	–	–	•	•	•	•	" "
24	–	H	H	H	H	–	–	–	L	H	–	–	–	–	–	–	–		–	–	–	H	–	–	–	–	•	•	•	•	" "
25	–	H	H	H	H	–	–	L	–	H	–	–	–	–	–	–	–		–	–	H	–	–	–	–	–	•	•	•	•	" "
26	–	H	H	H	H	–	L	–	–	H	–	–	–	–	–	–	–		–	H	–	–	–	–	–	–	•	•	•	•	" "
27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
28	–	H	H	L	L	–	–	–	–	H	–	–	–	–	–	–	–		–	H	H	H	H	H	H	H	•	•	•	•	TERM CLR. LOWER
29	–	H	H	L	H	–	–	–	–	H	–	–	–	–	–	–	–		–	H	H	H	H	H	H	H	•	•	•	•	TERM CLR. UPPER
30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
31	–	H	L	H	L	L	L	L	L	H	–	–	–	–	–	–	–		–	H	H	H	H	H	H	H	•	•	•	•	SYNC. RESET
FC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D3	–	H	L	L	–	–	–	–	–	H	–	–	–	–	–	–	–														
D2	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D1	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D0	–	H	L	L	–	–	–	–	–	H	–	–	–	–	–	–	–														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS		I DAV	C2	C1	C0	D3_BSC	D2 INC VAR	D1	D0_TERMLN	ON/OFF LN	VA6	VA5	VA4	VA3	VA2	VA1	VA0														

PLS159

TB01670S

Low Cost Programmer for PLD 20-Pin Series

Table B-3. Low Cost Programmer PLD #U4 Variable Address Generator

CODE NO. U5										FF MODE									E_B				E_A				POLARITY				
										•	•	•	•	•	•	•	•		•				•				H	H	H	H	
TERM	AND																		(OR)												
	C	I				B(I)				Q(P)								REMARKS	Q(N)								B(O)				REMARKS
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	H	L	L	–	–	–	–	H	H	–	–	–	–	–	–	–		–	–	–	–	–	–	–	O	•	•	•	•	INT. MODE CNT.
1	–	H	L	L	–	–	–	–	–	H	–	–	–	–	–	–	L		–	–	–	–	–	–	–	–	•	•	•	•	NOT USED
2	–	H	L	L	–	–	–	–	–	H	–	–	–	–	–	L	L		–	–	–	–	–	–	–	–	•	•	•	•	" "
3	–	H	L	L	–	–	–	–	–	H	–	–	–	–	L	L	L		–	–	–	–	–	–	–	–	•	•	•	•	" "
4	–	H	L	L	–	–	–	–	–	H	–	–	–	L	L	L	L		–	–	–	–	–	–	–	–	•	•	•	•	" "
5	–	H	L	L	–	–	–	–	–	H	–	–	L	L	L	L	L		–	–	–	–	–	–	–	–	•	•	•	•	" "
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
7	–	H	H	L	L	–	–	–	H	H	–	–	–	–	–	–	–		–	–	–	–	–	–	–	L	•	•	•	•	LOAD SET
8	–	H	H	L	L	–	–	H	–	H	–	–	–	–	–	–	–		–	–	–	–	–	–	L	–	•	•	•	•	" "
9	–	H	H	L	L	–	H	–	–	H	–	–	–	–	–	–	–		–	–	–	–	–	L	–	–	•	•	•	•	" "
10	–	H	H	L	L	H	–	–	–	H	–	–	–	–	–	–	–		–	–	–	–	L	–	–	–	•	•	•	•	" "
11	–	H	H	L	H	–	–	–	H	H	–	–	–	–	–	–	–		–	–	–	L	–	–	–	–	•	•	•	•	" "
12	–	H	H	L	H	–	–	H	–	H	–	–	–	–	–	–	–		–	–	L	–	–	–	–	–	•	•	•	•	" "
13	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
14	–	H	L	H	L	L	L	L	H	–	–	–	–	–	–	–	–		H	–	–	–	–	–	–	–	•	•	•	•	ON LINE
15	–	H	L	H	L	L	L	H	L	–	–	–	–	–	–	–	–		L	–	–	–	–	–	–	–	•	•	•	•	OFF LINE
16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
17	–	H	H	L	L	–	–	–	L	H	–	–	–	–	–	–	–		–	–	–	–	–	–	–	H	•	•	•	•	LOAD RESET
18	–	H	H	L	L	–	–	L	–	H	–	–	–	–	–	–	–		–	–	–	–	–	–	H	–	•	•	•	•	" "
19	–	H	H	L	L	–	L	–	–	H	–	–	–	–	–	–	–		–	–	–	–	–	H	–	–	•	•	•	•	" "
20	–	H	H	L	L	L	–	–	–	H	–	–	–	–	–	–	–		–	–	–	–	H	–	–	–	•	•	•	•	" "
21	–	H	H	L	H	–	–	–	L	H	–	–	–	–	–	–	–		–	–	–	H	–	–	–	–	•	•	•	•	" "
22	–	H	H	L	H	–	–	L	–	H	–	–	–	–	–	–	–		–	–	H	–	–	–	–	–	•	•	•	•	" "
23	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
24	–	H	L	L	–	–	–	–	H	H	–	–	–	–	–	–	L		–	–	–	–	–	–	O	–	•	•	•	•	INT. MODE COUNT
25	–	H	L	L	–	–	–	–	H	H	–	–	–	–	–	L	L		–	–	–	–	–	O	–	–	•	•	•	•	" "
26	–	H	L	L	–	–	–	–	H	H	–	–	–	–	L	L	L		–	–	–	–	O	–	–	–	•	•	•	•	" "
27	–	H	L	L	–	–	–	–	H	H	–	–	–	L	L	L	L		–	–	–	O	–	–	–	–	•	•	•	•	" "
28	–	H	L	L	–	–	–	–	H	H	–	–	L	L	L	L	L		–	–	O	–	–	–	–	–	•	•	•	•	" "
29	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	" "
30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
31	–	H	L	H	L	L	L	L	L	H	–	–	–	–	–	–	–		–	H	H	H	H	H	H	H	•	•	•	•	SYNC. RESET
FC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D3	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D2	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D1	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D0	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS		IDAV	C2	C1	C0	D3	D2	D1	DØ TERM CNT.	ON/OFF LN.	N/A	TA5	TA4	TA3	TA2	TA1	TA0														PLS159

TB01680S

Low Cost Programmer for PLD 20-Pin Series

AN12

Table B-4. Low Cost Programmer PLD #U2B Revision "3" Data Register

CODE NO.	FF MODE	E_B	E_A	POLARITY
U2B	A A A A A A A A	•	A	H H H H

TERM	C	AND																REMARKS	(OR)												REMARKS
		I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	-	-	-	-	-	-	-	-	-	-	-	-	-	L	-	-	-		-	-	-	-	-	-	-	-	•	•	•	A	B1+0 OUT
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
2	-	H	L	L	-	-	-	H	-	-	H	-	-	-	-	-	-		H	-	-	-	-	-	-	-	•	•	•	•	SHIFT DOWN
3	-	H	L	L	-	-	-	H	-	-	-	H	-	-	-	-	-		-	H	-	-	-	-	-	-	•	•	•	•	" "
4	-	H	L	L	-	-	-	H	-	-	-	-	H	-	-	-	-		-	-	H	-	-	-	-	-	•	•	•	•	" "
5	-	H	L	L	-	-	-	H	-	H	-	-	-	-	-	-	-		-	-	-	H	-	-	-	-	•	•	•	•	" "
6	-	H	L	L	-	-	-	H	-	-	-	-	-	-	H	-	-		-	-	-	-	H	-	-	-	•	•	•	•	" "
7	-	H	L	L	-	-	-	H	-	-	-	-	-	-	-	H	-		-	-	-	-	-	H	-	-	•	•	•	•	" "
8	-	H	L	L	-	-	-	H	-	-	-	-	-	-	-	-	H		-	-	-	-	-	-	H	-	•	•	•	•	" "
9	-	H	L	L	-	-	-	H	-	-	-	-	-	H	-	-	-		-	-	-	-	-	-	-	H	•	•	•	•	" "
10	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	" "
11	-	H	L	L	-	H	H	L	-	-	-	-	-	-	-	-	-		L	-	-	-	-	-	-	-	•	•	•	•	VARIFY IN
12	-	H	L	L	-	L	H	L	-	-	-	-	-	-	-	-	-		H	-	-	-	-	-	-	-	•	•	•	•	" "
13	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
14	A	H	L	L	-	-	-	H	-	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	-	•	•	•	•	SHIFT ENABLE
15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
17	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
18	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
19	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
20	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
21	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
22	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
23	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
24	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
26	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
28	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
29	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
31	-	H	L	H	L	-	-	-	-	-	-	-	-	-	-	-	-		H	H	H	H	H	H	H	H	•	•	•	•	SYNE RESET
FC	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-														
PB	-	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PA	-	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LA	-	H	L	H	H	-	-	-	-	-	-	-	-	-	-	-	-														
D3	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D2	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D1	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D0	-	H	L	L	-	-	-	-	-	-	-	-	-	-	-	-	-														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS																															PLS159

TB01690S

Low Cost Programmer for PLD 20-Pin Series

AN12

Table B-5. Low Cost Programmer PLD #U6 Revision "B" Results in New Timing Figures

CODE NO. U6										FF MODE									E_B				E_A				POLARITY				
										•	•	•	•	•	•	•	•		•				•				H	L	L	L	
	AND																		(OR)												
TERM	C	I				B(I)				Q(P)								REMARKS	Q(N)								B(O)				REMARKS
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	H	L	–	–	–	L	H	H	H	H	H	L	H	H	H	H		L	–	–	–	–	–	–	–	•	•	•	•	SET INT. MODE
1	–	–	L	–	–	–	–	–	–	L	–	–	–	–	–	–	–		–	–	–	–	–	–	–	–	•	A	A	•	SEND INT. MD. C4, C2
2	–	–	L	–	–	–	–	–	–	L	H	H	L	H	H	H	H		–	–	–	–	–	–	L	–	•	•	•	•	DELAY
3	–	H	L	–	H	–	–	–	–	L	H	H	L	H	H	L	H		–	–	L	–	–	–	H	–	•	•	•	•	SET PRO. MD. ZAP FSS
4	–	–	L	–	–	–	–	–	–	L	H	L	L	H	H	H	H		–	–	–	–	L	–	–	–	•	•	•	•	VSP ON
5	–	–	L	–	–	–	–	–	–	L	H	L	L	L	H	H	H		–	–	–	–	–	–	–	L	•	•	•	•	DELAY
6	–	–	L	–	–	–	–	–	–	L	H	L	L	L	H	H	L		–	–	–	H	–	L	–	H	•	•	•	•	STROBE ON & DOWN
7	–	–	L	–	–	–	–	–	–	L	H	L	H	L	L	H	H		–	–	–	L	–	–	–	–	•	•	•	•	STROBE OFF
8	–	–	L	–	–	–	–	–	–	L	H	L	L	L	L	H	H		–	–	–	–	H	–	–	–	•	•	•	•	VP OFF
9	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
10	–	–	L	–	–	–	–	–	–	L	H	L	L	H	L	H	H		–	–	H	–	–	–	–	–	•	•	•	•	SET VERIFY MODE
11	–	–	L	–	–	–	–	–	–	L	H	H	L	H	L	H	H		–	–	–	H	–	–	–	–	•	•	•	•	STROBE ON
12	–	–	L	–	–	–	–	–	–	L	H	H	H	H	L	H	H		–	L	–	–	–	–	–	–	•	•	•	•	INT. STROBE ON
13	–	–	L	–	–	–	–	–	–	L	L	H	H	H	L	H	H		–	H	–	–	–	–	L	–	•	•	•	•	INT. STROBE OFF
14	–	–	L	–	–	–	–	–	–	L	H	H	H	H	L	L	H		–	–	–	L	–	–	–	–	•	•	•	•	STROBE OFF
15	–	–	L	L	–	–	–	–	–	L	H	H	L	H	L	L	H		–	–	–	–	–	H	H	–	A	•	•	•	INCR. VAR ($\overline{\text{BSC}}$)
16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
17	–	–	L	H	–	–	–	–	–	L	H	H	L	H	L	L	H		–	–	–	–	–	H	–	L	A	•	•	•	BAIL OUT
18	A	–	L	–	–	–	–	–	–	L	H	H	L	H	H	L	L		–	–	–	–	–	–	H	–	•	•	•	•	SEND CYCLE COMP.
19	–	–	L	–	–	–	–	–	–	L	H	H	L	H	H	H	L		H	–	–	–	–	–	–	–	•	•	•	•	CLEAR INT. MODE
20	–	–	L	–	–	–	–	–	–	H	H	H	L	H	H	H	L		–	–	–	–	–	–	–	H	•	•	•	•	WAIT (EXT. MODE)
21	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
22	–	H	L	–	L	–	–	–	–	L	H	H	L	H	H	L	H		–	–	–	–	–	L	H	–	•	•	•	•	SET VFY (ZAP)
23	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
24	•	–	L	–	–	–	–	–	–	L	–	–	–	–	–	–	–		–	–	–	–	–	–	–	–	•	•	•	A	SEND INT MD (C0)
25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
26	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
28	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	A	A	A	A	
29	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	–		H	H	H	L	H	H	H	H	•	•	•	•	OFFLINE INITIAL
30	–	H	L	–	–	–	L	H	L	–	–	–	–	–	–	–	–		–	H	H	L	H	H	H	H	•	•	•	•	COMPUTER INITIAL
31	–	–	–	–	–	–	–	–	–	L	L	L	L	L	L	L	L		H	H	H	–	H	H	H	H	•	•	•	•	PWR UP INITIAL
FC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LB	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
PA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
RA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
LA	•	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0														
D3	–	–	–	–	–	–	–	–	–	L	–	–	–	–	–	–	–														
D2	–	–	–	–	–	–	–	–	–	L	–	–	–	–	–	–	–														
D1	–	–	–	–	–	–	–	–	–	L	–	–	–	–	–	–	–														
D0	–	–	–	–	–	–	–	–	–	L	–	–	–	–	–	–	–														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS		DAY	ONLINE	D3-BSC	D1-ZF	D2 INC. VAR.	C2	C1	C0	INT/EXT	VEY 5 B	MODE P/V	$\overline{\text{EN}}$	VFSP	UP-DOWN	TD1	TD0														PLS159

TB01700S

Low Cost Programmer for PLD 20-Pin Series AN12

Table B-6. Low Cost Programmer Parts List

REF. DES.	QUANT.	DESCRIPTION	RADIO SHACK#
Resistors			
R1	1	100Ω 1/4W 5%	
R2	1	620Ω 1/4W 5%	
R3, R5	2	1KΩ 1/4W 5%	271-1421
R14, R15	2	270Ω 1/4W 5%	
R4, R6	2	1.8KΩ 1/4W 5%	271-1324
R7	1	39Ω 1/4W 5%	
R8	1	3.3Ω 1/4W 5%	
R9	1	120Ω 1/4W 5%	
R10	1	75Ω 1/4W 5%	
R11	1	47Ω 1/4W 5%	271-1307
R12*	1	1KΩ 1/4W 5%	271-023
R13	1	10KΩ 1/4W 5%	
RN1	1	10KΩ 1/4W 5% 8-Pin SIP	
Capacitors			
C1	1	0.047μF	
C2, C4	2	4700μF Elec. 35V Axial	272-1022
C3	1	220μF Elec. 35V Axial	272-1017
C6, C7	2	470μF	
C5, C8 – C13	7	0.01μF	
Diodes			
D1A	1	6.2V Zener 1N4735	276-561
D1B	1	9.1V Zener 1N4739	276-563
D2	1	1N4001	276-1101
D3, D4	2	10mA Red LED	276-041
DB1, DB2	2	1.4A Full-Wave Bridge	276-1151
Voltage regulators			
VR1 – VR3	3	LM317 TO-220	276-1778
VR4	1	7805 TO-3	
Integrated circuits			
U1, U2, U4 – U6	5	PLS159IFL — Codes Req'd	
U3	1	AY-3-1015 UART	276-1794
Transformers			
T1, T2	2	18.0VAC CT, 2A	273-1515
FB1	1	Ferrite Bead FB-75B-01 Amidon Associates	
Transistors			
Q1 – Q4	4	2N2222 Transistors	276-2009
Q5	1	TIP 120 Power Dar.	

Low Cost Programmer for PLD 20-Pin Series

APPENDIX C


NO PARITY
NUMBER STOP BITS
ODD/EVEN PARITY SELECT
NUMBER DATA BITS
TRANSMITTER DATA BITS
DS8
DS1
CONTROL STROBE
DATA STROBE
SERIAL OUTPUT
TRANSMITTER
16 × T CLOCK
END OF CHARACTER
16 × R CLOCK
RECEIVER
EXTERNAL RESET
SERIAL INPUT
STATUS WORD ENABLE
RECEIVED DATA ENABLE
OVER RUN
FRAMING ERROR
PARITY ERROR
TRANSMITTER BUFFER EMPTY
DATA AVAILABLE
RESET DATA AVAILABLE
RD8
RD1
RECEIVER DATA BITS
BD01780S

Figure C-1. Block Diagram


TOP VIEW
V_{CC}(+5V) 1
NC 2
GND 3
RDE 4
RD6 5
RD7 6
RD6 7
RD5 8
RD4 9
RD3 10
RD2 11
RD1 12
PE 13
FE 14
OR 15
SWE 16
RCP 17
RDAV 18
DAV 19
S4 20
40 TCP
39 EPS
38 NB1
37 NB2
36 TSB
35 NP
34 CS
33 DB8
32 DB7
31 DB6
30 DB5
29 DB4
28 DB3
27 DB2
26 DB1
25 SO
24 EOC
23 DS
22 TBMT
21 XR
CD04510S

Figure C-2

Signetics

Application Specific Products

AN13
Oscillator With PLS159

Application Note

INTRODUCTION

The Field-Programmable Logic Sequencer PLS159 may be a self-contained system except that it requires a system clock which is generally provided by an external source. Using a simple R-C network, two bidirectional I/O pins, one can make a simple oscillator which can provide a clock frequency up to 7MHz (typical) with a pulse width of about 75ns. The frequency of oscillation is set by adjusting the RC network, or by adjusting a reference voltage, V. The circuit is shown in Figure 1. This circuit may be used to clock the flip flops on the same chip, or provide a clock for a bigger system. While this circuit uses only two AND-terms and one control term, the rest of the chip may be used for other circuits.

Initially, the capacitor has zero charge and thus is at zero volt. Output is also at a Low, which disables the tri-state buffer. As the capacitor is being charged up, its voltage increases. At about 1.6V, the non-inverting input buffer begins to turn on. One propagation delay later, the output goes High, which enables the tri-state buffer after another propagation delay. Since the tri-state buffer is unconditionally programmed to a Low, it begins to discharge the capacitor at a fast rate. As the input voltage to the non-inverting buffer drops below 1.6V, the buffer begins to change state. One propagation delay later, output goes Low, which disables the tri-state buffer after another propagation delay. The R-C network is ready to start all over again.

To implement this circuit, we first choose B_1 to input voltage from the RC network and B_0 to be the output pin. As shown in Table 1, we enable the output $B(O)_0$ by "dashing out" the AND-term D_0, make the output non-inverting by programming POLARITY "H" and connect it to term-0 by entering an A in column $B(O)_0$ term-0. We then program an H in $B(I)_1$, term-0 to connect the non-inverting input of B_1 to term-0. Since we don't need the rest of the inputs and outputs, we "dash out" all other input entries and "dot out" all unused outputs in term-0. To create a Low output on $B(O)_1$, we may either have a Low input on the OR and have the output non-inverted, or have a High on the input of OR and have the output inverted to produce a Low. We will arbitrarily use the second method. Here we dash out all inputs and outputs in term-1 except $B(O)_1$ which is programmed an A. We then program the POLARITY of $B(O)_1$ "L" to be inverting. Finally we program an H in $B(I)_0$ and term-D_1 and dash out all unused inputs so that when $B(O)_0$ becomes High, D_1 will enable the output buffer $B(O)_1$. The program is further illustrated by Figure 2.



Figure 1. R-C Network Circuit

Since the High output pulsewidth is about two propagation delays of B_1 to B_0, it is wide enough to drive the clock input of the PLS159. If a square wave is desired, one of the flip flops may be programmed to toggle, as shown in Table 1, term-4, in which case the output frequency of the square wave is half that of $B(O)_0$.

The stability of the output frequency can be controlled by:

1. Making V a stable voltage source,
2. making the charging current of the RC network much greater than the input current of $B(I)_1$ (see Figure 4 for input current characteristics),
3. making the period of oscillation much greater than four times the internal propagation delay (typical $t_{PD} = 35ns$).

Recommendations:

a) Use capacitance less than 500pf.

b) Choose R such that $V/R >> I_{IL}$ (since $I_{IL} = -100\mu A$, worst case, over temperature range, V/R may be 1mA, for example).

The recommendations above put a limit to the range of frequency which the PLS159 may operate in exchange for stable operating frequency. One may extend its range by reducing C to zero (remove the capacitor) and thus operate the circuit at its maximum frequency, or increase the resistance to infinite (remove the resistor), and let the external capacitor be charged by the input current I_{IL}, which gives a much lower frequency.

Oscillator With PLS159

AN13

Table 1. PLS159 FPLS Program Table

CODE NO.										FF MODE									EB				EA				POLARITY				
																													L	H	
	AND																		(OR)												
TERM	C	I				B(I)				Q(P)								REMARKS	Q(N)								B(O)				REMARKS
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	–	–	–	–	–	–	H	–	–	–	–	–	–	–	–	–		–	–	–	–	–	–	–	–	•	•	•	A	$B_0 = B_1$
1	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	–	–	–	–	–	–	•	•	A	•	$B_{(0)-1}$ =LOW
2																															
3																															
4	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	–	–	–	–	–	O	•	•	•	•	SQUARE WAVE
5																															SEE COMMENT #2
6																															
7																															
8																															
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1	–	–	–	–	–	–	–	–	H	–	–	–	–	–	–	–	–														
D0	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS																													SEE COMMENT[#1]	B(O)-ø ENABLED	PLS159

TB00510S

COMMENTS:

1. D_1 is controlled by $B(1)_0$, which enables $B(O)_1$ when $B(O)_0$ outputs a High.
2. $Q(N)_{-0}$ is programmed as J-K flip-flop, and will toggle automatically at each rising-edge of the clock.

NOTE:

1. In order for the flip-flop to work the clock out (B_O) must be externally connected to pin 1.

Oscillator With PLS159

AN13


V NOTE: V<5.5V
R
C
B1
D0
B0
OUTPUT
D1
0
1
X
X
X
TC00890S

Figure 2. Logic Diagram of Oscillator Circuit

Oscillator With PLS159


(LOGIC TERMS — T)
(CONTROL TERMS)
OE
11
I_0 2
I_1 3
I_2 4
I_3 5
F_0
F_1
F_2
F_3
F_4
F_5
F_6
F_7
B_0
B_1
B_2
B_3
$\overline{C}$
C
P_B
R_B
P_A
R_A
L_B
L_A
D_3
D_2
D_1
D_0
E_A
E_B
S_3
S_2
S_1
S_0
X_3
X_2
X_1
X_0
9 B_3
8 B_2
7 B_1
6 B_0
M_7
M_6
M_5
M_4
M_3
M_2
M_1
M_0
P
R
J
K
Q
CK'
19 F_7
18 F_6
17 F_5
16 F_4
15 F_3
14 F_2
13 F_1
12 F_0
31 • • • • • • • 24 23 • • • • • • • 16 15 • • • • • • • 8 7 • • • • • • • 0 F_C
CK
1 CK
LD01681S

NOTES:
1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.

Figure 3. Logic Diagram of PLS159 FPLS



OP00520S

Figure 4. Input Current vs Input Voltage Characteristics of I/O Pins



$V_{CC}=5.0V$, $V=5.0V$, $T_A=25$ C

R – 2.2K, C – 500pF

$V_{CC}=5.0V$, $V=5.0V$, $T_A=25$ C

R = 2.2K, C = 500pF

WF05030S

Figure 5. Output Waveforms of Oscillator Circuit

Signetics

Application Specific Products

AN14
Latches and Flip-Flops With PLS153

Application Note

DESCRIPTION

Using the simple AND, OR and INVERT logic functions of the PLS153, memory functions such as latches and edge-triggered flip-flops may be implemented with a relatively small part of the chip and without external wiring. In this application note, we will discuss the implementation of two R-S latches, a D-latch, an edge-triggered R-S flip-flop, and an edge-triggered D flip-flop.

INTRODUCTION TO PLS153

To implement this function, let's first take a look at the PLS153 logic diagram and its programming table as shown in Appendices A and B. On the left side of the logic diagram (Appendix A) are eight dedicated inputs, I_0 to I_7, each of which has a true and a complement output. Each output is connected to the inputs of 32 AND functions (we will call them AND-terms from now on), the outputs of which are, in turn, connected to the inputs of ten OR functions. The output of each OR function is connected to one input of an Exclusive-OR function, which is in turn connected to a non-inverting output buffer. The function of the XOR is to control the output polarity. The output, in its virgin state, is non-inverting, since one side of the XOR is connected to ground by the fuse X_n, where n = 0, 1, 3...9. To have the output inverted, one needs only to blow fuse X_n open so that the X_n input is unconditionally High. The output buffers are all three-state buffers which may be enabled or disabled by their corresponding AND gates. The output buffers are disabled in their virgin state. All pins labeled "B" are bidirectional. Input buffers of the "B" pins are identical to those of the "I" pins.

The programming table shown in Appendix B emulates a truth table. All the inputs to the device are positioned on the left side, and all the outputs are on the right side. Each row in the table corresponds to an 18-input AND-term with up to ten outputs. On the left side, or the input side of the table, each column represents an input. The 18 columns represent input buffers I_0 to I_7, B_0 to B_9. To distinguish between inputs and outputs of the bidirectional pin, B(I) is used for input and B(O) is used for outputs as shown in the programming table. On the right side of the table, each column represents an output circuit ($(B(O)_{0-9})$) which consists of an OR gate, an XOR, and a non-inverting three-state buffer. The output buffers are controlled by AND-terms D_0 to D_9, the inputs of which may be connected to any number of the 18 inputs. The polarity of the outputs is defined by the POLARITY entries which are on the upper right corner of the programming table.

To program the inputs to the AND-terms, an "H" will cause the fuse of the inverting input buffer to be blown, leaving the non-inverting buffer connected to the AND-term; an "L" will do the opposite. A " – " will cause both fuses to be blown, and therefore the programmed input is a "Don't care". A "0", the virgin state of the device, has both fuses intact, which causes the output of the AND-term to be unconditionally Low.

To program the outputs, a "." causes the fuse that connects the output of AND-term to the input of an OR to be blown and thus renders the output inactive. An "A" causes the fuse to remain intact and thus the output is active.

The output polarity of each output buffer may be programmed by entering an "H" or an "L" in the POLARITY section. An "L" causes the XOR to blow its grounding fuse and become inverted, whereas an "H" leaves the fuse intact and the output is non-inverted.

To AND several inputs, we put them in a row; to OR several inputs, we put them in different rows, as shown in illustrations in Appendix B.

Latches and Flip-Flops With PLS153

AN14

SIMPLE R-S LATCH

A simple R-S latch may be formed by cross-coupling two NAND functions together as shown in Figure 1.

As an illustration, let's assign the input R to I_0 of the PLS153, input S to I_1, output Q to B_0, and output $\overline{Q}$ to B_1. As shown in Table 1, to form the NAND gates we need to program the POLARITY Low on $B(O)_0$ and $B(O)_1$. To unconditionally enable the output buffers, we "dash" out all inputs to D_0 and D_1. As for the inputs, we put an "H" on I_0, term-0 for the input R, non-inverted; another "H" on $B(I)_1$, term-0 for the feedback from Q. In the same manner, we program I_1, term-1 and $B(O)_0$ "H". The POLARITY, rows 0, 1, D_0 and D_1, forms a "truth table" with which one can analyze his own or someone else's design. The program in Table 1 may be illustrated as shown in Figure 2.



Figure 1. RS Latch



Figure 2. RS Latch

Latches and Flip-Flops With PLS153

AN14

Table 1. PLS153/153A Programming Table

CODE NO.

TERM	AND																		REMARKS	POLARITY										REMARKS
																												L	L	
																				OR										
	I								B(I)											B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	
0	-	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	H	-		●	●	●	●	●	●	●	●	●	A	$Q=/(R\cdot\overline{Q})$
1	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	H		●	●	●	●	●	●	●	●	A	●	$\overline{Q}=/(S\cdot Q)$
2																														
3																														
4																														
5																														
6																														
7																														
8																														
9																														
10																														
11																														
12																														
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5																														
D4																														
D3																														
D2																														
D1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS							S	R									$\overline{Q}_0$	Q_0										$B(O)_1$ ($\overline{Q}_0$)	$B(O)_0$ (Q_0)	PLS153

TB00860S

ANOTHER SIMPLE R-S LATCH

Another way to implement a simple latch is shown in Figure 3, in which two NOR functions are cross-coupled to form a latch.

As with the previous example, we first define the input and output pins. For this example, we use I_2 for the R input, I_3 for the S input, B_2 for the Q output, and B_3 for the $\overline{Q}$ output. We program B_2 and B_3 to have inverted outputs by programming POLARITY of B_2 and B_3 Low, as shown in Table 2. Terms 6 and 7 are ORed together by $B(O)_2$, rows 6 and 7. In the same manner $B(O)_3$ ORs Terms 8 and 9. The programmed table of this design may be represented as shown in Figure 4.

Since each AND-term of the PLS153 can accommodate up to 18 inputs (true or inverting inputs of eight from I_0 to I_7 and ten from B_0 to B_9), and each OR circuit can be connected to up to thirty-two AND-terms, we can add additional features such as those shown in Figure 5.

The programming of this design is left to the reader as an exercise.



Figure 3. RS Latch



Figure 4. RS Latch



Figure 5. RS Latch

Table 2. PLS153/153A Programming Table

CODE NO.																				POLARITY										
																										L	L	L	L	
TERM	AND																			OR										
	I								B(I)											B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	REMARKS	9	8	7	6	5	4	3	2	1	0	REMARKS
0	-	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	H	-	$R \cdot \overline{Q}$	•	•	•	•	•	•	•	•	•	A	$Q=/(R \cdot \overline{Q})$
1	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	H	$S \cdot Q$	•	•	•	•	•	•	•	•	A	•	$\overline{Q}=/(S \cdot Q)$
2																														
3																														
4																														
5																														
6	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	R	•	•	•	•	•	•	•	A	•	•	$Q=/(R+\overline{Q})$
7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	-	$\overline{Q}$	•	•	•	•	•	•	•	A	•	•	$Q=/(R+\overline{Q})$
8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	Q	•	•	•	•	•	•	A	•	•	•	$\overline{Q}=/(Q+S)$
9	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	S	•	•	•	•	•	•	A	•	•	•	$\overline{Q}=/(Q+S)$
10																														
11																														
12																														
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5																														
D4																														
D3																														
D2																														
D1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		-												
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS					S	R	S	R							$\overline{Q}$	Q	$\overline{Q}$	Q								B_3 ($\overline{Q}_1$)	B_2 (Q_1)	B_2	B_0	

PLS153

TB00870S

Latches and Flip-Flops With PLS153

AN14

D-LATCH

A simple D-latch can be constructed with an PLS153 as shown in Figure 6.

This circuit may be easily programmed into the PLS153 as shown in Table 3. The program may, in turn, be represented as shown in Figure 7.

This circuit may be expanded to have multiple D-latches using the same latch enable (LE).


D
Q
LE
LS01750S

Figure 6. D Latch

R-S FLIP-FLOP

Two R-S latches may be combined to form a master-save flip-flop that is triggered at the rising-edge of the clock (or the falling-edge of the clock, if the designer so desires). Figure 8 shows a combination of two sets of cross-coupled NOR gates concatenated to form the flip-flop. The implementation of this circuit using PLS153 is as illustrated in Table 4 and Figure 9.


I_5
D
11
Q
B_4
12
I_6
LE
LS01760S

Figure 7. D-Latch


R
$\overline{Q}$
S
Q
CK
LS01770S

Figure 8. RS Flip-Flop


D_0
B_0
D_2
I_0
R
0
1
5
6
B_2
$\overline{Q}$
2
3
7
8
B_3
Q
I_1
S
CK
D_1
B_1
LS01780S

Figure 9. RS Flip-Flop

Latches and Flip-Flops With PLS153

Table 3. PLS153/153A Programming Table

CODE NO.																				POLARITY										
																										H	L	L	L	L	
TERM	AND																			OR										
	I								B(I)											B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	REMARKS	9	8	7	6	5	4	3	2	1	0	REMARKS
0	-	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	H	-	R • $\overline{Q}$	•	•	•	•	•	•	•	•	•	A	/(R • $\overline{Q}$)
1	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	H	S • Q	•	•	•	•	•	•	•	•	A	•	/(S • Q)
2																														
3																														
4																														
5																														
6	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	R	•	•	•	•	•	•	•	A	•	•	}/(R+$\overline{Q}$)
7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	-	$\overline{Q}$	•	•	•	•	•	•	•	A	•	•	)
8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	Q	•	•	•	•	•	•	A	•	•	•	}/(Q+S)
9	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	-	-	S	•	•	•	•	•	•	A	•	•	•	)
10																														
11	-	H	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	LE • D	•	•	•	•	•	A	•	•	•	•	}(LE • D+
12	-	L	-	-	-	-	-	-	-	-	-	-	-	H	-	-	-	-	$\overline{LE}$ • Q	•	•	•	•	•	A	•	•	•	•	) $\overline{LE}$ • Q)
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5																														
D4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS		LE	D		S	R	S	R						Q	$\overline{Q}$	Q	$\overline{Q}$	Q							B_4	B_3	B_2	B_1	B_0	PLS153

TB00850S

Latches and Flip-Flops With PLS153 AN14

Table 4. PLS153/153A Programming Table

CODE NO.

TERM	AND																		REMARKS	POLARITY										REMARKS
																										L	L	L	L	
	I								B(I)											OR B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	
0	-	-	-	-	-	L	-	H	-	-	-	-	-	-	-	-	-	-	$\overline{CK} \cdot R$	●	●	●	●	●	●	●	●	●	A	$/(R \cdot \overline{CK} + B_1)$
1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	B_1	●	●	●	●	●	●	●	●	●	A	
2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	B_0	●	●	●	●	●	●	●	●	A	●	$/(S \cdot \overline{CK} + B_0)$
3	-	-	-	-	-	L	H	-	-	-	-	-	-	-	-	-	-	-	$\overline{CK} \cdot S$	●	●	●	●	●	●	●	●	A	●	
4																														
5	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	H	$CK \cdot B_0$	●	●	●	●	●	●	●	A	●	●	$/(B_0 \cdot CK + B_3)$
6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	-	B_3	●	●	●	●	●	●	●	A	●	●	
7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	B_2	●	●	●	●	●	●	A	●	●	●	$/(B_1 \cdot CK + B_2)$
8	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	H	-	$CK \cdot B_1$	●	●	●	●	●	●	A	●	●	●	
9																														
10																														
11																														
12																														
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5																														
D4																														
D3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS						CK	S	R							$Q = B_3$	$\overline{Q} = B_2$	B_1	B_0								$B_3 = Q$	$B_2 = \overline{Q}$	B_1	B_0	

PLS153

TB00840S

D FLIP-FLOP

An edge-triggered master-slave D flip-flop may be constructed with two D-latches in the manner shown in Figure 10.

An PLS153 may be programmed as shown in Figure 11 to implement the D flip-flop which is equivalent to the circuit shown in Table 5 in the PLS153 logic representation.


D
CK
Q
LS01790S

Figure 10. D Flip-Flop


D4
I3
D
11
12
B4
D5
14
15
B5
Q
I4
CK
LS01800S

Figure 11. D Flip-Flop

Table 5. PLS153/153A Programming Table

CODE NO.																				POLARITY										
																								H	H	L	L	L	L	
TERM	AND																			OR										
	I								B(I)											B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	REMARKS	9	8	7	6	5	4	3	2	1	0	REMARKS
0	-	-	-	-	-	L	-	H	-	-	-	-	-	-	-	-	-	-	$R \cdot \overline{CK}$	•	•	•	•	•	•	•	•	•	A	$/(R \cdot \overline{CK} + B_1)$
1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	B_1	•	•	•	•	•	•	•	•	•	A	
2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	B_0									A		
3	-	-	-	-	-	L	H	-	-	-	-	-	-	-	-	-	-	-	$S \cdot \overline{CK}$									A		
4																														
5	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-	H	$CK \cdot B_0$								A			$/(B_0 \cdot CK + Q)$
6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	-	Q								A			
7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H	-	-	B_2							A				$/(B_1 \cdot CK + B_2)$
8	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	H	-	$B_1 \cdot CK$							A				
9																														
10																														
11	-	-	-	L	H	-	-	-	-	-	-	-	-	-	-	-	-	-	$\overline{CK} \cdot D$						A					$(\overline{CK} \cdot D + CK \cdot$
12	-	-	-	H	-	-	-	-	-	-	-	-	-	H	-	-	-	-	$CK \cdot B_4$						A					$B_4)$
13	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
14	-	-	-	H	-	-	-	-	-	-	-	-	-	H	-	-	-	-	$CK \cdot B_4$					A						$(CK \cdot B_4 + \overline{CK} \cdot$
15	-	-	-	L	-	-	-	-	-	-	-	-	H	-	-	-	-	-	$\overline{CK} \cdot Q$					A						$Q)$
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS				CK	D	$\overline{CK}$	S	R					B_5 (Q)	B_4	$Q = B_3$	$\overline{Q} = B_2$	B_1	B_0						B_5 (Q)	B_4	B_3	B_2	B_1	B_0	

PLS153

TB00830S

APPENDIX A


(LOGIC TERMS—P)
(CONTROL TERMS)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
I_8 9
I_9 10
I_{10} 11
I_{11} 13
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
B_9
D_9 D_8 D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
S_9 S_8 S_7 S_6 S_5 S_4 S_3 S_2 S_1 S_0
X_9 X_8 X_7 X_6 X_5 X_4 X_3 X_2 X_1 X_0
23 B_9
22 B_8
21 B_7
20 B_6
19 B_5
18 B_4
17 B_3
16 B_2
15 B_1
14 B_0
31 • • • • • • 24
23 • • • • • • • 16
15 • • • • • • • 8
7 • • • • • • • 0
TB00942S

NOTES:

1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. Programmable connection.

Figure A-1. FPLA Logic Diagram

Latches and Flip-Flops With PLS153

AN14

Appendix B. PLS153/153A Programming Table

CODE NO.																					POLARITY										
																					H	H	H	H	L	L	L	H	H	H	
TERM	AND																				OR										
	I								B(I)												B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	REMARKS	9	8	7	6	5	4	3	2	1	0	REMARKS
0	H	H	H	H	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A•B•C•D	A	•	•	•	A	•	•	•	•	•	{X = A•B•C•D
1																														T =/(A•B•C•D)
2																														
3																														
4	L	L	L	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	$\overline{A}\cdot\overline{B}\cdot\overline{C}\cdot\overline{D}$	•	A	•	•	•	A	•	•	•	•	{$Y=\overline{A}\cdot\overline{B}\cdot\overline{C}\cdot\overline{D}$
5																														$u=/(\overline{A}\cdot\overline{B}\cdot\overline{C}\cdot\overline{D})$
6																														
7																														
8																														
9	-	H	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-		$B\cdot\overline{C}$	•	•	A	•	•	•	A	•	•	•	$Z=(B\cdot\overline{C}+B\cdot\overline{D}+$
10	-	H	-	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	$B\cdot\overline{D}$	•	•	A	•	•	•	A	•	•	•	$\overline{C}\cdot\overline{D})$
11	-	-	L	L	-	-	-	-	-	-	-	-	-	-	-	-	-	-	$\overline{C}\cdot\overline{D}$	•	•	A	•	•	•	A	•	•	•	$V=/(B\cdot\overline{C}+B\cdot\overline{D}$
12																														$+\overline{C}\cdot\overline{D})$
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D6																														
D5		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D4			-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D3	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-												
D2																														
D1																														
D0																														
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS	A	B	C	D					X	Y	Z		T	U	V					X	Y	Z		T	U	V				

PLS153

TB00820S

APPENDIX C

R-S LATCH (Cross-Coupled NOR)
See Figures 3 and 4 and Table 2



R-S LATCH (Cross-Coupled NAND)
See Figures 1 and 2 and Table 1



D-LATCH
See Figures 6 and 7 and Table 3



Typical set-up time ≅ 0ns
Typical hold time ≅ 0 – 5ns
Typical propagation delay ≅ 20ns

EDGE-TRIGGERED R-S Flip-Flop
See Figures 8 and 9 and Table 4



NOTE: Timing requirements/performances are the same as the R-S latches

EDGE-TRIGGERED D Flip-Flop –
See Figures 10 and 11 and Table 5



NOTE: Timing requirements/performances are the same as the D-latch

Figure C-1. Timing Photos

AN15
PLS159 Primer

Application Note

Application Specific Products

INTRODUCTION

The PLS159 is a field programmable logic sequencer which consists of four dedicated inputs, four bidirectional I/O's, eight flip-flops, thirty two 16-input AND gates, twenty 32-input OR gates, and a complement array. Each flip-flop has a bidirectional I/O and may be individually programmed as J-K or D flip-flop, or switch between the two types dynamically. The flip-flops will accept data from the internal logic array or from the bidirectional I/O, or they may be set or reset asynchronously from the AND array. The output polarity of the four bidirectional I/O's are programmable and the direction is controlled by the AND array. Figure 1 is the logic diagram of PLS159.

PROGRAMMING THE PLS159

The programming table is shown in Table 1 where there is a place for everything that is shown in Figure 1. The program table is basically divided into two main sections. The left hand side of the table, section A, represents the input side of the AND gates, while the right hand side, section B, represents the OR gates sections which includes the flip-flops and the combinatorial outputs B(0) to B(3). The flip-flops modes are defined in section C and the output polarities of the combinatorial outputs are defined in section E. The programming symbols are detailed in Figure 2.

As shown in Table 1, the programming table is very similar to a truth table. Each column in section A represents an input to the 32 AND gates, and each row represents an AND gate connecting to 17 inputs. Columns I_0 to I_3 represent the 4 dedicated inputs, I_0 to I_3. Columns $B(I)_0$ to $B(I)_3$ represent the inputs of the 4 bidirectional I/O, B_0 to B_3. Columns $Q(P)_0$ to $Q(P)_7$ represent the feedback, F_0 to F_7, from the flip-flops (the present state). Column "C" represents the complement array.

As shown in Figure 1, the outputs of the AND gates are connected to an array of OR gates which, in turn, are connected to either flip-flops or output circuits. Columns $Q(N)_0$ to $Q(N)_7$ represent the next state which the flip-flops will be in. Columns $B(O)_0$ to $B(O)_3$ represent the combinatorial outputs B_0 to B_3.

Each row represents an AND gate with 17 inputs each of which may be true and/or complement and is, therefore, a perfect decoder. Referring to the programming symbols in Figure 2, to implement the equation

$$Z = A * B * C * D,$$

all one has to do is to enter one line as shown in Table 2, term-0.


(LOGIC TERMS — T)
(CONTROL TERMS)
OE
11
I_0 2
I_1 3
I_2 4
I_3 5
F_0
F_1
F_2
F_3
F_4
F_5
F_6
F_7
B_0
B_1
B_2
B_3
$\overline{C}$
C
S_3
S_2
S_1
S_0
X_3
X_2
X_1
X_0
P_B R_B P_A R_A L_B L_A D_3 D_2 D_1 D_0
E_A E_B
9 B_3
8 B_2
7 B_1
6 B_0
M_7 M_6 M_5 M_4 M_3 M_2 M_1 M_0
P
R
J Q
K
CK'
19 F_7
18 F_6
17 F_5
16 F_4
15 F_3
14 F_2
13 F_1
12 F_0
31 • • • • • • • 24 23 • • • • • • • 16 15 • • • • • • • 8 7 • • • • • • • 0 F_C
CK
1 CK
LD01681S

NOTES:
1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.

Figure 1. FPLS Logic Diagram

Table 1. FPLS Program Table


CODE NO.
SECTION C
FF MODE
EB
EA
POLARITY
SECTION D
AND
(OR)
SECTION E
TERM
C
I
B(I)
Q(P)
REMARKS
Q(N)
B(O)
REMARKS
3 2 1 0 3 2 1 0 7 6 5 4 3 2 1 0
7 6 5 4 3 2 1 0 3 2 1 0
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31
FC
PB
RB
LB
PA
RA
LA
D3
D2
D1
D0
PIN
5 4 3 2 9 8 7 6 19 18 17 16 15 14 13 12
19 18 17 16 15 14 13 12 9 8 7 6
REMARKS
SECTION A
SECTION B
PLS159
TB00051S

The FPLS can be programmed by means of Logic Programming equipment.

With Logic programming, the AND/OR-EX-OR input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Tables on the following pages.

In these Tables, the logic state or action of all I/O, control, and state variables is assigned a symbol which results in the proper fusing pattern of corresponding links defined as follows:


I, B, Q
I, B, Q
Ī, B̄, Q̄
(T, F_C, L, P, R, D)$_n$
STATE | CODE
INACTIVE^{1,2} | O
LD00080S
I, B, Q | H
LD00090S
Ī, B̄, Q̄ | L
LD00100S
DON'T CARE | –
LD00110S

"AND" ARRAY – (I), (B), (Qp)


C̄
C
(T_n, F_C)
ACTION | CODE
INACTIVE^{1,3,5} | O
LD00120S
GENERATE^5 | A
LD00130S
PROPAGATE | •
LD00140S
TRANSPARENT | –
LD00150S

"COMPLEMENT" ARRAY – (C)


C̄
C
(D_n L_n P_n R_n)
ACTION | CODE
PROPAGATE | •
LD00160S
TRANSPARENT | –
LD00170S
F_C
M
J
K
Q
J/K OR D (CONTROLLED) | A
LD00180S
J-K | •
LD00190S

"COMPLEMENT" ARRAY (cont.)

"OR" ARRAY – (MODE)


T_n
M = DISABLED
M = ENABLED
J
K
Q
T_n STATUS | CODE
ACTIVE (Set) | A
LD00202S
INACTIVE (Reset) | •
LD00210S

"OR" ARRAY – (Q_N = D-Type)

Figure 2


T_n
M = DISABLED
J
K
Q
LD00221S
LD00230S
LD00240S
LD00250S

T_n STATUS	CODE
TOGGLE	O

ACTION	CODE
SET	H

ACTION	CODE
RESET	L

ACTION	CODE
HOLD	–

"OR" ARRAY – (Q_n = J-K Type)


T_n
P, R, S
(OR B)
S
B
LD00260S
LD00270S
LD00280S
LD00290S

T_n STATUS	CODE
ACTIVE	A

T_n STATUS	CODE
INACTIVE	•

POLARITY	CODE
LOW	L

POLARITY	CODE
HIGH	H

"OR" ARRAY – (S or B), (P), (R)

"EX-OR" ARRAY – (B)


$\overline{OE}$
E_n
LD00300S
LD00310S
LD00320S
LD00330S

ACTION	CODE
IDLE[4]	O

ACTION	CODE
CONTROL	A

ACTION	CODE
ENABLE[4]	•

ACTION	CODE
DISABLE	–

"$\overline{OE}$" ARRAY – (E)

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates.
2. Any gate (T, F_C, L, P, R, D$)_n$ will be unconditionally inhibited if any one of the I, B, or Q link pairs is left intact.
3. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n, F_C.
4. E_n = O and E_n = • are logically equivalent states, since both cause F_n outputs to be unconditionally enabled.
5. These states are not allowed for control gates (L, P, R, D$)_n$ due to their lack of "OR" array links.

Figure 2 (continued)

Table 2. FPLS Program Table

CODE NO.	FF MODE	E_B	E_A	POLARITY			
				H	H	H	H

TERM	AND																	REMARKS	(OR)												REMARKS
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	H	H	H	H	–	–	–	–	–	–	–	–	–	–	–	–	A*B*C*D	–	–	–	–	–	–	–	–	•	•	•	A	Z=A*B*C*D
1																															
2	–	L	H	L	–	–	–	–	–	–	–	–	–	–	–	–	–	/A*B*/C	–	–	–	–	–	–	–	–	•	•	A	•	Y=/A*B*/C
3																															
4	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	"1"	–	–	–	–	–	–	–	–	•	A	•	•	X=1
5																															
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	"0"	0	0	0	0	0	0	0	0	A	A	A	A	VIRGIN CONDITION
7	–	–	–	0	–	–	–	–	–	–	–	–	–	–	–	–	–	"0"	–	–	–	–	–	–	–	–	A	•	•	•	W=0
8																															
9	–	H	L	–	–	–	–	–	–	–	–	–	–	–	–	–	–	A*/B	–	–	–	–	–	–	–	–	A	•	•	•	W=A*/B
10	–	–	–	H	L	–	–	–	–	–	–	–	–	–	–	–	–	C*/D	–	–	–	–	–	–	–	–	A	•	•	•	W=C*/D
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1																															
D0																															
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS		A	B	C	D																						W	X	Y	Z	

PLS159

TB00391S

Notice that only I_0 to I_3 on the left hand side and $B(O)_4$ on the right hand side have entries to implement the equation. All unused columns are dashed out or dotted out.

To implement the equation

Y = /A * B * /C,

enter one line as shown in Table 2, term-2 where the entry "H" represents the non-inverting input buffer while the entry "L" represents the inverting buffer. To have the AND gate to be unconditionally "High", dash out all the inputs of that particular AND gate as shown in Table 2, term-4. The virgin condition of the device, as shipped from the factory, has all connections intact, which means that the inverting and the non-inverting buffers of the same inputs are connected together. Such connection will cause the AND gate to be unconditionally "Low" as shown in Table 2, terms 6 and 7. The unconditional High and Low states are normally useful only internally and seldom brought out to the output pins.

To implement the equation

W = A * /B + C * /D,

enter one line for A * /B and another line for C * /D as shown in Table 2, terms 9 and 10. Use one line to AND something together; use different lines to OR something together — one line per item to be OR'ed.

All the pins which are labelled B's are bidirectional I/O pins. Their input buffers are represented by the B(I) columns on the left hand side of the programming table. An "H" entry represents the non-inverting buffer and an "L" entry represents the inverting buffer. Their output buffers are represented by the B(O) columns on the right hand side of the table. An "A" entry means that the output is active (connected to the AND gates); a "." entry means that the output is inactive (not connected). The outputs may be programmed to be inverting or noninverting. The polarity of each output is determined by its exclusive OR gate (Figure 1 and Figure 2). To have a non-inverting output, enter an "H" in the section labelled "POLARITY" (Table 1, Section E). To have an inverting output, enter an "L". For example, Table 3, terms-0 and-2 implement the equation

Z = /(A * B) and Y = A * B

respectively. The above two equations may also be implement by term-4 which uses the same AND gate to drive two OR gates.

Besides being able to have programmable Active-High or Active-Low output, the programmable output polarity feature also low output, the programmable output polarity feature also allows the user to minimize his AND term utilization by converting his logic equation into other forms such as conversion by De Morgan Theorem.

For example, the equation

X = A + B + C + D

takes four AND terms to implement as shown in Table 3, terms 6 to 9. By using De Morgan Theorem, the same equation is changed to

/W = /A * /B * /C * /D

The result is as shown in term 11 – a saving of three AND terms. The output buffers are disabled in their virgin states so that they all behave as inputs. The buffers are enabled or disabled by their corresponding Control AND terms D_0 to D_3 (see Figure 1). The Control AND terms are represented in the programming table on the last four rows on the left hand side. Dashing out all the inputs will cause the output buffer to be unconditionally enabled, whereas a "0" (zero) will cause the buffer to be unconditionally disabled. The buffers may also be controlled by a logical condition, e.g. A * /B * /C, etc.

There are eight flip-flops on the chip each of which may be programmed as a J/K or a D flip-flop, or they may be programmed to switch dynamically. As shown in Figure 1, each flip-flop is a J/K to begin with. A tri-state inverter is connected in between the J and K inputs of each flip-flop, which when enabled by the AND gate F_C, will cause the flip-flop to function as a D flip-flop. The inverters are enabled by F_C through fuses M_0 to M_7. A "." in the F/F Mode entry of the programming table means that particular fuse is to be disconnected and that particular flip-flop is to be J/K. An "A" entry will leave the M fuses intact, which allow the flip-flop to be D or J/K as controlled by the output of F_C (see Figure 2, "OR" ARRAY - (MODE)). The inputs to the flip-flops are represented by the programming table as the next state, $Q(N)_{0 \text{ to } 7}$ since their inputs are from the OR array. The outputs of these registers are connected to their respective tri-state inverting output buffers, four of which are controlled by EA and the other four by EB. A "." in EA will enable outputs F_0 to F_3, whereas a "-" will disable them. An "A" will allow the output buffers to be controlled by /OE, pin 11. Table 4, terms 0, 1 and 3 represent the following equations

Q_0: J = A * C + /B * /E eq. 1

Q_0: K = A * /C eq. 2

Notice that the J input in equation 1 is represented by the "H" entry in terms-0 and 1, column $Q(N)_0$ while the K input in equation 2 is represented by the "L" entry in term-3, column $Q(N)_0$. An undefined input, J or K, is considered "Low".

Table 3. FPLS Program Table

CODE NO.	FF MODE	EB	EA	POLARITY
				L H H L

TERM	AND																	REMARKS	(OR)												REMARKS
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	–	–	H	H	–	–	–	–	–	–	–	–	–	–	–	–	A*B	–	–	–	–	–	–	–	–	•	•	•	A	Z=/(A*B)
1																															
2	–	–	–	H	H	–	–	–	–	–	–	–	–	–	–	–	–	A*B	–	–	–	–	–	–	–	–	•	•	A	•	Y= A*B
3																															
4	–	–	–	H	H	–	–	–	–	–	–	–	–	–	–	–	–	A*B	–	–	–	–	–	–	–	–	•	•	A	A	Z = /(A*B)
5																															Y = A*B
6	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	A	–	–	–	–	–	–	–	–	•	A	•	•	
7	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	–	B	–	–	–	–	–	–	–	–	•	A	•	•	
8	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	C	–	–	–	–	–	–	–	–	•	A	•	•	X=A+B+C+D
9	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	D	–	–	–	–	–	–	–	–	•	A	•	•	
10																															
11	–	L	L	L	L	–	–	–	–	–	–	–	–	–	–	–	–	/A*/B*/C*/D	–	–	–	–	–	–	–	–	A	•	•	•	W=/(/A*/B*/C
12																															*/D)
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1																															
D0																															
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS			B	A																							W	X	Y	Z	

PLS159

TB00401S

Table 4. FPLS Program Table

CODE NO.										FF MODE									E_B				E_A				POLARITY				
										•	•	•				A	•		•				•								
	AND																		(OR)												
TERM	C	I				B(I)				Q(P)								REMARKS	Q(N)								B(O)				REMARKS
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	H	–	H	–	–	–	–	–	–	–	–	–	–	–	–	–	A*C	–	–	–	–	–	–	–	H					J= A*C
1	–	–	L	–	L	–	–	–	–	–	–	–	–	–	–	–	–	/B*/E	–	–	–	–	–	–	–	H					+/B*/E
2																															
3	–	H	–	L	–	–	–	–	–	–	–	–	–	–	–	–	–	A*/C	–	–	–	–	–	–	–	L					K= A*/C
4																															
5	–	L	L	L	–	–	–	–	–	–	–	–	–	–	–	–	–	/A*/B*/C	•	•	•	•	•	•	A	•					D=/A*/B*/C
6	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	E	•	•	•	•	•	•	A	•					+E
7																															
8	–	L	L	L	–	–	–	–	–	–	–	–	–	–	–	–	–	/A*/B*/C	–	–	–	–	–	–	H	–					D=/A*/B*/C
9	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–	–	–	E	–	–	–	–	–	–	H	–					+E
10																															
11	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	O	–	–	–	–	–					
12	–	–	–	–	–	–	–	–	–	–	–	H	–	–	–	–	–		–	O	–	–	–	–	–	–					T=1
13	–	–	–	–	–	–	–	–	–	–	H	H	–	–	–	–	–		O	–	–	–	–	–	–	–					$T=Q_5$
14																															$T=Q_5*Q_6$
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1																															
D0																															
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS		A	B	C	D																										PLS159

TB00411S

PLS159 Primer

AN15

A D flip-flop may be implemented by first entering an "A" in F/F MODE. Then enter "0" in the row F_C, which will unconditionally enable the tri-state inverter between the J and K inputs. The following logic equation may be implemented as shown in Table 4, term 5

Q_1: D = /A * /B * /C + E.

Notice that the entries in term 5, columns $Q(N)_{0 \text{ to } 7}$ are "A" and "." instead of "H" and "L" as in the case of J/K flip-flops. The entry "A" will cause the fuse connecting to the "K" input to be disconnected and the "J" fuse to be intact. Whereas the entry "." will cause both fuses to be disconnected. This feature enables the user to quickly recognize the mode in which the flip-flops are operating without having to go through the control terms. Some commercially available device programmers in the market may not have the software capability to implement this feature, in which case an "H" and a "-" may be used in place of "A" and "." respectively as shown in Table 4, terms 8 and 9.

Of course, the term F_C may have inputs instead of zeros and dashes, in which case the flip-flop modes are controlled dynamically.

When both the J and K inputs are "1's", the flip-flop will toggle. A simple 3-bit counter may be implemented using only AND terms as shown in Table 4 terms 11, 12 and 13. The logic equations for the three flip-flops are as the following:

Q_5: T = 1; (Q_5 toggles unconditionally)
Q_6: T = Q_5; (Q_6 toggles when $Q_5 = 1$)
Q_7: T = $Q_5 * Q_6$; (Q_7 toggles when $Q_5 * Q_6 = 1$)

The above equations represent an octal up-counter. However, since the outputs of the flip-flops are inverted, the counting sequence of the outputs is that of a down-counter.

The flip-flops may be asynchronously set and reset by the Control AND terms PA/PB and RA/RB respectively. As shown in Figure 1, PA and RA controls flip-flops F_0 to F_3, while PB and RB control F_4 to F_7.



Figure 3

In order to save the number of input pins, the eight flip-flops may be synchronously loaded directly from their own output pins. To use this feature, EA and/or EB must be programmed "A" or "-" so that the output buffers may be disabled before loading. As shown in Figure 1, every flip-flop has an OR/NOR gate the input of which is directly connected to the output pin and the outputs of the OR/NOR are connected to the K and J inputs respectively. This OR/NOR gate inverts the input and feeds it to the flip-flop in a "wire-OR" fashion. Therefore, when loading data directly into the flip-flops from the output pins, caution must be exercised to insure that the inputs from the OR array does not interfere with the data being loaded. For example, if the data being loaded is a "1" on the output pin, the J input will be a "0" and the K input will be a "1". If, at the same time, a "1" is present at the J-input from the OR array, the flip-flop will see "1's" in both J and K inputs. It will toggle as a result. The OR/NOR gates are enabled by the Control AND terms LA and LB. LA controls flip-flops F_0 to F_3 and LB controls F_4 to F_7.

All Control AND terms function and are programmed in the same manner as the other AND terms. The only difference is that the Control AND terms are not connected to the OR array.

The outputs of the flip-flops may be fed back into the AND array as the present state, Q(P). The output of the AND array into the OR array and the inputs to the flip-flops is the next state, Q(N). As an example, Figure 3 is a state machine implemented in a PLS159 as shown in Table 5, terms 0 to 6.

Table 5. FPLS Program Table

CODE NO.	FF MODE								E_B	E_A	POLARITY			
	•	•	•	•	•	•	•	•	•	•	H	H	H	H

TERM	AND																	REMARKS	(OR)												REMARKS
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	H	H	–	–	–	–	–	–	L	L	L	L	L	L	L	L		L	L	L	L	L	L	L	H	•	•	•	A	
1	–	–	–	H	L	–	–	–	–	L	L	L	L	L	L	L	H		L	L	L	H	L	L	L	H	•	A	•	•	
2	–	–	–	–	–	–	–	–	–	L	L	L	H	L	L	L	H		L	L	H	L	H	L	H	L	A	•	•	•	
3																															
4	–	H	L	–	–	–	–	–	–	L	L	L	L	L	L	L	L		L	L	L	L	L	L	H	L	•	•	A	•	
5	–	–	–	H	–	–	–	–	–	L	L	L	L	L	L	H	L		L	L	L	L	L	L	L	H	•	A	•	•	
6	–	–	–	H	L	–	–	–	–	L	L	L	L	L	L	H	L		L	L	L	L	L	L	L	H	•	A	A	•	
7																															
8																															
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
D2	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
D1	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
D0	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS		A	B	C	D																						W	X	Y	Z	PLS159

TB00091S

Signetics

AN16

PLS159 As Modulo Counters

Application Note

Application Specific Products

DESCRIPTION

The field-programmable logic sequencer (FPLS) PLS159 has eight edge-triggered flip-flops which may be individually programmed to be J/K, D, or toggle flip-flops. The detail logic diagram of the device is shown in Figure 2.

A counter may be constructed by having individual flip-flops toggle when they are at certain states. Implementing such counters requires one toggle flip-flop per bit and an associating AND gate as a decoder for each flip-flop. Such a method allows the PLS159 to be a counter from modulo 2 to 256 or from one bit to 8 bits.

MODULO-8 UP/DOWN COUNTER

The Up-Counter

The PLS159 has an inverting output buffer for each flip-flop. Therefore the counting sequence of the flip-flops is from 7 to 0 so that the outputs will count from 0 to 7. Table 1 is the truth table of the internal counting sequence.

Table 1

COUNT	Q_2	Q_1	Q_0
0	1	1	1
1	1	1	0
2	1	0	1
3	1	0	0
4	0	1	1
5	0	1	0
6	0	0	1
7	0	0	0

From Table 1, logic equations for the flip-flops may be generated as the following:

Q_0: T = 1; (Q_0 unconditionally toggles)

Q_1: T = $/Q_0$; (Q_1 toggles if $Q_0 = 0$)

Q_2: T = $/Q_0 * /Q_1$; (Q_2 toggles if both Q_0 and $Q_1 = 0$)

The equations are implemented as shown in Table 2, terms 0, 1, and 2. E_A is enabled, and the mode for the three flip-flops is set to J/K. All unused flip-flops and outputs (the B(0)'s) associating to AND-terms are "dashed" or "dotted" out. The event to be counted is connected to the clock input, pin 1 of the device.

The Down-Counter

The down-counter is constructed in the same manner as the up-counter except that the counting sequence is reversed. The down-counter is implemented in Table 2, terms 4 to 6 with the corresponding flip-flop mode set to J/K and E_B enabled.

Modulo-16 Counter

Expanding the modulo-8 counter to 4-bit, the counter becomes modulo-16, Table 3, terms 0 to 3 and the associating F/F MODE and E_A implement a modulo-16 up-counter, while terms 5 to 8 and the associating F/F MODE and E_B implement the modulo-16 down-counter.

PLS159 As Modulo Counters

Table 2

CODE NO.										FF MODE								REMARKS	E_B				E_A				POLARITY				REMARKS
										•	•	•	•	•	•	•	•		•				•								
TERM	AND																		(OR)												
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0		–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	–	–	–	–	–	O	•	•	•	•	
1		–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	L		–	–	–	–	–	–	O	–	•	•	•	•	
2		–	–	–	–	–	–	–	–	–	–	–	–	–	–	L	L		–	–	–	–	–	O	–	–	•	•	•	•	
3																															
4		–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	–	O	–	–	–	–	•	•	•	•	
5		–	–	–	–	–	–	–	–	–	–	–	H	–	–	–	–		–	–	O	–	–	–	–	–	•	•	•	•	
6		–	–	–	–	–	–	–	–	–	–	H	H	–	–	–	–		–	O	–	–	–	–	–	–	•	•	•	•	
7																															
8																															
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1																															
D0																															
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS																															



PLS159

TB00021S

PLS159 As Modulo Counters

Table 3

CODE NO.	FF MODE								E_B	E_A	POLARITY			
	•	•	•	•	•	•	•	•	•	•				

TERM	C	AND																REMARKS	(OR)												REMARKS
		I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	O	•	•	•	•	
1		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	L		-	-	-	-	-	-	O	-	•	•	•	•	
2		-	-	-	-	-	-	-	-	-	-	-	-	-	-	L	L		-	-	-	-	-	O	-	-	•	•	•	•	
3		-	-	-	-	-	-	-	-	-	-	-	-	-	L	L	L		-	-	-	-	O	-	-	-	•	•	•	•	
4																															
5		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	O	-	-	-	-	•	•	•	•	
6		-	-	-	-	-	-	-	-	-	-	-	H	-	-	-	-		-	-	O	-	-	-	-	-	•	•	•	•	
7		-	-	-	-	-	-	-	-	-	-	H	H	-	-	-	-		-	O	-	-	-	-	-	-	•	•	•	•	
8		-	-	-	-	-	-	-	-	-	H	H	H	-	-	-	-		O	-	-	-	-	-	-	-	•	•	•	•	
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1																															
D0																															
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS																															

PLS159

TB00011S

PLS159 As Modulo Counters AN16

DECADE COUNTER

The Decade Up-Counter

The truth table of a decade counter is as shown in Table 4.

Table 4

COUNT	Q_3	Q_2	Q_1	Q_0
0	1	1	1	1
1	1	1	1	0
2	1	1	0	1
3	1	1	0	0
4	1	0	1	1
5	1	0	1	0
6	1	0	0	1
7	1	0	0	0
8	0	1	1	1
9	0	1	1	0
0	1	1	1	1

Logic equations may be generated from Table 4 as the following:

Q_0: T = 1;
Q_1: T = $/Q_0$ * Q_3;
Q_2: T = $/Q_0$ * $/Q_1$ * Q_3;
Q_3: T = $/Q_0$ * $/Q_1$ * $/Q_2$ * Q_3 +
$/Q_0$ * Q_1 * Q_2 * $/Q_3$;



Figure 1

The equations are implemented as shown in Table 5, terms 0 to 4 and the associating flip-flop mode and E_A settings.

Decade Down-Counter

The decade down-counter is similar to the decade up-counter except that the counting sequence is reversed from 0 to 9 as shown in Table 5, terms 6 to 11 with the associating F/F MODE set to J/K and E_B to ENABLE.

Decade Down Counter

COUNT	Q_7	Q_6	Q_5	Q_4
9	0	1	1	0
8	0	1	1	1
7	1	0	0	0
6	1	0	0	1
5	1	0	1	0
4	1	0	1	1
3	1	1	0	0
2	1	1	0	1
1	1	1	1	0
0	1	1	1	1
9	0	1	1	0

Q_4: T = 1;
Q_5: T = Q_4 * Q_5 * Q_6 * $/Q_7$ +
Q_4 * $/Q_5$ * $/Q_6$ * Q_7 +
Q_4 * Q_5 * $/Q_6$ * Q_7 +
Q_4 * $/Q_5$ * Q_6 * Q_7 ;
Q_6: T = Q_4 * Q_5 * Q_6 * $/Q_7$ +
Q_4 * Q_5 * $/Q_6$ * Q_7 ;
Q_7: T = Q_4 * Q_5 * Q_6 * $/Q_7$ +
Q_4 * Q_5 * Q_6 * Q_7 ;

DIVIDE-BY-N COUNTER

This counter, shown in Figure 1 and Table 6, takes an input (maximum = 8 bits for each device), complements it, and counts until all flip-flops become 1, then a terminal count is sent out at $B(O)_0$ (divide-by-N). At the end of the count, where all flip-flops are 1's, terms LA and LB are activated which causes the flip-flops to load data from F_0 to F_7, and the cycle starts again. Since there are 8 flip-flops, the maximum count is 256.

Table 5

CODE NO.	FF MODE	E_B	E_A	POLARITY
	• • • • • • • •	•	•	☐ ☐ ☐ ☐

TERM	AND																	REMARKS	(OR)												REMARKS
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	–	–	–	–	–	O	•	•	•	•	
1	–	–	–	–	–	–	–	–	–	–	–	–	–	H	–	–	L		–	–	–	–	–	–	O	–	•	•	•	•	
2	–	–	–	–	–	–	–	–	–	–	–	–	–	H	–	L	L		–	–	–	–	–	O	–	–	•	•	•	•	
3	–	–	–	–	–	–	–	–	–	–	–	–	–	H	L	L	L		–	–	–	–	O	–	–	–	•	•	•	•	
4	–	–	–	–	–	–	–	–	–	–	–	–	–	L	H	H	L		–	–	–	–	O	–	–	–	•	•	•	•	
5																															
6	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–		–	–	–	O	–	–	–	–	•	•	•	•	
7	–	–	–	–	–	–	–	–	–	L	H	H	H	–	–	–	–		O	O	O	–	–	–	–	–	•	•	•	•	
8	–	–	–	–	–	–	–	–	–	H	L	L	H	–	–	–	–		–	–	O	–	–	–	–	–	•	•	•	•	
9	–	–	–	–	–	–	–	–	–	H	L	H	H	–	–	–	–		–	O	O	–	–	–	–	–	•	•	•	•	
10	–	–	–	–	–	–	–	–	–	H	H	L	H	–	–	–	–		–	–	O	–	–	–	–	–	•	•	•	•	
11	–	–	–	–	–	–	–	–	–	H	H	H	H	–	–	–	–		O	–	–	–	–	–	–	–	•	•	•	•	
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1																															
D0																															
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS																															

PLS159

TB00032S

Table 6

CODE NO.	FF MODE								EB	EA	POLARITY			
	•	•	•	•	•	•	•	•	—	—				H

TERM	C	AND																REMARKS	(OR)												REMARKS
		I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0		-	-	-	L	-	-	-	L	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	O	•	•	•	•	
1		-	-	-	L	-	-	-	L	-	-	-	-	-	-	-	H		-	-	-	-	-	-	O	-	•	•	•	•	
2		-	-	-	L	-	-	-	L	-	-	-	-	-	-	H	H		-	-	-	-	-	O	-	-	•	•	•	•	
3		-	-	-	L	-	-	-	L	-	-	-	-	-	H	H	H		-	-	-	-	O	-	-	-	•	•	•	•	
4		-	-	-	L	-	-	-	L	-	-	-	-	H	H	H	H		-	-	-	O	-	-	-	-	•	•	•	•	
5		-	-	-	L	-	-	-	L	-	-	-	H	H	H	H	H		-	-	O	-	-	-	-	-	•	•	•	•	
6		-	-	-	L	-	-	-	L	-	-	H	H	H	H	H	H		-	O	-	-	-	-	-	-	•	•	•	•	
7		-	-	-	L	-	-	-	L	-	H	H	H	H	H	H	H		O	-	-	-	-	-	-	-	•	•	•	•	
8		-	-	-	L	-	-	-	-	H	H	H	H	H	H	H	H		-	-	-	-	-	-	-	-	•	•	•	A	
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB	-	-	-	-	-	-	-	-	-	H	H	H	H	H	H	H	H														
PA																															
RA																															
LA	-	-	-	-	-	-	-	-	-	H	H	H	H	H	H	H	H														
D3																															
D2																															
D1																															
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS					/ENABLE																										PLS159

TB00043S

PLS159 As Modulo Counters


(LOGIC TERMS — T)
(CONTROL TERMS)
OE
11
I_0 2
I_1 3
I_2 4
I_3 5
F_0
F_1
F_2
F_3
F_4
F_5
F_6
F_7
B_0
B_1
B_2
B_3
$\overline{C}$
C
P_B R_B P_A R_A L_B L_A D_3 D_2 D_1 D_0
E_A E_B
S_3
S_2
S_1
S_0
X_3
X_2
X_1
X_0
9 B_3
8 B_2
7 B_1
6 B_0
P R
M_7
M_6
M_5
M_4
M_3
M_2
M_1
M_0
J Q
K
CK'
19 F_7
18 F_6
17 F_5
16 F_4
15 F_3
14 F_2
13 F_1
12 F_0
31 • • • • • • • 24 23 • • • • • • • 16 15 • • • • • • • 8 7 • • • • • • • 0 F_C
CK
1 CK
LD01681S

NOTES:

1. All OR gate inputs with a blown link float to logic "0".
2. All other gates and control inputs with a blown link float to logic "1".
3. ⊕ denotes WIRE-OR.

Figure 2

Signetics

AN17
Electronic Combination Lock

Application Note

Application Specific Products

INTRODUCTION

A combination lock may be opened by entering the correct numbers which match the preset security code that may be of any number of digits. Using a PLS157, an electronic combination lock with user settable security code may be constructed. The security code may be one to five hexadecimal digits that can be preset by the user. The lock takes a 4-bit binary input as the "combination" and a "Data Valid" input, which means that the combination may be five digits long and each digit may be from 0 to F. If the input matches the preset digit of the security code, the lock will wait for the next digit. If the input does not match the corresponding digit of the security code, the lock will reset itself to the first digit position again. The user may use as many as five digits for the combination which may be set by using five DIP switches or other means. The lock may be used in conjunction with a 4-bit binary encoded rotary switch, or an encoded push button key pad, or an optical card reader, or a magnetic strip reader. The design takes advantage of the six JK flip-flops of the PLS157, the bidirectional I/O's, the complement array, and the general architecture of common product terms.

DESCRIPTION

Figure 1 shows an example of an electronic lock which uses five DIP switches to set the security code (hexadecimal 0 to E, F is reserved for reset), a 4-bit binary encoded rotary switch to enter the combination at I_0 to I_3, and a single pole double throw push button switch, "Data Valid", as the clock which is debounced by the associated circuitry of pin B_5. The security code is set with five DIP switches which are connected to a four line input ($B(I)_0$ to $B(I)_3$). The five DIP switches are multiplexed by the outputs of the flip-flops, F_0 to F_4. In normal operation, one of the F/F outputs is Low (the content of the register being a "1") while the other five are High. The operation is actually a shift register with a zero bit shifting through five one's. Therefore only one DIP switch is pulled Low (selected) at any one time while the rest is deselected. The pin named "MATCH", $B(O)_4$, is an I/O which outputs a High if the input matches the corresponding digit of the security code, otherwise it outputs a Low. A High output of $B(O)_4$ enables the shift register to shift one position while a Low causes the shift register to reset to the starting position which is a "1" in F/F_0 (flip-flop 0) (F_0 is Low due the output inverter) and "0's" in the other five (F_1 to F_5 = High). The state diagram of the design is as shown in Figure 2 where the state numbers are expressed in two hexadecimal digits. The least significant digit consists of F_3, F_2, F_1, and F_0; whereas the most significant digit consists of F_5, and F_4. At the top of the state diagram, the power-up and reset state is 00 hex. When the outputs have more than one Low, as sometimes happens during power-up, the circuit automatically resets the registers to 00 hex which causes all outputs to be High in order to prevent more than one DIP switch being enabled. After power-up or reset, pushing the "Data Valid" button will initialize the circuit to have the first digit of the security code enabled. Subsequently, any false entry will cause the circuit to go back to the initialized state of 01 hex. When the first digit is correctly set and the "Data Valid" button pressed, the circuit goes to 02 hex and the second DIP switch is enabled while the first DIP switch is disabled. The circuit is now ready for the second digit. By repeating the process, the circuit keeps shifting the "1" in the shift register until it reaches F/F_5 at which time the Low output may be used to trigger a solenoid. If at any time of the sequence, an incorrect digit is entered, the circuit reverts back to the initialized state of 01 hex.

Notice that any of the five outputs from F_1 to F_5 may be used as an output. Therefore, if, for example, a two digit security code is used, only two DIP switches are needed and the output is taken from F_2 to trigger a solenoid. After the last digit has been entered, all DIP switches are deselected and the inputs $B(I)_0$ to $B(I)_3$ become 1111 binary, or F hex. Therefore, the hex number F is not used as a valid code but as an initialization input entered at I_0 to I_3. When the hex number F is entered, the circuit initializes itself to the 01 hex state. After the last digit of the security code has been entered, if the "Data Valid" button is pressed again, the circuit sees a false entry and reinitializes itself.

The design is implemented using a PLS157 as shown in Table 1, H/L Programming Table of Electronic Lock. P-terms 0 to 14 are programmed as decoders. If an input matches the corresponding digit of the security code, one of the p-terms will be active which causes $B(O)_4$ to output a High which, in turn, enables the registers to shift to the next digit by terms 16 to 20. In the event that an incorrect input is entered, $B(O)_4$ outputs a Low which, in turn, causes the registers to be set 000001 binary by term 21. If an input of F is entered, term 15 causes the registers to be 000001. Terms 22 to 29 and RB ensure that no more than one register is "1" at a time. Terms 22 to 28 are connected to the complement array, which in turn, drives terms 29 and RB to set the registers to 000000 when terms 22 to 28 are inactive.


BINARY
ENCODED
ROTARY
SWITCH
IN0
IN1
IN2
IN3
I0
I1
I2
I3
B0
B1
B2
B3
SC0
SC1
SC2
SC3
PLS157
+5V
DATA
VALID
NO
NC
DV
B5
F0
F1
F2
F3
F4
F5
OUTPUT
AF01381S

NOTES:
1. All diodes are Philips BAT81 Schottky diodes or equivalent.
2. Single pole double throw momentary switch.

Figure 1. Simple Block Diagram of Electronic Lock


POWER UP/RESET
00
INITIALIZATION
01
FALSE
ENTRY
1st DIGIT
02
F OR
FALSE ENTRY
2nd DIGIT
04
F OR
FALSE ENTRY
3rd DIGIT
08
F OR
FALSE ENTRY
4th DIGIT
10
F OR
FALSE ENTRY
5th DIGIT
20
PF00500S

Figure 2. State Diagram of Electronic Lock

Table 1. PLS157 H/L Programming Table

												F/F MODE						REMARKS	EA : EB								POLARITY						REMARKS
												•	•	•	•	•	•										H	H	H	H	H	H	
	AND																		OR														
		I				B(I)						Q(P)							Q(N)						P	R	B(O)						
T#	C	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0		5	4	3	2	1	0	A	A	5	4	3	2	1	0	
00	-	L	L	L	L	-	-	L	L	L	L	-	-	-	-	-	-	0	-	-	-	-	-	-	•	•	•	A	•	•	•	•	B4 = 1 IF
01	-	L	L	L	H	-	-	L	L	L	H	-	-	-	-	-	-	1	-	-	-	-	-	-	•	•	•	A					INPUT MATCHES
02	-	L	L	H	L	-	-	L	L	H	L	-	-	-	-	-	-	2	-	-	-	-	-	-	•	•	•	A					SECURITY CODE:
03	-	L	L	H	H	-	-	L	L	H	H	-	-	-	-	-	-	3	-	-	-	-	-	-	•	•	•	A					
04	-	L	H	L	L	-	-	L	H	L	L	-	-	-	-	-	-	4	-	-	-	-	-	-	•	•	•	A					
05	-	L	H	L	H	-	-	L	H	L	H	-	-	-	-	-	-	5	-	-	-	-	-	-	•	•	•	A					
06	-	L	H	H	L	-	-	L	H	H	L	-	-	-	-	-	-	6	-	-	-	-	-	-	•	•	•	A					
07	-	L	H	H	H	-	-	L	H	H	H	-	-	-	-	-	-	7	-	-	-	-	-	-	•	•	•	A					
08	-	H	L	L	L	-	-	H	L	L	L	-	-	-	-	-	-	8	-	-	-	-	-	-	•	•	•	A					
09	-	H	L	L	H	-	-	H	L	L	H	-	-	-	-	-	-	9	-	-	-	-	-	-	•	•	•	A					
10	-	H	L	H	L	-	-	H	L	H	L	-	-	-	-	-	-	A	-	-	-	-	-	-	•	•	•	A					
11	-	H	L	H	H	-	-	H	L	H	H	-	-	-	-	-	-	B	-	-	-	-	-	-	•	•	•	A					
12	-	H	H	L	L	-	-	H	H	L	L	-	-	-	-	-	-	C	-	-	-	-	-	-	•	•	•	A					
13	-	H	H	L	H	-	-	H	H	L	H	-	-	-	-	-	-	D	-	-	-	-	-	-	•	•	•	A					
14	-	H	H	H	L	-	-	H	H	H	L	-	-	-	-	-	-	E	-	-	-	-	-	-	•	•	•	A					
15	-	H	H	H	H	-	-	-	-	-	-	-	-	-	-	-	-	F	L	L	L	L	L	H	•	•	•	•					INITIALIZE TO 000001
16	-	-	-	-	-	-	H	-	-	-	-	L	L	L	L	L	H		L	L	L	L	H	L	•	•	•	•					SHIFT RIGHT
17	-	-	-	-	-	-	H	-	-	-	-	L	L	L	L	H	L		L	L	L	H	L	L	•	•	•	•					
18	-	-	-	-	-	-	H	-	-	-	-	L	L	L	H	L	L		L	L	H	L	L	L	•	•	•	•					
19	-	-	-	-	-	-	H	-	-	-	-	L	L	H	L	L	L		L	H	L	L	L	L	•	•	•	•					
20	-	-	-	-	-	-	H	-	-	-	-	L	H	L	L	L	L		H	L	L	L	L	L	•	•	•	•					
21	-	-	-	-	-	-	L	-	-	-	-	-	-	-	-	-	-	B4=0, FALSE ENTRY	L	L	L	L	L	H	•	•	•	•					INITIALIZE
22	A	-	-	-	-	-	-	-	-	-	-	L	L	L	L	L	L	IF ALL F/F = 0	-	-	-	-	-	-	•	•	•	•					
23	A	-	-	-	-	-	-	-	-	-	-	L	L	L	L	L	H	or more than 1	-	-	-	-	-	-	•	•	•	•					
24	A	-	-	-	-	-	-	-	-	-	-	L	L	L	L	H	L	F/F = 1	-	-	-	-	-	-	•	•	•	•					
25	A	-	-	-	-	-	-	-	-	-	-	L	L	L	H	L	L		-	-	-	-	-	-	•	•	•	•					
26	A	-	-	-	-	-	-	-	-	-	-	L	L	H	L	L	L		-	-	-	-	-	-	•	•	•	•					
27	A	-	-	-	-	-	-	-	-	-	-	L	H	L	L	L	L		-	-	-	-	-	-	•	•	•	•					
28	A	-	-	-	-	-	-	-	-	-	-	H	L	L	L	L	L		-	-	-	-	-	-	•	•	•	•					
29	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	/C = 1	-	-	-	-	-	-	•	A	•	•					RESET F0-F5
30																																	
31	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-	-	•	•	A	•					"DV" DEBOUNCE
FC																																	ALL F/F = JK
PB																																	
RB	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	/C = 1	RESET F0-F5														
LB																																	
LA																																	
D5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	ENABLE B(O)5															
D4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	ENABLE B(O)4															
D3																																	
D2																																	
D1																																	
D0																																	
PIN	#	5	4	3	2	19	12	9	8	7	6	18	17	16	15	14	13		18	17	16	15	14	13			19	12	9	8	7	6	
NAME		IN3	IN2	IN1	IN0	DV		SC3	SC2	SC1	SC0								SW5	SW4	SW3	SW2	SW1	SW0				MATCH					

TB00430S

Signetics

Application Specific Products

AN18

Schmitt Trigger Using PLS153 and PLS159

Application Note

INTRODUCTION

One of the many features of the PLS153 to 159 series is the availability of individually controlled Tri-state I/O pins. Taking advantage of this feature, a Schmitt trigger may be constructed using one input pin, two bidirectional I/O pins and additional components of three resistors. The two threshold voltages, as well as the hysterisis, are determined by the values of the three resistors and the parameters of the PLS153/159 device, which are 1) input threshold voltage, V_{TH}, 2) High output voltage, V_{OH}, and 3) Low output voltage, V_{OL}. The circuit may be simplified if Schmitt function is needed only on Low going High or High going Low, and if the hysterisis and threshold voltages are not important.

DESCRIPTION

A simplified block diagram of a non-inverting Schmitt trigger is shown in Figure 1 where R_1, R_2, and R_1, R_3, form two pairs of voltage dividers one of which get into action at input voltage direction of High going Low and the other Low going High. Assuming that input voltage starts at zero volt, the output voltage is therefore at V_{OL} which causes Q_2 to pull R_3 towards ground. As the input voltage increases, only a fraction of the voltage is impressed upon the input buffer due to the dividing network R_1 and R_3. As soon as the input voltage reaches a point where $V_1 = V_{TH}$ (V_{TH} = 1.38V typical), the output switches to V_{OH} which, in turn, turns off Q_2 and turns on Q_1. V_1 will jump to a value greater than V_{TH} and Q_1 then pulls the input pin, through R_2, towards V_{OH}, which in turn locks the output to a High state even if the input voltage fluctuates, as long as it does not fluctuate outside of the designed hysterisis. When the input voltage goes from a High to a Low, the Schmitt function repeats itself except that Q_1 and Q_2 reverse their roles.

The triggering voltages, V_H (Low going High) and V_L (High going Low) are:

$V_H = V_{TH}\ [(R_1 + R_3)/R_3] - V_{OL}\ (R_1/R_3)$;

$V_L = V_{TH}\ [(R_1 + R_2)/R_2] - V_{OH}\ (R_1/R_2)$;

where, at room temperature, V_{CC} = 5.0V, $I_{OH}/I_{OL} < 1mA$. V_{TH} is the threshold voltage of the device, typically 1.38V; V_{OL} is the output Low voltage of the device, typically 0.36V at $|I_{OL}| < 1mA$; V_{OH} is the output High voltage of the device, typically 3.8V at $|I_{OH}| < 1mA$.

The implementation of Figure 1 using PLS153/153A is as shown in Table 1, and Figure 2a. A scope photo of the operation of the circuit is shown in the Appendix. The implementation using PLS159 is shown in Table 2 and Figure 2b. In Tables 1 & 2, V_1 is the input pin, V_0 is the output pin, V_2 is the output which pulls down V_1 and V_3 is the output pin that pulls up V_1. The Schmitt output is available at pin B_0 for external use, and is available internally at the input buffers of I_0 and $B(I)_0$. However, there is a propagation delay between the two signals from the I_0 buffer and the $B(I)_0$ buffer.

An inverting Schmitt triggered buffer may be constructed using the same principle. A simple block diagram of such inverter is shown in Figure 3a. The circuit is implemented using H/L programming table as shown in Table 3 for PLS153 and Table 4 for PLS159. Table 3 is also represented in logic symbols in Figure 3b. If the voltage levels (V_L and V_H) and the hysterisis are not critical, one I/O pin may be used to pull the input pin High and Low. Therefore one I/O pin and a resistor may be saved. The drawback is that the range of V_H and V_L is quite limited. The circuit is as shown in Figure 4.

If Schmitt function is needed only in one direction, one of the resistor/output circuit may be eliminated. The circuit is as shown in Figure 5.



Figure 1. Simplified Block Diagram of a Schmitt Trigger

Table 1. PLS153/153A Programming Table

CODE NO.																				POLARITY										
																								L	H		H	H	H	
TERM	AND																			OR										
	I								B(I)											B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	REMARKS	9	8	7	6	5	4	3	2	1	0	REMARKS
0	-	-	-	-	-	-	-	H	-	-	-	-	-	-	-	-	-	-									●	●	A	NON-INV. BUFFER
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0									●	A	●	OUTPUT V_{OL}
2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-									A	●	●	OUTPUT V_{OH}
3																														
4																														
5																														
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0						A	A					SAME AS
7																														TERMS 1 & 2
8																														WITH
9																														$B(0)4 = V_2$
10																														$B(0)5 = V_3$
11																														
12																														
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5																														
D4																														
D3																														
D2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	H												
D1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	L												
D0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-												
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS								V_1																			V_3	V_2	V_0	PLS153

TB01730S

NOTE:
Schmitt trigger output may be obtained from both 1_0 and $B(1)_0$ to drive the AND-ARRAY.

Schmitt Trigger Using PLS153 and PLS159

AN18


PLS153/153A
INPUT
R1
TO OTHER AND TERMS
I0
B0
R2
B2
R3
B1
LD01530S

a. Using PLS153/153A


PLS159
INPUT
R1
TO OTHER AND TERMS
I0
B0
R2
B2
R3
B1
LD01540S

b. Using PLS159

Figure 2. Schmitt Trigger

Table 2. PLS159 FPLS Programming Table

CODE NO.										FF MODE									E												
																			E_B				E_A				POLARITY	H	H	H	
TERM		AND																	(OR)												
	C	I				B(I)				Q(P)								REMARKS	Q(N)								B(O)				REMARKS
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	—	—	—	—	H	—	—	—	—	—	—	—	—	—	—	—	—		—	—	—	—	—	—	—	—	•	•	•	A	NON-INV. BUFR
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		—	—	—	—	—	—	—	—	•	•	A	•	OUTPUT V_{OL}
2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		—	—	—	—	—	—	—	—	•	A	•	•	OUTPUT V_{OH}
3																															
4																															
5																															
6																															
7																															
8																															
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2	—	—	—	—	—	—	—	—	H	—	—	—	—	—	—	—	—														
D1	—	—	—	—	—	—	—	—	L	—	—	—	—	—	—	—	—														
D0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS					V_1	V_3		V_2	V_0																						PLS159

TB01740S

Schmitt Trigger Using PLS153 and PLS159 AN18


+V_{CC}
Q_1
R_2
R_1
INPUT
OUTPUT
R_3
Q_2
V_{OUT}
V_{IN}
BD01710S

a. Simplified Block Diagram


PLS159
INPUT
R_1
TO OTHER AND TERMS
I_0
B_0
R_2
B_2
R_3
B_1
LD01550S

b. Using PLS159

Figure 3. Inverting Schmitt Trigger

Schmitt Trigger Using PLS153 and PLS159

Table 3. PLS153/153A Programming Table

CODE NO.

TERM	AND																			POLARITY										
																											L	L	L	
																				OR										
	I								B(I)											B(O)										
	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	REMARKS	9	8	7	6	5	4	3	2	1	0	REMARKS
0	–	–	–	–	–	–	–	H	–	–	–	–	–	–	–	–	–	–									•	•	A	INV. BUFFER
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0									•	A	•	OUTPUT V_{OH}
2	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–									A	•	•	OUTPUT V_{OL}
3																														
4																														
5																														
6																														
7																														
8																														
9																														
10																														
11																														
12																														
13																														
14																														
15																														
16																														
17																														
18																														
19																														
20																														
21																														
22																														
23																														
24																														
25																														
26																														
27																														
28																														
29																														
30																														
31																														
D9																														
D8																														
D7																														
D6																														
D5																														
D4																														
D3																														
D2	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	H												
D1	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	L												
D0	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–												
PN	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	11	9		19	18	17	16	15	14	13	12	11	9	
REMARKS								V_1																			V_3	V_2	V_0	

PLS153

TB01580S

Table 4. PLS159 FPLS Program Table

CODE NO.	FF MODE	E_B	E_A	POLARITY
				H H L

TERM	AND																	REMARKS	(OR)												REMARKS
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	—	—	—	—	H	—	—	—	—	—	—	—	—	—	—	—	—		—	—	—	—	—	—	—	—	•	•	•	A	INV. BUFFER
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		—	—	—	—	—	—	—	—	•	•	A	•	OUTPUT V_{OL}
2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		—	—	—	—	—	—	—	—	•	A		•	OUTPUT V_{OH}
3																															
4																															
5																															
6																															
7																															
8																															
9																															
10																															
11																															
12																															
13																															
14																															
15																															
16																															
17																															
18																															
19																															
20																															
21																															
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2	—	—	—	—	—	—	—	—	L	—	—	—	—	—	—	—	—														
D1	—	—	—	—	—	—	—	—	H	—	—	—	—	—	—	—	—														
D0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—														
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS					V_1		V_3	V_2	V_0																						

PLS159

TB01590S


INPUT
4K
OUTPUT
16K
$V_L = 0.78V, V_H = 1.6V$
TC01890S

Figure 4. Schmitt Trigger Using One I/O Pin


INPUT
R_1
OUTPUT
R_2
TC01900S

a. High Going Low Direction


INPUT
R_1
OUTPUT
R_3
TC01910S

b. Low Going High Direction

Figure 5. Schmitt Trigger

APPENDIX A



NOTE:
$R_1 = 3.9k\Omega$, $R_2 = 10.8k\Omega$, $R_3 = 2.0k\Omega$, $V_{CC} = 5.0V$, Ambient temperature ≈ 25°C

Figure A-1. A Non-Inverting Schmitt Triggered Buffer

AN19
Electronic Dice

Application Note

Application Specific Products

DESCRIPTION

A PLS159 is used to implement a pair of dice. Each die is represented by a series of six different state transitions. Two push button switches are used to "roll" the dice; in other words start/stop the state transitions. Each push button controls one die. When the switches are held low, the state transitions take place for each die and the result is displayed when a push button is released.

Each die is made up of seven LED's which are connected to the outputs of the PLS159. The system also contains its own oscillator which generates the clock cycle necessary for the state transitions.

The random release of the push button provides a random output. The high frequency of the internal oscillator and the fact that the switches are not debounced, add more "randomness" to each event.

The overall system configuration is shown in Figure 3.

LOGIC IMPLEMENTATION

The configuration of each die is shown in Figure 1, with each letter representing an LED.

To represent the numbers one through six the LED's are turned on as shown in Figure 2.

Table 1 is the truth table generated from Figure 2.



AF01710S

Figure 1. Dice Configuration



AF01720S

Figure 2. Number Representation

Table 1. Truth Table for Dice

	A	B	C	D	E	F	G
One	0	0	0	1	0	0	0
Two	0	0	1	0	1	0	0
Three	0	0	1	1	1	0	0
Four	1	1	0	0	0	1	1
Five	1	1	0	1	0	1	1
Six	1	1	1	0	1	1	1

The result of Table 1 is the following logic equations:

A = Four + Five + Six;
B = Four + Five + Six;
C = Two + Three + Six;
D = One + Three + Five;
E = Two + Three + Six;
F = Four + Five + Six;
G = Four + Five + Six;

As can be seen from the above logic equations:

$A \equiv B \equiv F \equiv G$;
$C \equiv E$;

Table 2 is the result of Table 1 and the above common terms.

Table 2. Truth Table for PLS159 Outputs

	A, B, F, G	C, E	D
One	0	0	1
Two	0	1	0
Three	0	1	1
Four	1	0	0
Five	1	0	1
Six	1	1	0

For each die, three outputs of the PLS159 are needed to implement the logic in Table 2. These outputs are connected to the LED's as follows:

F0: A, B, F, G;
F1: C, E;
F2: D;

Similarly for the second die:

F3: A', B', F', G';
F4: C', E';
F5: D';


VCC
R
A′
B′
C′
D′
E′
F′
G′
PB1
PB2
CK
I0
I1
I2
I3
B0
B1
B2
B3
GND
VCC
F7
F6
F5
F4
F3
F2
F1
F0
OE
PLS159
A
B
C
D
E
F
G
R = 270Ω
TC01560S

Figure 3. Dice Implementation Using the PLS159

Electronic Dice

STATE TRANSITIONS

Figure 4 shows two arbitrary state transition sequences which are used to implement each die.

These state transitions are implemented in the program table of the PLS159.

INTERNAL OSCILLATOR

An internal oscillator is also implemented for the system. The internal configuration of the oscillator is shown in Figure 5. For a detailed explanation of the implementation of this oscillator see AN13: Oscillator with the PLS159. B0 is connected externally to the clock input of the PLS159.

EXPLANATION OF PROGRAM TABLE

The program table for the two dice is shown in Table 3.

Terms 0 – 5 and 7 – 12 represent the state transitions for each die.

Terms 14 – 15 and 17 – 18 reset the flip-flops to HLL and HLH if undefined states occur, such as during power up.

Terms 20 and 21 and output controls terms D1 and D2 are used to implement the internal oscillator (see AN13).

Inputs I0 and I1 are connected to the two push button switches which roll the dice. These inputs are programmed to be Active-Low. When the push button is closed the state transitions take place, and upon release of the push button, the current states are displayed on the outputs.

The outputs of the PLS159 are inverted and this must be taken into consideration when assigning "H" and "L"s to the F0, F1, F2, F3, F4, and F5. These assignments are shown in Table 4. All the flip-flops are set to be of the J – K type.

Table 4. H And L Assignment

	F2, F5	F1, F4	F0, F3
One	H	L	L
Two	L	H	L
Three	H	H	L
Four	L	L	H
Five	H	L	H
Six	L	H	H



Figure 4. Arbitrary State Transitions



Figure 5. Oscillator Configuration

Table 3. Program Table for 2 Dice

CODE NO.										FF MODE									E_B				E_A				POLARITY				
										A	A	•	•	•	•	•	•		•				•				L	L	H	L	
TERM	AND																	REMARKS	(OR)												REMARKS
	C	I				B(I)				Q(P)									Q(N)								B(O)				
		3	2	1	0	3	2	1	0	7	6	5	4	3	2	1	0		7	6	5	4	3	2	1	0	3	2	1	0	
0	—	—	—	—	L	—	—	—	—	—	—	—	—		H	L	L	100 → 101	—	—	—	—	—	H	L	H	•	•	•	•	
1	—	—	—	—	L	—	—	—	—	—	—	—	—		H	L	H	101 → 110	—	—	—	—	—	H	H	L	•	•	•	•	
2	—	—	—	—	L	—	—	—	—	—	—	—	—		H	H	L	110 → 011	—	—	—	—	—	L	H	H	•	•	•	•	DIE 1
3	—	—	—	—	L	—	—	—	—	—	—	—	—		L	H	H	011 → 010	—	—	—	—	—	L	H	L	•	•	•	•	
4	—	—	—	—	L	—	—	—	—	—	—	—	—		L	H	L	010 → 001	—	—	—	—	—	L	L	H	•	•	•	•	
5	—	—	—	—	L	—	—	—	—	—	—	—	—		L	L	H	001 → 100	—	—	—	—	—	H	L	L	•	•	•	•	
6																															
7	—	—	—	L	—	—	—	—	—	—	—	H	L	H	—	—	—	101 → 100	—	—	H	L	L	—	—	—	•	•	•	•	
8	—	—	—	L	—	—	—	—	—	—	—	H	L	L	—	—	—	100 → 110	—	—	H	H	L	—	—	—	•	•	•	•	
9	—	—	—	L	—	—	—	—	—	—	—	H	H	L	—	—	—	110 → 011	—	—	L	H	H	—	—	—	•	•	•	•	DIE 2
10	—	—	—	L	—	—	—	—	—	—	—	L	H	H	—	—	—	011 → 001	—	—	L	L	H	—	—	—	•	•	•	•	
11	—	—	—	L	—	—	—	—	—	—	—	L	L	H	—	—	—	001 → 010	—	—	L	H	L	—	—	—	•	•	•	•	
12	—	—	—	L	—	—	—	—	—	—	—	L	H	L	—	—	—	010 → 101	—	—	H	L	H	—	—	—	•	•	•	•	
13																															
14	—	—	—	—	—	—	—	—	—	—	—	—	—	—	L	L	L	Undefined	—	—	—	—	—	H	L	L	•	•	•	•	Go to 100
15	—	—	—	—	—	—	—	—	—	—	—	—	—	—	H	H	H	states for DIE 1	—	—	—	—	—	H	L	L	•	•	•	•	
16																															
17	—	—	—	—	—	—	—	—	—	—	—	L	L	L	—	—	—	Undefined	—	—	—	H	L	H	—	—	•	•	•	•	Go to 101
18	—	—	—	—	—	—	—	—	—	—	—	H	H	H	—	—	—	states for DIE 2	—	—	—	H	L	H	—	—	•	•	•	•	
19																															
20	—	—	—	—	—	—	—	—	H	—	—	—	—	—	—	—	—	Oscillator	—	—	—	—	—	—	—	—	•	•	A	•	$B_0 = B_1$
21	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		—	—	—	—	—	—	—	—	•	•	•	A	$B(O)_1$ = Low
22																															
23																															
24																															
25																															
26																															
27																															
28																															
29																															
30																															
31																															
FC																															
PB																															
RB																															
LB																															
PA																															
RA																															
LA																															
D3																															
D2																															
D1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Enable $B_{(o)}1$													
D0	—	—	—	—	—	—	—	H	—	—	—	—	—	—	—	—	—	Enable $B_{(o)}0$ for term 20													
PIN		5	4	3	2	9	8	7	6	19	18	17	16	15	14	13	12		19	18	17	16	15	14	13	12	9	8	7	6	
REMARKS																															

PLS159

TB00622S

9

Signetics

Application Specific Products

AN20

Single Pin Debouncer Using 82S153/159

Application Note

INTRODUCTION

The 82S159 is a field-programmable logic sequencer which is self-contained as a logic sequencer except for the need of a system clock and/or one or more debounced switches. Generally, most of the debouncers circuits utilize a cross-coupled NAND/NOR to form an RS-latch which takes two input pins. To economize the I/O pin consumption, a single I/O pin may be used to debounce a single pole double throw switch. This scheme is applicable to all Signetics PLD's (Programmable Logic Devices) that have non-registered bi-directional I/O's, including 82S153/153A, and 82S155.

DESCRIPTION

Figures 1a and 1b are logic diagrams of the circuit which utilizes one I/O pin of the 82S153/153A and 82S159 respectively to form a debouncer. The single pole double throw switch is connected, at one terminal, to V_{CC}, and, at another terminal, to ground. The blade of the switch is connected to B0. B0 is programmed as an output. The input buffer of B0 is programmed to drive a p-term which, in turn, drives the output B0. The circuit latches to whichever state it is in. As an example, assuming that the output B0 is connected to V_{CC} through the switch, and its output is a "1". When the switch is flipped from V_{CC} to ground, B0 is momentarily short circuited to ground. After one propagation delay (15-30ns), B0 is set to "0" and no more current will flow from B0. If the switch is flipped back to V_{CC}, B0 will be shorted to V_{CC} for one prop delay and will be set to a "1" and will stay a "1" until the switch is flipped again. The switch may bounce while the blade breaks from one terminal and bounce again while it makes contact with the other terminal. As long as the movement of the blade is smaller than the gap which separates the two terminals, the output will remain stable.

The circuit is implemented in an 82S159 using AMAZE as shown in Figures 2 & 3, and Table 1.


"1"
VCC
BO
DEBOUNCED INPUT TO OTHER GATES
DEBOUNCED SIGNAL TO OTHER PINS OR CHIPS
TC01780S

a. Using 82S153/153A


"1"
VCC
BO
"1"
DEBOUNCED INPUT TO OTHER GATES
DEBOUNCED SIGNAL TO OTHER PINS OR CHIPS
TC01790S

b. Using 82S159

Figure 1. Single Pin Switch Debouncer Circuit

Single Pin Debouncer Using 82S153/159

AN20

```
 ******************** DEBOUNCE ********************
###################### P I N   L I S T ######################

   LABEL       ** FNC **PIN --------- PIN** FNC **     LABEL
N/C            ** CK  **  1-|         |-20 ** +5V **VCC
N/C            ** I   **  2-|         |-19 ** B   **N/C
N/C            ** I   **  3-|         |-18 ** B   **N/C
N/C            ** I   **  4-|    8    |-17 ** B   **N/C
N/C            ** I   **  5-|    2    |-16 ** B   **N/C
SWITCH         ** O   **  6-|    S    |-15 ** O   **INPUT_LATCH
N/C            ** /B  **  7-|    1    |-14 ** B   **N/C
N/C            ** /B  **  8-|    5    |-13 ** B   **N/C
N/C            ** /B  **  9-|    9    |-12 ** B   **N/C
GND            ** 0V  ** 10-|         |-11 ** /OE **N/C
                             ---------
```

TB00550S

Figure 2. Pin List

```
 ******************** DEBOUNCE ********************
@DEVICE TYPE
82S159
@DRAWING
************ SINGLE PIN DEBOUNCER
@REVISION
************ REV -
@DATE
************ xx/xx/xxxx
@SYMBOL
************ DEBOUNCE
@COMPANY
************ SIGNETICS
@NAME
@DESCRIPTION
This circuit accepts a single pole double pole switch which switches between
Vcc and GROUND. BO is used as input, but it is defined in AMAZE  as output.
BO may be used to drive the rest of the logic circuit or it may be used
in conjunction with one of the internal flip flops as registered input to
handle asynchronous input to a state machine.
@COMMON PRODUCT TERM
@COMPLEMENT ARRAY
@I/O DIRECTION
@OUTPUT POLARITY
@FLIP FLOP CONTROL
@OUTPUT ENABLE
@REGISTER LOAD
@ASYNCHRONOUS PRESET/RESET
@FLIP FLOP MODE
@LOGIC EQUATION
SWITCH = SWITCH ;

" ***********************************************
  *          BO WITH LATCHED INPUT              *
  *********************************************** "
/INPUT_LATCH : D  =  SWITCH  ;
```

TB00560S

Figure 3. Boolean Equation File

9

Table 1. Programming Table

```
 ********************* DEBOUNCE *********************
Cust/Project  -
Date          - ************* xx/xx/xxxx
Rev/I. D.     - ************* REV -

82S159               ! F/F TYPE      ! E(b)= !E(a) = !POLARTY!
___                  !_______________!_______!_______!_______!
 T !                 !A:A:A:A:A:A:A:A!   0   !   0   !L:L:L:H!
 E !---------------------------------------------------------
 R ! !   I   ! B(i)  !     Q(p)      !     Q(n)      ! B(o)  !
 M !C!-------------------------------------------------------
___!_!3_2_1_0!3_2_1_0!7_6_5_4_3_2_1_0!7_6_5_4_3_2_1_0!3_2_1_0!
  0!A!- - - -!- - - H!- - - -,- - - -!0 0 0 0,A 0 0 0!A A A A!
  1!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  2!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  3!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  4!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  5!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  6!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  7!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  8!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
  9!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 10!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 11!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 12!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 13!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 14!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 15!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 16!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 17!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 18!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 19!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 20!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 21!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 22!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 23!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 24!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 25!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 26!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 27!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 28!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 29!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 30!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 31!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 Fc!0!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Pb!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Rb!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Lb!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Pa!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Ra!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 La!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D3!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D2!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D1!.!0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D0!-!- - - -!- - - -!- - - -,- - - -!                       .

      N N N N N N N S N N N N I N N N N N N N I N N N N N N S
      / / / / / / / W / / / / N / / / / / / / N / / / / / / W
      C C C C C C C I C C C C P C C C C C C C P C C C C C C I
                    T         U               U             T
                    C         T               T             C
                    H         _               _             H
                              L               L
                              A               A
                              T               T
                              C               C
                              H               H
```

TB00570S

Signetics

Application Specific Products

AN21

9-Bit Parity Generator/Checker With 82S153/153A

Application Note

INTRODUCTION

This application note presents the design of a parity generator using Signetics PLD, 82S153 or 82S153A, which enables the designers to customize their circuits in the form of "sum-of-products". The PLA architecture and the 10 bi-directional I/O's make it possible to implement the 9-bit parity generator/checker in one chip without any external wiring between pins. A logic diagram of the device is shown in Appendix A.

The parity of an 8-bit word is generated by counting the number of "1's" in the word. If the number is odd, the word has odd parity. If the number is even, the word has even parity. Thus, a parity generator designed for even parity, for example, will generate a "0" if the parity is even, or a "1" if parity is odd. Conversely, an odd parity generator will generate a "0" if the parity of the word is odd, or a "1" if the parity is even. This bit is then concatinated to the word making it 9-bits long. When the word is used elsewhere, its parity may be checked for correctness.

FEATURES

- **Generates even and odd parities (SUM_E and SUM_O)**
- **SUM_E = "1" for even parity, "0" for odd parity**
- **SUM_O = "1" for odd parity, "0" for even parity**
- **Generate parity or check for parity errors**
- **Cascaded to expand word length**

DESCRIPTION

The most straight forward way of implementing the parity generator/checker is to take the 9-input truth table (8 inputs for the 8-bit word, and 1 input for cascading the previous stage) and put it in a 256 × 4 PROM. Since there are 2^9 combinations and half of them is odd, the other half is even, the circuit will take 256 terms. An alternative is to divide the 9-bits into 3 groups of 3-bits as shown in Figure 1. If the sum of the 3-bits is odd, then the intermediate output SU1, or SU2, or SU3 equals 1. Otherwise it equals 0. The intermediate results are grouped together and SUM_O becomes "1" if the sum is odd, otherwise SUM_O equals "0". The circuit is implemented using AMAZE as shown in Figure 3. SU1 is an intermediate output for inputs I_0, I_1 and I_2. In the same manner, SU2 and SU3 are intermediate outputs for I_3, I_4, I_5 and I_6, I_7, I_8. The design uses up 16 product terms and 5 control terms leaving 16 product terms and 4 bi-directional I/O's to implement other logic designs.

The design is tested by using the logic simulator provided by AMAZE. The input test vector is chosen to exhaustively test for all 8 input combinations at all 4 sections of the circuit.

9-Bit Parity Generator/Checker With 82S153/153A

AN21



BD01670S

I_0	I_1	I_2	SU1
0	0	0	0
0	0	1	1
0	1	1	0
0	1	0	1
1	0	1	0
1	0	0	1
1	1	0	0
1	1	1	1

I_3	I_4	I_5	SU2
0	0	0	0
0	1	1	0
0	0	1	1
0	1	0	1
1	0	1	0
1	1	0	0
1	0	0	1
1	1	1	1

I_6	I_7	I_8	SU3
0	0	0	0
0	1	1	0
1	0	1	0
1	1	0	0
0	0	1	1
0	1	0	1
1	0	0	1
1	1	1	1

SU1	SU2	SU3	SUM_O	SUM_E
0	0	0	0	1
0	0	1	1	0
0	1	0	1	0
0	1	1	0	1
1	0	0	1	0
1	0	1	0	1
1	1	0	0	1
1	1	1	1	0

Figure 1. Block Diagram of 9-Bit Parity Generator/Checker

```
      ******************** PARGEN ********************
      ###################### P I N   L I S T ######################

   LABEL        ** FNC **PIN ---------- PIN** FNC **      LABEL
I0              ** I   **   1-|         |-20 ** +5V **VCC
I1              ** I   **   2-|         |-19 ** /O  **SUME
I2              ** I   **   3-|         |-18 ** O   **SUMO
I3              ** I   **   4-|    8    |-17 ** B   **N/C
I4              ** I   **   5-|    2    |-16 ** B   **N/C
I5              ** I   **   6-|    S    |-15 ** B   **N/C
I6              ** I   **   7-|    1    |-14 ** B   **N/C
I7              ** I   **   8-|    5    |-13 ** O   **SU3
I8              ** I   **   9-|    3    |-12 ** O   **SU2
GND             ** OV  **  10-|         |-11 ** O   **SU1
                               ----------
```

TB00590S

Figure 2. Pin List

```
 ******************** PARGEN ********************
@DEVICE TYPE
82S153
@DRAWING
******************************** PARITY GENERATOR/CHECKER
@REVISION
******************************** REV. -
@DATE
******************************** xx/xx/xxxx
@SYMBOL
******************************** FILE ID: PARGEN
@COMPANY
******************************** SIGNETICS
@NAME
@DESCRIPTION
**********************************************************************
*   This circuit is a 9-bit parity generator/checker commonly used   *
*   for error detection in high speed data transmission/retrieval.   *
*   The odd parity output (SUMO) is high when the sum of the data    *
*   bits is odd. Otherwise it is low.                                *
*   The even parity output (SUME) is high when the sum of the data   *
*   bits is even. It is low otherwise.                               *
**********************************************************************
@COMMON PRODUCT TERM
@I/O DIRECTION
"
**********************************************************************
*   SU1, SU2 and SU3 are outputs which are defined in the PIN LIST   *
*   and therefore they don't need to be defined here again.          *
**********************************************************************
"
@OUTPUT POLARITY
"
**********************************************************************
*   The output polarities of different outputs are defined in the    *
*   PIN LIST. They don't have to be defined again here.              *
**********************************************************************
"
@LOGIC EQUATION
"
**********************************************************************
*   SU1, SU2, and SU3 are intermediate terms                         *
**********************************************************************
                  TRUTH TABLE
         INPUTS                    OUTPUTS
    ----------------          ----------------------
    SU3    SU2    SU1          SUMO      SUME = /SUMO
     I8     I7     I6           SU3
     I5     I4     I3           SU2
     I2     I1     I0           SU1

     0      0      0            0          1
     0      0      1            1          0
     0      1      0            1          0
     0      1      1            0          1
     1      0      0            1          0
     1      0      1            0          1
     1      1      0            0          1
     1      1      1            1          0
"

SU1 = /I2 * /I1 *  I0 + /I2 *  I1 * /I0 +
       I2 * /I1 * /I0 +  I2 *  I1 *  I0 ;
SU2 = /I5 * /I4 *  I3 + /I5 *  I4 * /I3 +
       I5 * /I4 * /I3 +  I5 *  I4 *  I3 ;

SU3 = /I8 * /I7 *  I6 + /I8 *  I7 * /I6 +
       I8 * /I7 * /I6 +  I8 *  I7 *  I6 ;

SUMO = /SU1 * /SU2 *  SU3 + /SU1 *  SU2 * /SU3 +
        SU1 * /SU2 * /SU3 +  SU1 *  SU2 *  SU3 ;

SUME = /(/SU1 * /SU2 *  SU3 + /SU1 *  SU2 * /SU3 +
         SU1 * /SU2 * /SU3 +  SU1 *  SU2 *  SU3) ;
```

TB00580S

Figure 3. AMAZE Implementation of the Parity Generator/Checker Circuit

9

9-Bit Parity Generator/Checker With 82S153/153A

Table 1. Programming Table

```
 ******************** PARGEN ********************
Cust/Project -
Date         - ******************************** xx/xx/xxxx
Rev/I. D.    - ******************************** REV. -

82S153                                 !      POLARITY      !
---                                     --------------------
 T !                                   !L:H:H:H:H:H:H:H:H:H!
 E !---------------------------------------------------------
 R !      I        !       B(i)        !       B(o)        !
 M !---------------------------------------------------------
___!7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!
  0!- - - -,- L L H!- -,- - - -,- - - -!. .,A A A A,. . A A!
  1!- - - -,- L H L!- -,- - - -,- - - -!. .,A A A A,. . A A!
  2!- - - -,- H L L!- -,- - - -,- - - -!. .,A A A A,. . A A!
  3!- - - -,- H H H!- -,- - - -,- - - -!. .,A A A A,. . A A!
  4!- - L L,H - - -!- -,- - - -,- - - -!. .,A A A A,. A . A!
  5!- - L H,L - - -!- -,- - - -,- - - -!. .,A A A A,. A . A!
  6!- - H L,L - - -!- -,- - - -,- - - -!. .,A A A A,. A . A!
  7!- - H H,H - - -!- -,- - - -,- - - -!. .,A A A A,. A . A!
  8!L H - -,- - - -!- -,- - - -,- - - L!. .,A A A A,A . . A!
  9!H L - -,- - - -!- -,- - - -,- - - L!. .,A A A A,A . . A!
 10!L L - -,- - - -!- -,- - - -,- - - H!. .,A A A A,A . . A!
 11!H H - -,- - - -!- -,- - - -,- - - H!. .,A A A A,A . . A!
 12!- - - -,- - - -!- -,- - - -,H L L -!A A,A A A A,. . . A!
 13!- - - -,- - - -!- -,- - - -,L H L -!A A,A A A A,. . . A!
 14!- - - -,- - - -!- -,- - - -,L L H -!A A,A A A A,. . . A!
 15!- - - -,- - - -!- -,- - - -,H H H -!A A,A A A A,. . . A!
 16!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 17!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 18!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 19!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 23!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D8!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D7!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D6!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D5!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D4!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D3!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D2!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D1!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D0!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .

    I I I I I I I I S S N N N N S S S I S S N N N N S S S I
    7 6 5 4 3 2 1 0 U U / / / / U U U 8 U U / / / / U U U 8
                    M M C C C C 3 2 1   M M C C C C 3 2 1
                    E O                 E O
```

TB00610S

```
"
***********************************************************************
*   This is a test pattern for the 9-bit parity generator/checker    *
*   circuit. The simulator will use this file as an input to         *
*   simulate the logical function.                                    *
***********************************************************************

"          SS              EXPECTED
"          UU    SSS       OUTPUTS
"IIIIIIII MMBBBBUUUI        BBBBB
"76543210 E076543218        98321
 LLLLLLLL /////////L       "HLLLL
 HLHHLHLL /////////H       "LHLLH
 LHHLLHHL /////////H       "LHLHL
 HHLHLLHL /////////L       "HLLHH
 LLHLHHLH /////////H       "LHHLL
 HLLHHLLH /////////L       "HLHLH
 LHLLHLHH /////////L       "HLHHL
 HHHHHHHH /////////H       "LHHHH
QUIT
```

TB00600S

a. Input Pattern PARGEN.TST

```
82S153   A:pargen.STD
" This file is the result of logic simulation of the parity generator/checker
" circuit. The inputs are read from input file PARGEN.TST
"
"  INPUTS  <=B(I/O)=>   TRACE TERMS
" 76543210 9876543210
"
  00000000 HL....LLLO ;
  10110100 LH....LLH1 ;
  01100110 LH....LHL1 ;
  11010010 HL....LHHO ;
  00101101 LH....HLL1 ;
  10011001 HL....HLHO ;
  01001011 HL....HHLO ;
  11111111 LH....HHH1 ;
"
" -------- ----------   I/O CONTROL LINES
"          OOIIIIOOOI   DESIGNATED I/O USAGE
"          OOIIIIOOOI   ACTUAL I/O USAGE
"
" PIN LIST...
" 08 07 06 05 04 03 02 01 19 18 17 16 15 14 13 12 11 09 ;
```

TB00601S

b. Output File From SIMULATOR

Figure 4. Test Vectors

APPENDIX A


(LOGIC TERMS—P)
(CONTROL TERMS)
I0 1
I1 2
I2 3
I3 4
I4 5
I5 6
I6 7
I7 8
I8 9
I9 10
I10 11
I11 13
B0
B1
B2
B3
B4
B5
B6
B7
B8
B9
D9 D8 D7 D6 D5 D4 D3 D2 D1 D0
S9 S8 S7 S6 S5 S4 S3 S2 S1 S0
X9 X8 X7 X6 X5 X4 X3 X2 X1 X0
23 B9
22 B8
21 B7
20 B6
19 B5
18 B4
17 B3
16 B2
15 B1
14 B0
31 • • • • • • 24
23 • • • • • • 16
15 • • • • • • 8
7 • • • • • • 0
TB00942S

NOTES:
1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. Programmable connection.

Figure A-1. FPLA Logic Diagram

Signetics

Application Specific Products

AN22

PLS151 Toolkit

Application Note


A
B
D
E
"1"
"1"
"1"
"1"
"1"
"1"
$A \cdot B$
$\overline{D \cdot E}$
$A + B$
$\overline{A + B}$
$(A \cdot B) + (D \cdot E)$
$\overline{(A \cdot B) + (D \cdot E)}$
$A \cdot \overline{B}$
$\overline{A} \cdot B$
$A \oplus B$
$A \odot B$
BD01680S

a. Basic Gates Configuration

```
 ********************** TK151-1 ********************
######################## P I N   L I S T ######################

   LABEL      ** FNC **PIN ---------- PIN** FNC **     LABEL
A             ** I   **   1-!        !-20 ** +5V **VCC
B             ** I   **   2-!        !-19 ** 0   **A_NOR_B
D             ** I   **   3-!        !-18 ** /0  **A_OR_B
E             ** I   **   4-!    8   !-17 ** /0  **D_NAND_E
N/C           ** I   **   5-!    2   !-16 ** 0   **A_AND_B
N/C           ** I   **   6-!    S   !-15 ** /0  **AB_OR_DE
N/C           ** /B  **   7-!    1   !-14 ** 0   **AB_NOR_DE
N/C           ** /B  **   8-!    5   !-13 ** /0  **A_XOR_B
A-_N_B        ** 0   **   9-!    1   !-12 ** 0   **A_EQU_B
GND           ** 0V  **  10-!        !-11 ** 0   **A_N_B-
                          ----------
```

TB00640S

b. Pin List

Figure 1



```
 ********************* TK151-1 ********************
@DEVICE TYPE
************ 82S151
@DRAWING
************ FIGURE 1. BASIC GATE CONFIGURATIONS
@REVISION
************ TK151-1 REV. 0
@DATE
************ JULY 10, 1985
@SYMBOL
************ TK151-1
@COMPANY
************ SIGNETICS
@NAME
************ DAVID K. WONG
@DESCRIPTION
This file contains the 6 basic logic gates: AND, NAND, OR, NOR, XOR and EQU.
@COMMON PRODUCT TERM
@I/O DIRECTION
@OUTPUT POLARITY
@I/O STEERING
@LOGIC EQUATION
A_AND_B    = A * B ;
D_NAND_E   = /( D * E ) ;
A_OR_B     = /( /A * /B ) ;
A_NOR_B    = /A * /B ;
AB_OR_DE   = /( /(A_AND_B) * D_NAND_E ) ;
AB_NOR_DE  = /(A_AND_B) * D_NAND_E ;
A_N_B-     = A * /B ;
A-_N_B     = /A * B ;
A_XOR_B    = /(/(A_N_B-) * /(A-_N_B)) ; " Equivalent to (A * /B) + (/A * B) "
A_EQU_B    = /(A_N_B-) * /(A-_N_B) ;     " Equivalent to (/A * /B) + (A * B) "
```

TB00630S

c. Boolean Equations of Basic Gate Configurations

Figure 1 (Continued)

Table 1. Program Table of Basic Gate Configurations



```
 ********************* TK151-1 ********************
Cust/Project - ************ DAVID K. WONG
Date         - ************ JULY 10, 1985
Rev/I. D.    - ************ TK151-1 REV. 0
                   _________________________
82S151    DIR    !A:A:A:A:A:A:A:A:A:A:A:A!
___                _________________________
 T !      POL    !H:L:L:H:L:H:L:H:H:H:L:L!
 E !---------------------------------------
 R !      I     !          B(i)           !
 M !-----------!1 1 ----------------------
___!5_4_3_2_1_0!1_0_9_8_7_6_5_4_3_2_1_0!
  0!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  1!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  2!- -,- - H L!- - - -,- - - -,- - - -!
  3!- -,- - L H!- - - -,- - - -,- - - -!
  4!- -,- - - -!- - - -,- - - -,L L - -!
  5!- -,- - - -!- - - -,- - - -,L L - -!
  6!- -,- - - -!- - H L,- - - -,- - - -!
  7!- -,- - - -!- - H L,- - - -,- - - -!
  8!- -,- - H H!- - - -,- - - -,- - - -!
  9!- -,H H - -!- - - -,- - - -,- - - -!
 10!- -,- - L L!- - - -,- - - -,- - - -!
 11!- -,- - L L!- - - -,- - - -,- - - -!
 D2!- -,- - - -!- - - -,- - - -,- - - -!
 D1!- -,- - - -!- - - -,- - - -,- - - -!
 DO!- -,- - - -!- - - -,- - - -,- - - -!

    N N E D B A A A D A A A A A A A N N
    / /         _ _ _ _ B B _ _ _ - / /
    C C         N O N A _ _ X E N _ C C
                O R A N O N O Q _ N
                R _ N D R O R U B _
                _ B D _ _ R _ _ - B
                B   _ B D _ B B
                    E   E D
                          E
```

TB00680S


R1-
Q1-
Q1
S1-
LD01270S
RR2
Q2-
Q2
SS2
LD01280S
DIN
Q3
LE-
LD01290S

a. Basic Latches Configuration

```
 ********************** TK151-2 **********************
************************ P I N   L I S T ************************

   LABEL       ** FNC **PIN ---------- PIN** FNC **     LABEL
R1-            ** I   **  1-:         :-20 ** +5V **VCC
S1-            ** I   **  2-:         :-19 ** /O  **Q1
RR2            ** I   **  3-:         :-18 ** /O  **Q1-
SS2            ** I   **  4-:    8    :-17 ** O   **Q2
DIN            ** I   **  5-:    2    :-16 ** O   **Q2-
LE-            ** I   **  6-:    S    :-15 ** /O  **Q3
N/C            ** /B  **  7-:    1    :-14 ** O   **D_N_LE
N/C            ** /B  **  8-:    5    :-13 ** O   **Q3_N_LE-
N/C            ** /B  **  9-:    1    :-12 ** /B  **N/C
GND            ** OV  ** 10-:         :-11 ** /B  **N/C
                            ----------
```

TB00670S

b. Pin List

Figure 2

```
******************** TK151-2 ********************
@DEVICE TYPE
82S151
@DRAWING
************ FIGURE 2. BASIC LATCHES CONFIGURATION
@REVISION
************ TK151-2 REV. 0
@DATE
************ JULY 10, 1985
@SYMBOL
************ TK151-2
@COMPANY
************ SIGNETICS
@NAME
************ DAVID K. WONG
@DESCRIPTION
This files contains basic configurations of two RS-latches and a D-latch.
@COMMON PRODUCT TERM
@I/O DIRECTION
@OUTPUT POLARITY
@I/O STEERING
@LOGIC EQUATION

" *********************************
  *  CROSS-COUPLED NAND RS-LATCH  *
  ********************************* "
Q1-         = /( /R1- * Q1 ) ;
Q1          = /( /S1- * Q1- ) ;

" *********************************
  *  CROSS-COUPLED NOR RS-LATCH   *
  ********************************* "
Q2-         = RR2 * Q2 ;
Q2          = SS2 * Q2- ;

" *********************************
  *            D-LATCH            *
  ********************************* "
D_N_LE      = DIN * LE- ;
Q3_N_LE-    = Q3 * /LE- ;
Q3          = /( /(D_N_LE) * /(Q3_N_LE-) ) ;
```

TB00660S

c. Boolean Equations of Basic Latches Configuration

Figure 2 (Continued)

Table 2. Program Table of Basic Latches

```
 ******************** TK151-2 ********************
Cust/Project - ************ DAVID K. WONG
Date         - ************ JULY 10, 1985
Rev/I. D.    - ************ TK151-2 REV. 0
               _________________________
82S151     DIR !A:A:A:A:A:A:A:A:A:A:A:A!
___            _________________________
 T !       POL !L:L:H:H:L:H:H:L:L:L:L:L!
 E !------------------------------------
 R !        I  !          B(i)         !
 M !-----------!1 1 --------------------
___!5_4_3_2_1_0!1_0_9_8_7_6_5_4_3_2_1_0!
  0!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  1!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  2!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  3!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  4!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  5!L -,- - - -!- - - -,H - - -,- - - -!
  6!H H,- - - -!- - - -,- - - -,- - - -!
  7!- -,- - - -!- - - -,- L L -,- - - -!
  8!- -,- H - -!- - H -,- - - -,- - - -!
  9!- -,H - - -!- - - H,- - - -,- - - -!
 10!- -,- - - L!H - - -,- - - -,- - - -!
 11!- -,- - L -!- H - -,- - - -,- - - -!
 D2!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
 D1!- -,- - - -!- - - -,- - - -,- - - -!
 DO!- -,- - - -!- - - -,- - - -,- - - -!

    L D S R S R Q Q Q Q Q D Q N N N N N
    E I S R 1 1 1 1 2 2 3 _ 3 / / / / /
    - N 2 2 - -   -   -   N _ C C C C C
                          _ N
                          L _
                          E L
                            E
                            -
```

TB00710S


DIN3
DIN2
DIN1
DIN0
Q3
Q2
Q1
Q0
LE-
LD01300S

a. 4-Bit D-Latch

```
 ********************* TK151-3 *********************
####################### P I N   L I S T #######################

   LABEL     ** FNC **PIN ---------- PIN** FNC **     LABEL
DIN0         ** I   **   1-¦         ¦-20 ** +5V **VCC
DIN1         ** I   **   2-¦         ¦-19 ** B   **Q0
DIN2         ** I   **   3-¦         ¦-18 ** B   **Q1
DIN3         ** I   **   4-¦    8    ¦-17 ** B   **Q2
LE-          ** I   **   5-¦    2    ¦-16 ** B   **Q3
N/C          ** I   **   6-¦    S    ¦-15 ** B   **FB0
N/C          ** /B  **   7-¦    1    ¦-14 ** B   **FB1
N/C          ** /B  **   8-¦    5    ¦-13 ** B   **FB2
N/C          ** /B  **   9-¦    1    ¦-12 ** B   **FB3
GND          ** 0V  **  10-¦         ¦-11 ** /B  **N/C
                            ----------
```

TB00700S

b. Pin List

Figure 3

```
******************** TK151-3 ********************
@DEVICE TYPE
82S151
@DRAWING
************ FIGURE 3. 4 BIT D-LATCH
@REVISION
************ TK151-3 REV. 0
@DATE
************ JULY 10, 1985
@SYMBOL
************ TK151-3
@COMPANY
************ SIGNETICS
@NAME
************ DAVID K. WONG
@DESCRIPTION
This file contains a 4-bit D-latch. External jumper is required for each latch
between Qn and FBn. When LE- is HIGH, outputs Q0, Q1, Q2, and Q3 are active and
 outputs FB0, FB1, FB2, and FB3 are tri-stated. Qn, therefore, equals Dn when
LE- is HIGH. When LE- becomes LOW, Q outputs are tri-stated, and FB outputs are
active. Since FB outputs feedback to their own inputs, they are latched to
whatever level the Q outputs were in when LE- goes from HIGH to LOW.
@COMMON PRODUCT TERM
@I/O DIRECTION
D0   = /( /LE- ) ;
D1   = /(  LE- ) ;
@OUTPUT POLARITY
@I/O STEERING
@LOGIC EQUATION
Q0   = DIN0 ;
Q1   = DIN1 ;
Q2   = DIN2 ;
Q3   = DIN3 ;
FB0  = Q0   ;
FB1  = Q1   ;
FB2  = Q2   ;
FB3  = Q3   ;
```

TB00690S

c. Boolean Equations of 4-Bit D-Latch

Figure 3 (Continued)

Table 3. Program Table of 4-Bit D-Latch

```
 ******************** TK151-3 ********************
Cust/Project - ************ DAVID K. WONG
Date         - ************ JULY 10, 1985
Rev/I. D.    - ************ TK151-3 REV. 0

               -------------------------
82S151    DIR  !A:A:A:A:A:A:A:A:A:A:A:A!

---            -------------------------
 T !      POL  !H:H:H:H:H:H:H:H:L:L:L:L!
 E !------------------------------------
 R !       I   !          B(i)         !
 M !-----------!1 1 ---------------------
___!5_4_3_2_1_0!1_0_9_8_7_6_5_4_3_2_1_0!
  0!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  1!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  2!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  3!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  4!- -,- - - -!- - - H,- - - -,- - - -!
  5!- -,- - - -!- - H -,- - - -,- - - -!
  6!- -,- - - -!- H - -,- - - -,- - - -!
  7!- -,- - - -!H - - -,- - - -,- - - -!
  8!- -,H - - -!- - - -,- - - -,- - - -!
  9!- -,- H - -!- - - -,- - - -,- - - -!
 10!- -,- - H -!- - - -,- - - -,- - - -!
 11!- -,- - - H!- - - -,- - - -,- - - -!
 D2!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
 D1!- H,- - - -!- - - -,- - - -,- - - -!
 D0!- L,- - - -!- - - -,- - - -,- - - -!

    N L D D D D Q Q Q Q F F F F N N N N
    / E I I I I 0 1 2 3 B B B B / / / /
    C - N N N N         0 1 2 3 C C C C
        3 2 1 0
```

TB00740S



TC01800S

Switch Debouncer



LD01310S

Pulse Shaper

a. Single Pin Switch Debouncer and Pulse Shaper

```
 ******************** TK151-4 ********************
######################## P I N   L I S T ########################

   LABEL      ** FNC **PIN ---------- PIN** FNC **     LABEL
IN2           ** I    **   1-¦        ¦-20 ** +5V **VCC
N/C           ** I    **   2-¦        ¦-19 ** O   **IN1
N/C           ** I    **   3-¦        ¦-18 ** /O  **IN2-
N/C           ** I    **   4-¦    8   ¦-17 ** O   **OUT2
N/C           ** I    **   5-¦    2   ¦-16 ** /B  **N/C
N/C           ** I    **   6-¦    S   ¦-15 ** /B  **N/C
N/C           ** /B   **   7-¦    1   ¦-14 ** /B  **N/C
N/C           ** /B   **   8-¦    5   ¦-13 ** /B  **N/C
N/C           ** /B   **   9-¦    1   ¦-12 ** /B  **N/C
GND           ** OV   **  10-¦        ¦-11 ** /B  **N/C
                             ----------
```

TB00730S

b. Pin List

Figure 4

```
********************* TK151-4 ********************
@DEVICE TYPE
82S151
@DRAWING
************* PLS151 TOOLKIT FIGURE 4
@REVISION
************* tk151-4 REV. 0
@DATE
************* JULY 10, 1985
@SYMBOL
************* TK151-4
@COMPANY
************* SIGNETICS
@NAME
************* DAVID K. WONG
@DESCRIPTION
This file contains a single pin debouncer and a pulse shaper.
@COMMON PRODUCT TERM
@I/O DIRECTION
@OUTPUT POLARITY
@I/O STEERING
@LOGIC EQUATION
" ******************************************************************
  * DEBOUNCER -- This circuit uses one bidirectional pin to de-    *
  *              bounce a single pole double throw switch. When    *
  *              the switch is thrown to its opposit polarity,     *
  *              it shorts the output to Vcc or ground. One pro-   *
  *              pagation delay later, the output is switched to   *
  *              the same polarity as the switch.                  *
  ****************************************************************** "
 IN1     = IN1 ;

" ******************************************************************
  * PULSE SHAPER -- This circuit creates a LOW-to-HGH glitch       *
  *                 which has the pulse width of one prop delay.   *
  *                 Wider pulse width may be generated with add-   *
  *                 itional feedback loops.                        *
  ****************************************************************** "
IN2-    = /( IN2 ) ;
OUT2    = IN2- * IN2 ;
```

TB00720S

c. Boolean Equations of Single Pin and Pulse Shaper

Figure 4 (Continued)

Table 4. Program Table of Single Pin Debouncer and Shaper

```
 ********************* TK151-4 ********************
Cust/Project - ************* DAVID K. WONG
Date         - ************* JULY 10, 1985
Rev/I. D.    - ************* tk151-4 REV. 0
                        _________________________
82S151     DIR         !A:A:A:A:A:A:A:A:A:A:A:A!
___                     _________________________
 T !       POL         !H:L:H:L:L:L:L:L:L:L:L:L!
 E !--------------------------------------------
 R !       I     !             B(i)            !
 M !-------------!1 1 --------------------------
___!5_4_3_2_1_0!1_0_9_8_7_6_5_4_3_2_1_0!
  0!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  1!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  2!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  3!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  4!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  5!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  6!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  7!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  8!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
  9!- -,- - - H!- H - -,- - - -,- - - -!
 10!- -,- - - H!- - - -,- - - -,- - - -!
 11!- -,- - - -!H - - -,- - - -,- - - -!
 D2!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
 D1!0 0,0 0 0 0!0 0 0 0,0 0 0 0,0 0 0 0!
 D0!- -,- - - -!- - - -,- - - -,- - - -!

    N N N N N I I I O N N N N N N N N N
    / / / / / N N N U / / / / / / / / /
    C C C C C 2 1 2 T C C C C C C C C C
                  - 2
```

TB00650S

Signetics

AN23

PLS168/168A Primer

Application Note

Application Specific Products

INTRODUCTION

THE PLS168/168A is a bipolar Fieid-Programmable Logic Sequencer as shown in Figure 1, which consists of 12 inputs, a 48 product term PLA and 14 R/S flip-flops. Out of the 14 flip-flops, six are buried State Registers ($P_4 - P_9$), four Output Registers ($F_0 - F_3$), and four Dual-purpose Registers ($P_0 - P_3$), which may be used as Output or State Registers. All flip-flops are positive edge-triggered. They are preset to "1" at power-up, or may be asynchronously set to "1" by an optional PR/OE pin, which may be programmed either as a preset pin or as an Output Enable pin. Additional features includes the Complement Array and diagnostics features.

ARCHITECTURE

As shown in Figure 2, the device is organized as a decoding AND-OR network which drives a set of registers some of which, in turn, feedbacks to the AND/OR decoder while the rest serve as outputs. Outputs P_0 to P_3 may be programmed to feedback to the AND/OR decoder as State Registers and, at the same time, used as outputs. The user now can design a 10-bit state machine without external wiring. The AND/OR array is the classical PLA structure in which the outputs of all the AND gates can be programmed to drive all the OR gates. The schematic diagram of the AND-OR array is shown in Figure 3. This structure provides the user a very structured design methodology which can be automated by CAD tools, such as Signetics AMAZE software package. The output of the PLA is in the form of sum-of-products which, together with the RS flip-flops, is the ideal structure for implementation of state machines. (Refer to Appendix A for a brief description of synchronous finite state machines.)

Design Tools

A direct approach to implement a design using the PLS168/168A is the H/L table supplied in the data sheet as shown in Table 1. The table is organized according to input and output of the PLA decoding network. The lefthand side of the table represent the inputs to the AND-array, which includes input from input pins and present state information from the feedback buffers which feedback the contents of the State Register. The righthand side of the table represents the output of the OR-array, which drives the State and Output Registers as the next state and output. Each column in the lefthand side of the table represents an input buffer, which may be inverting, non-inverting, disconnected or unprogrammed. Each column in the righthand side of the table represents a pair of outputs to the flip-flops, which may be set, reset, disconnected, or unprogrammed. The programming symbols are H, L, –, and 0. (See Figure 4 for details.) For inputs buffers, "H" means that the non-inverting buffer is connected, "L" means that the inverting buffer is connected, "–" means that both inverting and non-inverting buffers are disconnected, and "0" means that both inverting and non-inverting buffers are connected which causes that particular AND-term to be unconditionally Low. On the output side of the table, "H" means that the particular AND-term is connected to the OR-term on the "S" input of the particular flip-flop, "L" means that the AND-term is connected to the "R" side, "–" means that the AND-term is not connected to the flip-flop at all, and "0" means that the AND-term is connected to both the "S" and "R" sides. More details of the symbols and their meanings are shown in Appendix B. Each row in the table represents an AND-term. There are 48 AND-terms in the device. Therefore, there are 48 rows in the table. An example of implementing a transition from one state to another is shown in Figure 4a. The state diagram can be implemented by the PLS168 as shown in Figure 4b. The state diagram is translated into H/L format as shown in Figure 4c. The first column on the lefthand side of the table is for the Complement Array which will be discussed in detail in the next section.


(LOGIC TERMS—T)
I_0
I_1
I_2
I_3
I_4
I_5
I_6
I_7
I_8
I_9
I_{10}
I_{11}
7
6
5
4
3
2
23
22
21
20
19
18
P
P_0
P_1
P_2
P_3
P_9
P_8
P_7
P_6
P_5
P_4
C
$\overline{C}$
C
N
F
I
P
E
OPTION
17
$PR/\overline{OE}$
S Q
R P
P_9
P_8
P_7
P_6
P_5
P_4
Q_3
Q_2
Q_1
Q_0
16
P_3/P_9
15
P_2/P_8
14
P_1/P_7
13
P_0/P_6
11
F_3/P_5
10
F_2/P_4
9
F_1
8
F_0
1
CK
47
0
TB00881S

NOTES:
1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. Programmable connection.

Figure 1. Logic Diagram of PLS168/168A

Table 1. PLS168/168A Programming Table

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # CF (XXXX) ____________
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ____________
REV ____________
DATE ____________

AND

INACTIVE	O	C_n
GENERATE	A	
PROPAGATE	•	
TRANSPARENT	—	
INACTIVE	O	I_m, P_s
I, P	H	
I, $\overline{P}$	L	
DON'T CARE	—	

OR

INACTIVE	O	N_s, F_r
SET	H	
RESET	L	
NO CHANGE	—	

OPTION

PRESET	H	P/E
OE	L	

AND																										OPTION (P/E) OR												
TERM	C_n	INPUT (Im)												PRESENT STATE (Ps) (Px)										REMARKS	NEXT STATE (Ns) (Px)						OUTPUT (Fr)							
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0		9	8	7	6	5	4	3	2	1	0	3	2	1	0
0																																						
1																																						
2																																						
3																																						
4																																						
5																																						
6																																						
7																																						
8																																						
9																																						
10																																						
11																																						
12																																						
13																																						
14																																						
15																																						
16																																						
17																																						
18																																						
19																																						
20																																						
21																																						
22																																						
23																																						
24																																						
25																																						
26																																						
27																																						
28																																						
29																																						
30																																						
31																																						
32																																						
33																																						
34																																						
35																																						
36																																						
37																																						
38																																						
39																																						
40																																						
41																																						
42																																						
43																																						
44																																						
45																																						
46																																						
47																																						
PIN NO.		18	19	20	21	22	23	2	3	4	5	6	7																		16	15	14	13	11	10	9	8
VARIABLE NAME																																						

TB02030S


12 INPUTS
10 REGISTER FEEDBACK
AND/OR DECODER
OUTPUT REGISTERS
STATE REGISTERS
I_0
I_{11}
F/F
6
F/F
4
P_0-P_3
F/F
4
F_0-F_3
LD02650S

Figure 2. The Architecture of PLS168/168A


V_CC
V_CC
AND-GATE
Ni-Cr FUSE
TO OTHER AND-GATES
TO OTHER AND-GATES
V_CC
V_CC
TO INPUTS OF FLIP-FLOPS
OR-GATE
TC02690S

Figure 3. Schematic Diagram of AND-OR Array



a. State Diagram

b. Implementation of State Diagram (a) With PLS168

TERM	AND																							OPTION (PR/OE) OR													
		INPUT												PRESENT STATE										NEXT STATE										OUTPUT			
	C	11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	3	2	1	0
00	–	*H*	*L*	–	–	–	–	–	–	–	–	–	–	–	–	–	–	*H*	*L*	–	–	–	–	–	–	–	–	*L*	*H*	–	–	–	–	*H*	–	–	–
01																																					
PIN NO.		18	19	20	21	22	23	2	3	4	5	6	7																	16	15	14	13	11	10	9	8
NAME		*IN1*	*INØ*																															*OUTØ*			

TB02010S

c. PLS168 Programming Table

Figure 4. Implementing State Machine With PLS168



Figure 5. Logic Diagram of Complement Array

Complement Array

An additional feature is the Complement Array, which is often used to provide escape vectors in case the state machines get into undefined states during power-up or a timing violation due to asynchronous inputs. A logic diagram of the Complement Array is shown in Figure 5. The output of the Complement Array is normally Low when one or more AND-terms are High. If all of the AND-terms are Low, then the output of the Complement Array will be High. In this example, if each AND-term is a decoder for a particular state and input combination, and if the circuit gets into an undefined state, none of the AND-terms will be High. Therefore, the output /C will be High, which will then enable the AND-term S which in turn may be used to reset all registers to Low or High as predefined. The state machine thus escapes from being in an undefined state by using the Complement Array and one AND-term. Without the Complement Array an alternate way of escaping from being in an undefined state is by defining all possible states which are not being defined. This method may require quite a few AND-terms depending on the design. Another application for the Complement Array is illustrated by the following example. As shown in Figure 6, when the machine is in state 23, if input vector equals 1001, it will go to next state 24. If the input is 1101, then go to state 25. But if the input is neither 1001 nor 1101, then go to state 03. It takes only two terms to implement the first two transition vectors. To implement the third vector ''go to state 03 if input is neither 1001 nor 1101'', the Complement Array accepts the outputs of the first two AND-terms as inputs. If the input vector is neither 1001 nor 1101, then both terms will be Low, which causes the output of the Complement Array (/C) to be High. A third AND-term is used to AND state 24 and /C together to set the registers to state 03. The State Diagram is translated into AMAZE syntex as shown in Figure 6b, where all vectors are in square brackets and the Complement Array is represented by the ELSE statement. The State diagram Figure 6a can also be expressed in the format of a program table as shown in Figure 6c. The complement array may be used to exit from different present states to different next states. It can be used many times in one state machine design as shown in Figures 7a, b, and c where the state diagram is implemented using the AMAZE state equation syntex and the H/L format.


$(PS)_8$
23
$1001/OUT_1$
$1101/OUT_2$
$\overline{1001}*\overline{1101}/OUT_9$
24
25
03
AF02241S

NOTE: $\overline{1001}*\overline{1101} = \overline{1001+1101}$

a. State Diagram

```
WHILE [23]
  IF [1001] THEN [24] WITH
[OUT1]
  IF [1101] THEN [25] WITH
[OUT2]
  ELSE: [03] WITH [OUT9]
```

b. AMAZE State Equation Syntex


COMPLEMENT ARRAY
PRESENT STATE=23 (HEX)
NEXT STATE: 24 (HEX)
25 (HEX)
03 (HEX)
OUT1 =0001
OUT2=0010
OUTG =1001
TB02001S

TERM	AND																							OPTION (PR/OE)													
																								OR													
		INPUT												PRESENT STATE										NEXT STATE										OUTPUT			
	C	11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	3	2	1	0
00	A	H	L	L	H	–	–	–	–	–	–	–	–	H	L	L	L	H	H	–	–	–		H	L	L	H	L	L	–	–	–		L	L	L	H
01	A	H	H	L	H	–	–	–	–	–	–	–	–	H	L	L	L	H	H	–	–	–		H	L	L	H	L	H	–	–	–		L	L	H	L
02	•	–	–	–	–	–	–	–	–	–	–	–	–	H	L	L	L	H	H	–	–	–		L	L	L	L	H	H	–	–	–		H	L	L	H
03																																					
04																																					
05																																					
PIN NO.		18	19	20	21	22	23	2	3	4	5	6	7																	16	15	14	13	11	10	9	8
NAME		IN3	IN2	IN1	IN0																													OP3	OP2	OP1	OP0

c. H/L Format

Figure 6. Application of Complement Array


00
0000/OUT$_0$
0001/OUT$_1$
01
ELSE/OUT$_9$
02
0010/OUT$_2$
0011/OUT$_3$
0100/OUT$_4$
0101/OUT$_5$
03
04
05
06
ELSE/OUT$_6$
3F
ELSE/OUT$_7$
2F

AF02250S

a. State Diagram

```
WHILE [00]
   IF [0000] THEN [01] WITH [OUT0]
   IF [0001] THEN [02] WITH [OUT1]
   ELSE: [3F] WITH [OUT9]
WHILE [01]
   IF [0010] THEN [03] WITH [OUT2]
   IF [0011] THEN [04] WITH [OUT3]
   ELSE: [2F] WITH [OUT6]
WHILE [02]
   IF [0100] THEN [05] WITH [OUT4]
   IF [0101] THEN [06] WITH [OUT5]
   ELSE: [2F] WITH [OUT7]
```

b. AMAZE State Equation

TERM	AND																							OPTION (PR/OE) OR													
	C	INPUT												PRESENT STATE										NEXT STATE										OUTPUT			
		11	10	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	9	8	7	6	5	4	3	2	1	0	3	2	1	0
00	A	L	L	L	L	–	–	–	–	–	–	–	–	L	L	L	L	L	L	–	–	–	–	L	L	L	L	L	H	–	–	–	–	L	L	L	L
01	A	L	L	L	H	–	–	–	–	–	–	–	–	L	L	L	L	L	L	–	–	–	–	L	L	L	L	H	L	–	–	–	–	L	L	L	H
02	•	–	–	–	–	–	–	–	–	–	–	–	–	L	L	L	L	L	L	–	–	–	–	H	H	H	H	H	H	–	–	–	–	H	L	L	H
03																																					
04	A	L	L	H	L	–	–	–	–	–	–	–	–	L	L	L	L	L	H	–	–	–	–	L	L	L	L	H	H	–	–	–	–	L	L	H	L
05	A	L	L	H	H	–	–	–	–	–	–	–	–	L	L	L	L	L	H	–	–	–	–	L	L	L	H	L	L	–	–	–	–	L	L	H	H
06	•	–	–	–	–	–	–	–	–	–	–	–	–	L	L	L	L	L	H	–	–	–	–	H	L	H	H	H	H	–	–	–	–	L	H	H	L
07																																					
08	A	L	H	L	L	–	–	–	–	–	–	–	–	L	L	L	L	H	L	–	–	–	–	L	L	L	H	L	H	–	–	–	–	L	H	L	L
09	A	L	H	L	H	–	–	–	–	–	–	–	–	L	L	L	L	H	L	–	–	–	–	L	L	L	H	H	L	–	–	–	–	L	H	L	H
10	•	–	–	–	–	–	–	–	–	–	–	–	–	L	L	L	L	H	L	–	–	–	–	H	L	H	H	H	H	–	–	–	–	L	H	H	H
11																																					
PIN NO.		18	19	20	21	22	23	2	3	4	5	6	7																	16	15	14	13	11	10	9	8
NAME		IN3	IN2	IN1	IN0																													OP3	OP2	OP1	OP0

TB01990S

c. PLS168 Programming Table

Figure 7. Applications of Complement Array



a. PLS168 Setup Time vs P-Term Loading

b. PLS168 Setup Time vs P-Term Loading

Figure 8


16ns DELAY
S
Q
CK'
R
P
18ns DELAY
S
Q
CK'
R
P
LD02590S

Figure 9. Difference in Propagation Delay Due to Different P-Term Loading


INPUT
t_{SU}
t_H
$t<t_{SU}$
CLOCK
OUTPUT
OUTPUT UNDETERMINED DUE TO METASTABLE CONDITION OF FLIP-FLOP
WF07180S

Figure 10. Change of t_{CKO} Due to Metastable Condition of Flip-Flop

Optional Preset/Output Enable

The PR/OE pin provides the user with the option of either using that pin to control the Tri-state output buffers of the Output Registers, or have that pin to asynchronously preset all registers to High. The purpose of the preset function is to provide the system a way to set the PLS168 to a known state, all Highs. The output enable function are sometimes used where the state machine is connected to a bus which is shared by other output circuits. It is also used during power-up sequence to keep the PLS168 from sending power glitches to other circuits which it drives. By programming the PR/OE pin to control the Tri-state output buffers, the preset function is permanently disabled. By programming the PR/OE pin to control the asynchronous preset of the registers, the output buffers are permanently enabled. While using the preset function to asynchronously preset the register, if a rising edge of the clock occurs while the preset input is High, the registers will remain preset. Normal flip-flop operation will resume only after the preset input is Low and the rising edge of the next clock. Setting the registers to a predefined pattern other than all Highs may be accomplished by using a dedicated p-term, which is activated by an input pin which will also inhibit all other p-terms which are being used. The inhibiting of other p-terms eliminates the problem of undetermined state of an RS flip-flop caused by having Highs on both R and S inputs.

Diagnostic Features

In debugging a state machine, sometimes it is necessary to know what is the content of the state register. The buried State Register may be read by applying +10V on I_0, which will cause the contents of register bits P_4 to P_5, P_6 to P_9 to be displayed on output pins F_2 to F_3 and P_0 and P_3 respectively. While the device can handle the +10V on pin I_0, prolonged and continuous use will cause the chip to heat up since more power is being dissipated at +10V. To facilitate more expedient functional tests, synchronous preset vectors as described above may be used to set the State Register to different states without having to go through the entire sequence.

Timing Requirements

Since the PLS168 is intended to be a synchronous finite state machine, the inputs are expected to be synchronous to the clock and set-up and hold time requirements are expected to be met. In general, the set-up time requirement is measured at its worst case as having the entire AND-array connected to the OR-term being measured and there is only one active AND-term to drive the entire line. The set-up time decreases from there as less p-terms are used. This is due to the capacitance of the unused AND-terms being removed from the line. Figure 8a shows the typical set-up time requirement of a PLS168A device. Figure 8b shows the normalized set-up time as a percentage of the worst case, which is with 48 terms connected. In a typical state machine design, some flip-flops will change states more frequently than others. Those that change more frequently will have more p-term loading on its OR gates than those that change states less frequently. The different loadings on the OR-terms cause different delay on the inputs of the flip-flops as shown in Figure 9. If an input fails to meet the set-up time specification, it is possible that the resultant of the input change gets to one set of flip-flops before the rising edge of the clock while it gets to other flip-flops during or after the clock's rising edge. The result is that some flip-flops have changed states and some have not, or some get into metastable condition as shown in Figure 10. The state machine is now either out of sequence or is in an undefined state. This problem often occurs with asynchronous inputs which is generated totally independent of the clock on the system. A common remedy for the problem of asynchronous inputs is to use latches or flip-flops to catch the input and then synchronously feed it to the state machine. This minimizes the problem with the different propagation delays due to different p-term loading. But there is still a finite probability that the external latches or flip-flops will get into metastable condition, which may be propagated into the state machine. Nevertheless, the window for the flip-flops in state machine to get into undefined states or metastable condition is narrowed by a great extent.

PLS168/168A Primer

AN23

APPENDIX A

INTRODUCTION TO STATE MACHINE

A state machine is a synchronous sequential circuit which interprets inputs and generates outputs in accordance with a predetermined logic sequence. It is analogous to running a computer program with a computer. The state machine, with its sequence coded in hardware, can run much faster than a computer running the sequence in software. Therefore, it is often used in controller applications where speed is important.

Generally, state machines may be classified as Mealy or Moore machines as shown in Figures 1a and 1b. The fundamental difference of the two types are: the output of a Moore machine is a dependent of only the state of the memory elements whereas the output of a Mealy machine is a dependent of both the state of the memory elements and the inputs to the state machine. The figures also show graphic representations of the logic sequence in the form of state diagram in which the bubbles represent state vectors, and the arrows represent transitions from present states to next states.


INPUTS
INPUT DECODER
MEMORY ELEMENTS
OUTPUT DECODER
OUTPUTS
STa
OUTa
INa
STb
OUTb
STa IS PRESENT STATE
OUTa IS OUTPUT VECTOR
INa IS INPUT VECTOR
STb IS NEXT STATE
OUTb IS OUTPUT VECTOR
AF02220S

Appendix A-1. Moore Machine Model


INPUTS
INPUT DECODER
MEMORY ELEMENTS
OUTPUT DECODER
OUTPUTS
STa
INa/OUTa
STb
STa IS PRESENT STATE
INa IS INPUT VECTOR
OUTa IS OUTPUT VECTOR
STb IS NEXT STATE
AF02230S

Appendix A-2. Mealy Machine Model

APPENDIX B

LOGIC PROGRAMMING

The FPLS can be programmed by means of Logic programming equipment.

With Logic programming, the AND/OR gate input connections necessary to implement the desired logic function are coded directly from the State Diagram using the Program Table on the following page.

In this table, the logic state or action of control variables C, I, P, N, and F, associated with each Transition Term T_n, is assigned a symbol which results in the proper fusing pattern of corresponding link pairs, defined as follows:

PRESET/$\overline{\text{OE}}$ OPTION – (P/E)


PR/$\overline{\text{OE}}$
P
E = 1
LS01810S

OPTION	CODE
PRESET	H


PR/$\overline{\text{OE}}$
P = 1
E
LS01820S

OPTION	CODE
$\overline{\text{OE}}$	L

PROGRAMMING:

The PLS168A has a power-up preset feature. This feature insures that the device will power-up in a known state with all register elements (state and output register) at a logic high (H). When programming the device it is important to realize this is the initial state of the device. You *must* provide a next state jump if you do not wish to use all highs (H) as the present state.

"AND" ARRAY – (I), (P)


I,P
i,p
$\overline{\text{i,p}}$
T_n
LS01850S

STATE	CODE
INACTIVE^{1,2}	O


I,P
i,p
$\overline{\text{i,p}}$
T_n
LS01860S

STATE	CODE
I, P	H


I,P
i,p
$\overline{\text{i,p}}$
T_n
LS01830S

STATE	CODE
$\overline{\text{I}}$, $\overline{\text{P}}$	L


I,P
i,p
$\overline{\text{i,p}}$
T_n
LS01840S

STATE	CODE
DON'T CARE	–

"OR" ARRAY – (N), (F)


T_n
n,f
$\overline{\text{n,f}}$
S
R
Q
LS01890S

ACTION	CODE
INACTIVE^{1,3}	O


T_n
n,f
$\overline{\text{n,f}}$
S
R
Q
LS01900S

ACTION	CODE
SET	H


T_n
n,f
$\overline{\text{n,f}}$
S
R
Q
LS01870S

ACTION	CODE
RESET	L


T_n
n,f
$\overline{\text{n,f}}$
S
R
Q
LS01880S

ACTION	CODE
NO CHANGE	–

"COMPLEMENT" ARRAY – (C)


$\overline{\text{c}}$
c
T_n
LS01930S

ACTION	CODE
INACTIVE^{1,4}	O


$\overline{\text{c}}$
c
T_n
LS01940S

ACTION	CODE
GENERATE	A


$\overline{\text{c}}$
c
T_n
LS01910S

ACTION	CODE
PROPAGATE	•


$\overline{\text{c}}$
c
T_n
LS01920S

ACTION	CODE
TRANSPARENT	–

NOTES:

1. This is the initial unprogrammed state of all link pairs. It is normally associated with all unused (inactive) AND gates T_n.
2. Any gate T_n will be unconditionally inhibited if any one of its I or P link pairs is left intact.
3. To prevent simultaneous Set and Reset flip-flop commands, this state is not allowed for N and F link pairs coupled to active gates T_n (see flip-flop truth tables).
4. To prevent oscillations, this state is not allowed for C link pairs coupled to active gates T_n.

Signetics

AN24

PLS173 as a 10-Bit Comparator, 74LS460

Application Note

Application Specific Products

DESCRIPTION

The PLS173 is a 24-pin PLA device which has 10 bidirectional outputs and 12 dedicated inputs. The output of the device is the sum of products of the inputs. The polarity of each output may be individually programmed as Active-High or Active-Low. A logic diagram of the device is shown in Appendix A. A 10-bit comparator similar to the 74LS460 compares two 10-bit data inputs to establish if EQUIVALENCE or NOT EQUIVALENCE exists. The output has True and Complement comparison status outputs. The logic diagram of the comparator is shown in Figure 1.

The truth table is as shown in Table 1 where vectors a and b are 10-bit inputs to A9 to A0 and B9 to B0. If the input to A9-A0 is bit-to-bit equivalent to the input to B9-B0, the two input vectors are considered EQUIVALENT, and output EQ goes High and NE goes Low. If the two input vectors are not bit-to-bit equivalent, then EQ goes Low and NE goes High. The circuit is implemented with AMAZE as shown in Figures 2a, 2b and 2c. The result of logic simulation of the circuit is shown in Figure 2d.

Notice that on the OR side of the program table in Figure 5, all the fuses in the OR-term are intact, which means that all the AND-terms are still connected to all the OR-terms. This feature provides for future modification. But if all the unused AND-terms are deleted, the device will run faster. There are also many unused AND-terms which will provide for future modification. But if they are deleted (both on the AND and OR side), it will amount to about 450μA per term power saving. Figure 3 is the program table with all unused terms deleted.

Table 1. Function Table

$A_9 - A_0$	$B_9 - B_0$	EQ	NE
a	a	H	L
b	b	H	L
a	b	L	H
b	a	L	H



Figure 1. Logical Equivalent Circuit of 10-Bit Comparator

```
 ******************** AN24_173 ********************
###################### P I N   L I S T ######################

   LABEL        ** FNC **PIN --------- PIN** FNC **     LABEL
A0              ** I   **  1-|         |-24 ** +5V **VCC
B0              ** I   **  2-|         |-23 ** I   **B9
A1              ** I   **  3-|         |-22 ** I   **A9
B1              ** I   **  4-|    8    |-21 ** I   **B8
A2              ** I   **  5-|    2    |-20 ** I   **A8
B2              ** I   **  6-|    S    |-19 ** O   **NE
A3              ** I   **  7-|    1    |-18 ** /O  **EQ
B3              ** I   **  8-|    7    |-17 ** I   **B7
A4              ** I   **  9-|    3    |-16 ** I   **A7
B4              ** I   ** 10-|         |-15 ** I   **B6
A5              ** I   ** 11-|         |-14 ** I   **A6
GND             ** OV  ** 12-|         |-13 ** I   **B5
                              ---------
```

TB01770S

a. Pin List of 10-Bit Comparator

Figure 2

PLS173 as a 10-Bit Comparator, 74LS460

AN24

```
 ********************* AN24_173 *********************
@DEVICE TYPE
82S173
@DRAWING
................... 10-BIT COMPARATOR USING PLS173
@REVISION
................... REV-0
@DATE
................... OCT-14-85
@SYMBOL
................... AN24_173
@COMPANY
................... SIGNETICS
@NAME
................... DAVID WONG
@DESCRIPTION
This circuit compares two 10-bit inputs. If they are bit-to-bit equivalent,
outputs EQ goes HIGH and NE goes LOW. If the inputs are not bit-to-bit equiv-
alent to each other, outputs EQ goes LOW and NE goes HIGH.
@COMMON PRODUCT TERM

TO  =  A0 * /B0 ;
T1  = /A0 *  B0 ;
T2  =  A1 * /B1 ;
T3  = /A1 *  B1 ;
T4  =  A2 * /B2 ;
T5  = /A2 *  B2 ;
T6  =  A3 * /B3 ;
T7  = /A3 *  B3 ;
T8  =  A4 * /B4 ;
T9  = /A4 *  B4 ;
T10 =  A5 * /B5 ;
T11 = /A5 *  B5 ;
T12 = /A6 *  B6 ;
T13 =  A6 * /B6 ;
T14 =  A7 * /B7 ;
T15 = /A7 *  B7 ;
T16 =  A8 * /B8 ;
T17 = /A8 *  B8 ;
T18 =  A9 * /B9 ;
T19 = /A9 *  B9 ;

@I/O DIRECTION
@OUTPUT POLARITY
@LOGIC EQUATION

EQ = /( TO + T1 + T2 + T3 + T4 + T5 + T6 + T7 + T8 + T9 +
        T10 + T11 + T12 + T13 + T14 + T15 + T16 + T17 + T18 + T19 ) ;

NE =    TO + T1 + T2 + T3 + T4 + T5 + T6 + T7 + T8 + T9 +
        T10 + T11 + T12 + T13 + T14 + T15 + T16 + T17 + T18 + T19 ;
```

TB01780S

b. Boolean Equations of 10-Bit Comparator

Figure 2 (Continued)

```
 ******************** AN24_173 ********************
Cust/Project  - .................. DAVID WONG
Date          - .................. OCT-14-85
Rev/I. D.     - .................. REV-0

82S173                                         !      POLARITY      !
---                                            ---------------------
 T !                                           !H:H:H:H:H:L:H:H:H:H!
 E !-----------------------------------------------------------------
 R !           I           !        B(i)       !        B(o)        !
 M !1 1 ------------------------------------------------------------
___!1_0_9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!
  0!- - - -,- - - -,- - L H!- -,- - - -,- - - -!A A,A A A A,A A A A!
  1!- - - -,- - - -,- - H L!- -,- - - -,- - - -!A A,A A A A,A A A A!
  2!- - - -,- - - -,L H - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
  3!- - - -,- - - -,H L - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
  4!- - - -,- - L H,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
  5!- - - -,- - H L,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
  6!- - - -,L H - -,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
  7!- - - -,H L - -,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
  8!- - L H,- - - -,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
  9!- - H L,- - - -,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
 10!L H - -,- - - -,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
 11!H L - -,- - - -,- - - -!- -,- - - -,- - - -!A A,A A A A,A A A A!
 12!- - - -,- - - -,- - - -!- -,- - - -,- - H L!A A,A A A A,A A A A!
 13!- - - -,- - - -,- - - -!- -,- - - -,- - L H!A A,A A A A,A A A A!
 14!- - - -,- - - -,- - - -!- -,- - - -,L H - -!A A,A A A A,A A A A!
 15!- - - -,- - - -,- - - -!- -,- - - -,H L - -!A A,A A A A,A A A A!
 16!- - - -,- - - -,- - - -!- -,L H - -,- - - -!A A,A A A A,A A A A!
 17!- - - -,- - - -,- - - -!- -,H L - -,- - - -!A A,A A A A,A A A A!
 18!- - - -,- - - -,- - - -!L H,- - - -,- - - -!A A,A A A A,A A A A!
 19!- - - -,- - - -,- - - -!H L,- - - -,- - - -!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A.A A A A,A A A A!
 23!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .
 D8!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .
 D7!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .
 D6!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .
 D5!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
 D4!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
 D3!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .
 D2!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .
 D1!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .
 D0!0 0 0 0,0 0 0 0.0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .

    B A B A B A B A B A B A B A B A N E B A B A B A B A N E B A B A
    5 5 4 4 3 3 2 2 1 1 0 0 9 9 8 8 E 0 7 7 6 6 9 9 8 8 E 0 7 7 6 6
```

TB01790S

c. Program Table of 10-Bit Comparator After Assembly of Boolean Equation File

Figure 2 (Continued)

```
82S173    A:AN24_173.STD
" AMAZE FILE ID: AN24_173
" LOGIC SIMULATION OF 10-BIT COMPARATOR
"
" <==INPUTS==> <=B(I/O)=>   TRACE TERMS
" 11
" 109876543210 9876543210
"
  000000000000 0000LH0000 ;
  010000000000 0000HL0000 ;
  100000000000 0000HL0000 ;
  110000000000 0000LH0000 ;
  000100000000 0000HL0000 ;
  001000000000 0000HL0000 ;
  001100000000 0000LH0000 ;
  000001000000 0000HL0000 ;
  000010000000 0000HL0000 ;
  000011000000 0000LH0000 ;
  000000010000 0000HL0000 ;
  000000100000 0000HL0000 ;
  000000110000 0000LH0000 ;
  000000000100 0000HL0000 ;
  000000001000 0000HL0000 ;
  000000001100 0000LH0000 ;
  000000000001 0000HL0000 ;
  000000000010 0000HL0000 ;
  000000000011 0000LH0000 ;
  000000000000 0100HL0000 ;
  000000000000 1000HL0000 ;
  000000000000 1100LH0000 ;
  000000000000 0001HL0000 ;
  000000000000 0010HL0000 ;
  000000000000 0011LH0000 ;
  000000000000 0000HL0100 ;
  000000000000 0000HL1000 ;
  000000000000 0000LH1100 ;
  000000000000 0000HL0001 ;
  000000000000 0000HL0010 ;
  000000000000 0000LH0011 ;
"
" ------------ ----------   I/O CONTROL LINES
"              IIIIOOIIII   DESIGNATED I/O USAGE
"              IIIIOOIIII   ACTUAL I/O USAGE
"
" PINLIST...
" 13 11 10 09 08 07 06 05 04 03 02 01
" 23 22 21 20 19 18 17 16 15 14 ;
```

TB01800S

d. Test Vectors Generated by AMAZE After Logic Simulation

Figure 2 (Continued)

PLS173 as a 10-Bit Comparator, 74LS460 AN24

```
 ******************** AN24_173 ********************
Cust/Project - .................. DAVID WONG
Date         - .................. OCT-14-85
Rev/I. D.    - .................. REV-0

82S173                                         !     POLARITY      !
---                                            ---------------------
 T !                                           !H:H:H:H:H:L:H:H:H:H!
 E !----------------------------------------------------------------
 R !           I           !       B(i)        !       B(o)        !
 M !1 1 ------------------------------------------------------------
___!1_0_9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!9_8_7_6_5_4_3_2_1_0!
  0!- - - -,- - - -,- - L H!- -,- - - -,- - - -!. .,. . A A,. . . .!
  1!- - - -,- - - -,- - H L!- -,- - - -,- - - -!. .,. . A A,. . . .!
  2!- - - -,- - - -,L H - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
  3!- - - -,- - - -,H L - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
  4!- - - -,- - L H,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
  5!- - - -,- - H L,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
  6!- - - -,L H - -,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
  7!- - - -,H L - -,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
  8!- - L H,- - - -,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
  9!- - H L,- - - -,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
 10!L H - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
 11!H L - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . A A,. . . .!
 12!- - - -,- - - -,- - - -!- -,- - - -,- - H L!. .,. . A A,. . . .!
 13!- - - -,- - - -,- - - -!- -,- - - -,- - L H!. .,. . A A,. . . .!
 14!- - - -,- - - -,- - - -!- -,- - - -,L H - -!. .,. . A A,. . . .!
 15!- - - -,- - - -,- - - -!- -,- - - -,H L - -!. .,. . A A,. . . .!
 16!- - - -,- - - -,- - - -!- -,L H - -,- - - -!. .,. . A A,. . . .!
 17!- - - -,- - - -,- - - -!- -,H L - -,- - - -!. .,. . A A,. . . .!
 18!- - - -,- - - -,- - - -!L H,- - - -,- - - -!. .,. . A A,. . . .!
 19!- - - -,- - - -,- - - -!H L,- - - -,- - - -!. .,. . A A,. . . .!
 20!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 21!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 22!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 23!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 24!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 25!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 26!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 27!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 28!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 29!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 30!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 31!- - - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,. . . .!
 D9!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D8!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D7!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D6!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D5!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D4!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D3!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D2!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D1!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D0!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .

    B A B A B A B A B A B A B A B A N E B A B A B A B A N E B A B A
    5 5 4 4 3 3 2 2 1 1 0 0 9 9 8 8 E Q 7 7 6 6 9 9 8 8 E Q 7 7 6 6
```

TB01810S

Figure 3. Program Table of 10-Bit Comparator With All Unused Terms Deleted

APPENDIX A

FPLA LOGIC DIAGRAM FOR PLS173


(LOGIC TERMS—P)
(CONTROL TERMS)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
I_8 9
I_9 10
I_{10} 11
I_{11} 13
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
B_9
D_9 D_8 D_7 D_6 D_5 D_4 D_3 D_2 D_1 D_0
S_9 X_9
S_8 X_8
S_7 X_7
S_6 X_6
S_5 X_5
S_4 X_4
S_3 X_3
S_2 X_2
S_1 X_1
S_0 X_0
23 B_9
22 B_8
21 B_7
20 B_6
19 B_5
18 B_4
17 B_3
16 B_2
15 B_1
14 B_0
31 • • • • • • 24
23 • • • • • • 16
15 • • • • • • 8
7 • • • • • • 0
TB00941S

NOTES:

1. All programmed "AND" gate locations are pulled to logic "1".
2. All programmed "OR" gate locations are pulled to logic "0".
3. Programmable connection.

Signetics

AN25
A Simple Entry/Exit Metering Device

Application Note

Application Specific Products

DESCRIPTION

The following is the implementation of a counter/controller using a PLS157. This system counts and controls the number of entries to a certain media. For example, it can be used as a parking-lot controller to keep track of the number of cars entering a parking lot, and restricting any entries when the parking lot is full.

The design utilizes the six registers, six bi-directional I/O lines and the general architecture of the PLS157. In this design, the user can set the maximum number of entries using external switches. Since the six registers in the device are used as a six-bit counter, the maximum number that can be set is 2^6. However, the design can be cascaded to increase the number of entries.

SYSTEM OPERATION

The basic system configuration is shown in Figure 1. As can be seen from this figure, the system can be expanded indefinitely. All the devices in cascade are identical to each other. Whenever there is a need for expanding the maximum number of counts, a device can be programmed identical to the device(s) already in the system and added in cascade.

There are external switches connected to the bi-directional inputs of the flip-flops. The user sets the maximum count in binary with the switches and loads the value into the registers. If the maximum count necessary exceeds the number available in one device, then another device is cascaded to the existing device. For example, in a system with two devices, the maximum available increases to 2^{12} or 4096.

When the maximum count is set, the control circuitry is used to keep track of the number of entries and exits. In the case of a parking lot, a pressure sensor can be used at the entrance and exit to generate a pulse which triggers the control circuitry. An alternative could be light beam sensors to generate the necessary pulses.

The operation of the system is such that each entry decreases the maximum count stored in the registers by one. When the count is zero, it means that the media is full and the control circuitry generates a signal to disable any further entries to the system. On the other hand, each exit increases the count by one. Since it is assumed that the media is empty when the maximum count is set, it is, therefore, impossible to physically count past the maximum set number. This is due to the fact that there cannot be more exits from the system than the actual number of objects residing in the system. If there are objects in the system when the maximum number is set, these objects should also be taken into consideration when setting the maximum count.



Figure 1. System Configuration



Figure 2. /ENAB_CTRL Output Configuration

CONTROL SIGNALS

The following is the explanation of the control signals shown in Figure 1.

The /ENTRY and /EXIT inputs signify an entrance or exit to or from the respective media and are triggered from the sensors at the entrance and exit. Each entry causes a count-down from the maximum set number until all the flip-flops are low. This means that the system is full and the count-down should be disabled.

A Simple Entry/Exit Metering Device AN25


CLK
CK
/FULL_N-1
/LOAD
/ENAB_DN
/ENTRY
/EXIT
/ALLHIGH_N-1
/ENAB_CTRL
EXOR
GND
I
/B
O
Vcc
/FULL_N
F5
F4
F3
F2
F1
F0
/ALL HIGH_N
N/C
/O
O
/OE
CD07390S

Figure 3. Single Device Configuration

When all the flip-flops are low, the /FULL_N signal which is an Active-Low output is activated. The count-down is enabled by the /ENAB_DN input, which is connected externally to the /ENAB_CTRL line. The /ENAB_CTRL is a Tri-state output which is controlled by the /FULL_N signal. When all the flip-flops are low, the /FULL_N signal deactivates the /ENAB_CTRL output as shown in Figure 2.

All of the /ENAB_CTRL outputs are connected to the /ENAB_CTRL bus as shown in Figure 1. When the media is full, all the /ENAB_CTRL signals are deactivated which cause the count-down to be disabled.

An exit causes a count up. As mentioned before, the total number of exits from the system cannot exceed the total number of entries.

The /ALLHIGH_N signal is an Active-Low output which becomes low when all the flip-flops are high. Figure 3 shows the configuration of a single device.

The /FULL_N and /ALLHIGH_N signals are used to activate the /FULL_N-1 and /ALLHIGH_N-1 of a cascaded device. These signals will be explained in detail shortly. The /FULL_N signal is also used to trigger any control circuitry used to restrict any further entries to the system. In the case of a parking lot, the /FULL_N can be used to activate a light or close the entrance gate.

The EXOR output is used to clock the system and is externally connected to the CLK input of the device. The EXOR generates a clock pulse when either an exit or entry take place. This restricts the system from counting if a simultaneous entry and exit takes place.

To set the maximum count, the user can use switches connected to inputs F0-F5 of the device(s). Then by bringing the /LOAD input low and triggering the /ENTRY or /EXIT inputs to generate a clock pulse, the data from these switches can be latched into the registers.

CASCADE DEVICE EXAMPLE

This is an example of two cascaded devices. Figure 4 shows the cascade configuration of devices 'A' and 'B'. For the sake of simplicity, it is assumed that each device contains only two registers. This assumption gives clarity to the explanation, and can be extended to cover the six registers contained in each device.

As an example, it is assumed that the maximum count to be implemented in this example is 1001 in binary. In other words, the maximum number of entries is set to be 'ten'. F0A and F1A are the registers in device A, and F0B and F1B are the registers in device B. 10 is the input sequence to device B and 01 is input sequence to device A.

The count-up and count-down sequences are shown in Table 1.


CLK
CK
/FULL_N-1
/LOAD
/ENAB_DN
/ENTRY
/EXIT
/ALLHIGH_N-1
/ENAB_CTRL
EXOR
GND
I
/B
O
Vcc
/FULL_N
F5
F4
F3
F2
F1
F0
TO SWITCH
/ALLHIGH_N
N/C
/O
O
/OE
DEV. A
CLK
CK
/FULL_N-1
/LOAD
/ENAB_DN
/ENTRY
/EXIT
/ALLHIGH_N-1
/ENAB_CTRL
EXOR
GND
Vcc
/FULL_N
F5
F4
F3
F2
F1
F0
TO SWITCH
/ALLHIGH_N
N/C
DEV. B
Vcc
TC03350S

Figure 4. Cascaded Configuration

Table 1. An Up/Down Count Sequence Example

DEV. B		DEV. A	
F0B	F1B	F0A	F1A
1	0	0	1
1	0	0	0
0	1	1	1
0	1	1	0
0	1	0	1
0	1	0	0
0	0	1	1
0	0	1	0
0	0	0	1
0	0	0	0

COUNT DOWN

DEV. B		DEV. A	
F0B	F1B	F0A	F1A
0	0	0	0
0	0	0	1
0	0	1	0
0	0	1	1
0	1	0	0
0	1	0	1
0	1	1	0
0	1	1	1
1	0	0	0
1	0	0	1

COUNT UP

TB02080S

Table 2. Count Sequence

NO.	F5	F4	F3	F2	F1	F0
0	0	0	0	0	0	0
1	0	0	0	0	0	1
2	0	0	0	0	1	0
3	0	0	0	0	1	1
4	0	0	0	1	0	0
	⋮	⋮	⋮	⋮	⋮	⋮
7	0	0	0	1	1	1
8	0	0	1	0	0	0
	⋮	⋮	⋮	⋮	⋮	⋮
15	0	0	1	1	1	1
16	0	1	0	0	0	0
	⋮	⋮	⋮	⋮	⋮	⋮
31	0	1	1	1	1	1
32	1	0	0	0	0	0
	⋮	⋮	⋮	⋮	⋮	⋮
62	1	1	1	1	1	0
63	1	1	1	1	1	1
0	0	0	0	0	0	0

TB02090S

A Simple Entry/Exit Metering Device

AN25

In the 1001 example, F0B is the MSB (Most Significant Bit) and F1A is the LSB (Least Significant Bit). As can be seen in Table 1, a count-down occurs in device 'B', when F0A and F1A are both low. When F0A and F1A are low, this means that the /FULL_N signal is active. The /FULL_N-1 input of device 'B' is connected to the FULL_N output of device 'A'. Therefore, a count down occurs in device 'B' only when the input to /FULL_N-1 goes low. In this manner, the count-down sequence in Table 1 can be implemented.

Similarly, for the count-up sequence, a count-up occurs in device 'B' only when both F0A and F1A are high. At this point, the /ALLHIGH_N signal becomes active. Therefore, a count-up occurs in device 'B' only when /ALLHIGH_N of device 'A' is active.

UP/DOWN COUNTERS

An up-down counter is implemented in each device to keep track of the number of entries and exits. To implement these counters the flip-flops are set in the toggle mode. Table 2 shows the count sequence.

The following conditions are true for the count-up sequence:

Table 3a

REGISTER	TRUE CONDITION FOR TOGGLE
F0	Unconditionally Toggle
F1	F0
F2	F0*F1
F3	F0*F1*F2
F4	F0*F1*F2*F3
F5	F0*F1*F2*F3*F4

Similarly, for the count-down sequence:

Table 3b

REGISTER	TRUE CONDITION FOR TOGGLE
F0	Unconditionally Toggle
F1	/F0
F2	/F0*/F1
F3	/F0*/F1*/F2*
F4	/F0*/F1*/F2*/F3
F5	/F0*/F1*/F2*/F3*/F4*



Figure 5. CNT-UP and CNT-DN Signals



Figure 6. System Clock



```
File Name : METER
Date : 10/31/1985
Time : 14:35:31

###################### P I N   L I S T ######################

   LABEL     ** FNC **PIN ---------- PIN** FNC **    LABEL
CLK          ** CK  **  1-¦          ¦-20 ** +5V **VCC
/FULL_N-1    ** I   **  2-¦          ¦-19 ** /O  **/FULL_N
/LOAD        ** I   **  3-¦          ¦-18 ** O   **F5
/ENAB_DN     ** I   **  4-¦    P     ¦-17 ** O   **F4
/ENTRY       ** I   **  5-¦    L     ¦-16 ** O   **F3
/EXIT        ** I   **  6-¦    X     ¦-15 ** O   **F2
/ALLHIGH_N-1** I    **  7-¦    1     ¦-14 ** O   **F1
/ENAB_CTRL   ** /B  **  8-¦    5     ¦-13 ** O   **F0
EXOR         ** O   **  9-¦    7     ¦-12 ** /O  **/ALLHIGH_N
GND          ** OV  ** 10-¦          ¦-11 ** /OE **N/C
                          ----------
```

TB01920S

Figure 7

CONTROL SIGNALS

The following are the control signals used to control the operation of the devices:

The logic diagram for generating the 'CNT-UP' and 'CNT-DN' signals is shown in Figure 5.

As can be seen from this figure, a count-up occurs when the following is true:

a) An exit takes place and,
b) the system is not loading in any data and,
c) the previous stage has generated the /ALLHIGH_N-1 signal.

A count-down occurs when:

a) An entry takes place and,
b) the system is not loading in any data and,
c) the previous stage has generated the /FULL_N-1 signal and,
d) the media is not full, thus /ENAB_DN signal is low.

The system clock is generated using the CNT-UP and CNT-DN signals. The system is to be clocked only when an exit or entry takes place. In order to prevent the system from being clocked when a simultaneous entry and exit takes place, these two signals are exclusive-OR'ed (Figure 6).

The equations shown in (Tables 3a and 3b) are generated using Signetics AMAZE software (Figures 7 and 8). The resulting program table is shown in Table 4.

```
@DEVICE TYPE
PLX157
@DRAWING
@REVISION
@DATE
10-31-85

@SYMBOL
ENTR/EXIT METER

@COMPANY
SIGNETICS

@NAME
ALI GHEISSARI

@DESCRIPTION
***********************************************************************
* The following is the implementation of a Entry/Exit Meter.    A     *
* application of this device would be in controlling the number of    *
* entries to a certain media. An example is a parking lot controller  *
* for restricting the number of cars entering the lot.                *
* The maximum number is programmable and the design can be cacaded to *
* Accomodate an increase in the number of entries.                    *
* The system counts down from the maximum set number to zero          *
* The number of exits cannot exceed the maximum count set by the      *
* external switches,therefore the upper limit on the count will never *
* be exceeded.                                                        *
***********************************************************************



@COMMON PRODUCT TERM
UPCNT = /LOAD * EXIT * ALLHIGH_N-1;      "UPCNT is the signal generated for      "
                                         "activating the count-up from the ENTRY "
                                         "input and the ALLHIGH signal from any  "
                                         "connected devices                      "

DNCNT = /LOAD * ENTRY * FULL_N-1;        "DNCNT is similar to UPCNT except it is "
                                         "generated for the count down           "


ALL-HIGH = /F0 * /F1 * /F2 * /F3 * /F4 * /F5;
ALL-LOW   = F0 * F1 * F2 * F3 * F4 * F5;

@COMPLEMENT ARRAY
/C = /(0);

@I/O DIRECTION
D0 = 0;                           "/EXIT is an input                          "
D1 = 0;                           "ALLHIGH_N-1 is an input                    "
D2 = /FULL_N;                     "When maximum count is reached /FULL_N      "
                                  "disables /ENAB-CTRL which in turn disables "
                                  "the device(s) from counting down           "
                                  "/ENAB-CTRL is connected to the ENAB_DN of the "
                                  " device(s)                                 "

D3 = 1;                           "EXOR is an output                          "
D4 = 1;                           "/ALLHIGH_N is an output                    "
D5 = 1;                           "/FULL_N is an output                       "
```

TB01930S

Figure 8

```
@OUTPUT POLARITY

X2 = 0;                             "/ENAB_CTRL is active low                      "
X3 = 1;                             "EXOR is active high                           "
X4 = 0;                             "/ALLHIGH_N is active low                      "
X5 = 0;                             "/FULL_N is active low                         "

@FLIP FLOP CONTROL
FC = 1;                              "All flip flops are J-K                       "

@OUTPUT ENABLE
"NOT USED"

@REGISTER LOAD
LA = LOAD;                           "Load the registers with the number set       "
LB = LOAD;                           "by the input switches                        "

@ASYNCHRONOUS PRESET/RESET
"NOT USED"

@FLIP FLOP MODE
"NOT USED"

@LOGIC EQUATION
EXOR = UPCNT*/DNCNT + DNCNT*/UPCNT;  "Output count pulse only if there is not  "
                                     "a simultaneous entry and exit            "
/FULL_N = /( ALL-LOW * /LOAD);       "indicates when maximum count is reached  "
/ALLHIGH_N = /( ALL-HIGH * /LOAD);   "shows when empty                         "
/ENAB_CTRL = /(1);                   "puts low on the ENAB_CTRL bus            "

"The following is the implementation of the counter together with the          "
"necessary logic."

/F0: T = (ENAB_DN * DNCNT) + UPCNT;


/F1: T = (ENAB_DN * F0 * DNCNT) + (/F0 * UPCNT);


/F2: T = (ENAB_DN * F0 * F1 * DNCNT) + (/F0 * /F1 * UPCNT);


/F3: T = (ENAB_DN * F0 * F1 * F2 * DNCNT) +
         (/F0 * /F1 * /F2 * UPCNT);


/F4: T = (ENAB_DN * F0 * F1 * F2 * F3 * DNCNT) +
         (/F0 * /F1 * /F2 * /F3 * UPCNT);


/F5: T = (ENAB_DN * F0 * F1 * F2 * F3 * F4 * DNCNT) +
         (/F0 * /F1 * /F2 * /F3 * /F4 * UPCNT);
```

TB01940S

Figure 8 (Continued)

Table 4. Program Table for Entry/Exit Meter

```
Cust/Project - ALI GHEISSARI
Date         - 10-31-85
Rev/I. D.    -

PLx157                   ! F/F TYPE  !EB !  EA   !   ! POLARITY  !
.....                    !___________!___!_______!   !___________!
 T !                    .!A:A:A:A:A:A!O  !   O   !   !L:L:H:L:L:L!
 E !--------------------------------------------------------------
 R ! !   I   !   B(i)    !   Q(p)    !   Q(n)    !P!R!   B(o)    !
 M !C!-------------------------------------------!A!A!-----------
___!_!3_2_1_0!5_4_3_2_1_0!5_4_3_2_1_0!5_4_3_2_1_0!_!_!5_4_3_2_1_0!
  0!-!- - H H!- -,- - L L!- -,- - - -!- -,- - - -!.!.!. .,A . A A!
  1!-!H - H -!- -,- - L L!- -,- - - -!- -,- - - -!.!.!. .,A . A A!
  2!-!L - H L!- -,- - - H!- -,- - - -!- -,- - - -!.!.!. .,A . A A!
  3!-!L - H L!- -,- - H -!- -,- - - -!- -,- - - -!.!.!. .,A . A A!
  4!-!- - H -!- -,- - - -!L L,L L L L!- -,- - - -!.!.!A .,. . A A!
  5!-!- - H -!- -,- - - -!H H,H H H H!- -,- - - -!.!.!. A,. . A A!
  6!-!- - - -!- -,- - - -!- -,- - - -!- -,- - - -!.!.!. .,. A A A!
  7!-!L L H L!- -,- - - -!- -,- - - -!- -,- - - 0!.!.!. .,. . A A!
  8!-!- - H -!- -,- - L L!- -,- - - -!- -,- - - 0!.!.!. .,. . A A!
  9!-!L L H L!- -,- - - -!- -,- - - L!- -,- - 0 -!.!.!. .,. . A A!
 10!-!- - H -!- -,- - L L!- -,- - - H!- -,- - 0 -!.!.!. .,. . A A!
 11!-!L L H L!- -,- - - -!- -,- - L L!- -,- 0 - -!.!.!. .,. . A A!
 12!-!- - H -!- -,- - L L!- -,- - H H!- -,- 0 - -!.!.!. .,. . A A!
 13!-!L L H L!- -,- - - -!- -,- L L L!- -,0 - - -!.!.!. .,. . A A!
 14!-!- - H -!- -,- - L L!- -,- H H H!- -,0 - - -!.!.!. .,. . A A!
 15!-!L L H L!- -,- - - -!- -,L L L L!- 0,- - - -!.!.!. .,. . A A!
 16!-!- - H -!- -,- - L L!- -,H H H H!- 0,- - - -!.!.!. .,. . A A!
 17!-!L L H L!- -,- - - -!- L,L L L L!0 -,- - - -!.!.!. .,. . A A!
 18!-!- - H -!- -,- - L L!- H,H H H H!0 -,- - - -!.!.!. .,. . A A!
 19!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 20!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 21!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A.A A A A!
 22!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 23!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A.A A A A!
 24!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A.A A A A!
 25!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 26!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 27!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A.A A A A!
 28!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 29!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 30!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 31!0!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!A!A!A A,A A A A!
 Fc!-!- - - -!- -,- - - -!- -,- - - -!                           .
 Pb!.!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!                           .
 Rb!.!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!                           .
 Lb!-!- - L -!- -,- - - -!- -,- - - -!                           .
 La!-!- - L -!- -,- - - -!- -,- - - -!                           .
 D5!-!- - - -!- -,- - - -!- -,- - - -!                           .
 D4!-!- - - -!- -,- - - -!- -,- - - -!                           .
 D3!-!- - - -!- -,- - - -!- -,- - - -!                           .
 D2!-!- - - -!H -,- - - -!- -,- - - -!                           .
 D1!.!0 0 0 0!0 0,0 0 0 0!0 0,0 0 0 0!                           .
 D0!.!0 0 0 0!0 0,0 0 0 0!0 0.0 0 0 0!                           .

      / / / / / E / / / / F F F F F F F F F F F F     / E / / / /
      F E E E L X E A F A 5 4 3 2 1 0 5 4 3 2 1 0     L X E A F A
      U N N X O O N L U L                             U O N L U L
      L A T I A R A L L L                             A R A L L L
      L B R T D   B H L H                             D   B H L H
        - Y         I   I                                   I   I
      N D         C G N G                                 C G N G
      - N         T H   H                                 T H   H
      1           R _   _                                 R _
                  L N   N                                 L N   N
                        -                                       -
                        1                                       1
```

TB01950S

AN26
PLHS18P8A Primer

Application Note

Application Specific Products

FEATURES

- **100% functional replacement for all 20-pin PALs**
- **I/O propagation delay: 15ns (max)**
- **Security fuse lock**
- **10 inputs**
- **8 bidirectional I/O lines**
- **Tri-state outputs have programmable polarity**
- **Architecture: 8 groups of nine AND gates. Total of 72 product terms**
- **Software support on Signetics AMAZE**
- **Complete TTL compatibility**
- **Each bidirectional I/O has individually controllable output enable**

ARCHITECTURE

The PLHS18P8A is an oxide-isolated, bipolar field-programmable logic array. This device is configured as a decoding two-level AND-OR (sum of products) structure. The PLHS18P8A block diagram is shown in Figure 1. All the AND gates are linked to ten inputs ($I_0 - I_9$) and eight bidirectional I/O lines ($B_{(0)} - B_{(7)}$). These links can be made via the on-chip true/complement buffers. The 72 AND gates are configured in 8 groups which contain 9 AND gates each. In every group, eight AND gates are used for user-defined logic functions and the ninth AND gate is used as a tri-state output enable control. This gives the user capability to control the output enable by means of a product term. The outputs of the eight logical product terms are ORed together (see Figure 1). The output polarity of each OR gate is individually programmable via an Exclusive-OR gate. The user has a choice of Active-Low or Active-High on each of the eight outputs. Figure 2 shows the logic diagram of the PLHS18P8A.

HOW A DEVICE IS PROGRAMMED

There are three main programmable sections on the PLHS18P8A:

A. The AND array.

B. The output polarity.

C. The security fuse.

A. The AND array — The AND array fuses are back-to-back diode pairs which act as open connections in a virgin device. These open connections are configured as 'Don't Cares' (' – ') in an unprogrammed device. The open connections are pulled to a logic high ('1') (see Figure 3). Consequently, all unprogrammed AND locations are pulled to a logic high ('1') state. This means that in an unprogrammed device, all the product terms are active. During fusing, current is avalanched across individual diode pairs. This essentially short circuits the diode and provides a connection for the associated product term. Figure 3 shows how a typical connection is made to the AND array (see Appendix B for a description of the vertical fuses).

The inputs to the AND array consist of 10 dedicated inputs (I0 – I9) and 8 bidirectional I/Os (B(0) – B(7)). Initially, all these inputs are configured as 'Don't Cares' (' – '). These inputs can be connected to the AND array through an inverting or non-inverting buffer. The AND gate can be connected to the inverting buffer by programming the inverting fuse. Similarly, a connection can be made to the non-inverting buffer by programming the non-inverting fuse. Disabling an AND term is achieved by implementing a logical low ('0') on the output of the specified AND gate. At least one pair of fuses must be programmed for one input to disable the product term. When both fuses are programmed, both the inverting and non-inverting buffers are connected to the inputs of the AND gate. This will in turn create a logical Low ('0') on the output.

In each block of nine AND gates, one gate is used as an output enable control for the tri-state output. The remaining eight gates are connected to a fixed OR gate. Since in the unprogrammed state the outputs of all the AND gates are at logic High ('1'), the output of the OR gate also acquires a logic High state. Therefore the user is responsible for deactivating any unwanted product terms. This is done by creating a logic Low ('0') on the outputs of the unwanted product terms as previously explained. Moreover, the output buffer is always enabled since the product term controlling the tri-state output buffer also has a logic High state. If any of the bidirectional pins are to be defined as inputs, the product term controlling the specified bidirectional pin must be disabled. The bidirectional pin can also be configured as a dynamic I/O by defining the required logic for the output-enable-control product term.

B. The Output Polarity — In an unprogrammed device, all the output polarities are configured as inverting buffers. The outputs of the PLHS18P8A are configured as tri-state buffers. The two inputs of each Ex-OR gate are connected as follows: one input is connected to the output of the fixed OR gate. The second input is a connection to ground (logic low) through a fusible link. Figure 4 shows how an Ex-OR gate is used to define the output polarity.

As mentioned earlier, an unprogrammed fuse acts as an open connection which is pulled to a logic high. Therefore the output of the Ex-OR gate acts as an inverting buffer. When the fuse is programmed, there is a connection between ground (logic Low) and the input of the Ex-OR gate. This will cause the Ex-OR gate to act as a non-inverting buffer.

C. The Security Fuse — Programming equipment used to program the PLHS18P8A are capable of determining the logic pattern stored in this device (see Appendix A). The security fuse can be blown to disable the programmer from reading the pattern in a programmed device. This feature adds a measure of protection for proprietary designs.

The procedure for programming this fuse depends on the programmer manufacturer and is explained in the manufacturer's operations manual.

DESIGN TOOLS FOR THE PLHS18P8A

Many CAD tools such as Signetics' AMAZE software[1] are available to implement designs using the PLHS18P8A. The AMAZE software enables the user to enter the design in the form of Boolean equations or via the program table shown in Table 1. This program table is a one-to-one map of all the programmable links of Figure 2. The following explains the implementation of designs using the program table. Also, an example on using the Boolean Logic Entry program of the AMAZE software is given.

Using PTE (Program Table Entry) — Assume that Z is a typical logic function with the following equation:

Z = P0 + P1

Where P0 and P1 are product terms with the following equations:

P0 = A * /B * C

P1 = /A * B * /D

NOTE:

[1] Refer to Signetics Programmable Logic Data Manual for a complete description of the AMAZE programmable logic development software.


CONTROL AND TERM
8 LOGICAL AND TERMS
8
I/O
INPUTS
I0-I9
AND ARRAY
BD03120S

Figure 1. Block Diagram of the PLHS18P8A


INPUTS (0–35)
0
35
PRODUCT TERMS (0–71)
I0
1
0
8
I1
2
9
17
I2
3
18
26
I3
4
27
35
I4
5
36
44
I5
6
45
53
I6
7
54
62
I7
8
63
71
I8
9
19
B7
18
B6
17
B5
16
B4
15
B3
14
B2
13
B1
12
B0
11
I9
LD02620S

NOTES:

1. All unprogrammed or virgin "AND" gate locations are pulled to logic "1".
2. All unprogrammed or virgin "OR" gate locations are pulled to logic "1".
3. Programmable corrections.

Figure 2. Logic Diagram of the PLHS18P8A



a. Unprogrammed Connection   **b. Programmed. The Non-Inverting Buffer is Connected to the AND Gate**

Figure 3. How a Fuse is Programmed



	FUSE	P-TERM	OUTPUT	OUTPUT POLARITY
FUSE INTACT	1	0	1	
	1	1	0	
FUSE PROGRAMMED	0	0	0	
	0	1	1	

LD06010S

Figure 4. How the Output Polarity is Defined

The program table in Table 1 is used to implement this equation. Table 2 shows the implementation of the logic function using the PTE. The first group of AND terms is used to implement this function. B(7) is used for the output, I0, I1, and I2 as inputs.

- Term 0 is the direction control term. It is the tri-state output enable control term. Since Z is configured as an output, leaving Term 0 in its unprogrammed state causes the output to be unconditionally enabled.
- Term 1 is the P-term labeled P0, where A*/B*C is designated by HLH in columns I0, I1, and I2.
- Term 2 is the P-term labeled P1, where /A*B*/D is designated by LHL in columns I0, I1, and I2.
- Terms 3, 4, 5, 6, 7. At least one input (or all the inputs) *must be set to zero* to disconnect these terms from the OR gate.
- The output polarity for B(7) is H, and this is entered in the 'Polarity' section.

Using BLAST (Boolean Logic And State Transfer) — The BLAST module in AMAZE can be used to implement the above equation. Figures 5 and 6 show the pin list and logic equation format. Table 3 is the program table generated from these equations.

APPENDIX A

Programmers

The PLHS18P8A can be programmed by means of logic programming equipment. With Logic Programming, the AND/Ex-OR gate input connections necessary to implement the desired logic are coded directly from the logic equations using the program table shown in Table 1.

The symbols used in the program table correspond to the fusing pattern of the corresponding link pairs, defined in Figure 6.

To program the device, the address of every fuse to be programmed must be entered in the programmer. This is a tedious and error-prone method of implementing the required logic pattern. Using CAD software, such as Signetics' AMAZE software, enables users to go directly from program table or logic equations to a fuse plot. The fuse plot can be downloaded to a programmer through a serial port.

APPENDIX B

The vertical fuse is the latest in programmable logic technology. It combines reliability, low capacitance and testability in an incredibly small space.

The vertical fuse takes advantage of the properties of silicon and aluminum. The virgin fuse is a three-layer device: a shallow layer of N-type silicon on top, a layer of P-type silicon in the middle, and a layer of N-type silicon on the bottom. This forms a pair of PN diodes, back-to-back, which will not allow current to pass under normal circumstances.

There is a cap of aluminum on top of this structure. During programming, high current conditions (50 to 100 times what is seen during normal operation) is induced by avalanche breakdown of the reverse-biased diode. The aluminum will "spike" through the shallow N-type layer. Once the aluminum has spiked through, the top diode in the pair is shorted out. The whole vertical fuse will then look like a pure PN diode. Before programming, the fuse is an excellent blocking element, having current leakages in the order of nanoamps. After programming, the fuse is set as a small, well-defined diode.

QUALITY

Besides the AC and C parametrics, each and every fuse goes through three tests for forward characteristics, reverse characteristics, and programmability. Extensive on-chip test circuitry ensures full AC parametric testing before and after the part is programmed. This insures that the customer receives the highest possible fusing yield which is made possible by vertical fuses. Vertical fuses also offer the smallest and fastest array structure together with the highest reliability possible.

PLHS18P8A Primer

CUSTOMER NAME ________

PURCHASE ORDER # ________

SIGNETICS DEVICE # ________ CF (XXXX) ________

CUSTOMER SYMBOLIZED PART # ________

TOTAL NUMBER OF PARTS ________

PROGRAM TABLE # ________ REV ________ DATE ________

AND

INACTIVE	O	
I, B	H	I,B(I)
Ī, B̄	L	
DON'T CARE	—	

CONTROL

HIGH	H	(POL)
LOW	L	

Notes

1. The FPLA is shipped with all links open.
2. Unused I and B bits in the AND array exist as Don't Care (–) in the virgin state.
3. All p-terms are active until programmed otherwise.
4. Unused p-terms must be disabled or programmed with at least one pair of fuses.

																			POLARITY							
TERM	AND																		OR (FIXED)							
	I										B (I)								B (O)							
	9	8	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
0																			D							
1																			A							
2																			A							
3																			A							
4																			A							
5																			A							
6																			A							
7																			A							
8																			A							
9																				D						
10																				A						
11																				A						
12																				A						
13																				A						
14																				A						
15																				A						
16																				A						
17																				A						
18																					D					
19																					A					
20																					A					
21																					A					
22																					A					
23																					A					
24																					A					
25																					A					
26																					A					
27																						D				
28																						A				
29																						A				
30																						A				
31																						A				
32																						A				
33																						A				
34																						A				
35																						A				
36																							D			
37																							A			
38																							A			
39																							A			
40																							A			
41																							A			
42																							A			
43																							A			
44																							A			
45																								D		
46																								A		
47																								A		
48																								A		
49																								A		
50																								A		
51																								A		
52																								A		
53																								A		
54																									D	
55																									A	
56																									A	
57																									A	
58																									A	
59																									A	
60																									A	
61																									A	
62																									A	
63																										D
64																										A
65																										A
66																										A
67																										A
68																										A
69																										A
70																										A
71																										A
PIN	11	9	8	7	6	5	4	3	2	1	19	18	17	16	15	14	13	12	19	18	17	16	15	14	13	12
VARIABLE NAME																										

TB02020S

Table 1. Program Table

```
Cust/project  -PLHS18P8A  Primer
Date          -May 1986
Rev/I. D.     -
Comments:
Program Table for implementing
                  Z = P0 + P1
where:
                  P0 = A.(/B).C
                  P1 = (/A).B.(/D)
-----------------------------------------------------------
PLHS18P8                                 !    POLARITY    !
                VARIABLE
---               NAME                   ------------------
 T !                                     !L:L:L:L:L:L:L:L!
 E !-------------------------------------------------------
 R !              I |D|C|B|A|     B(i)   |Z|   B(o)       !
 M !-------------------------------------------------------
___!9_8_7_6_5_4_3_2_1_0!7_6_5_4_3_2_1_0!7_6_5_4_3_2_1_0!
  0!- -,- - - -,- - - -!- - - -,- - - -!D / / /,/ / / /!→ Tri-state always enable
  1!- -,- - - -,- H L H!- - - -,- - - -!A / / /,/ / / /!→ P0 = A*/B*C
  2!- -,- - - -,L - H L!- - - -,- - - -!A / / /,/ / / /!→ P1 = /A*B*/D
  3!- -,- - - -,- - - -!- - - -,- - - -!A / / /,/ / / /!
  4!- -,- - - -,- - - -!- - - -,- - - -!A / / /,/ / / /!
  5!- -,- - - -,- - - -!- - - -,- - - -!A / / /,/ / / /!
  6!- -,- - - -,- - - -!- - - -,- - - -!A / / /,/ / / /!
  7!- -,- - - -,- - - -!- - - -,- - - -!A / / /,/ / / /!
  8!- -,- - - -,- - - -!- - - -,- - - -!A / / /,/ / / /!
  9!- -,- - - -,- - - -!- - - -,- - - -!/ D / /,/ / / /!
 10!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 11!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 12!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 13!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 14!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 15!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 16!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 17!- -,- - - -,- - - -!- - - -,- - - -!/ A / /,/ / / /!
 18!- -,- - - -,- - - -!- - - -,- - - -!/ / D /,/ / / /!
 19!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 20!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 21!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 22!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 23!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 24!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 25!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 26!- -,- - - -,- - - -!- - - -,- - - -!/ / A /,/ / / /!
 27!- -,- - - -,- - - -!- - - -,- - - -!/ / / D,/ / / /!
 28!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 29!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 30!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 31!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 32!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 33!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 34!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 35!- -,- - - -,- - - -!- - - -,- - - -!/ / / A,/ / / /!
 36!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,D / / /!
 37!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 38!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 39!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 40!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 41!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 42!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 43!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 44!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,A / / /!
 45!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ D / /!
 46!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 47!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 48!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 49!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 50!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 51!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 52!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 53!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 54!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / D /!
 55!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 56!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 57!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 58!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 59!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 60!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 61!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 62!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 63!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / D!
 64!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 65!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 66!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 67!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 68!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 69!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 70!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 71!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
```

TB03071S

Table 2. Implementation of the Function "Z" Using PTE

PLHS18P8A Primer

AN26

```
File Name : 18PRIMER
Date : 5/22/1986
Time : 13:52:54

###################### P I N   L I S T ######################

   LABEL       ** FNC **PIN ---------- PIN** FNC **     LABEL
A              ** I   **  1-|    P    |-20 ** +5V **VCC
B              ** I   **  2-|    L    |-19 ** O   **Z
C              ** I   **  3-|    H    |-18 ** /O  **INVERT
D              ** I   **  4-|    S    |-17 ** I   **INPUT
N/C            ** I   **  5-|    1    |-16 ** B   **BIDIR
N/C            ** I   **  6-|    8    |-15 ** /B  **/BDIR
N/C            ** I   **  7-|    P    |-14 ** /B  **N/C
N/C            ** I   **  8-|    8    |-13 ** /B  **N/C
N/C            ** I   **  9-|    A    |-12 ** /B  **N/C
GND            ** OV  ** 10-|         |-11 ** I   **N/C
                             ----------
```

TB03051S

Figure 5

```
File Name : 18PRIMER
Date : 5/22/1986
Time : 13:53:59

@DEVICE TYPE
PLHS18P8A
@DRAWING
.............. PLHS18P8A PRIMER

@REVISION
.............. PLHS18P8A REV '-'

@DATE
.............. May 1986

@SYMBOL
.............. PLHS18P8A

@COMPANY
.............. SIGNETICS

@NAME
.............. Ali Gheissari

@DESCRIPTION

************************************************************************
*     This is an example of implementing equations for                 *
*     the PLHS18P8A using AMAZE                                        *
************************************************************************

@COMMON PRODUCT TERM
P0 = A * /B * C;        " P0 and P1 are used to declare common            "
P1 = /A * /B * /D;      " product terms.                                  "

@I/O DIRECTION
D7 = 1;                 " Defines B7 to be an output                      "
D6 = 1;                 " Defines B6 to be an output                      "
D5 = 0;                 " Defines B5 to be an input                       "
D4 = A;                 " B4 an output when A is true otherwise an input "
D3 = B;                 " B3 an output when B is true otherwise an input "

@OUTPUT POLARITY
X7 = 0;                 " Documents the output polarity as active high    "
X6 = 1;                 " Documents the output polarity as active high    "
X4 = 0;                 " Documents the output polarity as active high    "
X3 = 1;                 " Documents the output polarity as active high    "

@LOGIC EQUATION
                        "Examples of some simple equations                "
Z = P0 + P1;

INVERT = /( INPUT );

BIDIR = /BDIR * B ;

/BDIR = /( A * C * D * /Z * INVERT * INPUT * BIDIR );
```

TB03061S

Figure 6. Boolean Equation File

PLHS18P8A Primer



```
File Name : 18PRIMER
Date : 5/22/1986
Time : 13:56:15

Cust/Project - ............... Ali Gheissari
Date         - ............... May 1986
Rev/I. D.    - ............... PLHS18P8A REV '-'

PLHS18P8                               !   POLARITY    !

---                                    -----------------
 T !                                   !H:L:L:H:L:L:L:L!
 E !----------------------------------------------------
 R !         I         !      B(i)     !      B(o)     !
 M !----------------------------------------------------
___!9_8_7_6_5_4_3_2_1_0!7_6_5_4_3_2_1_0!7_6_5_4_3_2_1_0!
  0!- -,- - - -,- - - -!- - - -,- - - -!D / / /,/ / / /!
  1!- -,- - - -,- H L H!- - - -,- - - -!A / / /,/ / / /!
  2!- -,- - - -,L - L L!- - - -,- - - -!A / / /,/ / / /!
  3!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A / / /,/ / / /!
  4!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A / / /,/ / / /!
  5!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A / / /,/ / / /!
  6!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A / / /,/ / / /!
  7!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A / / /,/ / / /!
  8!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A / / /,/ / / /!
  9!- -,- - - -,- - - -!- - - -,- - - -!/ D / /,/ / / /!
 10!- -,- - - -,- - - -!- - H -,- - - -!/ A / /,/ / / /!
 11!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ A / /,/ / / /!
 12!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ A / /,/ / / /!
 13!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ A / /,/ / / /!
 14!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ A / /,/ / / /!
 15!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ A / /,/ / / /!
 16!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ A / /,/ / / /!
 17!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ A / /,/ / / /!
 18!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / D /,/ / / /!
 19!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 20!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 21!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 22!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 23!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 24!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 25!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 26!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / A /,/ / / /!
 27!- -,- - - -,- - - H!- - - -,- - - -!/ / / D,/ / / /!
 28!- -,- - - -,- - H -!- - - -,H - - -!/ / / A,/ / / /!
 29!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / A,/ / / /!
 30!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / A,/ / / /!
 31!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / A,/ / / /!
 32!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / A,/ / / /!
 33!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / A,/ / / /!
 34!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / A,/ / / /!
 35!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / A,/ / / /!
 36!- -,- - - -,- - H -!- - - -,- - - -!/ / / /,D / / /!
 37!- -,- - - -,H H - H!L H H H,- - - -!/ / / /,A / / /!
 38!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / /,A / / /!
 39!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / /,A / / /!
 40!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / /,A / / /!
 41!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / /,A / / /!
 42!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / /,A / / /!
 43!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / /,A / / /!
 44!0 0,0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!/ / / /,A / / /!
 45!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ D / /!
 46!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 47!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 48!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 49!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 50!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 51!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 52!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 53!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ A / /!
 54!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / D /!
 55!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 56!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 57!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 58!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 59!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 60!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 61!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 62!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / A /!
 63!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / D!
 64!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 65!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 66!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 67!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 68!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 69!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 70!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!
 71!- -,- - - -,- - - -!- - - -,- - - -!/ / / /,/ / / A!

    N N N N N N D C B A Z I I B / N N N Z I I B / N N N
    / / / / / /           N N I B / / /   N N I B / / /
    C C C C C C           V P D D C C C   V P D D C C C
                          E U I I         E U I I
                          R T R R         R T R R
                          T               T
```

TB03081S

Table 3. Programming Table Generated by AMAZE

Signetics

AN27

PLHS473 Primer

Application Note

Application Specific Products

INTRODUCTION

The PLHS473 is a 24-pin field- programmable logic array (FPLA) which has 11 dedicated inputs, 2 dedicated outputs and 9 bidirectional I/Os. The logic array consists of 24 programmable product terms which are connected to 22 programmable OR terms in the classical PLA architecture. A functional diagram is shown in Figure 1. The shaded areas represent programmable interconnects between vertical and horizontal lines. Eleven dedicated inputs, I_0 to I_{10}, are located on the upper lefthand corner of the diagram, and the 9 bidirectional I/Os, B_0 to B_8 are located on the lower righthand corner. All inputs to the AND array have true and inverting input buffers. The output portion of the 9 bidirectional I/Os and 2 outputs may be programmed to be Active-High or Active-Low by altering fuses X_0 to X_8, X_A and X_B which are connected to one leg of the Exclusive-OR gates. Each output is connected to two OR-terms, one of which provides the logic function OR to the output while the other provides the ENABLE function for the tri-state output buffer. Alternatively, each output may be configured to emulate an open-collector output by programming the output to an unconditional LOW and apply the logic function on the tri-state controlling OR-term as shown in Figure 2. In addition, the PLHS473 has a security fuse which may be programmed to lock out unauthorized access to the fuse map of the design.

This device is fabricated with an oxide-isolation process for the best speed/power performance. The programmable element is a ''vertical fuse'' which is actually two PN diodes connected back-to-back (anode-to-anode stacked on top of one another) as shown in the insets of Figure 1. The fuses are normally open-circuited. To program a fuse, a sufficiently high voltage is applied across the two diodes such that one diode breaks down which induces metal migration across the PN junction of the avalanched diode. This technology allows smaller chip size and faster speed performance. The guaranteed propagation delay may be tested by using the two factory-programmed test columns and a test row as a test vehicle for speed testing. These test columns are to be deleted automatically in the process of programming.

The vertical fuses of an unprogrammed device, being normally open-circuited, set all AND terms to a High state and disconnected to all OR terms. The OR terms are normally Low when they are not connected to the AND terms. Once an AND term is programmed to make connections with the OR array, it cannot be disconnected. However, AND terms may be disabled by having the true and inverting input buffers (e.g., A * /A, B * /B, etc.) of all inputs connected to the AND term which is to be disabled.

While even a single input, (A * /A), will hold the AND term to a Low, glitches may develop if the input voltage changes state. Therefore, it is recommended that the complementary buffers of all inputs in the disabled AND term be connected.

Programming the PLHS473

The programming table and symbols of the PLHS473 are shown in Table 1 where there is a place for every function that is shown in Figure 1. The table is divided into two main sections. The left side of the table, sections A and B, represents the input side of the AND array (section A has all dedicated inputs I_0 to I_{10}, section B has inputs from the bidirectional I/Os B_0 to B_8), whereas the right side, sections C, D, and E, represents the outputs of the OR array. Section C represents the OR array which controls the tri-state output buffers of the bidirectional I/Os B_0 to B_8 and outputs O_A and O_B, while section D represents the OR array which drives the outputs. Section E controls the output polarity of each output. As shown in Table 1, the program table is very similar to a truth table. Each row represents one of the 24 product terms, while each column in sections A and B represents an input to the 24 product terms and in sections C and D, each column represents an output. The intersection of a column and a row in sections A and B represents four possible fuse configurations, namely, 1) both inverting and non-inverting input buffers are connected to the AND term, 2) only the inverting buffer is connected, 3) only the non-inverting input buffer is connected, and 4) both inverting and non-inverting buffers are disconnected. These four configurations are represented as ''0'', ''L'', ''H'', and '' – '', respectively. Each intersection of a row and a column in sections C and D involves only two fuse configurations, either connected or disconnected. Therefore, the entry there is either ''A'' or '' – '', respectively. In the polarity control section (section E), each square represents the configuration of the fuse connected to the Exclusive-OR, which is connected to a particular output pin. An ''H'' represents an Active-High or non-inverting output, an ''L'' represents an Active-Low or inverting output. See Table 1 for further details.


(LOGIC TERMS–P)
I_0 1
I_1 2
I_2 3
I_3 4
I_4 5
I_5 6
I_6 7
I_7 8
I_8 9
I_9 10
I_{10} 11
B_0
B_1
B_2
B_3
B_4
B_5
B_6
B_7
B_8
D_8
S_8
D_7
S_7
D_6
S_6
D_5
S_5
D_4
S_4
D_3
S_3
D_2
S_2
D_1
S_1
D_0
S_0
E_B
S_B
E_A
S_A
X_8
X_7
X_6
X_5
X_4
X_3
X_2
X_1
X_0
X_B
X_A
23 B_8
22 B_7
21 B_6
20 B_5
17 B_4
16 B_3
15 B_2
14 B_1
13 B_0
19 O_B
18 O_A
23 • • • • • • 16 15 • • • • • • 8 7 • • • • • • 0
TC11310S

NOTES:

1. All unprogrammed or virgin "AND" gate locations are pulled to logic "1".
2. All unprogrammed or virgin "OR" gate locations are pulled to logic "0".
3. Programmable connections.

Figure 1. PLHS473 Logic Diagram



Figure 2. Emulation of Open-Collector Output

Notice that as shown in Figure 1, all fuses in their unprogrammed state are normally open-circuited. This means that all product terms are initially disconnected to the OR array, all OR gates are initially at a logic LOW, and all output pins are initially in High-Z state. Therefore, if anys of the outputs are to be enabled, its controlling OR term must be set to a logic HIGH. An example is shown in Table 2, term 0 where pins O_A, O_B $B(O)_8$ are programmed as dedicated outputs. The input section of term 0 is entirely "dashed out" (this is actually its unprogrammed state) which causes the AND term to be unconditionally HIGH. OR terms E_A, E_B, and D_8 are connected to product term 0 by the "A" entries in their respective squares. The rest of the D section and the B(O) section are "dotted out" (left unconnected) since we are not concerned with them for the moment. If more outputs are needed later on, their corresponding squares may be changed to "As" from "dots" as the need arises.

Table 1. PLHS473 Programming Table

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # ____________ CF (XXXX) ____________
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ________ REV ________ DATE ________

AND

INACTIVE	0	I, B(I)
I, B	H	
Ī, B̄	L	
DON'T CARE	—	

OR

ACTIVE	A	B(O)
INACTIVE	•	

CONTROL

HIGH	H	(POL)
LOW	L	

SECTION E

POLARITY										

TERM	AND																			TERM	OR																					
	I											B (I)										E		D									O		B (O)								
	10	9	8	7	6	5	4	3	2	1	0	8	7	6	5	4	3	2	1	0		B	A	8	7	6	5	4	3	2	1	0	B	A	8	7	6	5	4	3	2	1	0
0																					0																						
1																					1																						
2																					2																						
3																					3																						
4																					4																						
5																					5																						
6																					6																						
7																					7																						
8																					8																						
9																					9																						
10																					10																						
11						SECTION A										SECTION B					11						SECTION C											SECTION D					
12																					12																						
13																					13																						
14																					14																						
15																					15																						
16																					16																						
17																					17																						
18																					18																						
19																					19																						
20																					20																						
21																					21																						
22																					22																						
23																					23																						
PIN	11	10	9	8	7	6	5	4	3	2	1	23	22	21	20	17	16	15	14	13													19	18	23	22	21	20	17	16	15	14	13
VARIABLE NAME																																											

Notes
1. The FPLA is shipped with all links open.
2. Unused I and B bits in the AND array exist as Don't Care (–) in the virgin state.
3. All P-terms are inactive on all outputs (B, O) in the virgin array.
4. Unused product terms can be left blank.

OUTPUT POLARITY — (0, B)


S
X
$\bar{O}, \bar{B}$

ACTIVE LEVEL	CODE
LOW[1]	L

TC02560S



ACTIVE LEVEL	CODE
HIGH	H

TC02570S

AND ARRAY — (I, B)


I,B
I,B
$\bar{I}, \bar{B}$
P

STATE	CODE
DON'T CARE[1]	–

TC02600S


I,B
I,B
$\bar{I}, \bar{B}$
P

STATE	CODE
INACTIVE[2]	O

TC02630S


I,B
I,B
$\bar{I}, \bar{B}$
P

STATE	CODE
I, B	H

TC02610S


I,B
I,B
$\bar{I}, \bar{B}$
P

STATE	CODE
$\bar{I}, \bar{B}$	L

TC02620S

OR ARRAY — (O, B)



P_n STATUS	CODE
INACTIVE[1]	●

TC02580S



P_n STATUS	CODE
ACTIVE[1]	A

TC02590S

NOTES:

1. This is the initial unprogrammed state of all link pairs.
2. Any gate P_n will be unconditionally inhibited if any one of its (I, B) link pairs is programmed for a connection.


INPUT-1*INPUT-2
(INPUT-1*INPUT-2)+(INPUT-3*INPUT-4)
INPUT-3*INPUT-4
O-C = $\overline{\text{(INPUT-1*INPUT-2)+(INPUT-3*INPUT-4)}}$
TC11330S

Figure 3. Emulation of Open-Collector Output

VIRGIN STATE

A factor shipped virgin device contains all fusible links.

1. All output at "L" polarity.
2. All P_n terms are enable.
3. All P_n terms are active on all outputs.

Once we have determined the outputs, we can proceed with defining the logic functions. As an example, the logic function

OUT-0 = INPUT-1* /INPUT-2

is shown in Table 2, term #2 where in the column labeled "INPUT-1", an "H" is entered to represent a connection of the non-inverting input buffer of INPUT-1 and the AND term 2. In the column labelled "INPUT-2", an "L" is entered to represent the connection of the inverting input buffer of INPUT-1 and the AND term 2. On the output side of the table, O_B in term 0 is programmed "A" to make a connection between term 2 and the OR term which is connected to the output pin O_B: The output polarity of O_B is arbitrarily set to Active-High by programming an "H" in the O_B column of the polarity section.

A sum of several product terms (AND-OR) is implemented by connecting multiple AND terms to the same OR term. An example is shown in Table 2, terms 4 and 5, which implement the logic function

OUT-1 = (INPUT-1 */INPUT-2) +
(INPUT-3 * INPUT-4)

The logic function

OUT-2 = /((INPUT-1 * INPUT-2) +
(INPUT-3 * INPUT-4))

is shown in terms 9 and 10. The output is Active-Low as programmed "L" in the polarity section of OUT-2. As a rule, the AND function is implemented in a row, whereas the OR function is implemented in a column. Since the AND portions of terms 2 and 4 are the same, they may be combined as shown in term 7, which saves a duplicated term.

Table 2 terms 12 and 13 together emulate an open-collector output as an example. The logic equation

O-C = /((INPUT-1 * INPUT-2) +
(INPUT-3 * INPUT-4))

is implemented by first programming O-C Active-High in the polarity section. Terms 12 and 13 implement the sum of product function. Notice that the B(O) of O-C is programmed as a "dot" in both terms 12 and 13, which, together with the polarity control, causes it to be unconditionally Low, since a disconnected OR term is unconditionally Low. The intersections of column D_7 and terms 12 and 13 are programmed "A" so that the tri-state output buffer of $B(O)_7$ is enabled at input conditions (INPUT-1 * INPUT-2) = 1 or (INPUT-3 * INPUT-4) = 1. Terms 10 and 11 may be represented as shown in Figure 3.

Signetics produces a software package, AMAZE, as a design tool which assists implementation of logic design and documentation. For further information on AMAZE software, refer to the AMAZE User's Manual. Two simple circuits shown as examples are implemented using AMAZE. The first circuit is a simple cross-coupled RS latch. The second circuit is a multiplexer/demultiplexer which multiplexes four inputs to one output or demultiplexes one input into four outputs. Both circuits are put into the same PLHS473 device.

Table 2. Examples of Programming PLHS473

CUSTOMER NAME ____________
PURCHASE ORDER # ____________
SIGNETICS DEVICE # ________ **CF (XXXX)** ________
CUSTOMER SYMBOLIZED PART # ____________
TOTAL NUMBER OF PARTS ____________
PROGRAM TABLE # ______ **REV** ______ **DATE** ______

AND

INACTIVE	0	I,B(I)
I, B	H	
Ī, B̄	L	
DON'T CARE	—	

OR

ACTIVE	A	B(O)
INACTIVE	•	

CONTROL

HIGH	H	(POL)
LOW	L	

TERM	AND																			
	I											B (I)								
	10	9	8	7	6	5	4	3	2	1	0	8	7	6	5	4	3	2	1	0
0	—	—	—	—	—	—	—	—	—	—			—	—	—	—	—	—	—	—
1																				
2	H	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
3																				
4	H	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
5	—	—	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
6																				
7	H	L	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
8																				
9	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
10	—	—	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
11																				
12	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
13	—	—	H	H	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
14																				
15																				
16																				
17																				
18																				
19																				
20																				
21																				
22																				
23																				
PIN	11	10	9	8	7	6	5	4	3	2	1	23	22	21	20	17	16	15	14	13
VARIABLE NAME	INPUT-1	INPUT-2	INPUT-3	INPUT-4																

TERM	OR																					
POLARITY												H	H	L								
	E		D									O		B (O)								
	B	A	8	7	6	5	4	3	2	1	0	B	A	8	7	6	5	4	3	2	1	0
0	A	A	A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1																						
2	•	•	•	•	•	•	•	•	•	•	•	A	•	•	•	•	•	•	•	•	•	•
3																						
4	•	•	•	•	•	•	•	•	•	•	•	•	A	•	•	•	•	•	•	•	•	•
5	•	•	•	•	•	•	•	•	•	•	•	•	A	•	•	•	•	•	•	•	•	•
6																						
7	•	•	•	•	•	•	•	•	•	•	•	A	A	•	•	•	•	•	•	•	•	•
8																						
9	•	•	•	•	•	•	•	•	•	•	•	•	•	A	•	•	•	•	•	•	•	•
10	•	•	•	•	•	•	•	•	•	•	•	•	•	A	•	•	•	•	•	•	•	•
11																						
12	•	•	•	A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
13	•	•	•	A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
14																						
15																						
16																						
17																						
18																						
19																						
20																						
21																						
22																						
23																						
PIN												19	18	23	22	21	20	17	16	15	14	13
VARIABLE NAME												OUT-0	OUT-1	OUT-2	O-C							

Notes
1. The FPLA is shipped with all links open.
2. Unused I and B bits in the AND array exist as Don't Care (–) in the virgin state.
3. All P-terms are inactive on all outputs (B, O) in the virgin array.
4. Unused product terms can be left blank.

TB03100S

```
File Name : 473PRIME
Date : 9/4/1986
Time : 15:53:28

###################### P I N   L I S T ######################

   LABEL      ** FNC **PIN --------- PIN** FNC **    LABEL
/S            ** I   **  1-¦        ¦-24 ** +5V **VCC
/R            ** I   **  2-¦        ¦-23 ** /O  **Q
N/C           ** I   **  3-¦   P    ¦-22 ** /O  **QNOT
N/C           ** I   **  4-¦   L    ¦-21 ** /B  **N/C
N/C           ** I   **  5-¦   H    ¦-20 ** B   **F
N/C           ** I   **  6-¦   S    ¦-19 ** O   **N/C
N/C           ** I   **  7-¦   4    ¦-18 ** O   **N/C
N/C           ** I   **  8-¦   7    ¦-17 ** /B  **N/C
S0            ** I   **  9-¦   3    ¦-16 ** B   **D
S1            ** I   ** 10-¦        ¦-15 ** B   **C
DIR           ** I   ** 11-¦        ¦-14 ** B   **B
GND           ** 0V  ** 12-¦        ¦-13 ** B   **A
                           ---------
```

TB03170S

Figure 4. Pin List

```
File Name : 473PRIME
Date : 9/4/1986
Time : 15:54:14

@DEVICE TYPE
PLHS473
@DRAWING
@REVISION
@DATE
@SYMBOL
         File name = 473PRIME
@COMPANY
@NAME
@DESCRIPTION
@COMMON PRODUCT TERM
@I/O DIRECTION

  "The I/O DIRECTION definition is optional, and may be defaulted
   to the PIN LIST unless it is bidirectional and is controlled by
   a logic equation. "

  "******************** I/O DEFINITION FOR R/S LATCH ****************** "

    D8 = 1 ;    " Each output must be defined seperately by its own
                  logic equation. "
    D7 = 1 ;

  "*************** I/O DEFINITION FOR MUX/DEMUX CIRCUIT *************** "

    D3 = DIR ;  " When DIR = 1, B3, B2, B1, B0 become outputs. Data flows
                  from F to A, B, C, D. "
    D2 = DIR ;
    D1 = DIR ;
    D0 = DIR ;

    D5 = /DIR ; " When DIR = 0, B5 becomes an output, output buffers
                  of B0 to B3 are disabled. Data flows from A, B, C,
                  D to F. "
```

TB03180S

Figure 5. Boolean Equations



```
@OUTPUT POLARITY

  " The definition of output polarity is optional and may be defaulted
    the PIN LIST. "

  " *************** POLARITY DEFINITION FOR R/S LATCH ************* "

     X8, X7 = 1 ;      " Outputs with the same polarity may be defined
                         in the same equation. Since the outputs Q and
                         QNOT are defined as active LOW, this equation
                         causes the XOR to function as an inverter. "

  " ********** POLARITY DEFINITION FOR MUX/DEMUX CIRCUIT *********** "

     X5, X3, X2, X1, X0 = 0 ;  " Outputs B0, B1, B2, B3, B5 are active
                                 HIGH. "

@LOGIC EQUATION

  " ****************** EQUATIONS FOR R/S LATCH ********************** "

     Q     = /( /S * QNOT ) ;  " The equation must used the format
                                 output = /( ...... ); since output
                                 Q is defined as active LOW. "
     QNOT  = /( /R * Q ) ;

  " ************** EQUATIONS FOR MUX/DEMUX CIRCUIT ****************** "

     F = ( A * /S0 * /S1 )  +
         ( B *  S0 * /S1 )  +
         ( C * /S0 *  S1 )  +
         ( D *  S0 *  S1 )  ;

     A = ( F * /S0 * /S1 )  ;
     B = ( F *  S0 * /S1 )  ;
     C = ( F * /S0 *  S1 )  ;
     D = ( F *  S0 *  S1 )  ;
```

TB03190S

Figure 5. Boolean Equations (Continued)

```
File Name : 473PRIME
Date : 9/4/1986
Time : 15:56:24

Cust/Project -
Date         -
Rev/I. D.    -

PLHS473                              !  POLARITY !
---                                  -------------
 T !                                 !LLLLLHLHHHH!
 E !----------------------------------------------
 R !_____I_____!___B(i)__!E ____D____!O __B(o)___!
 M !19876543210!876543210!BA876543210!BA876543210!
---!0----------!---------!-----------!-----------!
  0!----------H!-H-------!AA..A.A....!AAA.A.A....!
  1!---------H-!H--------!AA..A.A....!AA.AA.A....!
  2!-LL--------!--------H!AA..A.A....!AA..AAA....!
  3!-LH--------!-------H-!AA..A.A....!AA..AAA....!
  4!-HL--------!------H--!AA..A.A....!AA..AAA....!
  5!-HH--------!-----H---!AA..A.A....!AA..AAA....!
  6!-LL--------!---H-----!AA..A.A....!AA..A.A...A!
  7!-LH--------!---H-----!AA..A.A....!AA..A.A..A.!
  8!-HL--------!---H-----!AA..A.A....!AA..A.A.A..!
  9!-HH--------!---H-----!AA..A.A....!AA..A.AA...!
 10!-----------!---------!AAAAA.A....!AA..A.A....!
 11!H----------!---------!AA..A.AAAAA!AA..A.A....!
 12!L----------!---------!AA..AAA....!AA..A.A....!
 13!-----------!---------!...........!...........!
 14!-----------!---------!...........!...........!
 15!-----------!---------!...........!...........!
 16!-----------!---------!...........!...........!
 17!-----------!---------!...........!...........!
 18!-----------!---------!...........!...........!
 19!-----------!---------!...........!...........!
 20!-----------!---------!...........!...........!
 21!-----------!---------!...........!...........!
 22!-----------!---------!...........!...........!
 23!-----------!---------!...........!...........!

    DSSNNNNNN// QQNFNDCBA             NNQQNFNDCBA
    I10//////RS  N/ /                 // N/ /
    R  CCCCCC    OC C                 CC OC C
                 T                       T
```

TB03160S

Figure 6. Program Table

AN28
High-Speed 12-Bit Tracking A/D Converter Using PLS179

Application Note

INTRODUCTION

The general technique underlying the operation of this A/D converter is illustrated by the fuctional block diagram in Figure 1. The system consists of a D/A converter, a comparator circuit, and digital logic circuitry. The digital logic circuitry outputs a digital vaue which is converted to analog by the D/A converter.

The comparator senses when the output is greater or less than the input and causes the digital circuit to decrement or increment its digital output respectively. The initial conversion is completed in 13 clock cycles. If tracking mode is used, the A/D converter then tracks the input voltage as it changes by incrementing or decrementing 1-LSB per clock. The tracking function makes it possible to make an A/D conversion in one clock cycle if the input changes less than the value of 1-LSB per clock period. The conversion may be halted and the digital output, as well as the converted analog output from DAC, will hold their output constant indefinitely. This feature works well as sample-and-hold since its output voltage will not decay over time whereas the output of an analog sample/hold will decay due to charge leakages.

In order to avoid the violation of setup time by the output of the comparator, its output is latched. There is a built-in 2-phase clock in U2 which may be used to drive the logic circuitry and the latch of the comparator (see Signetics NE5105 data sheet for details on output latches of voltage comparators).

The analog input voltage may be sampled and held by an analog sample/hold circuit to keep the input to the ADC from changing. The DONE output may be used to control the sample-and-hold if needed.

This paper discusses only the digital circuit which contains the SAR and the Up/Down Counter. The analog circuits are not within the scope of this paper.

SAR

Two PLS179s are connected together to form a 12-bit shift register and up/down counter. The schematic diagram of the A/D converter is shown in Figure 2. U2 contains bits 0 to 4 and U1 contains Bits 5 to 11. Interconnects are made as shown in the diagram. The digital output to the DAC is in natural binary format (e.g. 0000 0000 0000 equal zero, and 1111 1111 1111 is full scale or 4095). After the/ST input becomes 0, at the rising edge of the next clock, the SAR is initialized to half-scale (1000 0000 0000) and the DONE flip-flop is reset to output 0 which causes the open-collector output /DONE_OC to become high impedance. The digital output is converted by the DAC and is compared to the analog input voltage by the comparator. If the digital output is greater than the analog input, the SAR shifts the 1 to next MSB on the right. The content of the SAR becomes (0100 0000 0000). If the digital output is still greater than the input, the SAR shifts right one bit again. The content of the SAR then becomes (0010 0000 0000). The shifting of 1 to the next MSB in equivalent to reducing by half the value of the bit under consideration. If the output is still too large, the SAR reduces it by half again by shifting to the right one more time. The SAR keeps shifting to the right until the digital output is less than the input. When the output is less than the input, the SAR adds one bit to the next MSB while keeping all the higher order bits unchanged. For example, if the current output is 0001 0000 0000 and the output is less than the input, the SAR adds one bit to the right at the next clock. The output becomes 0001 1000 0000. The output is again compared to the input. If the addition of that one bit is too much, it will be shifted to the right until the output becomes less than the input. When that happens, that SAR will again add one bit to the right. The algorithm of the SAR may be summarized as the following: If the output is greater than the input, shift to the right; otherwise add one bit to the right. This process continues until all 12 bits have been operated on. The last bit (Bit 0) is always changed from 0 to 1, which is used as the condition to set DONE to 1 which, in turn, sets open-collector output, /DONE_OC, to 0.

UP/DOWN COUNTER

After DONE becomes 1, if /ST and /HOLD are 1 and /TRACK is 0, the SAR turns into a 12-bit up/down counter. If the analog input voltage increases, the counter will increment by 1 at every clock until it matches the input. If the input decreases, the counter will decrement by 1. When /HOLD becomes 0, the counter is inhibited and the output is held indefinitely. The counters consist of 12 toggle flip-flops and 2 p-terms per flip-flop for directional control. The counter will operate only



Figure 1. Functional Block Diagram of 12-Bit High-Speed A/D Converter

High-Speed 12-Bit Tracking A/D Converter Using PLS179


ST
TRACK
HOLD
1
2
5
3
PLS179
U1
START
4
22
21
20
19
18
17
16
15
6
7
8
9
10
11
+V$_{CC}$
R
C
10
21
HLD
2
6
20
19
18
17
16
15
1
PLS179
U2
14
11
5
4
3
23
CLOCK 2
CLOCK 1
DONE_OC
DONE
MSB
12-BIT
DIGITAL
OUTPUT
LSB
LATCH ENABLE
CLOCK 1
COMPARATOR
- +
MSB
LSB
12-BIT DAC
V$_{IN}$ (ANALOG INPUT)
LD07890S

Figure 2. Schematic Diagram of 12-Bit High-Speed A/D Converter

after the approximation cycle is completed and DONE is 1.

Since the /ST and /HOLD inputs may be asynchronous with the clock, in order to minimize the possibilities of having a metastable condition from happening, these inputs close-up are latched by flip-flops /START of U1 and /HLD of U2 respectively. Once they are latched, subsequent operation begins at the rising-edge of the next clock. The output of the comparator may be latched to prevent setup time violation. (Signetics NE5105 is a high-speed comparator with an output latch. External latch may be used with other comparators.)

CLOCKS

U2 generates an optional 2-phase clock which may be used to control the latch of the comparator. The two clocks are basically 180° out of phase and CLOCK2 has an additional 25ns propagation delay behind CLOCK1. CLOCK2 is used to drive the clock-inputs of the PLS179 devices.

The clock frequency is controlled by R and C. Those who want to use the built-in clock should experiment with RC time constants for the best value. It is recommended that the capacitance should be less than 1000pF for best results (see Ap Note AN13 for more detail).

DONE AND /DONE_OC

The output DONE is reset to 0 when /ST is 0. It remains 0 until the approximation cycle is completed. After the least significant bit becomes 1, the DONE bit becomes 1 at the next clock. It remains 1 until it is reset again by input /ST.

The /DONE_OC output is configured to emulate an open-collector output. The output is programmed to have a logic 0. When DONE is 0, the Tri-state output buffer is set to Hi-Z condition. As soon as DONE equals 1, the Tri-state buffer is enabled and /DONE_OC becomes 0.

In the initial phase of A/D conversion, 13 clock cycles are required. It is essential that the input voltage to the comparator remains unchanged while the SAR is converting. It may be necessary to have a sample/hold at the front end. The DONE output may be used to control the analog sample/hold circuit.

INPUT LATCHES

Flip-flop /START and 2 p-terms in U1 are configured as a non-inverting D flip-flop. The input, /ST, and the output /START have the same polarities. Flip-flop /HLD and 2 p-terms in U2 also form a non-inverting D flip-flop. The output /HLD and the input /HOLD have the same polarities.

AMAZE INPLEMENTATION

The implementation of the logic circuit using AMAZE is as shown in the appendices. The SAR circuit is first designed as a state machine (file name: ADCS.SEE). It is then partitioned into two PLS179s after proper pin assignments are made. Then the up/down counter, input latches, 2-phase clocks and the open-collector output, are implemented by using Boolean equations in their respective .BEE files (file names: ADCB1.BEE and ADCB2.BEE) in AMAZE. The files are then assembled to produce the fuse-maps of PLS179 (ADCB1.STD and ADCB2.STD).



Figure 3. Timing Diagram of Successive Approximation Cycle

APPENDIX A: STATE EQUATIONS OF SAR

```
File Name : ADCS
Date : 10/21/1986
Time : 11:2:14

@DEVICE SELECTION
ADCB1/PLS179
ADCB2/PLS179

@STATE VECTORS
[ /START, BIT11, BIT10, BIT9, BIT8, BIT7, BIT6, BIT5, BIT4, BIT3, BIT2,
BIT1, BIT0, DONE ]

INIT       = 0 ---- ---- ---- - b ;   "START CONVERSION PROCESS"
HALFSCALE. = - 1000 0000 0000 0 b ;   "SET SAR TO HALF SCALE"
ST2048     = 1 1000 0000 0000 0 b ;   "PRESENT STATE = 2048 (HALF SCALE)"
ST1024     = 1 -100 0000 0000 0 b ;
ST512      = 1 --10 0000 0000 0 b ;
ST256      = 1 ---1 0000 0000 0 b ;
ST128      = 1 ---- 1000 0000 0 b ;
ST64       = 1 ---- -100 0000 0 b ;
ST32       = 1 ---- --10 0000 0 b ;
ST16       = 1 ---- ---1 0000 0 b ;
ST8        = 1 ---- ---- 1000 0 b ;
ST4        = 1 ---- ---- -100 0 b ;
ST2        = 1 ---- ---- --10 0 b ;
ST1        = 1 ---- ---- ---1 0 b ;

AD1024     = - -1-- ---- ---- - b ;   "ADD 1 BIT TO THE RIGHT"
AD512      = - --1- ---- ---- - b ;
AD256      = - ---1 ---- ---- - b ;
AD128      = - ---- 1--- ---- - b ;
AD64       = - ---- -1-- ---- - b ;
AD32       = - ---- --1- ---- - b ;
AD16       = - ---- ---1 ---- - b ;
AD8        = - ---- ---- 1--- - b ;
AD4        = - ---- ---- -1-- - b ;
AD2        = - ---- ---- --1- - b ;
AD1        = - ---- ---- ---1 - b ;
END        = - ---- ---- ---- 1 b ;

SH1024     = - 01-- ---- ---- - b ;   "SHIFT ONE BIT TO THE RIGHT"
SH512      = - -01- ---- ---- - b ;
SH256      = - --01 ---- ---- - b ;
SH128      = - ---0 1--- ---- - b ;
SH64       = - ---- 01-- ---- - b ;
SH32       = - ---- -01- ---- - b ;
SH16       = - ---- --01 ---- - b ;
SH8        = - ---- ---0 1--- - b ;
SH4        = - ---- ---- 01-- - b ;
SH2        = - ---- ---- -01- - b ;
SH1        = - ---- ---- --01 - b ;
SH0        = - ---- ---- ---0 1 b ;

@INPUT VECTORS
[ COMPARE ]
GREATER = 1 b ;  "IF DIGITAL OUTPUT IS GREATER THAN ANALOG INPUT, ...."
LESS    = 0 b ;  "IF DIGITAL OUTPUT IS LESS THAN ANALOG INPUT, ...."

@OUTPUT VECTORS
```

TB03320S

APPENDIX A: STATE EQUATIONS OF SAR (Continued)

```
@TRANSITIONS
WHILE [ INIT ]
        IF [] THEN [ HALFSCALE ]  "INITIALIZE REGISTER TO HALF SCALE"
WHILE [ ST2048 ]
        IF [ GREATER ] THEN [ SH1024 ] "IF GREATER THAN, SHIFT 1 BIT"
        IF [ LESS ] THEN [ AD1024 ]    "IF LESS THAN, ADD 1 BIT"
WHILE [ ST1024 ]
        IF [ GREATER ] THEN [ SH512 ]
        IF [ LESS ] THEN [ AD512 ]
WHILE [ ST512 ]
        IF [ GREATER ] THEN [ SH256 ]
        IF [ LESS ] THEN [ AD256 ]
WHILE [ ST256 ]
        IF [ GREATER ] THEN [ SH128 ]
        IF [ LESS ] THEN [ AD128 ]
WHILE [ ST128 ]
        IF [ GREATER ] THEN [ SH64 ]
        IF [ LESS ] THEN [ AD64 ]
WHILE [ ST64 ]
        IF [ GREATER ] THEN [ SH32 ]
        IF [ LESS ] THEN [ AD32 ]
WHILE [ ST32 ]
        IF [ GREATER ] THEN [ SH16 ]
        IF [ LESS ] THEN [ AD16 ]
WHILE [ ST16 ]
        IF [ GREATER ] THEN [ SH8 ]
        IF [ LESS ] THEN [ AD8 ]
WHILE [ ST8 ]
        IF [ GREATER ] THEN [ SH4 ]
        IF [ LESS ] THEN [ AD4 ]
WHILE [ ST4 ]
        IF [ GREATER ] THEN [ SH2 ]
        IF [ LESS ] THEN [ AD2 ]
WHILE [ ST2 ]
        IF [ GREATER ] THEN [ SH1 ]
        IF [ LESS ] THEN [ AD1 ]
WHILE [ ST1 ]
        IF [ GREATER ] THEN [ SH0 ]
        IF [] THEN [END]
```

TB03330S

High-Speed 12-Bit Tracking A/D Converter Using PLS179

AN28

APPENDIX B: PIN LISTS



```
File Name : ADCB2
Date : 10/21/1986
Time : 10:58:26

####################### P I N   L I S T #######################

   LABEL       ** FNC **PIN --------- PIN** FNC **    LABEL
CLOCK          ** CK  **   1-|        |-24 ** +5V **VCC
/START         ** I   **   2-|        |-23 ** /B  **/DONE_OC
COMPARE        ** I   **   3-|        |-22 ** B   **N/C
/HOLD          ** I   **   4-|   P    |-21 ** O   **/HLD
/TRACK         ** I   **   5-|   L    |-20 ** O   **BIT4
BIT5           ** I   **   6-|   S    |-19 ** O   **BIT3
N/C            ** I   **   7-|   1    |-18 ** O   **BIT2
N/C            ** I   **   8-|   7    |-17 ** O   **BIT1
N/C            ** I   **   9-|   9    |-16 ** O   **BIT0
RC             ** /B  **  10-|        |-15 ** O   **DONE
CLOCK1         ** O   **  11-|        |-14 ** /O  **CLOCK2
GND            ** OV  **  12-|        |-13 ** /OE **N/C
                             ---------
```

TB03340S



```
File Name : ADCB1
Date : 10/21/1986
Time : 10:53:7

####################### P I N   L I S T #######################

   LABEL       ** FNC **PIN --------- PIN** FNC **    LABEL
CLOCK          ** CK  **   1-|        |-24 ** +5V **VCC
/ST            ** I   **   2-|        |-23 ** /B  **N/C
COMPARE        ** I   **   3-|        |-22 ** O   **/START
/HLD           ** I   **   4-|   P    |-21 ** O   **BIT11
/TRACK         ** I   **   5-|   L    |-20 ** O   **BIT10
BIT4           ** I   **   6-|   S    |-19 ** O   **BIT9
BIT3           ** I   **   7-|   1    |-18 ** O   **BIT8
BIT2           ** I   **   8-|   7    |-17 ** O   **BIT7
BIT1           ** I   **   9-|   9    |-16 ** O   **BIT6
BIT0           ** I   **  10-|        |-15 ** O   **BIT5
DONE           ** I   **  11-|        |-14 ** /B  **N/C
GND            ** OV  **  12-|        |-13 ** /OE **N/C
                             ---------
```

TB03370S

APPENDIX C: BOOLEAN EQUATIONS OF UP/DOWN COUNTER AND INPUT LATCH



```
File Name : ADCB1
Date : 10/21/1986
Time : 10:54:48

@DEVICE TYPE
PLS179
@DRAWING
@REVISION
@DATE
@SYMBOL
    FILE NAME : ADCB1

@COMPANY
@NAME
@DESCRIPTION
@COMMON PRODUCT TERM
@COMPLEMENT ARRAY
@I/O DIRECTION
@OUTPUT POLARITY
@FLIP FLOP CONTROL
     FC = 1 ;          "SET ALL FLIP FLOP TO BE J/K"

@OUTPUT ENABLE
@REGISTER LOAD
@ASYNCHRONOUS PRESET/RESET
@FLIP FLOP MODE
@LOGIC EQUATION
 "NON-INVERTING INPUT LATCH: /START = /ST "
  START  : J =  ST ;
           K = /ST ;
 "UP/DOWN COUNTER ROUTINE"
  /BIT5  : T = /START * TRACK * DONE * /HLD *  COMPARE * /BIT0 * /BIT1 *
               /BIT2 * /BIT3 * /BIT4 +
               /START * TRACK * DONE * /HLD * /COMPARE *  BIT0 *  BIT1 *
                BIT2 *  BIT3 * BIT4 ;
  /BIT6  : T = /START * TRACK * DONE * /HLD *  COMPARE * /BIT0 * /BIT1 *
               /BIT2 * /BIT3 * /BIT4 * /BIT5 +
               /START * TRACK * DONE * /HLD * /COMPARE *  BIT0 *  BIT1 *
                BIT2 *  BIT3 * BIT4 *  BIT5 ;
  /BIT7  : T = /START * TRACK * DONE * /HLD *  COMPARE *
               /BIT0 * /BIT1 * /BIT2 * /BIT3 * /BIT4 * /BIT5 * /BIT6 +
               /START * TRACK * DONE * /HLD * /COMPARE *
                BIT0 *  BIT1 *  BIT2 *  BIT3 *  BIT4 *  BIT5 *  BIT6 ;
  /BIT8  : T = /START * TRACK * DONE * /HLD *  COMPARE * /BIT0 * /BIT1 *
               /BIT2 * /BIT3 * /BIT4 * /BIT5 * /BIT6 * /BIT7 +
               /START * TRACK * DONE * /HLD * /COMPARE *  BIT0 *  BIT1 *

                BIT2 *  BIT3 *  BIT4 *  BIT5 *  BIT6 *  BIT7 ;
  /BIT9  : T = /START * TRACK * DONE * /HLD *  COMPARE * /BIT0 * /BIT1 *
               /BIT2 * /BIT3 * /BIT4 * /BIT5 * /BIT6 * /BIT7 * /BIT8 +
               /START * TRACK * DONE * /HLD * /COMPARE *  BIT0 *  BIT1 *

                BIT2 *  BIT3 *  BIT4 *  BIT5 *  BIT6 *  BIT7 *  BIT8 ;
  /BIT10 : T = /START * TRACK * DONE * /HLD *  COMPARE * /BIT0 * /BIT1 *
               /BIT2 * /BIT3 * /BIT4 * /BIT5 * /BIT6 * /BIT7 * /BIT8 *
               /BIT9 +
               /START * TRACK * DONE * /HLD * /COMPARE *  BIT0 *  BIT1 *

                BIT2 *  BIT3 *  BIT4 *  BIT5 *  BIT6 *  BIT7 *  BIT8 *
                BIT9 ;
  /BIT11 : T = /START * TRACK * DONE * /HLD *  COMPARE * /BIT0 * /BIT1 *
               /BIT2 * /BIT3 * /BIT4 * /BIT5 * /BIT6 * /BIT7 * /BIT8 *
               /BIT9 *
               /BIT10 +
               /START * TRACK * DONE * /HLD * /COMPARE * BIT0 * BIT1 *
                BIT2 *  BIT3 *  BIT4 *  BIT5 *  BIT6 *  BIT7 *  BIT8 *
                BIT9 *  BIT10 ;
```

TB03390S

APPENDIX C: BOOLEAN EQUATIONS OF UP/DOWN COUNTER AND INPUT LATCH (Continued)

```
       File Name : ADCB2
       Date : 10/21/1986
       Time : 10:58:56

       @DEVICE TYPE
       PLS179
       @DRAWING
       @REVISION
       @DATE
       @SYMBOL
         FILE NAME :  ADCB2

       @COMPANY
       @NAME
       @DESCRIPTION
       @COMMON PRODUCT TERM
       @COMPLEMENT ARRAY
       @I/O DIRECTION
            DO = RC ;             "RC OSCILLATOR"
            D3 = DONE ;           "ENABLE /DONE_OC TO OUTPUT A LOGIC LOW."
       @OUTPUT POLARITY
       @FLIP FLOP CONTROL
            FC = 1 ;
       @OUTPUT ENABLE
       @REGISTER LOAD
       @ASYNCHRONOUS PRESET/RESET
       @FLIP FLOP MODE
            "MO, M1, M2, M3, M4, M5 = 1 ;  SET FO - F5 TO J/K FLIP FLOPS."

       @LOGIC EQUATION
        "NON-INVERTING INPUT LATCH :  /HLD = /HOLD "
         HLD   : J =  HOLD ;
                 K = /HOLD ;

        "UP/DOWN COUNTER ROUTINE"
        /BITO  : T = /START * TRACK * DONE * /HLD ;
        /BIT1  : T = /START * TRACK * DONE * /HLD * /COMPARE *  BITO +
                     /START * TRACK * DONE * /HLD *  COMPARE * /BITO ;
        /BIT2  : T = /START * TRACK * DONE * /HLD * /COMPARE *  BITO *  BIT1 +
                     /START * TRACK * DONE * /HLD *  COMPARE * /BITO * /BIT1 ;
        /BIT3  : T = /START * TRACK * DONE * /HLD * /COMPARE *  BITO *  BIT1 *
BIT2 +
                     /START * TRACK * DONE * /HLD *  COMPARE * /BITO * /BIT1 * /
BIT2 ;
        /BIT4  : T = /START * TRACK * DONE * /HLD * /COMPARE *  BITO *  BIT1 *
BIT2 *
                      BIT3 +
                     /START * TRACK * DONE * /HLD *  COMPARE * /BITO * /BIT1 * /
BIT2 *
                     /BIT3 ;
        /DONE_OC     = /( 1 ) ;

        "RC OSCILLATOR"
         RC          = /(1) ;
         CLOCK1      = RC ;
         CLOCK2      = /( CLOCK1 ) ;          "BUILT-IN DELAY OF 1 tPD"
```

TB03380S

APPENDIX D: U1 ADCB1 FUSE MAP

```
File Name : ADCB1
Date : 10/21/1986
Time : 10:56:5

Cust/Project -
Date         -
Rev/I. D.    -

PLS179                       ! F/F TYPE      ! E(b)= !E(a) = !POLARTY!
___                          !_______________!_______!_______!_______!
 T !                         !A:A:A:A:A:A:A:A!  O    !  O    !L:L:L:L!
 E !------------------------------------------------------------------
 R ! !       I       ! B(i)  !    Q(p)       !     Q(n)      ! B(o)  !
 M !C!----------------------------------------------------------------
___!_!7_6_5_4_3_2_1_0!3_2_1_0!7_6_5_4_3_2_1_0!7_6_5_4_3_2_1_0!3_2_1_0!
  0!A!- - - -,- - - L!- - - -!- - - -,- - - -!H - - -,- - - -!A A A A!
  1!A!- - - -,- - - H!- - - -!- - - -,- - - -!L - - -,- - - -!A A A A!
  2!A!L L L L,L H H -!- - H L!L - - -,- - - -!- - - -,- - - 0!A A A A!
  3!A!H H H H,L H L -!- - H H!L - - -,- - - -!- - - -,- - - 0!A A A A!
  4!A!L L L L,L H H -!- - H L!L - - -,- - - H!- - - -,- - 0 -!A A A A!
  5!A!H H H H,L H L -!- - H H!L - - -,- - - L!- - - -,- - 0 -!A A A A!
  6!A!L L L L,L H H -!- - H L!L - - -,- - H H!- - - -,- 0 - -!A A A A!
  7!A!H H H H,L H L -!- - H H!L - - -,- - L L!- - - -,- Q - -!A A A A!
  8!A!L L L L,L H H -!- - H L!L - - -,- H H H!- - - -,0 - - -!A A A A!
  9!A!H H H H,L H L -!- - H H!L - - -,- L L L!- - - -,0 - - -!A A A A!
 10!A!L L L L,L H H -!- - H L!L - - -,H H H H!- - - 0,- - - -!A A A A!
 11!A!H H H H,L H L -!- - H H!L - - -,L L L L!- - - 0,- - - -!A A A A!
 12!A!L L L L,L H H -!- - H L!L - - H,H H H H!- - 0 -,- - - -!A A A A!
 13!A!H H H H,L H L -!- - H H!L - - L,L L L L!- - 0 -,- - - -!A A A A!
 14!A!L L L L,L H H -!- - H L!L - H H,H H H H!- 0 - -,- - - -!A A A A!
 15!A!H H H H,L H L -!- - H H!L - L L,L L L L!- 0 - -,- - - -!A A A A!
 16!A!- - - -,- - - -!- - - -!H - - -,- - - -!- L H H,H H H H!A A A A!
 17!A!L L L L,- - H -!- - L L!L L H H,H H H H!- H L -,- - - -!A A A A!
 18!A!L L L L,- - L -!- - L L!L L H H,H H H H!- - L -,- - - -!A A A A!
 19!A!L L L L,- - H -!- - L L!L - L H,H H H H!- - H L,- - - -!A A A A!
 20!A!L L L L,- - L -!- - L L!L - L H,H H H H!- - - L,- - - -!A A A A!
 21!A!L L L L,- - H -!- - L L!L - - L,H H H H!- - - H,L - - -!A A A A!
 22!A!L L L L,- - L -!- - L L!L - - L,H H H H!- - - -,L - - -!A A A A!
 23!A!L L L L,- - H -!- - L L!L - - -,L H H H!- - - -,H L - -!A A A A!
 24!A!L L L L,- - L -!- - L L!L - - -,L H H H!- - - -,- L - -!A A A A!
 25!A!L L L L,- - H -!- - L L!L - - -,- L H H!- - - -,- H L -!A A A A!
 26!A!L L L L,- - L -!- - L L!L - - -,- L H H!- - - -,- - L -!A A A A!
 27!A!L L L L,- - H -!- - L L!L - - -,- - L H!- - - -,- - H L!A A A A!
 28!A!L L L L,- - L -!- - L L!L - - -,- - L H!- - - -,- - - L!A A A A!
 29!A!L L L L,- - H -!- - L L!L - - -,- - - L!- - - -,- - - H!A A A A!
 30!0!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 31!0!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 Fc!A!- - - -,- - - -!- - - -!- - - -,- - - -!                       .
 Pb!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Rb!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Lb!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Pa!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Ra!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 La!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D3!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D2!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D1!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D0!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .

      B B B B / / C / N N D B / B B B B B B B / B B B B B B B N N D B
      I I I I T H O S / / O I S I I I I I I I S I I I I I I I / / O I
      T T T T R L M T C C N T T T T T T T T T T T T T T T T T C C N T
      1 2 3 4 A D P       E 0 A 1 1 9 8 7 6 5 A 1 1 9 8 7 6 5     E 0
              C   A           R 1 0           R 1 0
              K   R           T               T
                  E
```

TB03360S

APPENDIX D: U2 ADCB2 FUSE MAP (Continued)

```
File Name : ADCB2
Date : 10/21/1986
Time : 11:0:7

Cust/Project -
Date         -
Rev/I. D.    -

PLS179                       ! F/F TYPE      ! E(b)= !E(a) = !POLARTY!
___                          !_______________!_______!_______!_______!
 T !                         !A:A:A:A:A:A:A:A!   0   !   0   !L:L:H:L!
 E !------------------------------------------------------------------
 R ! !        I      ! B(i)  !      Q(p)      !      Q(n)     ! B(o)  !
 M !C!----------------------------------------------------------------
___!_!7_6_5_4_3_2_1_0!3_2_1_0!7_6_5_4_3_2_1_0!7_6_5_4_3_2_1_0!3_2_1_0!
  0!A!- - - -,- L - -!- - - -!- - - -,- - - -!0 H - -,- - - -!. . . .!
  1!A!- - - -,- H - -!- - - -!- - - -,- - - -!0 L - -,- - - -!. . . .!
  2!A!- - - -,L - - H!- - - -!- L - -,- - - L!0 - - -,- - 0 -!. . . .!
  3!A!- - - -,L - L H!- - - -!- L - -,- - L L!0 - - -,- 0 - -!. . . .!
  4!A!- - - -,L - H H!- - - -!- L - -,- - H L!0 - - -,- 0 - -!. . . .!
  5!A!- - - -,L - L H!- - - -!- L - -,- L L L!0 - - -,0 - - -!. . . .!
  6!A!- - - -,L - H H!- - - -!- L - -,- H H L!0 - - -,0 - - -!. . . .!
  7!A!- - - -,L - L H!- - - -!- L - -,L L L L!0 - - 0,- - - -!. . . .!
  8!A!- - - -,L - H H!- - - -!- L - -,H H H L!0 - - 0,- - - -!. . . .!
  9!A!- - - -,L - L H!- - - -!- L - L,L L L L!0 - 0 -,- - - -!. . . .!
 10!A!- - - -,L - H H!- - - -!- L - H,H H H L!0 - 0 -,- - - -!. . . .!
 11!A!- - - -,- - - -!- - - -!- - - -,- - - -!0 - - -,- - - -!A . . .!
 12!A!- - - -,- - - -!- - - H!- - - -,- - - -!0 - - -,- - - -!. . A .!
 13!A!- - - -,- - - -!- - H -!- - - -,- - - -!0 - - -,- - - -!. A . .!
 14!A!- - - -,- - - L!- - - -!- - - -,- - - -!0 - H H,H H H H!. . . .!
 15!A!- - - H,- - H H!- - - -!- - H H,H H H H!0 - L -,- - - -!. . . .!
 16!A!- - - H,- - L H!- - - -!- - H H,H H H H!0 - L -,- - - -!. . . .!
 17!A!- - - -,- - H H!- - - -!- - L H,H H H H!0 - H L,- - - -!. . . .!
 18!A!- - - -,- - L H!- - - -!- - L H,H H H H!0 - - L,- - - -!. . . .!
 19!A!- - - -,- - H H!- - - -!- - - L,H H H H!0 - - H,L - - -!. . . .!
 20!A!- - - -,- - L H!- - - -!- - - L,H H H H!0 - - -,L - - -!. . . .!
 21!A!- - - -,- - H H!- - - -!- - - -,L H H H!0 - - -,H L - -!. . . .!
 22!A!- - - -,- - L H!- - - -!- - - -,L H H H!0 - - -,- L - -!. . . .!
 23!A!- - - -,- - H H!- - - -!- - - -,- L H H!0 - - -,- H L -!. . . .!
 24!A!- - - -,- - L H!- - - -!- - - -,- L H H!0 - - -,- - L -!. . . .!
 25!A!- - - -,- - H H!- - - -!- - - -,- - L H!0 - - -,- - H L!. . . .!
 26!A!- - - -,- - - H!- - - -!- - - -,- - L H!0 - - -,- - - L!. . . .!
 27!0!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 28!0!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 29!0!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 30!0!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 31!0!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!0 0 0 0,0 0 0 0!A A A A!
 Fc!A!- - - -,- - - -!- - - -!- - - -,- - - -!                       .
 Pb!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Rb!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Lb!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Pa!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 Ra!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 La!.!0 0 0 0,0 0 0 0!0 0 0 0!0 0 0 0,0 0 0 0!                       .
 D3!-!- - - -,- - - -!- - - -!- - - -,- - - -!                       .
 D2!-!- - - -,- - - -!- - - -!- - - -,- - - -!                       .
 D1!-!- - - -,- - - -!- - - -!- - - -,- - - -!                       .
 D0!-!- - - -,- - - -!- - - -!- - - -,- - - -!                       .

      N N N B / / C / / C C R N / B B B B B D N / B B B B B D / C C R
      / / / I T H O S D L L C / H I I I I I O / H I I I I I O D L L C
      C C C T R O M T O O O   C L T T T T T N C L T T T T T N O O O
            5 A L P A N C C     D 4 3 2 1 0 E   D 4 3 2 1 0 E N C C
              C D A R E K K                                   E K K
              K   R T _ 2 1                                   _ 2 1
                  E   O                                       O
                      C                                       C
```

TB03350S

Signetics

Application Specific Products

AN29
PLHS501 Programmable Macro Logic Primer

Application Note

SUMMARY

The evolution of Programmable Logic Devices (PLD's) has led to the birth of a new generation of programmable devices designated as PML (Programmable Macro Logic). The immense versatility of these devices brings them closer as plausible alternatives to semicustom design approaches in low-to-medium ranges of applications. The following paper begins with a background on PML and a brief description of the PML basic architecture (See Reference 1.) Next, the first PML devices are introduced with a detailed discussion of the PLHS501. The implementation of PML in the AMAZE software package is presented. A system level example intends to demonstrate the capabilities of PML as an eloquent and efficient design alternative.

THE EMERGENCE OF THE THIRD GENERATION PLD ARCHITECTURE

PML was introduced at WESCON '85 by Signetics Corporation. The unique architecture of PML breaks away into a new era of programmable logic devices. The purpose of the PML architecture is to overcome the two level AND-OR bottleneck and provide the user with a higher level of logic integration. Current PLD's rely on two levels of logic transformation to implement combinational logic in Sum-Of-Products (SOP) form. In addition various PLD's make use of higher level macros such as flip-flops to form sequential logic functions. These macros connect the AND-OR chain to dedicated I/O pins.



Figure 1. One of the Latest Registered PALs™

Figure 1 show the basic architecture of one of the most recent PAL™ devices. It is clear that this architecture is inefficient in making full use of the available on-chip resources. This is due to the fact that an unused I/O macro will be wasted and remains futile.

For example, if an I/O pin is used as an input, the output macros are all wasted. Obviously, such an architecture cannot provide the user with an increase in the levels of logic integration. The PML device takes advantage of the fundamental architecture shown in Figure 2 to overcome these deficiencies and waste of on-chip resources. As shown in Figure 2, PML incorporates the NAND-NAND gate equivalence to break the AND-OR bottleneck.

The core of the PML is the programmable NAND-NAND network which connects the input and output macros to each other. Thus the inputs, outputs, and function macros are all connected by a single array.

At the present, two devices are under development which employ the above architecture. Both devices are fabricated by the Signetics state-of-the-art oxide isolation process and are packaged in 52-pin PLCC.

The first device available will be the PLHS501. The seemingly simple structure of this device can implement every logic function furnished by the current PAL™/PLA devices. Although the PLHS501 is principally a combinational logic device, its unique architecture makes it an ideal tool for applications involving asynchronous state machines (See Reference 2.)

The PLHS502 is a sequential logic device. It supplements the PLHS501 features with sixteen edge-triggered flip-flops. The device can provide diverse applications encompassing synchronous and asynchronous state machine designs.

PAL™ is a Trademark of Monolithic Memories, Inc.

Table 1. Functional Description of PLHS501 I/O Pins

PIN NO.	IDENTIFIER	FUNCTION
41-45, 47-52, 1-7, 9-14	I0-I23	Dedicated inputs
37-40	/B0-/B3	Fuse-programmable bidirectional I/Os with Active-Low outputs. Can be configured as open-collector outputs.
15-18	B4-B7	Logic controlled bidirectional I/Os with Active-High Tri-state outputs.
28-29 30-31 32-33 35-36	X0-X1 X2-X3 X4-X5 X6-X7	Pairs of Tri-state Exclusive-OR outputs that have common Output Enable.
19, 21 22-23	O0-O1 O2-O3	Pairs of dedicated Active-Low Tri-state output buffers. Each pair has common Output Enable control.
24-25 26-27	O4-O5 O6-O7	Pairs of dedicated Active-High Tri-state output buffers. Each pair has common Output Enable control.


N × M NAND ARRAY
0
1
2
3
N
0
1
2
3
M
I
INPUT MACRO
O
OUTPUT MACRO (2)
FUNCTION MACRO
OUTPUT MACRO (1)
O
FUNCTION MACRO
LD06820S

Figure 2. PML Fundamental Architecture

THE PLHS501 PML

The PLHS501 architecture in Figure 3 exhibits an exquisite logic tool. The device provides a combination of 72 NAND terms, 24 dedicated inputs (I0-I23), eight bidirectional I/O's (B0-B7), eight exclusive-OR outputs (X0-X7), and eight dedicated outputs (O0-O7). Figure 4 shows the PLHS501 logic diagram and Table 1 illustrates the functional breakdown of the PLHS501 I/O pins.

Since the output of each NAND term feeds back to the inputs of the NAND array, intricate logic functions can be implemented without wasting valuable I/O pins. For example, in order to implement an internal 'RS' latch in a combinational PAL™/PLD, at least two inputs and two outputs are required. The same internal latch can be configured by the PLHS501 without using any I/O pins.



Figure 3. PLHS501 Logic Diagram


I_{17}
I_{11}
I_5
7
1
47
V_{CC} 8
46 V_{CC}
I_{23} 14
40 O_{15}
GND 20
34 GND
21
27
33
$\overline{B}_5$
O_3
O_9
TOP VIEW

CD12980S

Figure 4. PLHS501 Pin Assignments

Figure 5 illustrates how 'RS' and 'D' latches are implemented in the PLHS501.

Another eminent application of the PLHS501 is in generating asynchronous state machines.

The blend of internal feedback paths together with the abundant number of gates makes this device suitable for designing asynchronous state machines which employ propagation delays of feedback paths as memory elements as shown in Figure 6. (See Reference 2.)


INPUT
$\overline{S}$
INPUT
$\overline{R}$
Q
OUTPUT
$\overline{Q}$
OUTPUT
$\overline{S}$
$\overline{R}$
Q
$\overline{Q}$

LD07920S

a. RS Latch


INPUT
D
INPUT
$\overline{LE}$
A
B
C
Q
OUTPUT
D
$\overline{LE}$
$\overline{B}$
Q
$\overline{C}$
$\overline{A}$

LD07910S

b. D Latch

Figure 5. R/S and D Latch Implementation With PML


INPUT 0
INPUT n
OUTPUT 0
OUTPUT m
COMBINATIONAL LOGIC
PRESENT STATE
y0
YO
PROPAGATION DELAY
NEXT STATE
yp
Yp
PROPAGATION DELAY
AF05060S

Figure 6. Model of Asynchronous State Machines Using Propagation Delays of the Feedback Path as Memory Elements

PML DEVELOPMENT SOFTWARE

Programmable logic development software has become an integral part of the PLD design process. Without software tools PLDs become perplexing devices which are inconvenient to use. Development software enables the user to take full advantage of the programmable logic's resources. The complexity of the PML devices makes software an indispensable element in the design process.

The AMAZE PLD design software, as noted in Reference 3, has been developed for Signetics programmable logic devices. PML design and development will be fully supported by AMAZE. Figure 7 shows the AMAZE configuration for supporting PML. The structure of the software is based on the following modules:

.BLAST	(Boolean Logic And State Transfer entry)
.DPI	(Device Programmer Interface)
.SIM	(PLD functional SIMulator)
.PI	(PML Integrator)

The foundation for the above modules is an AMAZE standard fuse file (STD). The STD file is the common means of communication between all the modules. The following paragraphs briefly explain the implementation of PML in the AMAZE structure.

BLAST

The basic elements of BLAST are:

1. Boolean Equation Entry (BEE).
2. State Equation Entry (SEE).
3. Schematic To Boolean Converter (STBC).

1. BEE accepts user defined logic in the form of boolean equations and produces an AMAZE standard fuse file. The boolean notation in BEE will account for the following PML features.

a. The single array architecture provides an option to specify the number of logic (gate) levels that accommodate a specified function. The number of gate levels dictate the delay between the inputs and outputs. The number of logic levels for each function can be specified using the following notation:

LABEL [number of logic levels] = equation; where LABEL is the user designated name of the output pin.

b. Some outputs have more than one gate associated with them (for example registered or EXOR outputs). The input SIDE of these outputs can be specifically defined. For example:

Pin Label: R = eqn;
S = eqn;

c. User definable CLOCK Logic (e.g. as in the PLHS502) can be specified.

d. For PML devices the Sum-of-Products (SOP) can be defined as common terms.


LOGIC SIMULATOR
PML INTEGRATOR
DEVICE PROGRAMMER INTERFACE
DEVICE PROGRAMMER
STANDARD FUSE FILE
BOOLEAN EQUATION ENTRY
STATE EQUATION ENTRY
SCHEMATIC TO BOOLEAN CONVERTER
BLAST
AF05080S

Figure 7. AMAZE Configuration for PML

2. SEE accepts state machine definitions and produces the AMAZE standard fuse file. Particularly, SEE will include asynchronous state machine implementations utilizing the PLHS501.

3. STBC converst schematic netlists produced by CAD systems such as Futurenet^{TM}, Daisy, and Mentor into an AMAZE BEE file. STBC will fully embody the PML in the following manner:

a. De Morgan's theorem is applied to produce equations in SOP form. All the functions in SOP form are then converted into their NAND- NAND equivalent.

b. The converter will determine the polarity and the number of levels in each equation and will automatically determine the correct output polarity.

DPI

Device Programmer Interface provides the interface between the AMAZE standard fuse file and a commercial programmer. It allows the transmission of data to and from the device programmer.

SIM

The functional simulator uses the AMAZE standard fuse file in the following manner:

a. An event driven simulator will assess the delays within the PML in order to properly simulate the pattern.

b. Automatically generates test vectors for the pattern simulation.

PI

The PML Integrator is a conversion that transforms various PAL^{TM} or PLD circuits into a PML device. It will automatically fit multiple PAL^{TM}/PLD devices into a single PML. It is capable of automatically receiving patterns from a commercial device programmer and downloading it back to the programmer after the PML transformation. The implementation of an 'Integrator' will allow the automatic conversion of numerous PAL^{TM}/PLDs into a single PML device.

AMAZE will not be the total extent of development software available for the PML devices. The task of implementing PML design software is already underway by a number of different vendors of CAD software.

PLHS501 DESIGN EXAMPLE

The following example intends to manifest the capabilities of the PLHS501. Figure 8 shows a system formed with TTL logic. The system requirements make it imperative only to use discrete asynchronous latches. Thus, none of the 7 latches in the system can be directly replaced by registers. The system diagram is drafted using Futurenet^{TM} DASH-2 Schematic Designer. The system is partitioned into two PLS173s and one PLS153. In order to convert the system into its targeted PLD's, the PINLIST (see Figures 9a-9c) has to be defined. Using the AMAZE PIN-LIST editor, the specified PLD's are labeled with the same labels as those on the system schematic (Figure 8). After the declaration of labels, AMAZE automatically converts the system to the designated PLDs. The AMAZE generated boolean equation files are shown in Figures 9a, 9b, and 9c. Figure 10 shows the overall system implemented with PLDs. The logic condensation capabilities of PML makes it feasible to replace the whole system by a single PLHS501 (Figure 11). The PLHS501 in this design will still have ample space for any future additions.

The above example demonstrates only part of the PLHS501 capabilities. The introduction of PML devices and their immense logic power will pave the way for a new generation of efficient and elegant systems.

REFERENCES

1. Cavlan, Napoleone 1985. "Third Generation PLD Architecture Breaks AND-OR Bottleneck", WESCON 1985 Conference Proceedings.

2. Wong, David K. "Third Generation PLS Architecture and its Applications", Electro 1986 Conference Proceedings.

3. "1986 PLD Data Manual", Signetics Corporation.


OUT1A
OUT3B
OT3AIN1F
OUT2A
OT2FIN3I
OUT3C
OT2GIN3E
OUT1I
OUT1D
OUT3F
OT3E1N1K
OT3AIN1F
OUT2B
OUT2A
OUT2C
OT2FIN3D
OT3D
OUT2B
OT3H
OT3G
OT1F
OT1C
OT1BIN3A
OT1EIN3B
OUT1
OUT1H
OT2CIN1M
OUT2E
1N1A
1N1B
1N1I
1N1D
1N1E
1N2B
1N1G
1N1H
1N3C
1N1J
1N1L
1N2C
LD07930S

Figure 8. System Implemented With TTL Logic

```
####################### P I N   L I S T #######################

   LABEL      ** FNC **PIN ----------- PIN** FNC **     LABEL
IN1A          ** I   **  1-|         |-24 ** +5V **VCC
IN1B          ** I   **  2-|         |-23 ** O   **OUT1I
OT3G          ** I   **  3-|         |-22 ** O   **OUT1H
IN1D          ** I   **  4-|    P    |-21 ** O   **OUT1G
IN1E          ** I   **  5-|    L    |-20 ** O   **OT1F
OT3AIN1F      ** I   **  6-|    S    |-19 ** O   **OT1EIN3B
IN1G          ** I   **  7-|    1    |-18 ** O   **OUT1D
IN1H          ** I   **  8-|    7    |-17 ** O   **OT1C
IN1I          ** I   **  9-|    3    |-16 ** O   **OT1BIN3A
IN1J          ** I   ** 10-|         |-15 ** O   **OUT1A
OT3EIN1K      ** I   ** 11-|         |-14 ** I   **OT2CIN1M
GND           ** OV  ** 12-|         |-13 ** I   **IN1L
                           -----------
```

```
@DEVICE TYPE
 PLS173
@DRAWING
@REVISION
@DATE
@SYMBOL
@COMPANY
@NAME
 PART1
@DESCRIPTION
@I/O DIRECTION
@LOGIC EQUATION
     OUT1A =/IN1A*/IN1B*(IN1J+/OT3AIN1F);
     OT1BIN3A =/IN1B*IN1I;
     OT1C =/IN1H+OT2CIN1M+/IN1D*/OT3AIN1F+OT3EIN1K;
     OUT1D =IN1B+/IN1J;
     OT1EIN3B =/IN1B*IN1J+OT2CIN1M+/OT3G*IN1A+/IN1A*/IN1G;
     OT1F =OT2CIN1M*/IN1G*/IN1L;
     OUT1G =OT2CIN1M+/IN1G*IN1E+IN1B+/OT3G*IN1A;
     OUT1H =/IN1H*(IN1E)+OT3AIN1F+/IN1A+IN1B+IN1D;
     OUT1I =(/IN1E)*OT3G;
```

```
PLS173                                        !     POLARITY      !
                                              -------------------
T !                                           !H:H:H:H:H:H:H:H:H:H!
E !-----------------------------------------------------------------
R !           I           !        B(i)       !        B(o)       !
M !1 1 -------------------------------------------------------------
  !1 0 9 8 7 6 5 4 3 2 1 0!9 8 7 6 5 4 3 2 1 0!9 8 7 6 5 4 3 2 1 0!
 0!- - H -,- - - -,- - L L!- -,- - - -,- - - -!. .,. . . .,. . A A!
 1!- - - -,- - L -,- - L L!- -,- - - -,- - - -!. .,. . . .,. . A A!
 2!- - - H,- - - -,- - L -!- -,- - - -,- - - -!. .,. . . .,. A . A!
 3!- - - -,L - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,A . . A!
 4!- - - -,- - - -,- - - -!- -,- - - -,- - - H!. .,A . A .,A . . A!
 5!- - - -,- - L -,L - - -!- -,- - - -,- - - -!. .,. . . .,A . . A!
 6!- H - -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . .,A . . A!
 7!- - - -,- - - -,- - H -!- -,- - - -,- - - -!. A,A . . A,. . . A!
 8!- - L -,- - - -,- - - -!- -,- - - -,- - - -!. .,. . . A,. . . A!
 9!- - H -,- - - -,- - L -!- -,- - - -,- - - -!. .,. . A .,. . . A!
10!- - - -,- - - -,- L - H!- -,- - - -,- - - -!. .,A . A .,. . . A!
11!- - - -,- L - -,- - - L!- -,- - - -,- - - -!. .,. . A .,. . . A!
12!L - - -,- L - -,- - - -!- -,- - - -,- - - H!. .,. A . .,. . . A!
13!- - - -,- L - H,- - - -!- -,- - - -,- - - -!. .,A . . .,. . . A!
14!- - - -,L - - H,- - - -!- -,- - - -,- - - -!. A,. . . .,. . . A!
15!- - - -,- - H -,- - - -!- -,- - - -,- - - -!. A,. . . .,. . . A!
16!- - - -,- - - -,- - - L!- -,- - - -,- - - -!. A,. . . .,. . . A!
17!- - - -,- - - -,H - - -!- -,- - - -,- - - -!. A,. . . .,. . . A!
18!- - - -,- - - L,- H - -!- -,- - - -,- - - -!A .,. . . .,. . . A!
19!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
20!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
21!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
22!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
23!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
24!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
25!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
26!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
27!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
28!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
29!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
30!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
31!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
D9!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D8!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D7!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D6!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D5!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D4!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D3!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D2!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D1!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                   .
D0!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                   .

   I O I I I I O I I O I I O O O O O O O O O O O O O O O O O O O O
   N T N N N N T N N T N N U U U T T U T T U T U U U T T U T T U T
   1 3 1 1 1 1 3 1 1 3 1 1 T T T 1 1 T 1 1 T 2 T T T 1 1 T 1 1 T 2
   L E J I H G A E D G B A 1 1 1 F E 1 C B 1 C 1 1 1 F E 1 C B 1 C
     I         I           I H G   I D   I A I I H G   I D   I A I
     N         N                   N     N   N         N     N   N
     1         1                   3     3   1         3     3   1
     K         F                   B     A   M         B     A   M
```

Figure 9. Part 1: PLS173

```
####################### P I N   L I S T #######################

   LABEL      ** FNC **PIN ---------- PIN** FNC **      LABEL
IN1A          ** I   **   1-!          !-24 ** +5V **VCC
IN2B          ** I   **   2-!          !-23 ** B   **N/C
IN2C          ** I   **   3-!          !-22 ** B   **N/C
IN1G          ** I   **   4-!    P     !-21 ** O   **OT2GIN3E
IN1I          ** I   **   5-!    L     !-20 ** O   **/OT2FIN3D
IN1J          ** I   **   6-!    S     !-19 ** O   **OT2CIN1M
IN1B          ** I   **   7-!    1     !-18 ** O   **OUT2E
OUT1G         ** I   **   8-!    7     !-17 ** O   **OUT2D
OUT1H         ** I   **   9-!    3     !-16 ** O   **OUT2C
OT1C          ** I   **  10-!          !-15 ** O   **OUT2B
OT3AIN1F      ** I   **  11-!          !-14 ** /O  **/OUT2A
GND           ** OV  **  12-!          !-13 ** I   **OT3G
                            ----------
```

```
@DEVICE TYPE
 PLS173
@DRAWING
@REVISION
@DATE
@SYMBOL
@COMPANY
@NAME
 PART2
@DESCRIPTION
@I/O DIRECTION
@LOGIC EQUATION
     /OUT2A =/((OUT2B*/OUT1G));
     OUT2B =OUT1H+OUT2A;
     OUT2C =OT2CIN1M+/IN1G+OT2FIN3D;
     OUT2D =OT3AIN1F*/IN1G+(/OT3AIN1F*((IN1B+/IN1J)*/IN1I))*IN1B
           +(OT2FIN3D*/OT3G*/IN1A)*((/IN1A*/IN1B*(IN1J+/OT3AIN1F))
           *(/IN1B*IN1J))+/OT2GIN3E;
     OUT2E =/OT2CIN1M*/IN2C;
     OT2CIN1M =IN1G*/OUT2E;
     /OT2FIN3D =/((OUT2C*(IN2B)));
     OT2GIN3E =/OUT2D+OT1C;
```

```
 PLS173                                        !     POLARITY      !
                                               ---------------------
 T !                                           !H:H:H:H:H:H:H:H:H:L!
 E !----------------------------------------------------------------
 R !           I           !       B(i)        !       B(o)        !
 M !1 1 ------------------------------------------------------------
   !1 0 9 8 7 6 5 4 3 2 1 0!9 8 7 6 5 4 3 2 1 0!9 8 7 6 5 4 3 2 1 0!
  0!- - - -,L - - -,- - - -!- -,- - - -,- - H -!A A,. . . .,. . . A!
  1!- - - H,- - - -,- - - -!- -,- - - -,- - - -!A A,. . . .,. . A .!
  2!- - - -,- - - -,- - - -!- -,- - - -,- - - L!A A,. . . .,. . A .!
  3!- - - -,- - - -,- - - -!- -,- - H -,- - - -!A A,. . . .,. A . .!
  4!- - - -,- - - -,L - - -!- -,- - - -,- - - -!A A,. . . .,. A . .!
  5!- - - -,- - - -,- - - -!- -,- L - -,- - - -!A A,. . . .,. A . .!
  6!- H - -,- - - -,L - - -!- -,- - - -,- - - -!A A,. . . .,A . . .!
  7!- L - -,- H - L,- - - -!- -,- - - -,- - - -!A A,. . . .,A . . .!
  8!- L - -,- H L L,- - - -!- -,- - - -,- - - -!A A,. . . .,A . . .!
  9!L L - -,- L H -,- - - L!- -,- L - -,- - - -!A A,. . . .,A . . .!
 10!L - - -,- L H -,- - - L!- -,- L - -,- - - -!A A,. . . .,A . . .!
 11!- - - -,- - - -,- - - -!- -,L - - -,- - - -!A A,. . . .,A . . .!
 12!- - - -,- - - -,- L - -!- -,- - L -,- - - -!A A,. . . A,. . . .!
 13!- - - -,- - - -,H - - -!- -,- - - L,- - - -!A A,. . A .,. . . .!
 14!- - - -,- - - -,- - - -!- -,- - - -,- L - -!A A,. A . .,. . . .!
 15!- - - -,- - - -,- - L -!- -,- - - -,- - - -!A A,. A . .,. . . .!
 16!- - - -,- - - -,- - - -!- -,- - - -,L - - -!A A,A . . .,. . . .!
 17!- - H -,- - - -,- - - -!- -,- - - -,- - - -!A A,A . . .,. . . .!
 18!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 19!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 23!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D8!0 0 0 0,0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D7!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D6!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D5!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D4!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D3!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D2!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D1!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .
 D0!- - - -,- - - -,- - - -!- -,- - - -,- - - -!                  .

    O O O O O I I I I I I I N N O / O O O O O / N N O / O O O O O /
    T T T U U N N N N N N N / / T O T U U U U O / / T O T U U U U O
    3 3 1 T T 1 1 1 1 2 2 1 C C 2 T 2 T T T T U C C 2 T 2 T T T T U
    G A C 1 1 B J I G C B A     G 2 C 2 2 2 2 T     G 2 C 2 2 2 2 T
      I   H G                   I F I E D C B 2     I F I E D C B 2
      N                         N I N         A     N I N         A
      1                         3 N 1               3 N 1
      F                         E 3 M               E 3 M
                                  D                   D
```

Figure 9b. Part 2: PLS173

```
######################## P I N   L I S T ########################

    LABEL      ** FNC **PIN ---------- PIN** FNC **      LABEL
OT1BIN3A       ** I   **   1-|         |-20 ** +5V **VCC
OT1EIN3B       ** I   **   2-|         |-19 ** B   **N/C
IN3C           ** I   **   3-|    P    |-18 ** B   **N/C
OT2IN3D        ** I   **   4-|    L    |-17 ** O   **OT3H
OT2GIN3E       ** I   **   5-|    S    |-16 ** /O  **/OT3G
OT1F           ** I   **   6-|    1    |-15 ** O   **OUT3F
IN1L           ** I   **   7-|    5    |-14 ** O   **OT3EIN1K
IN1H           ** I   **   8-|    3    |-13 ** O   **OUT3D
/OT3AIN1F      ** /O  **   9-|         |-12 ** O   **OUT3C
GND            ** OV  **  10-|         |-11 ** I   **IN1G
                             ----------
```

```
@DEVICE TYPE
PLS153
@DRAWING
@REVISION
@DATE
@SYMBOL
@COMPANY
@NAME
@DESCRIPTION
@COMMON PRODUCT TERM
@I/O DIRECTION
@OUTPUT POLARITY
@LOGIC EQUATION
```

```
Cust/Project  -
Date          -
Rev/I. D.     -

PLS153                                 !     POLARITY      !
---                                    ---------------------
 T !                                   !H:H:H:L:H:H:H:H:H:L!
 E !--------------------------------------------------------
 R !       I       !        B(i)       !       B(o)        !
 M !--------------------------------------------------------
   !7 6 5 4 3 2 1 0!9 8 7 6 5 4 3 2 1 0!9 8 7 6 5 4 3 2 1 0!
  0!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  1!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  2!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  3!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  4!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  5!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  6!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  7!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  8!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
  9!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 10!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 11!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 12!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 13!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 14!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 15!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 16!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 17!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 18!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 19!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 20!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 21!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 22!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 23!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 24!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 25!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 26!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 27!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 28!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 29!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 30!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 31!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!A A,A A A A,A A A A!
 D9!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D8!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D7!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D6!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D5!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D4!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D3!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D2!- - - -,- - - -!- -,- - - -,- - - -!                  .
 D1!0 0 0 0,0 0 0 0!0 0,0 0 0 0,0 0 0 0!                  .
 D0!- - - -,- - - -!- -,- - - -,- - - -!                  .

    I I O O O I O O N N O / O O O O I / N N O / O O O O I /
    N N T T T N T T / / T O U T U U N O / / T O U T U U N O
    1 1 1 2 2 3 1 1 C C 3 T T 3 T T 1 T C C 3 T T 3 T T 1 T
    H L F G I C E B     H 3 3 E 3 3 G 3     H 3 3 E 3 3 G 3
          I N   I I       G F I D C   A       G F I D C   A
          N 3   N N           N       I           N       I
          3 D   3 3           1       N           1       N
          E     B A           K       1           K       1
                                      F                   F
```

Figure 9c. Part 3: PLS153


IN1A
IN1B
IN1D
IN1E
IN1G
IN1H
IN1I
IN1J
IN1L
IN2B
IN2C
IN3C
PLS173 PART 1
IN1A
IN1B
OT3G
IN1D
IN1E
OT3AIN1F
IN1G
IN1H
IN1I
IN1J
OT3EIN1K
GND
VCC
OUT1I
OUT1H
OUT1G
OT1F
OT1EIN3B
OUT1D
OT1C
OT1BIN3A
OUT1A
OT2CIN1M
IN1L
OUT1I
OUT1D
OUT1A
PLS173 PART 2
IN1A
IN2B
IN2C
IN1G
IN1I
IN1J
IN1B
OUT1G
OUT1H
OT1C
OT3AIN1F
GND
VCC
B
B
OT2GIN3E
OT2FIN3D
OT2CIN1M
OUT2E
OUT2D
OUT2C
OUT2B
OUT2A
OT3G
OT2GIN3E
OUT2A
PLS153 PART 3
OT1BIN3A
OT1EIN3B
IN3C
OT2FIN3D
OT2GIN3E
OT1F
IN1L
IN1H
OT3AIN1F
GND
VCC
B
B
OT3H
OT3G
OUT3F
OT2EIN1K
OUT3D
OUT3C
IN1G
OT3G
OUT3F
OUT3D
OUT3C
OT3AIN1F
CD12990S

Figure 10. System in Figure 8 Implemented With PLD's


IN1A
IN1B
IN1D
IN1E
IN1G
IN1H
IN1I
IN1J
IN1L
IN2B
IN2C
IN3C
V_{CC}
V_{CC}
OUT1A
OUT1D
OUT1I
OUT2A
OT2GIN3E
GND
GND
OT3AIN1F
OT3G
OUT3C
OUT3D
OUT3F
I/Ō
O
O_x
CD13000S

Figure 11. System in Figure 10 Implemented With PLHS501

Section 10
Package Outlines

INDEX

Section 10

Package Outlines

A PLASTIC: Leaded Chip Carrier 10-3
F CERAMIC: Dual-In-Line 10-5
FA CERAMIC: Dual-In-Line With Quartz Window 10-7
N PLASTIC: Dual-In-Line 10-9

Package Outlines

PLASTIC PLCC

1. Package dimensions conform to JEDEC specifications for standard Leaded Chip Carrier outline (PLCC) package.
2. Controlling dimensions are given in inches with dimensions in millimeters contained in parentheses.
3. Dimensions and tolerancing per ANSI Y14.5M - 1982.
4. "D-E" and "F-G" are reference datums on the molded body and do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm (0.006") on any side.
5. Pin numbers start with pin #1 and continue counterclockwise when viewed from the top.
6. Lead material: Olin 194 (Copper Alloy) or equivalent, solder dipped.
7. Body material: Plastic (Epoxy).
8. Thermal resistance values are determined by temperature sensitive parameter (TSP) method. This method uses the forward voltage drop of a calibrated diode to measure the change in junction temperature due to a known power application. Test condition for these values follow:

   Test Ambient — Still Air
   Test Fixture — θ_{JA} - Glass epoxy test board (2.24" × 2.24" × 0.062".)
   θ_{JC} - Water cooled heat sink

PLASTIC LEADED CHIP CARRIER (PLCC)

NO. OF LEADS	PACKAGE CODE	DESCRIPTION
20	A	350mil-wide
28	A	450mil-wide
52	A	750mil-wide

TYPICAL θ_{JA}/θ_{JC} VALUES (°C/W)			
Die Size	**Power Dissipation (W)**	**Average θ_{JA}**	**Average θ_{JC}**
20K	.75	70	30
25K	1.0	61	23
50K	1.0	42	15

20-PIN PLASTIC PLCC (A PACKAGE)



.395 (10.03)
.385 (9.78)
B D-E Ⓢ .007 (0.18) Ⓢ
⊥ B Ⓢ .002 IN/IN
-A-
.010 (.25) MAX. R TYP. 3 PLACES
A F-G Ⓢ .007 (0.18) Ⓢ
.200 (5.08) BSC
B D-E Ⓢ .007 (0.18) Ⓢ
-G-
-D-
.356 (9.04)
.350 (8.89)
PIN #1
.200 (5.08) BSC
.395 (10.03)
.385 (9.78)
-E-
.048 (1.22)
.042 (1.07) X 45°
-F-
.050 (1.27) BSC 4 SIDES
A F-G Ⓢ .007 (0.18) Ⓢ
⊥ A Ⓢ .002 IN/IN
-B-
.356 (9.04)
.350 (8.89)
.056 (1.42)
.042 (1.07) X 45°
.032 (.81)
.026 (.66)
.060 (1.52) MIN
0.025 (0.64) MIN
-H-
-C-
.004 (.10)
.120 (3.05)
.090 (2.29)
.180 (4.57)
.165 (4.19)
.021 (.53)
.013 (.33)
D-E Ⓢ F-G Ⓢ .007 (0.18) Ⓜ
.045 (1.14)
.025 (0.64) R
.330 (8.38)
.290 (7.37)
⊕ F-G .015 (.38)
.015 (.38)
.005 (.13)
SEATING PLANE
.198 (5.03)
.194 (4.93)
A B Ⓢ .010 (0.25) Ⓛ
.330 (8.38)
.290 (7.37)
⊕ D-E Ⓢ .015 (.38)

853-0400 84711

PO00633S

NOTES:

1. Package dimensions conform to JEDEC specification MO-047-AA for plastic leaded chip carrier 20 leads, .050 inch lead spacing, square. (issue A, 10/31/84).
2. Controlling dimensions: inches. Metric are shown in parentheses.
3. Dimensions and tolerancing per ANSI Y14.5M-1982.
4. "A" and "B" are reference datums on the molded body at plane "H" and do not include mold flash. Mold flash protrusion shall not exceed .006" (.15mm) on any side.
5. Datum "D-E" and "F-G" are determined where these center leads exit from the body at plane "H".
6. Pin numbers continue counterclockwise to pin #20 (top view).
7. Signetics order code for product packaged in a PLCC is the suffix A after the product number.

Package Outlines

28-PIN PLASTIC PLCC (A PACKAGE)


.495 (12.57)
.485 (12.32)
A F-G S .007 (0.18) S
.300 (7.62) BSC
B D-E S .007 (0.18) S
B D-E S .007 (0.18) S
⊥ B S .002 IN/IN
-A-
-G-
.010 (.25)
MAX. R
TYP. 3 PLACES
.456 (11.58)
.450 (11.43)
PIN #1
-D-
-E-
.300 (7.62) BSC
.495 (12.57)
.485 (12.32)
.048 (1.22)
.042 (1.07)
X 45°
-F-
.050 (1.27) BSC
4 SIDES
.060 (1.52)
MIN.
A F-G S .007 (0.18) S
⊥ A S .002 IN/IN
-B-
.456 (11.58)
.450 (11.43)
.025 (0.64)
MIN.
.032 (.81)
.026 (.66)
.056 (1.42)
.042 (1.07)
X 45°
.120 (3.05)
.090 (2.29)
-H-
-C-
.004 (.10)
.180 (4.57)
.165 (4.19)
.021 (.53)
.013 (0.33)
D-E S F-G S .007 (0.18) M
.045 (1.14)
.025 (0.64)
R
.430 (10.92)
.390 (9.96)
F-G S .015 (.38)


.015 (0.38)
.005 (0.13)
SEATING
PLANE
.224 (5.69)
.218 (5.54)
A B S .010 (0.25) L
.430 (10.92)
.390 (9.91)
D-E S .015 (.30)

NOTES:
1. Package dimensions conform to JEDEC specification MO-047-AB for plastic leaded chip carrier 28 leads, .050 inch lead spacing, square. (issue A, 10/31/84).
2. Controlling dimensions: inches. Metric are shown in parentheses.
3. Dimensions and tolerancing per ANSI Y14.5M-1982.
4. "A" and "B" are reference datums on the molded body at plane "H" and do not include mold flash. Mold flash protrusion shall not exceed .006" (.15mm) on any side.
5. Datum "D-E" and "F-G" are determined where these center leads exit from the body at plane "H".
6. Pin numbers continue counterclockwise to pin #28 (top view).
7. Signetics order code for product packaged in a PLCC is the suffix A after the product number.

853-0401 84711

PO00613S

52-PIN PLASTIC PLCC (A PACKAGE)


B D-E S .007 (0.18) S
⊥ B S .002 IN/IN
-A-
.795 (20.19)
.785 (19.94)
A F-G S .007 (0.18) S
.600 (15.24) BSC
B D-E S .007 (0.18) S
-G-
.010 (.25)
MAX. R
TYP. 3 PLACES
.756 (19.20)
.750 (19.05)
.600 (15.24)
BSC
PIN #1
-D-
-E-
.795 (20.19)
.785 (19.94)
-F-
.048 (1.22)
.042 (1.07)
X 45°
.050 (1.27) BSC
4 SIDES
.060 (1.52)
MIN
A F-G S .007 (0.18) S
⊥ A S .002 IN/IN
-B-
.756 (19.20)
.750 (19.05)
0.025 (0.64)
MIN
.056 (1.42)
.042 (1.07)
X 45°
.032 (.81)
.026 (.66)
.120 (3.05)
.090 (2.29)
-H-
-C-
.004 (.10)
.180 (4.57)
.165 (4.19)
.021 (0.53)
.013 (0.33)
D-E S F-G S .007 (0.18) M
.045 (1.14)
.025 (0.64)
R
.730 (18.54)
.690 (17.53)
F-G S .015 (.38)


.015 (0.38)
.005 (0.13)
SEATING
PLANE
.364 (9.25)
.358 (9.09)
A B S .010 (0.25) L
.730 (18.54)
.690 (17.53)
D-E S .015 (.38)

NOTES:
1. Package dimensions conform to JEDEC specification MO-047-AA for plastic leaded chip carrier 20 leads, .050 inch lead spacing, square. (issue A, 10/31/84).
2. Controlling dimensions: inches. Metric are shown in parentheses.
3. Dimensions and tolerancing per ANSI Y14.5M-1982.
4. "A" and "B" are reference datums on the molded body at plane "H" and do not include mold flash. Mold flash protrusion shall not exceed .006" (.15mm) on any side.
5. Datum "D-E" and "F-G" are determined where these center leads exit from the body at plane "H".
6. Pin numbers continue counterclockwise to pin #20 (top view).
7. Signetics order code for product packaged in a PLCC is the suffix A after the product number.

853-0397 84711

PO00643S

Package Outlines

HERMETIC CERDIP

1. Package dimensions conform to JEDEC specifications for standard Ceramic Dual Inline (Cerdip) package.
2. Controlling dimensions are given in inches with dimensions in millimeters, mm, contained in parentheses.
3. Dimensions and tolerancing per ANSI Y14.5M - 1982.
4. Pin numbers start with pin #1 and continue counterclockwise when viewed from the top.
5. These dimensions measured with the leads constrained to be perpendicular to plane T.
6. Lead material: ASTM alloy F-30 (Alloy 42) or equivalent – tin plated or solder dipped.
7. Body Material: Ceramic with glass seal at leads.
8. Thermal resistance values are determined by temperature sensitive parameter (TSP) method. This method uses the forward voltage drop of a calibrated diode to measure the change in junction temperature due to a known power application. Test condition for these values follow:

   Test Ambient — Still Air
   Test Fixture — θ_{JA} – Textool ZIF socket with 0.04″ standoff
   θ_{JC} – Water cooled heat sink

HERMETIC DUAL-IN-LINE PACKAGES

NO. OF LEADS	PACKAGE CODE	DESCRIPTION
20	F	300mil-wide
24	F	300mil-wide
28	F	600mil-wide

TYPICAL θ_{JA}/θ_{JC} VALUES (°C/W)			
Die Size	Power Dissipation (W)	Average θ_{JA}	Average θ_{JC}
20K	.75	70	7.8
25K	1.0	62	6.9
30K	1.0	48	6.3

20-PIN CERAMIC DIP (F PACKAGE)


.078 (1.98)
.012 (.30)
.078 (1.98)
.012 (.30)
-E-
.306 (7.77)
.285 (7.24)
PIN # 1
.100 (2.54) BSC
-D-
.975 (24.73)
.940 (23.88)
.058 (1.47)
.030 (.76)
.070 (1.78)
.050 (1.27)
-T-
SEATING PLANE
.200 (5.08)
.165 (4.19)
.165 (4.19)
.125 (3.18)
.023 (.58)
.015 (.38)
T E D S .010 (.254) M
.320 (8.13)
.290 (7.37)
(NOTE 4)
.175 (4.45)
.145 (3.68)
.035 (.89)
.020 (.51)
BSC
.300 (7.62)
(NOTE 4)
.015 (.38)
.010 (.25)
.395 (10.03)
.300 (7.62)
853-0584 81594
PO00430S

NOTES:
1. Controlling dimension: inches. Millimeters are shown in parentheses.
2. Dimensions and tolerancing per ANSI Y14.5M - 1982.
3. "T", "D", and "E" are reference datums on the body and include allowance for glass overrun and meniscus on the seal line, and lid to base mismatch.
4. These dimensions measured with the leads constrained to be perpendicular to plane T.
5. Pin numbers start with pin #1 and continue counterclockwise to pin #20 when viewed from the top.

Package Outlines

24-PIN CERAMIC DIP (F PACKAGE)


.098 (2.49)
.030 (.76)
SEE NOTE 6
.098 (2.49)
.030 (.76)
-E-
.306 (7.77)
.285 (7.24)
PIN # 1
.100 (2.54) BSC
-D-
1.280 (32.51)
1.240 (31.40)
.070 (1.47)
.050 (.76)
-T-
SEATING PLANE
.200 (5.08)
.165 (4.19)
.165 (4.19)
.125 (3.18)
.175 (4.45)
.145 (3.68)
.320 (8.13)
.290 (7.37)
(NOTE 4)
.035 (.89)
.020 (.51)
BSC
.300 (7.62)
(NOTE 4)
.015 (.38)
.010 (.25)
.395 (10.03)
.300 (7.62)
.023 (.58)
.015 (.38)
⊕ T E D Ⓢ .010 (.254) Ⓜ

NOTES:
1. Controlling dimension: inches. Millimeters are shown in parentheses.
2. Dimensions and tolerancing per ANSI Y14.5M – 1982.
3. "T", "D", and "E" are reference datums on the body and include allowance for glass overrun and meniscus on the seal line, and lid to base mismatch.
4. These dimensions measured with the leads constrained to be perpendicular to plane T.
5. Pin numbers start with pin #1 and continue counterclockwise to pin #24 when viewed from the top.
6. Denotes window location for EPROM products.

853-0586 84000

PO00402S

28-PIN CERAMIC DIP (F PACKAGE)


.098 (2.49)
.040 (1.02)
SEE NOTE 6
.098 (2.49)
.040 (1.02)
-E-
.598 (15.19)
.514 (13.06)
PIN # 1
.100 (2.54) BSC
-D-
1.485 (37.72)
1.440 (36.58)
.070 (1.78)
.050 (1.27)
-T-
SEATING PLANE
.225 (5.72) max.
.165 (4.19)
.125 (3.18)
.175 (4.45)
.145 (3.68)
.620 (15.75)
.590 (14.99)
(NOTE 4)
.055 (1.40)
(.020 (.51)
.600 (15.24) BSC
(NOTE 4)
.015 (.38)
.010 (.25)
.695 (17.65)
.600 (15.24)
.023 (.58)
.015 (.38)
⊕ T E D Ⓢ .010 (.254) Ⓜ

NOTES:
1. Controlling dimension: inches. Millimeters are shown in parentheses.
2. Dimensions and tolerancing per ANSI Y14.5M – 1982.
3. "T", "D", and "E" are reference datums on the body and include allowance for glass overrun and meniscus on the seal line, and lid to base mismatch.
4. These dimensions measured with the leads constrained to be perpendicular to plane T.
5. Pin numbers start with pin #1 and continue counterclockwise to pin #28 when viewed from the top.
6. Denotes window location for EPROM products.

853-0589 84000

PO00391S

Package Outlines

HERMETIC CERDIP WITH QUARTZ WINDOW

1. Package dimensions conform to JEDEC specifications for standard Ceramic Dual Inline (Cerdip) package.
2. Controlling dimensions are given in inches with dimensions in millimeters, mm, contained in parentheses.
3. Dimensions and tolerancing per ANSI Y14.5M - 1982.
4. Pin numbers start with pin #1 and continue counterclockwise when viewed from the top.
5. These dimensions measured with the leads constrained to be perpendicular to plane T.
6. Lead material: ASTM alloy F-30 (Alloy 42) or equivalent – tin plated or solder dipped.
7. Body Material: Ceramic with glass seal at leads.
8. Thermal resistance values are determined by temperature sensitive parameter (TSP) method. This method uses the forward voltage drop of a calibrated diode to measure the change in junction temperature due to a known power application. Test condition for these values follow:

   Test Ambient — Still Air
   Test Fixture — θ_{JA} – Textool ZIF socket with 0.04″ standoff
   θ_{JC} – Water cooled heat sink

HERMETIC DUAL-IN-LINE PACKAGES WITH QUARTZ WINDOW

NO. OF LEADS	PACKAGE CODE	DESCRIPTION
24	F	300mil-wide
28	F	600mil-wide

TYPICAL θ_{JA}/θ_{JC} VALUES (°C/W)			
Die Size	**Power Dissipation (W)**	**Average θ_{JA}**	**Average θ_{JC}**
25K	.5	67	7.8
30K	.5	52	7.0

24-PIN CERAMIC DIP WITH QUARTZ WINDOW (FA PACKAGE)


.098 (2.49)
.030 (.76)
SEE NOTE 6
.098 (2.49)
.030 (.76)
-E-
.306 (7.77)
.285 (7.24)
PIN # 1
.100 (2.54) BSC
-D-
1.280 (32.51)
1.240 (31.40)
.070 (1.47)
.050 (.76)
-T-
SEATING PLANE
.200 (5.08)
.165 (4.19)
.165 (4.19)
.125 (3.18)
.023 (.58)
.015 (.38)
⊕ T E D Ⓢ .010 (.254) Ⓜ


.320 (8.13)
.290 (7.37)
(NOTE 4)
.175 (4.45)
.145 (3.68)
.035 (.89)
.020 (.51)
BSC
.300 (7.62)
(NOTE 4)
.015 (.38)
.010 (.25)
.395 (10.03)
.300 (7.62)

NOTES:
1. Controlling dimension: inches. Millimeters are shown in parentheses.
2. Dimensions and tolerancing per ANSI Y14.5M - 1982.
3. "T", "D", and "E" are reference datums on the body and include allowance for glass overrun and meniscus on the seal line, and lid to base mismatch.
4. These dimensions measured with the leads constrained to be perpendicular to plane T.
5. Pin numbers start with pin #1 and continue counterclockwise to pin #20 when viewed from the top.
6. Denotes window location for EPROM products.

853-0586 84000

PO00402S

Package Outlines

28-PIN CERAMIC DIP WITH QUARTZ WINDOW (FA PACKAGE)


SEE NOTE 6
.098 (2.49)
.040 (1.02)
.098 (2.49)
.040 (1.02)
-E-
.598 (15.19)
.514 (13.06)
PIN # 1
.100 (2.54) BSC
-D-
1.485 (37.72)
1.440 (36.58)
.070 (1.78)
.050 (1.27)
.175 (4.45)
.145 (3.68)
.620 (15.75)
.590 (14.99)
(NOTE 4)
-T-
SEATING PLANE
.225 (5.72) max.
.165 (4.19)
.125 (3.18)
.055 (1.40)
(.020 (.51)
.015 (.38)
.010 (.25)
.600 (15.24) BSC
(NOTE 4)
.023 (.58)
.015 (.38)
T E D S .010 (.254) M
.695 (17.65)
.600 (15.24)
853-0589 84000
P00391S

NOTES:

1. Controlling dimension: inches. Millimeters are shown in parentheses.
2. Dimensions and tolerancing per ANSI Y14.5M – 1982.
3. "T", "D", and "E" are reference datums on the body and include allowance for glass overrun and meniscus on the seal line, and lid to base mismatch.
4. These dimensions measured with the leads constrained to be perpendicular to plane T.
5. Pin numbers start with pin #1 and continue counterclockwise to pin #24 when viewed from the top.
6. Denotes window location for EPROM products.

Package Outlines

PLASTIC DIP

1. Package dimensions conform to JEDEC specification MS-001-AA for standard Plastic Dual Inline (DIP) package.
2. Controlling dimensions are given in inches with dimensions in millimeters, mm, contained in parentheses.
3. Dimensions and tolerancing per ANSI Y14.5M - 1982.
4. "T", "D" and "E" are reference datums on the molded body and do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.01 inch (0.25mm) on any side.
5. These dimensions measured with the leads constrained to be perpendicular to plane T.
6. Pin numbers start with pin #1 and continue counterclockwise when viewed from the top.
7. Lead material: Olin 194 (Copper Alloy) or equivalent, solder dipped.
8. Body material: Plastic (Epoxy)
9. Thermal resistance values are determined by temperature sensitive parameter (TSP) method. This method uses the forward voltage drop of a calibrated diode to measure the change in junction temperature due to a known power application. Test condition for these values follow:

Test Ambient — Still Air
Test Fixture — θ_{JA} – Textool ZIF socket with 0.04″ standoff
θ_{JC} – Water cooled heat sink

PLASTIC DUAL-IN-LINE PACKAGES

NO. OF LEADS	PACKAGE CODE	DESCRIPTION
20	N	Cu. Lead Frame 300mil-wide
24	N	Cu. Lead Frame 300mil-wide
28	N	Cu. Lead Frame 600mil-wide

TYPICAL θ_{JA}/θ_{JC} VALUES (°C/W)			
Die Size	**Power Dissipation (W)**	**Average θ_{JA}**	**Average θ_{JC}**
20K	.75	61	25
25K	1.0	55	25
50K	1.0	46	18

20-PIN PLASTIC (N PACKAGE)


⊕ D Ⓢ .004 (.10)
-E-
PIN #1
.255 (6.48)
.245 (6.22)
.100 (2.54) BSC
1.057 (26.85)
1.045 (26.54)
-D-
.064 (1.63)
.045 (1.14)
.160 (4.06)
.135 (3.43)
-T-
SEATING PLANE
.138 (3.51)
.120 (3.05)
.022 (.56)
.017 (.43)
⊕ T E D Ⓢ .010 (.25) Ⓜ
.322 (8.18)
.300 (7.62)
(NOTE 5)
.125 (3.18)
.115 (2.92)
.035 (.89)
.020 (.51)
BSC
.300 (7.62)
(NOTE 5)
.015 (.38)
.010 (.25)
.395 (10.03)
.300 (7.62)
853-0408 81234
PO00290S

NOTES:
1. Controlling dimension: inches. Metric are shown in parentheses.
2. Package dimensions conform to JEDEC specification MS-001-AE for standard dual in-line (DIP) package .300 inch row spacing (PLASTIC) 20 leads (issue B. 7/85)
3. Dimensions and tolerancing per ANSI Y14. 5M-1982.
4. "T", "D" and "E" are reference datums on the molded body and do not include mold flash or protrusions. Mold flash or protrusions shall not exceed .010 inch (.25mm) on any side.
5. These dimensions measured with the leads constrained to be perpendicular to plane T.
6. Pin numbers start with pin #1 and continue counterclockwise to pin #20 when viewed from the top.

Package Outlines

24-PIN PLASTIC (N PACKAGE)


⊕ D Ⓢ .004 (.10)
- E -
PIN # 1
.255 (6.48)
.245 (6.22)
.100 2.54 (BSC)
- D -
1.256 (31.90)
1.240 (31.50)
.064 (1.63)
.045 (1.14)
- T -
SEATING PLANE
.160 (4.06)
.135 (3.43)
.138 (3.51)
.120 (3.05)
.022 (.56)
.017 (.43)
⊕ T E D Ⓢ .010 (.25) Ⓜ
.322 (8.18)
.300 (7.62)
(NOTE 5)
.125 (3.18)
.115 (2.92)
.035 (.89)
.020 (.51)
BSC
.300 (7.62)
(NOTE 5)
.015 (.38)
.010 (.25)
.395 (10.03)
.300 (7.62)
853-0410 81236
PO00320S

NOTES:

1. Controlling dimension: inches. Metric are shown in parentheses.
2. Package dimensions conform to JEDEC specification MS-001-AR for standard dual in-line (DIP) package .300 inch row spacing (PLASTIC) 24 leads (issue B. 7/85)
3. Dimensions and tolerancing per ANSI Y14. 5M-1982.
4. "T", "D" and "E" are reference datums on the molded body and do not include mold flash or protrusions. Mold flash or protrusions shall not exceed .010 inch (.25mm) on any side.
5. These dimensions measured with the leads constrained to be perpendicular to plane T.
6. Pin numbers start with pin #1 and continue counterclockwise to pin #24 when viewed from the top.

28-PIN PLASTIC (N PACKAGE)


⊕ D Ⓢ .004 (.10)
- E -
PIN # 1
.560 (14.22)
.545 (13.84)
.100 (2.54) BSC
- D -
1.460 (37.08)
1.415 (35.94)
.064 (1.63)
.045 (1.14)
- T -
SEATING PLANE
.200 (5.08)
.165 (4.19)
.138 (3.51)
.120 (3.05)
.022 (.56)
.017 (.43)
⊕ T E D Ⓢ .010 (.25) Ⓜ
.155 (3.94)
.145(3.68)
.620 (15.75)
.600 (15.24)
(NOTE 5)
.045 (1.14)
.020 (.51)
.600 (15.24) BSC
(NOTE 5)
.015 (.38)
.010 (.25)
.695 (17.65)
.600 (15.24)
853-0413 84099
PO00372S

NOTES:

1. Controlling dimension: inches. Metric are shown in parentheses.
2. Package dimensions conform to JEDEC specification MS-011-AB for standard dual in-line (DIP) package .600 inch row spacing (PLASTIC) 28 leads (issue B. 7/85)
3. Dimensions and tolerancing per ANSI Y14. 5M-1982.
4. "T", "D" and "E" are reference datums on the molded body and do not include mold flash or protrusions. Mold flash or protrusions shall not exceed .010 inch (.25mm) on any side.
5. These dimensions measured with the leads constrained to be perpendicular to plane T.
6. Pin numbers start with pin #1 and continue counterclockwise to pin #28 when viewed from the top.

Section 11
Sales Offices

Sales Offices

SIGNETICS HEADQUARTERS

811 East Arques Avenue
P.O. Box 3409
Sunnyvale,
California 94088-3409
Phone: (408) 991-2000

ALABAMA
Huntsville
Phone: (205) 830-4001

ARIZONA
Phoenix
Phone: (602) 265-4444

CALIFORNIA
Canoga Park
Phone: (818) 340-1431

Irvine
Phone: (714) 833-8980
(213) 588-3281

Los Angeles
Phone: (213) 670-1101

San Diego
Phone: (619) 560-0242

Sunnyvale
Phone: (408) 991-3737

COLORADO
Aurora
Phone: (303) 751-5011

FLORIDA
Clearwater
Phone: (813) 796-7086

Ft. Lauderdale
Phone: (305) 486-6300

GEORGIA
Atlanta
Phone: (404) 953-0067

ILLINOIS
Itasca
Phone: (312) 250-0050

INDIANA
Kokomo
Phone: (317) 453-6462

KANSAS
Overland Park
Phone: (913) 469-4005

MARYLAND
Glen Burnie
Phone: (301) 787-0220

MASSACHUSETTS
Littleton
Phone: (617) 486-8411

MICHIGAN
Farmington Hills
Phone: (313) 476-1610

MINNESOTA
Edina
Phone: (612) 835-7455

NEW JERSEY
Parsippany
Phone: (201) 334-4405

NEW YORK
Hauppauge
Phone: (516) 348-7877

Wappingers Falls
Phone: (914) 297-4074

NORTH CAROLINA
Cary
Phone: (919) 481-0400

OHIO
Worthington
Phone: (614) 888-7143

OREGON
Portland
Phone: (503) 297-5592

PENNSYLVANIA
Plymouth Meeting
Phone: (215) 825-4404

TENNESSEE
Greeneville
Phone: (615) 639-0251

TEXAS
Austin
Phone: (512) 339-9944

Richardson
Phone: (214) 644-3500

CANADA
SIGNETICS CANADA, LTD.
Etobicoke, Ontario
Phone: (416) 626-6676

Nepean, Ontario
Signetics, Canada, Ltd.
Phone: (613) 726-9576

REPRESENTATIVES

ARIZONA
Scottsdale
Thom Luke Sales, Inc.
Phone: (602) 941-1901

CALIFORNIA
Santa Clara
Magna Sales
Phone: (408) 727-8753

CONNECTICUT
Brookfield
M & M Associates
Phone: (203) 775-6888

FLORIDA
Clearwater
Sigma Technical Sales
Phone: (813) 791-0271

Ft. Lauderdale
Sigma Technical Sales
Phone: (305) 731-5995

ILLINOIS
Hoffman Estates
Micro-Tex, Inc.
Phone: (312) 382-3001

INDIANA
Indianapolis
Mohrfield Marketing Inc.
Phone: (317) 546-6969

KANSAS
Kansas City
B.C. Electronic Sales
Phone: (913) 342-1211

MASSACHUSETTS
Needham Heights
Kanan Associates
Phone: (617) 449-7400
Com-Sales, Inc.
Phone: (617) 444-8071

MICHIGAN
Bloomfield Hills
Enco Marketing
Phone: (313) 642-0203

MINNESOTA
Eden Prairie
High Technology Sales
Phone: (612) 944-7274

MISSOURI
St. Louis
B.C. Electronic Sales
Phone: (314) 521-6683

NEW JERSEY
East Hanover
Emtec Sales, Inc.
Phone: (201) 428-0600

NEW MEXICO
Albuquerque
F.P. Sales
Phone: (505) 345-5553

NEW YORK
Ithaca
Bob Dean, Inc.
Phone: (607) 257-1111

OHIO
Cleveland
Covert & Newman
Phone: (216) 663-3331
Dayton
Covert & Newman
Phone: (513) 439-5788
Worthington
Covert & Newman
Phone: (614) 888-2442

OKLAHOMA
Tulsa
Jerry Robinson and
Associates
Phone: (918) 665-3562

OREGON
Hillsboro
Western Technical Sales
Phone: (503) 640-4621

PENNSYLVANIA
Pittsburgh
Covert & Newman
Phone: (412) 531-2002

Willow Grove
Delta Technical Sales Inc.
Phone: (215) 657-7250

TEXAS
Houston
OM Sales
Phone: (713) 789-4426

UTAH
Salt Lake City
Electrodyne
Phone: (801) 486-3801

WASHINGTON
Bellevue
Western Technical Sales
Phone: (206) 641-3900

Spokane
Western Technical Sales
Phone: (509) 922-7600

WISCONSIN
Waukesha
Micro-Tex, Inc.
Phone: (414) 542-5352

CANADA
Burnaby, British Columbia
Tech-Trek, Ltd.
Phone: (604) 439-1367

Mississauga, Ontario
Tech-Trek, Ltd.
Phone: (416) 238-0366

Nepean, Ontario
Tech-Trek, Ltd.
Phone: (613) 726-9562

Richmond, British Columbia
Tech-Trek, Ltd.
Phone: (604) 271-3149

Ville St. Laurent, Quebec
Tech-Trek, Ltd.
Phone: (514) 337-7540

Sales Offices

DISTRIBUTORS

ALABAMA
Huntsville
Arrow Electronics
Phone: (205) 837-6955
Hamilton/Avnet Electronics
Phone: (205) 837-7210
Schweber Electronics
Phone: (205) 882-2200

ARIZONA
Phoenix
Schweber Electronics
Phone: (602) 997-4874
Wyle LEMG
Phone: (602) 249-2232

Tempe
Anthem Electronics
Phone: (602) 966-6600
Arrow Electronics
Phone: (602) 968-4800
Hamilton/Avnet Electronics
Phone: (602) 231-5100

CALIFORNIA
Calabasas
Wyle LEMG
Phone: (818) 880-9000

Canoga Park
Schweber Electronics
Phone: (818) 999-4702

Chatsworth
Anthem Electronics
Phone: (818) 700-1000
Arrow Electronics
Phone: (818) 701-7500
Hamilton/Avnet Electronics
Phone: (818) 700-2600
Hamilton/Avnet Electronics
Phone: (818) 700-6500

Costa Mesa
Avnet Electronics
Phone: (714) 754-6111
Hamilton Electro Sales
Phone: (714) 641-4100

Culver City
Hamilton/Avnet Electronics
Phone: (213) 558-2121

El Segundo
Wyle LEMG
Phone: (213) 322-8100

Garden Grove
Wyle LEMG Computer Products
Phone: (714) 891-1717

Gardena
Hamilton/Avnet Electronics
Phone: (213) 217-6364
Schweber Electronics
Phone: (213) 327-8409

Hayward
Arrow Electronics
Phone: (415) 487-4600

Irvine
Anthem Electronics
Phone: (714) 768-4444
Schweber Electronics
Phone: (714) 863-0200
Wyle LEMG
Phone: (714) 863-1611

Ontario
Hamilton/Avnet Electronics
Phone: (714) 989-4602

Rancho Cordova
Wyle LEMG
Phone: (916) 638-5282

Sacramento
Hamilton/Avnet Electronics
Phone: (916) 925-2216
Schweber Electronics
Phone: (916) 929-9732

San Diego
Anthem Electronics
Phone: (619) 453-4871
Arrow Electronics
Phone: (619) 565-4800
Hamilton/Avnet Electronics
Phone: (619) 571-7510
Schweber Electronics
Phone: (619) 450-0454
Wyle LEMG
Phone: (619) 565-9171

San Jose
Anthem Electronics Inc.
Phone: (408) 295-4200
Schweber Electronics
Phone: (408) 946-7171

Santa Clara
Wyle LEMG
Phone: (408) 727-2500

Sunnyvale
Arrow Electronics
Phone: (408) 745-6600
Hamilton/Avnet Electronics
Phone: (408) 743-3355

Torrance
Hamilton/Avnet Electronics
Phone: (213) 615-3962

Tustin
Arrow Electronics
Phone: (714) 838-5422

COLORADO
Aurora
Arrow Electronics
Phone: (303) 696-1111

Denver
Wyle Distribution Group
Phone: (303) 457-9953

Englewood
Anthem Electronics
Phone: (303) 790-4500
Hamilton/Avnet Electronics
Phone: (303) 779-9998
Schweber Electronics
Phone: (303) 799-0258

Thornton
Wyle LEMG
Phone: (303) 457-9953

CONNECTICUT
Danbury
Hamilton/Avnet Electronics
Phone: (203) 797-2800
Schweber Electronics
Phone: (203) 748-7080

Meriden
Lionex Corp.
Phone: (203) 237-2282

Wallingford
Arrow Electronics
Phone: (203) 265-7741

FLORIDA
Altamonte Springs
Schweber Electronics
Phone: (305) 331-7555
Clearwater
Arrow Electronics
Phone: (813) 576-8995

Deerfield Beach
Arrow Electronics
Phone: (305) 429-8200

Ft. Lauderdale
Hamilton/Avnet Electronics
Phone: (305) 971-2900

Hollywood
Schweber Electronics
Phone: (305) 927-0511

Palm Bay
Arrow Electronics
Phone: (305) 725-1480

St. Petersburg
Hamilton/Avnet Electronics
Phone: (813) 576-3930

Winter Park
Hamilton/Avnet Electronics
Phone: (305) 628-3888

GEORGIA
Norcross
Arrow Electronics
Phone: (404) 449-8252
Hamilton/Avnet Electronics
Phone: (404) 447-7507
Q.C. Southeast, Inc.
Phone: (404) 449-9508
Schweber Electronics
Phone: (404) 449-9170

ILLINOIS
Elk Grove
Schweber Electronics
Phone: (312) 364-3750

Schaumburg
Arrow Electronics
Phone: (312) 397-3440

Bensenville
Hamilton/Avnet Electronics
Phone: (312) 860-7700

INDIANA
Carmel
Hamilton/Avnet Electronics
Phone: (317) 844-9333

Indianapolis
Arrow Electronics
Phone: (317) 243-9353

IOWA
Cedar Rapids
Arrow Electronics
Phone: (319) 395-7230
Hamilton/Avnet Electronics
Phone: (319) 362-4757
Schweber Electronics
Phone: (319) 373-1417

KANSAS
Overland Park
Arrow Electronics
Phone: (913) 642-0592
Hamilton/Avnet Electronics
Phone: (913) 888-8900
Schweber Electronics
Phone: (913) 492-2922

MARYLAND
Columbia
Arrow Electronics
Phone: (301) 995-0003
Hamilton/Avnet Electronics
Phone: (301) 995-3500
Lionex Corp.
Phone: (301) 964-0040

Gaithersburg
Schweber Electronics
Phone: (301) 840-5900

MASSACHUSETTS
Peabody
Hamilton/Avnet Electronics
Phone: (617) 531-7430
Wilmington
Lionex Corp.
Phone: (617) 657-5170
Schweber Electronics
Phone: (617) 275-5100

Woburn
Arrow Electronics
Phone: (617) 933-8130
Hamilton/Avnet Electronics
Phone: (617) 273-7500

Sales Offices

MICHIGAN
Ann Arbor
Arrow Electronics
Phone: (313) 971-8220

Grand Rapids
Arrow Electronics
Phone: (616) 243-0912
Hamilton/Avnet Electronics
Phone: (616) 243-8805

Livonia
Hamilton/Avnet Electronics
Phone: (313) 522-4700
Schweber Electronics
Phone: (313) 525-8100

MINNESOTA
Edina
Arrow Electronics
Phone: (612) 830-1800
Schweber Electronics
Phone: (612) 941-5280

Minnetonka
Hamilton/Avnet Electronics
Phone: (612) 932-0600

MISSOURI
Earth City
Hamilton/Avnet Electronics
Phone: (314) 344-1200
Schweber Electronics
Phone: (314) 739-0526

St. Louis
Arrow Electronics
Phone: (314) 567-6888

NEW HAMPSHIRE
Manchester
Arrow Electronics
Phone: (603) 668-6968
Hamilton/Avnet Electronics
Phone: (603) 624-9400
Schweber Electronics
Phone: (603) 625-2250

NEW JERSEY
Cherry Hill
Hamilton/Avnet Electronics
Phone: (609) 424-0100

Fairfield
Arrow Electronics
Phone: (201) 575-5300
Hamilton/Avnet Electronics
Phone: (201) 575-3390
Lionex Corporation
Phone: (201) 227-7960
Schweber Electronics
Phone: (201) 227-7880

Marlton
Arrow Electronics
Phone: (609) 596-8000

NEW MEXICO
Albuquerque
Hamilton/Avnet Electronics
Phone: (505) 765-1500
Arrow Electronics
Phone: (505) 243-4566

NEW YORK
Buffalo
Summit Distributors
Phone: (716) 887-2800

East Syracuse
Hamilton/Avnet Electronics
Phone: (315) 437-2641

Hauppauge, L.I.
Arrow Electronics
Phone: (516) 231-1000
Hamilton/Avnet Electronics
Phone: (516) 231-9800
Lionex Corp.
Phone: (516) 273-1660

Liverpool
Arrow Electronics
Phone: (315) 652-1000

Rochester
Arrow Electronics
Phone: (716) 427-0300
Hamilton/Avnet Electronics
Phone: (716) 475-9130
Schweber Electronics
Phone: (716) 424-2222

Westbury, L.I.
Schweber Electronics
Phone: (516) 334-7474

NORTH CAROLINA
Raleigh
Arrow Electronics
Phone: (919) 876-3132
Hamilton/Avnet Electronics
Phone: (919) 878-0810
Schweber Electronics
Phone: (919) 876-0000

OHIO
Beechwood
Schweber Electronics
Phone: (216) 464-2970

Centerville
Arrow Electronics
Phone: (513) 435-5563

Cleveland
Hamilton/Avnet Electronics
Phone: (216) 831-3500

Columbus
Arrow Electronics
Phone: (614) 885-8362

Dayton
Hamilton/Avnet Electronics
Phone: (513) 439-6700
Schweber Electronics
Phone: (513) 439-1800

Solon
Arrow Electronics
Phone: (216) 248-3990

Westerville
Hamilton/Avnet Electronics
Phone: (614) 882-7004

OKLAHOMA
Tulsa
Arrow Electronics
Phone: (918) 665-7700
Quality Components
Phone: (918) 664-8812
Schweber Electronics
Phone: (918) 622-8000

OREGON
Hillsboro
Wyle LEMG
Phone: (503) 640-6000

Lake Oswego
Anthem Electronics
Phone: (503) 684-2661
Hamilton/Avnet Electronics
Phone: (503) 635-8831

Tigard
Arrow Electronics
Phone: (503) 684-1690

PENNSYLVANIA
Horsham
Lionex Corp.
Phone: (215) 443-5150
Schweber Electronics
Phone: (215) 441-0600

Monroeville
Arrow Electronics
Phone: (412) 856-7000

Pittsburgh
Hamilton/Avnet Electronics
Phone: (412) 281-4150
Schweber Electronics
Phone: (412) 782-1600

RHODE ISLAND
E. Providence
Arrow Electronics
Phone: (401) 431-0980

TEXAS
Addison
Quality Components
Phone: (214) 733-4300

Austin
Arrow Electronics
Phone: (512) 835-4180
Hamilton/Avnet Electronics
Phone: (512) 837-8911
Quality Components
Phone: (512) 835-0220
Wyle LEMG
Phone: (512) 834-9957
Schweber Electronics
Phone: (512) 458-8253

Carrolton
Arrow Electronics
Phone: (214) 380-6464

Dallas
Schweber Electronics
Phone: (214) 661-5010

Houston
Arrow Electronics
Phone: (713) 530-4700
Hamilton/Avnet Electronics
Phone: (713) 780-1771
Schweber Electronics
Phone: (713) 784-3600
Wyle LEMG
Phone: (713) 879-9953

Irving
Hamilton/Avnet Electronics
Phone: (214) 659-4111

Richardson
Wyle LEMG
Phone: (214) 235-9953

Sugar Land
Quality Components
Phone: (713) 240-2255

UTAH
Salt Lake City
Anthem Electronics
Phone: (801) 973-8555
Arrow Electronics
Phone: (801) 972-0404
Hamilton/Avnet Electronics
Phone: (801) 972-2800
Wyle LEMG
Phone: (801) 974-9953

WASHINGTON
Bellevue
Arrow Electronics
Phone: (206) 643-4800
Hamilton/Avnet Electronics
Phone: (206) 453-5844
Wyle LEMG
Phone: (206) 453-8300

Redmond
Anthem Electronics
Phone: (206) 881-0850

WISCONSIN
Brookfield
Arrow Electronics
Phone: (414) 792-0150
Schweber Electronics
Phone: (414) 784-9020

New Berlin
Hamilton/Avnet Electronics
Phone: (414) 784-4510

CANADA
Brampton, Ontario
Zentronics, Ltd.
Phone: (416) 451-9600

Sales Offices

Burnaby, British Columbia
Hamilton/Avnet Electronics
Phone: (604) 437-6667

Calgary, Alberta
Hamilton/Avnet Electronics
Phone: (403) 230-3586
Zentronics, Ltd.
Phone: (403) 272-1021

Mississauga, Ontario
Hamilton/Avnet Electronics
Phone: (416) 677-7432

Montreal, Québec
Arrow Canada
Phone: (514) 735-5511

Nepean, Ontario
Arrow Canada
Phone: (613) 226-6903
Hamilton/Avnet Electronics
Phone: (613) 226-1700
Zentronics, Ltd.
Phone: (613) 226-8840

Québec, Québec
Arrow Canada
Phone: (418) 687-4231

Richmond, British Columbia
Zentronics, Ltd.
Phone: (604) 273-5575

Saskatoon, Saskatchewan
Zentronics, Ltd.
Phone: (306) 955-2202

Toronto, Ontario
Arrow Canada
Phone: (416) 661-0220

Ville St. Laurent, Québec
Hamilton/Avnet Electronics
Phone: (514) 335-1000
Zentronics, Ltd.
Phone: (514) 737-9700

Waterloo, Ontario
Zentronics, Ltd.
Phone: (519) 884-5700

Winnipeg, Manitoba
Zentronics, Ltd.
Phone: (204) 775-8661

FOR SIGNETICS PRODUCTS WORLDWIDE:

ARGENTINA
Philips Argentina S.A.
Buenos Aires
Phone: 54-1-541-7141

AUSTRALIA
Philips Electronic Components and Materials, Ltd.
Artarmon, N.S.W.
Phone: 61-2-439-3322

AUSTRIA
Osterrichische Philips Bauelemente
Wien
Phone: 43-222-62-91-11

BELGIUM
N.V. Philips & MBLE
Bruxelles
Phone: 32-2-5-23-00-00

BRAZIL
Philips Do Brasil, Ltda.
Sao Paulo
Phone: 55-11-211-2600

CHILE
Philips Chilena S.A.
Santiago
Phone: 56-02-077-3816

COLOMBIA
Iprelenso, Ltda.
Bogota
Phone: 57-1-2497624

DENMARK
Miniwatt A/S
Copenhagen S
Phone: 45-1-54-11-33

FINLAND
Oy Philips Ab
Helsinki
Phone: 358-0-172-71

FRANCE
R.T.C. La Radiotechnique-Compelec
Paris
Phone: 33-1-43-38-80-00

GERMANY
Valvo
Hamburg
Phone: 49-40-3-296-1

GREECE
Philips Hellenique S.A.
Athens
Phone: 30-1-9-21-5111

HONG KONG
Philips Hong Kong, Ltd.
Kwai Chung
Phone: 852-0-245-121

INDIA
Peico Electronics & Elect. Ltd.
Bombay
Phone: 91-22-493-8721

INDONESIA
P.T. Philips-Ralin Electronics
Jakarta Selatan
Phone: 62-21-512-572

IRELAND
Philips Electrical Ltd.
Dublin
Phone: 353-1-69-33-55

ISRAEL
Rapac Electronics, Ltd.
Tel Aviv
Phone: 972-3-477115

ITALY
Philips S.p.A.
Milano
Phone: 39-2-67-52-1

JAPAN
Nikon Philips Corp.
Tokyo
Phone: 81-3-448-5617
Signetics Japan Ltd.
Phone: 81-3-230-1521/2

KOREA
Philips Industries, Ltd.
Seoul
Phone: 82-2-794-5011/2/3
/4/5

MEXICO
Electronica S.A. de C.V.
Toluca
Phone: (721) 613-00

NETHERLANDS
Philips Nederland B.V.
Eindhoven
Phone: 31-40-793-333

NEW ZEALAND
Philips New Zealand Ltd.
Auckland
Phone: 64-9-605914

NORWAY
Norsk A/S Philips
Oslo
Phone: 47-2-68-02-00

PERU
Cadesa
Lima
Phone: 51-14-319253

PHILIPPINES
Philips Industrial Dev., Inc.
Makati
Phone: 63-2-868951-9

PORTUGAL
Philips Portuguesa SARL
Lisbon
Phone: 351-1-65-71-85

SINGAPORE
Philips Project Dev. Pte., Ltd.
Singapore
Phone: 65-350-2000

SOUTH AFRICA
E.D.A.C. (PTY), Ltd.
Joubert Park
Phone: 27-11-402-4600

SPAIN
Miniwatt S.A.
Barcelona
Phone: 34-3-301-63-12

SWEDEN
Philips Komponenter A.B.
Stockholm
Phone: 46-8-782-10-00

SWITZERLAND
Philips A.G.
Zurich
Phone: 41-1-488-2211

TAIWAN
Philips Taiwan, Ltd.
Taipei
Phone: 886-2-712-0500

THAILAND
Philips Electrical Co. of Thailand Ltd.
Bangkok
Phone: 66-2-233-6330-9

TURKEY
Turk Philips Ticaret A.S.
Istanbul
Phone: 90-11-43-59-10

UNITED KINGDOM
Mullard, Ltd.
London
Phone: 44-1-580-6633

UNITED STATES
Signetics International Corp.
Sunnyvale, California
Phone: (408) 991-2000

URUGUAY
Luzilectron, S.A.
Montevideo
Phone: 598-91-56-41/42
/43/44

VENEZUELA
Magnetica, S.A.
Caracas
Phone: 58-2-241-7509

Effective 12-16-86

Signetics
a subsidiary of U.S. Philips Corporation

Signetics Corporation
811 E. Arques Avenue
P.O. Box 3409
Sunnyvale, California 94088-3409
Telephone 408/991-2000

98-7001-230

© Copyright 1987 Signetics Corporation
Printed in USA

AIS/BC80MCR21286
544 pages